

Package ‘DemografixeR’

May 6, 2020

Title Extrapolate Gender, Age and Nationality of a Name

Version 0.1.1

Description

Connects to the <<https://genderize.io/>>, <<https://agify.io/>> and <<https://nationalize.io/>> APIs to estimate gender, age and nationality of a first name.

License MIT + file LICENSE

URL <https://matbmeijer.github.io/DemografixeR>,
<https://github.com/matbmeijer/DemografixeR>

BugReports <https://github.com/matbmeijer/DemografixeR/issues>

Encoding UTF-8

LazyData true

Imports httr, jsonlite, magrittr

RoxygenNote 7.1.0

Suggests covr, testthat, knitr, rmarkdown, dplyr

VignetteBuilder knitr

NeedsCompilation no

Author Matthias Brenninkmeijer [aut, cre]

Maintainer Matthias Brenninkmeijer <matthias@brennotten.net>

Repository CRAN

Date/Publication 2020-05-06 12:50:22 UTC

R topics documented:

agify	2
DemografixeR	3
genderize	4
get_api_key	5
nationalize	6
remove_api_key	8
save_api_key	9
supported_countries	10

agify	<i>'Agifies' a name</i>
-------	-------------------------

Description

Function to estimate the age from a first name. Connects directly to the [agify.io API](#) sending a request with a name and parses the response to return the predicted age.

Usage

```
agify(
  name,
  country_id = NULL,
  simplify = TRUE,
  apikey = get_api_key(),
  meta = FALSE
)
```

Arguments

name	Name/s to estimate the age. Can be a single character string or a character vector. Obligatory parameter.
country_id	Responses will in a lot of cases be more accurate if the data is narrowed to a specific country. This optional parameter allows to specify a specific country. The parameter must be a country code following the common ISO 3166-1 alpha-2 country code convention. To see a list of the supported countries use the supported_countries function or visit the following link .
simplify	Logical parameter, which defines if the result should be returned as a character vector or a <code>data.frame</code> with additional information. By default set to TRUE, which returns a vector.
apikey	Optional parameter to pass the API key. The API is free for up to 1000 names/day. No sign up or API key needed. Yet, if more requests would be needed, visit the agify.io store and the obtained API key can be passed through this parameter. The API can also be saved one time through the save_api_key function, so it is not necessary to call again.
meta	Logical parameter to define if API related information should be returned. By default set to FALSE. Returns information about: <ul style="list-style-type: none"> • The amount of names available in the current time window • The number of names left in the current time window • Seconds remaining until a new time window opens

Details

The function automatically handles pagination (max. 10 names per API request), missing values & duplicated values. If a name is duplicated for the same country_id (if given), it will handle the request as a single name to save requests, returning the same value for the duplicated names. To see more details about the API documentation, visit the [agify.io website](#).

Value

The estimated age in a single character vector form or a `data.frame` with additional information.

Warning

Please be aware about local privacy protection regulations such as **GDPR** when dealing with personal data.

Author(s)

Matthias Brenninkmeijer - <https://github.com/matbmeijer>

See Also

[genderize](#), [nationalize](#)

Examples

```
agify(name=c("Ben", "Maria"))
```

Description

The DemografixeR is an API wrapper for the genderize.io, agify.io & nationalize.io APIs. Through the APIs it retrieves the estimated gender, estimated age and/or estimated nationality from a name. The package most important functions are the following:

- [genderize](#)
- [agify](#)
- [nationalize](#)

genderize	<i>'Genderizes' a name</i>
-----------	----------------------------

Description

Function to estimate the gender from a first name. Connects directly to the [genderize.io API](#) sending a request with a name and parses the response to return the predicted gender.

Usage

```
genderize(
  name,
  country_id = NULL,
  simplify = TRUE,
  apikey = get_api_key(),
  meta = FALSE
)
```

Arguments

name	Name/s to estimate the gender. Can be a single character string or a character vector. Obligatory parameter.
country_id	Responses will in a lot of cases be more accurate if the data is narrowed to a specific country. This optional parameter allows to specify a specific country. The parameter must be a country code following the common ISO 3166-1 alpha-2 country code convention. To see a list of the supported countries use the supported_countries function or visit the following link .
simplify	Defines if the result should be returned as a single vector or a <code>data.frame</code> with additional information. By default set to <code>TRUE</code> , which returns a vector. If set to <code>FALSE</code> , it will include additional information about: <ul style="list-style-type: none"> The probability indicating the certainty of the assigned gender. Basically the ratio of male to females. The count representing the number of data rows examined in order to calculate the response.
apikey	Optional parameter to pass the API key. The API is free for up to 1000 names/day. No sign up or API key needed. Yet, if more requests would be needed, visit the genderize.io store and the obtained API key can be passed through this parameter. The API can also be saved one time through the save_api_key function, so it is not necessary to call again.
meta	Logical parameter to define if API related information should be returned. By default set to <code>FALSE</code> . Returns information about: <ul style="list-style-type: none"> The amount of names available in the current time window The number of names left in the current time window Seconds remaining until a new time window opens

Details

The function automatically handles pagination (max. 10 names per API request), missing values & duplicated values. If a name is duplicated for the same country_id (if the parameter has been passed), it will handle the request as a single name to save requests, returning the same value for the duplicated names. To see more details about the API documentation, visit the [genderize.io website](#).

Value

The estimated age in a single character vector form or a `data.frame` with additional information.

Warning

Please be aware about local privacy protection regulations such as [GDPR](#) when dealing with personal data.

Author(s)

Matthias Brenninkmeijer - <https://github.com/matbmeijer>

See Also

[nationalize](#), [agify](#)

Examples

```
genderize(name=c("Ben", "Maria"))
```

get_api_key

Get previously saved API keys

Description

Function to get the previously saved API key. It has the advantage that it is not necessary to explicitly publish the key in the users code. Just do it one time and you're set. To save an API, use the [save_api_key](#) function. To remove a previously saved key, use the [remove_api_key](#) function.

Usage

```
get_api_key()
```

Value

Returns the saved API key in the environment. If no API key has been saved, returns NULL value.

Warning

Please be careful when dealing with API keys and other secrets & tokens - keep them private and do not publish them.

Author(s)

Matthias Brenninkmeijer - <https://github.com/matbmeijer>

See Also

[save_api_key](#), [remove_api_key](#)

Examples

```
## Not run:
get_api_key(type="genderize")
get_api_key(type="agify")
get_api_key(type="nationalize")

## End(Not run)
```

nationalize	<i>'Nationalizes' a name</i>
-------------	------------------------------

Description

Returns the estimated nationality from a given name.

Usage

```
nationalize(
  name,
  simplify = TRUE,
  sliced = TRUE,
  apikey = get_api_key(),
  meta = FALSE
)
```

Arguments

name	Name/s to estimate the nationality. Can be a single character string or a character vector. Obligatory parameter.
simplify	Defines if the result should be returned as a single vector or a <code>data.frame</code> with additional information. By default set to TRUE, which returns a vector.
sliced	Names can have multiple estimated nationalities ranked by probability. This logical parameter allows to "slice"/keep only the parameter with the highest probability to keep a single estimate for each name. By default set to TRUE.

apikey	Optional parameter to pass the API key. The API is free for up to 1000 names/day. No sign up or API key needed. Yet, if more requests would be needed, visit the nationalize.io store and the obtained API key can be passed through this parameter. The API can also be saved one time through the <code>save_api_key</code> function, so it is not necessary to call again.
meta	Logical parameter to define if API related information should be returned. By default set to FALSE. Returns information about: <ul style="list-style-type: none">• The amount of names available in the current time window• The number of names left in the current time window• Seconds remaining until a new time window opens

Details

The function automatically handles pagination (max. 10 names per API request), missing values & duplicated values. If a name is duplicated for the same country_id (if the parameter has been passed), it will handle the request as a single name to save requests, returning the same value for the duplicated names. To see more details about the API documentation, visit the [nationalize.io website](#).

Value

Returns the estimated nationality as the common [ISO 3166-1 alpha-2](#) country code. The result can be in a single character vector form or a `data.frame` with additional information.

Warning

Please be aware about local privacy protection regulations such as [GDPR](#) when dealing with personal data.

Author(s)

Matthias Brenninkmeijer - <https://github.com/matbmeijer>

See Also

[genderize](#), [agify](#)

Examples

```
nationalize(name=c("Ben", "Maria"))
```

remove_api_key	<i>Removes saved API key</i>
----------------	------------------------------

Description

Removes saved API keys for the DemografixeR APIs (Genderize.io, Agify.io, Nationalize.io).

Usage

```
remove_api_key(verbose = TRUE)
```

Arguments

verbose	Logical parameter to define if a verbose message should be printed. By default set to TRUE.
---------	---

Value

Does not return any object.

Warning

Please be careful when dealing with API keys and other secrets & tokens - keep them private and do not publish them.

Author(s)

Matthias Brenninkmeijer - <https://github.com/matbmeijer>

See Also

[save_api_key](#), [get_api_key](#)

Examples

```
## Not run:  
remove_api_key()  
  
## End(Not run)
```

save_api_key	<i>Saves the API key for future functions</i>
--------------	---

Description

Saves the all in one genderize.io, agify.io & nationalize.io API key in the users environment. It has the advantage that it is not necessary to explicitly publish the key in the users code. Just do it one time and you're set. To update the key just save again and it will overwrite the old key. To explicitly print the key, use the [get_api_key](#) function. To remove the key use the [remove_api_key](#) function.

Usage

```
save_api_key(key)
```

Arguments

key	API key obtained from the specific website. Visit the one of the following websites to obtain an API key: <ul style="list-style-type: none">• genderize.io• agify.io• nationalize.io
-----	--

Value

Does save the key in the environment.

Warning

Please be careful when dealing with API keys and other secrets & tokens - keep them private and do not publish them.

Author(s)

Matthias Brenninkmeijer - <https://github.com/matbmeijer>

See Also

[get_api_key](#), [remove_api_key](#)

Examples

```
## Not run:  
save_api_key(key="__YOUR_API_KEY__")  
  
## End(Not run)
```

supported_countries *Retrieve the supported countries for each API*

Description

Scrapes the API websites to retrieve an updated list of supported countries for each API.

Usage

```
supported_countries(type)
```

Arguments

type	Obligatory parameter to define the API from which to obtain the supported countries. Must be one of the following character strings:
	• genderize - Available countries for the Genderize.io API.
	• agify - Available countries for the Agify.io API.
	• nationalize - Available countries for the Nationalize.io API.

Value

Returns a `data.frame` with the supported ISO 3166-1 alpha-2 country code, country name the number of items (names) for each country.

Warning

Please be conscious that this function directly scrapes the website, do not overuse it as it might overwhelm the server.

Examples

```
## Not run:  
supported_countries(type="genderize")  
  
## End(Not run)
```

Index

agify, 2, 3, 5, 7

DemografixeR, 3

genderize, 3, 4, 7

get_api_key, 5, 8, 9

nationalize, 3, 5, 6

remove_api_key, 5, 6, 8, 9

save_api_key, 2, 4–8, 9

supported_countries, 2, 4, 10