

Package ‘Julia’

April 19, 2022

Type Package

Title Fractal Image Data Generator

Version 1.3.4

Date 2022-04-19

Maintainer Mehmet Suzen <mehmet.suzen@physics.org>

URL <https://github.com/msuzen/Julia>

BugReports <https://github.com/msuzen/Julia/issues>

Description Generates image data for fractals (Julia and Mandelbrot sets) on the complex plane in the given region and resolution. Benoit B Mandelbrot (1982).

License GPL-3

NeedsCompilation no

Author Mehmet Suzen [aut, cre]

Repository CRAN

Date/Publication 2022-04-19 21:42:33 UTC

R topics documented:

Julia-package	2
JuliaImage	3
JuliaIterate	4
MandelImage	5
MandelIterate	6
Index	8

Julia-package

Julia

Description

Generates image data for fractals (Julia and Mandelbrot sets) on the complex plane in the given region and resolution.

Details

Package: Julia
Type: Package
Version: 1.1
Date: 2014-11-25
License: GPL-3
LazyLoad: yes

Author(s)

Mehmet Suzen Maintainer: Mehmet Suzen <mehmet.suzen@physics.org>

References

The Fractal Geometry of Nature, Benoit B. Mandelbrot, W.H.Freeman & Co Ltd (18 Nov 1982)

See Also

[JuliaIterate](#) and [MandelIterate](#)

Examples

```
# Julia Set
imageN <- 5;
centre <- -1.0
L <- 2.0
file <- "julia1a.png"
C <- 1-1.6180339887i;# Golden Ration
image <- JuliaImage(imageN,centre,L,C);
# writePNG(image,file);# possible visulisation
# Mandelbrot Set
imageN <- 5;
centre <- 0.0
L <- 4.0
file <- "mandelbrot1.png"
image<-MandelImage(imageN,centre,L);
```

```
# writePNG(image,file);# possible visulisation
```

JuliaImage

Julia Set Generator in a Square Region

Description

'JuliaImage' returns two dimensional array representing escape values from on the square region in complex plane. Escape values (which measures the number of iteration before the lenght of the complex value reaches to 2).

Usage

```
JuliaImage(imageN, centre, L, C)
```

Arguments

imageN	Number of pixels to equally space division of one side if the square region.
centre	A complex number that determines the centre of the square region
L	A side length of the square region on the complex plane.
C	Complex coefficient

Details

Julia Set is defined as the set of initial complex values where the $z = z^2 + C$ does not diverge to infinity. C is an arbitrary complex constant that does not change during the iteration by definition.

Value

It returns a 2D array of real values from 0 to 1. The array correspods to image on the complex plane.

Note

Post processing to plot/color mapping of the Julia set for visualisation can be done by using the array generated. See examples to get a png output.

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

References

Gaston Julia (1918) "Memoire sur l'iteration des fonctions rationnelles," Journal de Mathematiques Pures et Appliquees, vol. 8, pages 47-245.

See Also

[MandelImage](#)

Examples

```

#
# Generating png of the Julia set
# C is 1 minus the golden ratio
#
imageN <- 5; # increase this to see images
centre <- 0.0
L <- 4.0
C <- 1i-1.6180339887;# Golden Ratio
image <- JuliaImage(imageN,centre,L,C);
#library(png)
#file <- "julia1.png"
#writePNG(image,file); # possible visulation
#
# Generating png of the Julia set
# different coefficient.
#
imageN <- 5; # increase this to see images
centre <- 0.0
L <- 4.0
C <- -0.70176-0.3842i
image <- JuliaImage(imageN,centre,L,C);
#library(png)
#file <- "julia2.png"
#writePNG(image,file); # possible visulation

```

JuliaIterate

JuliaIterate

Description

'JuliaIterate' returns the number of iteration until a complex value diverges for the Julia map for a give complex number.

Usage

```
JuliaIterate(z, C)
```

Arguments

z A complex coordinate (initial value for the map).
C A complex constant.

Details

'JuliaIterate' returns the number of iteration until a complex value diverges for the Julia map for a give complex number.

Value

Number of iterations.

Note

Iterative function.

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

References

The Fractal Geometry of Nature, Benoit B. Mandelbrot, W.H.Freeman & Co Ltd (18 Nov 1982)

See Also

[JuliaIterate](#) and [MandelIterate](#)

Examples

```
z<-0+0i
C <- 1-1.6180339887;# Golden Ratio
it<- JuliaIterate(z,C)
```

MandelImage

Mandelbrot Set Generator in a Square Domain

Description

'MandelImage' returns two dimensional array representing escape values from on the square region in complex plane. Escape values (which measures the number of iteration before the length of the complex value reaches to 2.)

Usage

```
MandelImage(imageN, centre, L)
```

Arguments

imageN	Number of pixels to equally space division of one side if the square region.
centre	A complex number that determines the centre of the square region.
L	A side length of the square region on the complex plane.

Details

Mandelbrot set is defined as the set of initial complex values where the $z = z^2 + z_0$ does not diverge to infinity. Initial value for the map is taken to be zero and z_0 is the complex coordinate.

Value

Returns a matrix.

Note

Returns a matrix

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

References

The Fractal Geometry of Nature, Benoit B. Mandelbrot, W.H.Freeman & Co Ltd (18 Nov 1982)

See Also

[JuliaImage](#)

Examples

```
# png image
imageN <- 5; # increase this to see image
centre <- 0.0
L <- 4.0
image<-MandelImage(imageN,centre,L);
#file <- "mandelbrot1.png"
# writePNG(image,file); # possible visualisation
# Closer lookup to set
imageN <- 5;
centre <- -0.5
L <- 2.0
image<-MandelImage(imageN,centre,L);
# file <- "mandelbrot.png"
#writePNG(image,file); # possible visualisation
```

MandelIterate

MandelIterate

Description

'MandelIterate' returns the number of iteration until a complex value diverges for the Mandelbrot map for a give complex number.

Usage

```
MandelIterate(z_0)
```

Arguments

`z_0` A complex coordinate (constant coefficient value for the map)

Details

Iterate function.

Value

Returns an integer

Note

Iterate function

Author(s)

Mehmet Suzen <mehmet.suzen@physics.org>

References

The Fractal Geometry of Nature, Benoit B. Mandelbrot, W.H.Freeman & Co Ltd (18 Nov 1982)

See Also

[JuliaIterate](#) and [MandelIterate](#)

Examples

```
z_0 <- 0-0.5i
it <- MandelIterate(z_0)
```

Index

* package

Julia-package, [2](#)

Julia (Julia-package), [2](#)

Julia-package, [2](#)

JuliaImage, [3](#), [6](#)

JuliaIterate, [2](#), [4](#), [5](#), [7](#)

MandelImage, [3](#), [5](#)

MandelIterate, [2](#), [5](#), [6](#), [7](#)