

Package ‘SparseM’

February 18, 2021

Version 1.81

Maintainer Roger Koenker <rkoenker@uiuc.edu>

Depends R (>= 2.15), methods

Imports graphics, stats, utils

Author Roger Koenker [cre, aut],
Pin Tian Ng [ctb] (Contributions to Sparse QR code),
Yousef Saad [ctb] (author of sparskit2),
Ben Shaby [ctb] (author of chol2csr)

Description Some basic linear algebra functionality for sparse matrices is provided: including Cholesky decomposition and backsolving as well as standard R subsetting and Kronecker products.

License GPL (>= 2)

Title Sparse Linear Algebra

URL <http://www.econ.uiuc.edu/~roger/research/sparse/sparse.html>

NeedsCompilation yes

Repository CRAN

Date/Publication 2021-02-18 12:00:02 UTC

R topics documented:

| | |
|-----------------------------------|----|
| character or NULL-class | 2 |
| lsq | 2 |
| matrix.coo-class | 4 |
| matrix.csc-class | 4 |
| matrix.csc.hb-class | 5 |
| matrix.csr-class | 6 |
| matrix.csr.chol-class | 8 |
| matrix.ssc-class | 9 |
| matrix.ssc.hb-class | 10 |
| matrix.ssr-class | 11 |
| mshl-class | 12 |
| numeric or NULL-class | 12 |

| | |
|------------------------------|----|
| slm | 13 |
| slm-class | 15 |
| slm.fit | 15 |
| slm.methods | 17 |
| SparseM.hb | 19 |
| SparseM.image | 21 |
| SparseM.ontology | 22 |
| SparseM.ops | 24 |
| SparseM.solve | 25 |
| summary.mslm-class | 27 |
| summary.slm-class | 28 |
| triogramX | 28 |

Index **29**

character or NULL-class
Class "character or NULL"

Description

A virtual class needed by the "matrix.csc.hb" class

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

No methods defined with class "character or NULL" in the signature.

lsq *Least Squares Problems in Surveying*

Description

One of the four matrices from the least-squares solution of problems in surveying that were used by Michael Saunders and Chris Paige in the testing of LSQR

Usage

data(lsq)

Format

A list of class `matrix.csc.hb` or `matrix.ssc.hb` depending on how the coefficient matrix is stored with the following components:

- `ra` `ra` component of the `csc` or `ssc` format of the coefficient matrix, `X`.
- `ja` `ja` component of the `csc` or `ssc` format of the coefficient matrix, `X`.
- `ia` `ia` component of the `csc` or `ssc` format of the coefficient matrix, `X`.
- `rhs.ra` `ra` component of the right-hand-side, `y`, if stored in `csc` or `ssc` format; right-hand-side stored in dense vector or matrix otherwise.
- `rhs.ja` `ja` component of the right-hand-side, `y`, if stored in `csc` or `ssc` format; a null vector otherwise.
- `rhs.ia` `ia` component of the right-hand-side, `y`, if stored in `csc` or `ssc` format; a null vector otherwise.
- `xexactvector` of the exact solutions, `b`, if they exist; a null vector otherwise.
- `guessvector` of the initial guess of the solutions if they exist; a null vector otherwise.
- `dimdimension` of the coefficient matrix, `X`.
- `rhs.dimdimension` of the right-hand-side, `y`.
- `rhs.modestorage` mode of the right-hand-side; can be full storage or same format as the coefficient matrix.

References

Koehler, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

Matrix Market, <https://math.nist.gov/MatrixMarket/data/Harwell-Boeing/lsq/lsq.html>

See Also

`read.matrix.hb`

Examples

```
data(lsq)
class(lsq) # -> [1] "matrix.csc.hb"
model.matrix(lsq)->X
class(X) # -> "matrix.csr"
dim(X) # -> [1] 1850 712
y <- model.response(lsq) # extract the rhs
length(y) # [1] 1850
```

matrix.coo-class *Class "matrix.coo"*

Description

A new class for sparse matrices stored in coordinate format

Objects from the Class

Objects can be created by calls of the form `new("matrix.coo", ...)`.

Slots

ra: Object of class `numeric`, a real array of `nnz` elements containing the non-zero elements of `A`.

ja: Object of class `integer`, an integer array of `nnz` elements containing the column indices of the elements stored in 'ra'.

ia: Object of class `integer`, an integer array of `nnz` elements containing the row indices of the elements stored in 'ra'.

dimension: Object of class `integer`, dimension of the matrix

Methods

as.matrix.csr signature(x = "matrix.coo"): ...

as.matrix signature(x = "matrix.coo"): ...

dim signature(x = "matrix.coo"): ...

See Also

[matrix.csr-class](#)

matrix.csc-class *Class "matrix.csc"*

Description

A new class for sparse matrices stored in compressed sparse column format

Objects from the Class

Objects can be created by calls of the form `new("matrix.csc", ...)`.

Slots

- ra:** Object of class `numeric`, a real array of `nnz` elements containing the non-zero elements of `A`, stored in column order. Thus, if $i < j$, all elements of column `i` precede elements from column `j`. The order of elements within the column is immaterial.
- ja:** Object of class `integer`, an integer array of `nnz` elements containing the row indices of the elements stored in `'ra'`.
- ia:** Object of class `integer`, an integer array of `n+1` elements containing pointers to the beginning of each column in the arrays `'ra'` and `'ja'`. Thus `'ia[i]'` indicates the position in the arrays `'ra'` and `'ja'` where the `i`th column begins. The last, `(n+1)`st, element of `'ia'` indicates where the `n+1` column would start, if it existed.
- dimension:** Object of class `integer`, dimension of the matrix

Methods

- as.matrix.csr** signature(x = "matrix.csc"): ...
- as.matrix.ssc** signature(x = "matrix.csc"): ...
- as.matrix.ssr** signature(x = "matrix.csc"): ...
- as.matrix** signature(x = "matrix.csc"): ...
- chol** signature(x = "matrix.csc"): ...
- dim** signature(x = "matrix.csc"): ...
- t** signature(x = "matrix.csc"): ...

See Also

[matrix.csr-class](#)

matrix.csc.hb-class *Class "matrix.csc.hb"*

Description

A new class consists of the coefficient matrix and the right-hand-side of a linear system of equations, initial guess of the solution and the exact solutions if they exist stored in external files using the Harwell-Boeing format.

Objects from the Class

Objects can be created by calls of the form `new("matrix.csc.hb", ...)`.

Slots

- ra:** Object of class `numeric`, ra component of the csc or ssc format of the coefficient matrix, X.
- ja:** Object of class `integer`, ja component of the csc or ssc format of the coefficient matrix, X.
- ia:** Object of class `numeric`, ia component of the csc or ssc format of the coefficient matrix, X.
- rhs.ra:** Object of class `numeric`, ra component of the right-hand-side, y, if stored in csc or ssc format; right-hand-side stored in dense vector or matrix otherwise.
- guess:** Object of class `numeric` or `NULL` vector of the initial guess of the solutions if they exist; a null vector otherwise.
- xexact:** Object of class `numeric` or `NULL` vector of the exact solutions, b, if they exist; a null vector otherwise.
- dimension:** Object of class `integer`, dimension of the coefficient matrix, X.
- rhs.dim:** Object of class `integer`, dimension of the right-hand-side, y.
- rhs.mode:** Object of class `character` or `NULL` storage mode of the right-hand-side; can be full storage or same format as the coefficient matrix.

Methods

model.matrix signature(object = "matrix.csc.hb"): ...

See Also

[model.matrix](#), [model.response](#), [read.matrix.hb](#), [matrix.ssc.hb-class](#)

| | |
|-------------------------------|---------------------------|
| <code>matrix.csr-class</code> | <i>Class "matrix.csr"</i> |
|-------------------------------|---------------------------|

Description

A new class for sparse matrices stored in compressed sparse row format

Objects from the Class

Objects can be created by calls of the form `new("matrix.csr", ...)`. and coerced from various other formats. Coercion of integer scalars and vectors into identity matrices and diagonal matrices respectively is accomplished by `as(x, "matrix.diag.csr")` which generates an object that has all the rights and responsibilities of the `matrix.csr` class. The default `matrix.csr` object is a scalar (1 by 1) matrix with element 0.

Slots

- ra:** Object of class `numeric`, a real array of `nnz` elements containing the non-zero elements of `A`, stored in row order. Thus, if $i < j$, all elements of row `i` precede elements from row `j`. The order of elements within the rows is immaterial.
- ja:** Object of class `integer`, an integer array of `nnz` elements containing the column indices of the elements stored in `'ra'`.
- ia:** Object of class `integer`, an integer array of `n+1` elements containing pointers to the beginning of each row in the arrays `'ra'` and `'ja'`. Thus `'ia[i]'` indicates the position in the arrays `'ra'` and `'ja'` where the `i`th row begins. The last, `(n+1)`st, element of `'ia'` indicates where the `n+1` row would start, if it existed.
- dimension:** Object of class `integer`, dimension of the matrix

Methods

```
%*% signature(x = "matrix.csr",y = "matrix.csr"): ...
%*% signature(x = "matrix.csr",y = "matrix"): ...
%*% signature(x = "matrix.csr",y = "numeric"): ...
%*% signature(x = "matrix",y = "matrix.csr"): ...
%*% signature(x = "numeric",y = "matrix.csr"): ...
as.matrix.csc signature(x = "matrix.csr"): ...
as.matrix.ssc signature(x = "matrix.csr"): ...
as.matrix.ssr signature(x = "matrix.csr"): ...
as.matrix.coo signature(x = "matrix.csr"): ...
as.matrix signature(x = "matrix.csr"): ...
chol signature(x = "matrix.csr"): ...
diag signature(x = "matrix.csr"): ...
diag<- signature(x = "matrix.csr"): ...
dim signature(x = "matrix.csr"): ...
image signature(x = "matrix.csr"): ...
solve signature(a = "matrix.csr"): ...
t signature(x = "matrix.csr"): ...
diff signature(x = "matrix.csr"): ...
```

See Also

[matrix.csc-class](#)

matrix.csr.chol-class *Class "matrix.csr.chol"*

Description

A class of objects returned from Ng and Peyton's (1993) block sparse Cholesky algorithm

Objects from the Class

Objects can be created by calls of the form `new("matrix.csr.chol", ...)`.

Slots

nrow: Object of class `integer`, number of rows in the linear system of equations
nnzindx: Object of class `numeric`, number of non-zero elements in `indx`
nsuper: Object of class `integer`, number of supernodes
indx: Object of class `integer`, vector of integer containing, in column major order, the row subscripts of the non-zero entries in the Cholesky factor in a compressed storage format
xindx: Object of class `integer`, vector of integer of pointers for `indx`
nnz1: Object of class `numeric`, number of non-zero entries, including the diagonal entries, of the Cholesky factor stored in `lnz`
lnz: Object of class `numeric`, contains the entries of the Cholesky factor
log.det: Object of class `numeric`, log determinant of the Cholesky factor
xlnz: Object of class `integer`, column pointer for the Cholesky factor stored in `lnz`
invp: Object of class `integer`, vector of integer of inverse permutation vector
perm: Object of class `integer`, vector of integer of permutation vector
xsuper: Object of class `integer`, array containing the supernode partitioning
det: Object of class `numeric`, determinant of the Cholesky factor
ierr: Object of class `integer`, error flag
time: Object of class `numeric` execution time

Methods

backsolve signature(`r = "matrix.csr.chol"`): ...
as.matrix.csr signature(`x = "matrix.csr.chol"`, `upper.tri=TRUE`): ...

See Also

[chol](#), [backsolve](#)

| | |
|------------------|--------------------|
| matrix.ssc-class | Class "matrix.ssc" |
|------------------|--------------------|

Description

A new class for sparse matrices stored in symmetric sparse column format

Objects from the Class

Objects can be created by calls of the form `new("matrix.ssc", ...)`.

Slots

ra: Object of class `numeric`, a real array of `nnz` elements containing the non-zero elements of the lower triangular part of `A`, stored in column order. Thus, if $i < j$, all elements of column `i` precede elements from column `j`. The order of elements within the column is immaterial.

ja: Object of class `integer`, an integer array of `nnz` elements containing the row indices of the elements stored in `'ra'`.

ia: Object of class `integer`, an integer array of `n+1` elements containing pointers to the beginning of each column in the arrays `'ra'` and `'ja'`. Thus `'ia[i]'` indicates the position in the arrays `'ra'` and `'ja'` where the `i`th column begins. The last, `(n+1)`st, element of `'ia'` indicates where the `n+1` column would start, if it existed.

dimension: Object of class `integer`, dimension of the matrix

Methods

as.matrix.csc signature(x = "matrix.ssc"): ...

as.matrix.csr signature(x = "matrix.ssc"): ...

as.matrix.ssr signature(x = "matrix.ssc"): ...

as.matrix signature(x = "matrix.ssc"): ...

dim signature(x = "matrix.ssc"): ...

See Also

[matrix.csr-class](#)

matrix.ssc.hb-class *Class "matrix.ssc.hb"*

Description

A new class consists of the coefficient matrix and the right-hand-side of a linear system of equations, initial guess of the solution and the exact solutions if they exist stored in external files using the Harwell-Boeing format.

Objects from the Class

Objects can be created by calls of the form `new("matrix.ssc.hb", ...)`.

Slots

ra: Object of class `numeric`, ra component of the csc or ssc format of the coefficient matrix, X.

ja: Object of class `integer`, ja component of the csc or ssc format of the coefficient matrix, X.

ia: Object of class `integer`, ia component of the csc or ssc format of the coefficient matrix, X.

rhs.ra: Object of class `numeric`, ra component of the right-hand-side, y, if stored in csc or ssc format; right-hand-side stored in dense vector or matrix otherwise.

guess: Object of class `numeric` or `NULL` vector of the initial guess of the solutions if they exist; a null vector otherwise.

xexact: Object of class `numeric` or `NULL` vector of the exact solutions, b, if they exist; a null vector otherwise.

dimension: Object of class `integer`, dimension of the coefficient matrix, X.

rhs.dim: Object of class `integer`, dimension of the right-hand-side, y.

rhs.mode: Object of class `character` or `NULL` storage mode of the right-hand-side; can be full storage or same format as the coefficient matrix.

Extends

Class `"matrix.csc.hb"`, directly.

Methods

model.matrix signature(object = "matrix.ssc.hb"): ...

See Also

[model.matrix](#), [model.response](#), [read.matrix.hb](#), [matrix.csc.hb-class](#)

| | |
|------------------|--------------------|
| matrix.ssr-class | Class "matrix.ssr" |
|------------------|--------------------|

Description

A new class for sparse matrices stored in symmetric sparse row format

Objects from the Class

Objects can be created by calls of the form `new("matrix.ssr", ...)`.

Slots

ra: Object of class `numeric`, a real array of `nnz` elements containing the non-zero elements of the lower triangular part of `A`, stored in row order. Thus, if $i < j$, all elements of row `i` precede elements from row `j`. The order of elements within the rows is immaterial.

ja: Object of class `integer`, an integer array of `nnz` elements containing the column indices of the elements stored in `'ra'`.

ia: Object of class `integer`, an integer array of `n+1` elements containing pointers to the beginning of each row in the arrays `'ra'` and `'ja'`. Thus `'ia[i]'` indicates the position in the arrays `'ra'` and `'ja'` where the `i`th row begins. The last, `(n+1)`st, element of `'ia'` indicates where the `n+1` row would start, if it existed.

dimension: Object of class `integer`, dimension of the matrix

Methods

as.matrix.csc signature(x = "matrix.ssr"): ...

as.matrix.csr signature(x = "matrix.ssr"): ...

as.matrix.ssr signature(x = "matrix.ssr"): ...

as.matrix signature(x = "matrix.ssr"): ...

dim signature(x = "matrix.ssr"): ...

See Also

[matrix.csr-class](#)

 mslm-class

 Class "mslm"

Description

A sparse extension of lm

Objects from the Class

Objects can be created by calls of the form `new("mslm", ...)`.

Slots

coefficients: Object of class `numeric` estimated coefficients
chol: Object of class `matrix.csr.chol` generated by the function `chol`
residuals: Object of class `"numeric"` residuals
fitted: Object of class `"numeric"` fitted values

Extends

Class `"lm"`, directly. Class `"slm"`, directly. Class `"oldClass"`, by class `"lm"`.

Methods

coef signature(object = "mslm"): ...
fitted signature(object = "mslm"): ...
residuals signature(object = "mslm"): ...
summary signature(object = "mslm"): ...

See Also

[slm](#)

 numeric or NULL-class *Class "numeric or NULL"*

Description

A virtual class needed by the `"matrix.csc.hb"` class

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

No methods defined with class `"numeric or NULL"` in the signature.

slm

Fit a linear regression model using sparse matrix algebra

Description

This is a function to illustrate the use of sparse linear algebra to solve a linear least squares problem using Cholesky decomposition. The syntax and output attempt to emulate `lm()` but may fail to do so fully satisfactorily. Ideally, this would eventually become a method for `lm`. The main obstacle to this step is that it would be necessary to have a `model.matrix` function that returned an object in sparse `csr` form. For the present, the objects represented in the formula must be in dense form. If the user wishes to specify fitting with a design matrix that is already in sparse form, then the lower level function `slm.fit()` should be used.

Usage

```
slm(formula, data, weights, na.action, method = "csr", contrasts = NULL, ...)
```

Arguments

| | |
|-----------|--|
| formula | a formula object, with the response on the left of a <code>~</code> operator, and the terms, separated by <code>+</code> operators, on the right. As in <code>lm()</code> , the response variable in the formula can be matrix valued. |
| data | a <code>data.frame</code> in which to interpret the variables named in the formula, or in the subset and the weights argument. If this is missing, then the variables in the formula should be on the search list. This may also be a single number to handle some special cases – see below for details. |
| weights | vector of observation weights; if supplied, the algorithm fits to minimize the sum of the weights multiplied into the absolute residuals. The length of weights must be the same as the number of observations. The weights must be nonnegative and it is strongly recommended that they be strictly positive, since zero weights are ambiguous. |
| na.action | a function to filter missing data. This is applied to the <code>model.frame</code> after any subset argument has been used. The default (with <code>na.fail</code>) is to create an error if any missing values are found. A possible alternative is <code>na.omit</code> , which deletes observations that contain one or more missing values. |
| method | there is only one method based on Cholesky factorization |
| contrasts | a list giving contrasts for some or all of the factors default = <code>NULL</code> appearing in the model formula. The elements of the list should have the same name as the variable and should be either a contrast matrix (specifically, any full-rank matrix with as many rows as there are levels in the factor), or else a function to compute such a matrix given the number of levels. |
| ... | additional arguments for the fitting routines |

Value

A list of class `slm` consisting of:

| | |
|---------------------------|------------------------------|
| <code>coefficients</code> | estimated coefficients |
| <code>chol</code> | cholesky object from fitting |
| <code>residuals</code> | residuals |
| <code>fitted</code> | fitted values |
| <code>terms</code> | terms |
| <code>call</code> | call |
| ... | |

Author(s)

Roger Koenker

References

Koenker, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

See Also

`slm.methods` for methods `summary`, `print`, `fitted`, `residuals` and `coef` associated with class `slm`, and `slm.fit` for lower level fitting functions. The latter functions are of special interest if you would like to pass a sparse form of the design matrix directly to the fitting process.

Examples

```
data(lsq)
X <- model.matrix(lsq) #extract the design matrix
y <- model.response(lsq) # extract the rhs
X1 <- as.matrix(X)
slm.time <- system.time(slm(y~X1-1) -> slm.o) # pretty fast
lm.time <- system.time(lm(y~X1-1) -> lm.o) # very slow
cat("slm time =",slm.time,"\n")
cat("slm Results: Reported Coefficients Truncated to 5 ", "\n")
sum.slm <- summary(slm.o)
sum.slm$coef <- sum.slm$coef[1:5,]
sum.slm
cat("lm time =",lm.time,"\n")
cat("lm Results: Reported Coefficients Truncated to 5 ", "\n")
sum.lm <- summary(lm.o)
sum.lm$coef <- sum.lm$coef[1:5,]
sum.lm
```

| | |
|-----------|--------------------|
| slm-class | <i>Class "slm"</i> |
|-----------|--------------------|

Description

A sparse extension of `lm`

Objects from the Class

Objects can be created by calls of the form `new("slm", ...)`.

Slots

coefficients: Object of class `numeric` estimated coefficients
chol: Object of class `matrix.csr.chol` generated by function `chol`
residuals: Object of class `"numeric"` residuals
fitted: Object of class `"numeric"` fitted values

Extends

Class `"lm"`, directly. Class `"oldClass"`, by class `"lm"`.

Methods

coef signature(object = "slm"): ...
fitted signature(object = "slm"): ...
residuals signature(object = "slm"): ...
summary signature(object = "slm"): ...

See Also

[slm](#)

| | |
|----------------------|---------------------------------------|
| <code>slm.fit</code> | <i>Internal slm fitting functions</i> |
|----------------------|---------------------------------------|

Description

Fitting functions for sparse linear model fitting.

Usage

```
slm.fit(x,y,method, ...)
slm.wfit(x,y,weights,...)
slm.fit.csr(x, y, ...)
```

Arguments

| | |
|---------|---|
| x | design matrix. |
| y | vector of response observations. |
| method | only csr is supported currently |
| weights | an optional vector of weights to be used in the fitting process. If specified, weighted least squares is used with weights 'weights' (that is, minimizing |

$$\sum w_i * e_i^2$$

The length of weights must be the same as the number of observations. The weights must be nonnegative and it is strongly recommended that they be strictly positive, since zero weights are ambiguous.

... additional arguments.

Details

slm.fit and slm.wfit call slm.fit.csr to do Cholesky decomposition and then backsolve to obtain the least squares estimated coefficients. These functions can be called directly if the user is willing to specify the design matrix in matrix.csr form. This is often advantageous in large problems to reduce memory requirements.

Value

A list of class slm consisting of:

| | |
|-------------|------------------------------|
| coef | estimated coefficients |
| chol | cholesky object from fitting |
| residuals | residuals |
| fitted | fitted values |
| df.residual | degrees of freedom |
| terms | terms |
| call | call |
| ... | |

Author(s)

Roger Koenker

References

Koenker, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

See Also

[slm](#)

Examples

```

data(lsq)
X <- model.matrix(lsq) #extract the design matrix
y <- model.response(lsq) # extract the rhs
class(X) # -> "matrix.csr"
class(y) # -> NULL
slm.fit(X,y)->slm.fit.o # this is much more efficient in memory usage than slm()
slm(y~as.matrix(X)-1) -> slm.o # this requires X to be transformed into dense mode
cat("Difference between `slm.fit` and `slm` estimated coefficients =",
sum(abs(slm.fit.o$coef-slm.o$coef)), "\n")

```

slm.methods

*Methods for slm objects***Description**

Summarize, print, and extract objects from `slm` objects.

Usage

```

## S3 method for class 'slm'
summary(object, correlation, ...)
## S3 method for class 'mslm'
summary(object, ...)
## S3 method for class 'slm'
print(x, digits, ...)
## S3 method for class 'summary.slm'
print(x, digits, symbolic.cor, signif.stars, ...)
## S3 method for class 'slm'
fitted(object, ...)
## S3 method for class 'slm'
residuals(object, ...)
## S3 method for class 'slm'
coef(object, ...)
## S3 method for class 'slm'
extractAIC(fit, scale = 0, k = 2, ...)
## S3 method for class 'slm'
deviance(object, ...)

```

Arguments

`object, x, fit` object of class `slm`.

`digits` minimum number of significant digits to be used for most numbers.

`scale` optional numeric specifying the scale parameter of the model, see 'scale' in 'step'. Currently only used in the "lm" method, where 'scale' specifies the estimate of the error variance, and 'scale = 0' indicates that it is to be estimated by maximum likelihood.

| | |
|--------------|--|
| k | numeric specifying the "weight" of the equivalent degrees of freedom ('edf') part in the AIC formula. |
| symbolic.cor | logical; if TRUE, the correlation of coefficients will be printed. The default is FALSE |
| signif.stars | logical; if TRUE, P-values are additionally encoded visually as "significance stars" in order to help scanning of long coefficient tables. It defaults to the 'show.signif.stars' slot of 'options'. |
| correlation | logical; if TRUE, the correlation matrix of the estimated parameters is returned and printed. |
| ... | additional arguments passed to methods. |

Value

`print.slm` and `print.summary.slm` return invisibly. `fitted.slm`, `residuals.slm`, and `coef.slm` return the corresponding components of the `slm` object. `extractAIC.slm` and `deviance.slm` return the AIC and deviance values of the fitted object.

Author(s)

Roger Koenker

References

Koenker, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

See Also

`slm`

Examples

```
data(lsq)
X <- model.matrix(lsq) #extract the design matrix
y <- model.response(lsq) # extract the rhs
X1 <- as.matrix(X)
slm.time <- system.time(slm(y~X1-1) -> slm.o) # pretty fast
cat("slm time =",slm.time,"\n")
cat("slm Results: Reported Coefficients Truncated to 5 ", "\n")
sum.slm <- summary(slm.o)
sum.slm$coef <- sum.slm$coef[1:5,]
sum.slm
fitted(slm.o)[1:10]
residuals(slm.o)[1:10]
coef(slm.o)[1:10]
```

SparseM.hb

*Harwell-Boeing Format Sparse Matrices***Description**

Read, and extract components of data in Harwell-Boeing sparse matrix format.

Usage

```
read.matrix.hb(file)
model.matrix(object, ...)
model.response(data, type)
```

Arguments

| | |
|--------------|--|
| file | file name to read from or |
| data, object | an object of either 'matrix.csc.hb' or 'matrix.ssc.hb' class |
| type | One of "any", "numeric", "double". Using the either of latter two coerces the result to have storage mode "double" |
| ... | additional arguments to model.matrix |

Details

Sparse coefficient matrices in the Harwell-Boeing format are stored in 80-column records. Each file begins with a multiple line header block followed by two, three or four data blocks. The header block contains summary information on the storage formats and storage requirements. The data blocks contain information of the sparse coefficient matrix and data for the right-hand-side of the linear system of equations, initial guess of the solution and the exact solutions if they exist. The function `model.matrix` extracts the X matrix component. The function `model.response` extracts the y vector (or matrix). The function `model.guess` extracts the guess vector. The function `model.xexact` extracts the xexact vector. This function is written in R replacing a prior implementation based on `iohb.c` which had memory fault difficulties. The function `write.matrix.hb` has been purged; users wishing to write matrices in Harwell-Boeing format are advised to convert SparseM matrices to Matrix classes and use `writeHB` from the Matrix package. Contributions of code to facilitate this conversion would be appreciated!

Value

The function `read.matrix.hb` returns a list of class `matrix.csc.hb` or `matrix.ssc.hb` depending on how the coefficient matrix is stored in the file.

| | |
|--------|---|
| ra | ra component of the csc or ssc format of the coefficient matrix, X. |
| ja | ja component of the csc or ssc format of the coefficient matrix, X. |
| ia | ia component of the csc or ssc format of the coefficient matrix, X. |
| rhs.ra | ra component of the right-hand-side, y, if stored in csc or ssc format; right-hand-side stored in dense vector or matrix otherwise. |

| | |
|-----------|---|
| rhs.ja | ja component of the right-hand-side, y, if stored in csc or ssc format; a null vector otherwise. |
| rhs.ia | ia component of the right-hand-side, y, if stored in csc or ssc format; a null vector otherwise. |
| xexact | vector of the exact solutions, b, if they exist; a null vector otherwise. |
| guess | vector of the initial guess of the solutions if they exist; a null vector otherwise. |
| dimension | dimension of the coefficient matrix, X. |
| rhs.dim | dimension of the right-hand-side, y. |
| rhs.mode | storage mode of the right-hand-side; can be full storage or same format as the coefficient matrix, for the moment the only allowed mode is "F" for full, or dense mode. |

The function `model.matrix` returns the X matrix of class `matrix.csr`. The function `model.response` returns the y vector (or matrix). The function `model.guess` returns the guess vector (or matrix). The function `model.xexact` returns the xexact vector (or matrix).

Author(s)

Pin Ng

References

Duff, I.S., Grimes, R.G. and Lewis, J.G. (1992) User's Guide for Harwell-Boeing Sparse Matrix Collection at <https://math.nist.gov/MatrixMarket/collections/hb.html>

See Also

`s1m` for sparse version of `lm`
`SparseM.ops` for operators on class `matrix.csr`
`SparseM.solve` for linear equation solving for class `matrix.csr`
`SparseM.image` for image plotting of class `matrix.csr`
`SparseM.ontology` for coercion of class `matrix.csr`

Examples

```
Xy <- read.matrix.hb(system.file("extdata","lsq.rra",package = "SparseM"))
class(Xy) # -> [1] "matrix.csc.hb"
X <- model.matrix(Xy)->X
class(X) # -> "matrix.csr"
dim(X) # -> [1] 1850 712
y <- model.response(Xy) # extract the rhs
length(y) # [1] 1850
Xy <- read.matrix.hb(system.file("extdata","rua_32_ax.rua",package = "SparseM"))
X <- model.matrix(Xy)
y <- model.response(Xy) # extract the rhs
g <- model.guess(Xy) # extract the guess
a <- model.xexact(Xy) # extract the xexact
fit <- solve(t(X) %*% X, t(X) %*% y) # compare solution with xexact solution
```

 SparseM.image

Image Plot for Sparse Matrices

Description

Display the pattern of non-zero entries of a matrix of class `matrix.csr`.

Usage

```
## S4 method for signature 'matrix.csr'
image(x, col=c("white","gray"),
      xlab="column", ylab="row", ...)
```

Arguments

| | |
|------------------------|---|
| <code>x</code> | a matrix of class <code>matrix.csr</code> . |
| <code>col</code> | a list of colors such as that generated by rainbow . Defaults to <code>c("white","gray")</code> |
| <code>xlab,ylab</code> | each a character string giving the labels for the x and y axis. |
| <code>...</code> | additional arguments. |

Details

The pattern of the non-zero entries of a sparse matrix is displayed. By default nonzero entries of the matrix appear as gray blocks and zero entries as white background.

References

Koenker, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

See Also

`SparseM.ops`, `SparseM.solve`, `SparseM.ontology`

Examples

```
a <- rnorm(20*5)
A <- matrix(a,20,5)
A[row(A)>col(A)+4|row(A)<col(A)+3] <- 0
b <- rnorm(20*5)
B <- matrix(b,20,5)
B[row(A)>col(A)+2|row(A)<col(A)+2] <- 0
image(as.matrix.csr(A)%*%as.matrix.csr(t(B)))
```

Description

This group of functions evaluates and coerces changes in class structure.

Usage

```
## S3 method for class 'matrix.csr'
as(x, nrow = 1, ncol = 1, eps = .Machine$double.eps, ...)
## S3 method for class 'matrix.csc'
as(x, nrow = 1, ncol = 1, eps = .Machine$double.eps, ...)
## S3 method for class 'matrix.ssr'
as(x, nrow = 1, ncol = 1, eps = .Machine$double.eps, ...)
## S3 method for class 'matrix.ssc'
as(x, nrow = 1, ncol = 1, eps = .Machine$double.eps, ...)
## S3 method for class 'matrix.csr'
is(x, ...)
## S3 method for class 'matrix.csc'
is(x, ...)
## S3 method for class 'matrix.ssr'
is(x, ...)
## S3 method for class 'matrix.ssc'
is(x, ...)
```

Arguments

| | |
|-------------------|--|
| <code>x</code> | is a matrix, or vector object, of either dense or sparse form |
| <code>nrow</code> | number of rows of matrix |
| <code>ncol</code> | number of columns of matrix |
| <code>eps</code> | A tolerance parameter: elements of <code>x</code> such that $\text{abs}(x) < \text{eps}$ set to zero. This argument is only relevant when coercing matrices from dense to sparse form. Defaults to <code>eps = .Machine\$double.eps</code> |
| <code>...</code> | other arguments |

Details

The function `matrix.csc` acts like `matrix` to coerce a vector object to a sparse matrix object of class `matrix.csr`. This aspect of the code is in the process of conversion from S3 to S4 classes. For the most part the S3 syntax prevails. An exception is the code to coerce vectors to diagonal matrix form which uses `as(v, "matrix.diag.csr")`. The generic functions `as.matrix.xxx` coerce a matrix `x` into a matrix of storage class `matrix.xxx`. The argument matrix `x` may be of conventional dense form, or of any of the four supported classes: `matrix.csr`, `matrix.csc`, `matrix.ssr`, `matrix.ssc`. The generic functions `is.matrix.xxx` evaluate whether the argument is of class `matrix.xxx`. The function `as.matrix` transforms a matrix of any sparse class into conventional dense form. The

primary storage class for sparse matrices is the compressed sparse row `matrix.csr` class. An n by m matrix A with real elements a_{ij} , stored in `matrix.csr` format consists of three arrays:

- `ra`: a real array of nnz elements containing the non-zero elements of A , stored in row order. Thus, if $i < j$, all elements of row i precede elements from row j . The order of elements within the rows is immaterial.
- `ja`: an integer array of nnz elements containing the column indices of the elements stored in `ra`.
- `ia`: an integer array of $n+1$ elements containing pointers to the beginning of each row in the arrays `ra` and `ja`. Thus `ia[i]` indicates the position in the arrays `ra` and `ja` where the i th row begins. The last, $(n+1)$ st, element of `ia` indicates where the $n+1$ row would start, if it existed.

The compressed sparse column class `matrix.csc` is defined in an analogous way, as are the `matrix.ssr`, symmetric sparse row, and `matrix.ssc`, symmetric sparse column classes.

Note

`as.matrix.ssr` and `as.matrix.ssc` should ONLY be used with symmetric matrices.

`as.matrix.csr(x)`, when x is an object of class `matrix.csr`.`chol` (that is, an object returned by a call to `chol(a)` when a is an object of class `matrix.csr` or `matrix.csc`), by default returns an upper triangular matrix, which is *not* consistent with the result of `chol` in the **base** package. To get an lower triangular `matrix.csr` matrix, use either `as.matrix.csr(x, upper.tri = FALSE)` or `t(as.matrix.csr(x))`.

References

Koenker, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

See Also

`SparseM.hb` for handling Harwell-Boeing sparse matrices.

Examples

```
n1 <- 10
p <- 5
a <- rnorm(n1*p)
a[abs(a)<0.5] <- 0
A <- matrix(a,n1,p)
B <- t(A)%*%A
A.csr <- as.matrix.csr(A)
A.csc <- as.matrix.csc(A)
B.ssr <- as.matrix.ssr(B)
B.ssc <- as.matrix.ssc(B)
is.matrix.csr(A.csr) # -> TRUE
is.matrix.csc(A.csc) # -> TRUE
is.matrix.ssr(B.ssr) # -> TRUE
is.matrix.ssc(B.ssc) # -> TRUE
as.matrix(A.csr)
```

```

as.matrix(A.csc)
as.matrix(B.ssr)
as.matrix(B.ssc)
as.matrix.csr(rep(0,9),3,3) #sparse matrix of all zeros
as(4,"matrix.diag.csr") #identity matrix of dimension 4

```

SparseM.ops

Basic Linear Algebra for Sparse Matrices

Description

Basic linear algebra operations for sparse matrices of class `matrix.csr`.

Arguments

| | |
|--------------------------|--|
| <code>x</code> | matrix of class <code>matrix.csr</code> . |
| <code>y</code> | matrix of class <code>matrix.csr</code> or a dense matrix or vector. |
| <code>value</code> | replacement values. |
| <code>i, j</code> | vectors of elements to extract or replace. |
| <code>nrow</code> | optional number of rows for the result. |
| <code>lag</code> | an integer indicating which lag to use. |
| <code>differences</code> | an integer indicating the order of the difference. |

Details

Linear algebra operations for matrices of class `matrix.csr` are designed to behave exactly as for regular matrices. In particular, matrix multiplication, kronecker product, addition, subtraction and various logical operations should work as with the conventional dense form of matrix storage, as does indexing, `rbind`, `cbind`, and diagonal assignment and extraction. The method `diag` may be used to extract the diagonal of a `matrix.csr` object, to create a sparse diagonal see `SparseM.ontology`.

The function `determinant` computes the (log) determinant, of the argument, returning a "det" object as the base function. This is *preferred* over using the function `det()` which is a simple wrapper for `determinant()`. Using `det()` in the following way is somewhat deprecated: `det()` computes the determinant of the argument matrix. If the matrix is of class `matrix.csr` then it must be symmetric, or an error will be returned. If the matrix is of class `matrix.csr.chol` then the determinant of the Cholesky factor is returned, ie the product of the diagonal elements.

The function `norm` is used to check for symmetry by computing the maximum of the elements of the difference between the matrix and its transpose. Optionally, this sup norm can be replaced by the Hilbert-Schmidt norm, or the l1 norm.

References

Koehler, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

See Also

slm for sparse linear model fitting. SparseM.ontology for coercion and other class relations involving the sparse matrix classes.

Examples

```
n1 <- 10
n2 <- 10
p <- 6
y <- rnorm(n1)
a <- rnorm(n1*p)
a[abs(a) < 0.5] <- 0
A <- matrix(a,n1,p)
A.csr <- as.matrix.csr(A)
b <- rnorm(n2*p)
b[abs(b)<1.0] <- 0
B <- matrix(b,n2,p)
B.csr <- as.matrix.csr(B)

# matrix transposition and multiplication
A.csr%*%t(B.csr)

# kronecker product - via kronecker() methods:
A.csr %x% matrix(1:4,2,2)
```

 SparseM.solve

Linear Equation Solving for Sparse Matrices

Description

chol performs a Cholesky decomposition of a symmetric positive definite sparse matrix x of class matrix.csr.

backsolve performs a triangular back-fitting to compute the solutions of a system of linear equations in one step.

backsolve and forwardsolve can also split the functionality of backsolve into two steps.

solve combines chol and backsolve and will compute the inverse of a matrix if the right-hand-side is missing.

Usage

```
chol(x, ...)
## S4 method for signature 'matrix.csr.chol'
backsolve(r, x, k = NULL, upper.tri = NULL,
          transpose = NULL, twice = TRUE, ...)
forwardsolve(l, x, k = ncol(l), upper.tri = FALSE, transpose = FALSE)
solve(a, b, ...)
```

Arguments

| | |
|------------------------|---|
| <code>a</code> | symmetric positive definite matrix of class <code>matrix.csr</code> . |
| <code>r</code> | object of class <code>matrix.csr.chol</code> returned by the function <code>chol</code> . |
| <code>l</code> | object of class <code>matrix.csr.chol</code> returned by the function <code>chol</code> . |
| <code>x,b</code> | vector(regular matrix) of right-hand-side(s) of a system of linear equations. |
| <code>k</code> | inherited from the generic; not used here. |
| <code>upper.tri</code> | inherited from the generic; not used here. |
| <code>transpose</code> | inherited from the generic; not used here. |
| <code>twice</code> | Logical flag: If true <code>backsolve</code> solves twice, see below. |
| <code>...</code> | further arguments passed to or from other methods. |

Details

`chol` performs a Cholesky decomposition of a symmetric positive definite sparse matrix `a` of class `matrix.csr` using the block sparse Cholesky algorithm of Ng and Peyton (1993). The structure of the resulting `matrix.csr.chol` object is relatively complicated. If necessary it can be coerced back to a `matrix.csr` object as usual with `as.matrix.csr`. `backsolve` does triangular back-fitting to compute the solutions of a system of linear equations. For systems of linear equations that only vary on the right-hand-side, the result from `chol` can be reused. Contrary to the behavior of `backsolve` in base R, the default behavior of `backsolve(C, b)` when `C` is a `matrix.csr.chol` object is to produce a solution to the system $Ax = b$ where $C \leftarrow \text{chol}(A)$, see the example section. When the flag `twice` is `FALSE` then `backsolve` solves the system $Cx = b$, up to a permutation – see the comments below. The command `solve` combines `chol` and `backsolve`, and will compute the inverse of a matrix if the right-hand-side is missing. The determinant of the Cholesky factor is returned providing a means to efficiently compute the determinant of sparse positive definite symmetric matrices.

There are several integer storage parameters that are set by default in the call to the Cholesky factorization, these can be overridden in any of the above functions and will be passed by the usual "dots" mechanism. The necessity to do this is usually apparent from error messages like: Error in local(X...) increase tmpmax. For example, one can use, `solve(A,b,tmpmax = 100*nrow(A))`. The current default for `tmpmax` is `50*nrow(A)`. Some experimentation may be needed to select appropriate values, since they are highly problem dependent. See the code of `chol()` for further details on the current defaults.

Note

Because the sparse Cholesky algorithm re-orders the positive definite sparse matrix `A`, the value of `x <- backsolve(C,b)` does *not* equal the solution to the triangular system $Cx = b$, but is instead the solution to the system $CPx = Pb$ for some permutation matrix P (and analogously for `x <- forwardsolve(C,b)`). However, a little algebra easily shows that `backsolve(C, forwardsolve(C,b), twice = FALSE)` is the solution to the equation $Ax = b$. Finally, if $C \leftarrow \text{chol}(A)$ for some sparse covariance matrix `A`, and `z` is a conformable standard normal vector, then the product `y <- as.matrix.csr(C) %*% z` is normal with covariance matrix `A` irrespective of the permutation of the Cholesky factor.

References

Koenker, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

Ng, E. G. and B. W. Peyton (1993), "Block sparse Cholesky algorithms on advanced uniprocessor computers", *SIAM J. Sci. Comput.*, **14**, pp. 1034-1056.

See Also

s1m for sparse version of lm

Examples

```
data(lsq)
class(lsq) # -> [1] "matrix.csc.hb"
model.matrix(lsq)->design.o
class(design.o) # -> "matrix.csr"
dim(design.o) # -> [1] 1850 712
y <- model.response(lsq) # extract the rhs
length(y) # [1] 1850

t(design.o) %%% design.o -> XpX
t(design.o) %%% y -> Xpy
chol(XpX) -> chol.o

b1 <- backsolve(chol.o,Xpy) # least squares solutions in two steps
b2 <- solve(XpX,Xpy) # least squares estimates in one step
b3 <- backsolve(chol.o, forwardsolve(chol.o, Xpy),
               twice = FALSE) # in three steps
## checking that these three are indeed equal :
stopifnot(all.equal(b1, b2), all.equal(b2, b3))
```

```
summary.mslm-class      Class "summary.mslm"
```

Description

Sparse version of summary.lm

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

print signature(x = "summary.mslm"): ...

summary.slm-class *Class "summary.slm"*

Description

Sparse version of summary.lm

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

print signature(x = "summary.slm"): ...

triogramX *A Design Matrix for a Triogram Problem*

Description

This is a design matrix arising from a bivariate smoothing problem using penalized triogram fitting. It is used in the SparseM vignette to illustrate the use of the sparse matrix image function.

Usage

```
data(triogramX)
```

Format

A 375 by 100 matrix stored in compressed sparse row format

References

Koenker, R and Ng, P. (2002). SparseM: A Sparse Matrix Package for R,
<http://www.econ.uiuc.edu/~roger/research/home.html>

Index

- !=, matrix.csr-method (SparseM.ops), 24
- * **IO**
 - SparseM.hb, 19
- * **algebra**
 - SparseM.image, 21
 - SparseM.ontology, 22
 - SparseM.ops, 24
 - SparseM.solve, 25
- * **classes**
 - character or NULL-class, 2
 - matrix.coo-class, 4
 - matrix.csc-class, 4
 - matrix.csc.hb-class, 5
 - matrix.csr-class, 6
 - matrix.csr.chol-class, 8
 - matrix.ssc-class, 9
 - matrix.ssc.hb-class, 10
 - matrix.ssr-class, 11
 - mssl-class, 12
 - numeric or NULL-class, 12
 - slm-class, 15
 - summary.mssl-class, 27
 - summary.slm-class, 28
- * **datasets**
 - lsq, 2
 - triogramX, 28
- * **hplot**
 - SparseM.image, 21
- * **regression**
 - slm, 13
 - slm.fit, 15
 - slm.methods, 17
- *, matrix.csr-method (SparseM.ops), 24
- +, matrix.csr-method (SparseM.ops), 24
- , matrix.csr-method (SparseM.ops), 24
- /, matrix.csr-method (SparseM.ops), 24
- <, matrix.csr-method (SparseM.ops), 24
- <=, matrix.csr-method (SparseM.ops), 24
- ==, matrix.csr-method (SparseM.ops), 24
- >, matrix.csr-method (SparseM.ops), 24
- >=, matrix.csr-method (SparseM.ops), 24
- [.matrix.coo (SparseM.ops), 24
- [.matrix.csr (SparseM.ops), 24
- [.matrix.diag.csr (SparseM.ops), 24
- [<- .matrix.coo (SparseM.ops), 24
- [<- .matrix.csr (SparseM.ops), 24
- [<- .matrix.diag.csr (SparseM.ops), 24
- %*, ANY, ANY-method (SparseM.ops), 24
- %*, matrix, matrix.csr-method (SparseM.ops), 24
- %*, matrix.csr, matrix-method (SparseM.ops), 24
- %*, matrix.csr, matrix.csr-method (SparseM.ops), 24
- %*, matrix.csr, numeric-method (SparseM.ops), 24
- %*, numeric, matrix.csr-method (SparseM.ops), 24
- %*-methods (SparseM.ops), 24
- %/, matrix.csr-method (SparseM.ops), 24
- %, matrix.csr-method (SparseM.ops), 24
- &, matrix.csr-method (SparseM.ops), 24
- ^, matrix.csr-method (SparseM.ops), 24
- as.matrix, ANY-method (SparseM.ontology), 22
- as.matrix, coo-methods (SparseM.ontology), 22
- as.matrix, csc-methods (SparseM.ontology), 22
- as.matrix, csr-method (SparseM.ontology), 22
- as.matrix, matrix.coo-method (SparseM.ontology), 22
- as.matrix, matrix.csc-method (SparseM.ontology), 22
- as.matrix, matrix.csr-method (SparseM.ontology), 22

- as.matrix,matrix.ssc-method
(SparseM.ontology), 22
- as.matrix,matrix.ssr-method
(SparseM.ontology), 22
- as.matrix,ssc-methods
(SparseM.ontology), 22
- as.matrix,ssr-methods
(SparseM.ontology), 22
- as.matrix.coo (SparseM.ontology), 22
- as.matrix.coo,ANY-method
(SparseM.ontology), 22
- as.matrix.coo,matrix.coo-method
(SparseM.ontology), 22
- as.matrix.coo,matrix.csc-method
(SparseM.ontology), 22
- as.matrix.coo,matrix.csr-method
(SparseM.ontology), 22
- as.matrix.coo,matrix.ssc-method
(SparseM.ontology), 22
- as.matrix.coo,matrix.ssr-method
(SparseM.ontology), 22
- as.matrix.csc (SparseM.ontology), 22
- as.matrix.csc,ANY-method
(SparseM.ontology), 22
- as.matrix.csc,matrix.coo-method
(SparseM.ontology), 22
- as.matrix.csc,matrix.csc-method
(SparseM.ontology), 22
- as.matrix.csc,matrix.csr-method
(SparseM.ontology), 22
- as.matrix.csc,matrix.ssc-method
(SparseM.ontology), 22
- as.matrix.csc,matrix.ssr-method
(SparseM.ontology), 22
- as.matrix.csr (SparseM.ontology), 22
- as.matrix.csr,ANY-method
(SparseM.ontology), 22
- as.matrix.csr,matrix.coo-method
(SparseM.ontology), 22
- as.matrix.csr,matrix.csc-method
(SparseM.ontology), 22
- as.matrix.csr,matrix.csr.chol-method
(SparseM.ontology), 22
- as.matrix.csr,matrix.ssc-method
(SparseM.ontology), 22
- as.matrix.csr,matrix.ssr-method
(SparseM.ontology), 22
- as.matrix.ssc (SparseM.ontology), 22
- as.matrix.ssc,ANY-method
(SparseM.ontology), 22
- as.matrix.ssc,matrix.coo-method
(SparseM.ontology), 22
- as.matrix.ssc,matrix.csc-method
(SparseM.ontology), 22
- as.matrix.ssc,matrix.csr-method
(SparseM.ontology), 22
- as.matrix.ssc,matrix.ssc-method
(SparseM.ontology), 22
- as.matrix.ssc,matrix.ssr-method
(SparseM.ontology), 22
- as.matrix.ssc,matrix.csr-method
(SparseM.ontology), 22
- as.matrix.ssr (SparseM.ontology), 22
- as.matrix.ssr,ANY-method
(SparseM.ontology), 22
- as.matrix.ssr,matrix.coo-method
(SparseM.ontology), 22
- as.matrix.ssr,matrix.csc-method
(SparseM.ontology), 22
- as.matrix.ssr,matrix.csr-method
(SparseM.ontology), 22
- as.matrix.ssr,matrix.ssc-method
(SparseM.ontology), 22
- as.matrix.ssr,matrix.ssr-method
(SparseM.ontology), 22
- backsolve, 8
- backsolve (SparseM.solve), 25
- backsolve,ANY-method (SparseM.solve), 25
- backsolve,matrix.csr.chol-method
(SparseM.solve), 25
- backsolve-methods (SparseM.solve), 25
- cbind.matrix.csr (SparseM.ops), 24
- character or NULL-class, 2
- chol, 8
- chol (SparseM.solve), 25
- chol,ANY-method (SparseM.solve), 25
- chol,matrix-method (SparseM.solve), 25
- chol,matrix.csc-method (SparseM.solve),
25
- chol,matrix.csr-method (SparseM.solve),
25
- coef.slm (slm.methods), 17
- coerce,matrix,matrix.csr-method
(SparseM.ontology), 22

- coerce,matrix.csr,matrix.diag.csr-method
(SparseM.ontology), 22
- coerce,numeric,matrix.diag.csr-method
(SparseM.ontology), 22
- coerce,vector,matrix.csr-method
(SparseM.ontology), 22
- coerce,vector,matrix.diag.csr-method
(SparseM.ontology), 22

- det,ANY-method (SparseM.ops), 24
- det,matrix-method (SparseM.ops), 24
- det,matrix.csr-method (SparseM.ops), 24
- det,matrix.csr.chol-method
(SparseM.ops), 24
- determinant, 24
- determinant,matrix.csr,logical-method
(SparseM.ops), 24
- determinant,matrix.csr,missing-method
(SparseM.ops), 24
- determinant,matrix.csr.chol,logical-method
(SparseM.ops), 24
- determinant,matrix.csr.chol,missing-method
(SparseM.ops), 24
- deviance.slm (slm.methods), 17
- diag,ANY-method (SparseM.ops), 24
- diag,matrix.csr-method (SparseM.ops), 24
- diag.assign,matrix.csr-method
(SparseM.ops), 24
- diag<- ,ANY-method (SparseM.ops), 24
- diag<- ,matrix.csr-method (SparseM.ops),
24
- diag<- ,matrix.diag.csr-method
(SparseM.ops), 24
- diff,matrix.csr-method (SparseM.ops), 24
- diff<- ,ANY-method (SparseM.ops), 24
- diff<- ,matrix.csr-method (SparseM.ops),
24
- dim,ANY-method (SparseM.ops), 24
- dim,matrix.coo-method (SparseM.ops), 24
- dim,matrix.csc-method (SparseM.ops), 24
- dim,matrix.csr-method (SparseM.ops), 24
- dim,matrix.ssc-method (SparseM.ops), 24
- dim,matrix.ssr-method (SparseM.ops), 24

- extractAIC.slm (slm.methods), 17

- fitted.slm (slm.methods), 17
- forwardsolve (SparseM.solve), 25

- image (SparseM.image), 21
- image,matrix.csr-method
(SparseM.image), 21
- initialize,ANY-method
(SparseM.ontology), 22
- initialize,matrix.coo-method
(SparseM.ontology), 22
- initialize,matrix.csr-method
(SparseM.ontology), 22
- is.matrix,coo-methods
(SparseM.ontology), 22
- is.matrix,csc-methods
(SparseM.ontology), 22
- is.matrix,csr-methods
(SparseM.ontology), 22
- is.matrix,ssc-methods
(SparseM.ontology), 22
- is.matrix,ssr-methods
(SparseM.ontology), 22
- is.matrix.coo (SparseM.ontology), 22
- is.matrix.csc (SparseM.ontology), 22
- is.matrix.csr (SparseM.ontology), 22
- is.matrix.ssc (SparseM.ontology), 22
- is.matrix.ssr (SparseM.ontology), 22

- kronecker,matrix,matrix.csr-method
(SparseM.ops), 24
- kronecker,matrix.csr,matrix-method
(SparseM.ops), 24
- kronecker,matrix.csr,matrix.csr-method
(SparseM.ops), 24
- kronecker,matrix.csr,numeric-method
(SparseM.ops), 24
- kronecker,numeric,matrix.csr-method
(SparseM.ops), 24
- kronecker-methods (SparseM.ops), 24

- lsq, 2

- matrix.coo-class, 4
- matrix.csc (SparseM.ontology), 22
- matrix.csc-class, 4
- matrix.csc.hb-class, 5
- matrix.csr (SparseM.ontology), 22
- matrix.csr-class, 6
- matrix.csr.chol-class, 8

- matrix.diag.csr-class
 - (matrix.csr-class), 6
- matrix.ssc (SparseM.ontology), 22
- matrix.ssc-class, 9
- matrix.ssc.hb-class, 10
- matrix.ssr (SparseM.ontology), 22
- matrix.ssr-class, 11
- model.guess (SparseM.hb), 19
- model.guess,matrix.csc.hb-method
 - (SparseM.hb), 19
- model.guess,matrix.ssc.hb-method
 - (SparseM.hb), 19
- model.matrix, 6, 10
- model.matrix (SparseM.hb), 19
- model.matrix,ANY-method (SparseM.hb), 19
- model.matrix,matrix.csc.hb-method
 - (SparseM.hb), 19
- model.matrix,matrix.ssc.hb-method
 - (SparseM.hb), 19
- model.matrix.matrix.ssc.hb
 - (SparseM.hb), 19
- model.response, 6, 10
- model.response (SparseM.hb), 19
- model.response,ANY-method (SparseM.hb), 19
- model.response,matrix.csc.hb-method
 - (SparseM.hb), 19
- model.response,matrix.ssc.hb-method
 - (SparseM.hb), 19
- model.xexact (SparseM.hb), 19
- model.xexact,matrix.csc.hb-method
 - (SparseM.hb), 19
- model.xexact,matrix.ssc.hb-method
 - (SparseM.hb), 19
- mslm-class, 12

- ncol,matrix.csr-method (SparseM.ops), 24
- norm (SparseM.ops), 24
- norm,ANY-method (SparseM.ops), 24
- norm,matrix.csr,character-method
 - (SparseM.ops), 24
- norm,matrix.csr,missing-method
 - (SparseM.ops), 24
- norm,matrix.csr-method (SparseM.ops), 24
- nrow,matrix.csr-method (SparseM.ops), 24
- numeric or NULL-class, 12

- Ops.matrix.csr (SparseM.ops), 24
- Ops.matrix.diag.csr (SparseM.ops), 24

- print.slm (slm.methods), 17
- print.summary.slm (slm.methods), 17

- rainbow, 21
- rbind.matrix.csr (SparseM.ops), 24
- read.matrix.hb, 6, 10
- read.matrix.hb (SparseM.hb), 19
- residuals.slm (slm.methods), 17

- slm, 12, 13, 15–17
- slm-class, 15
- slm.fit, 15
- slm.methods, 17
- slm.wfit (slm.fit), 15
- solve (SparseM.solve), 25
- solve,ANY-method (SparseM.solve), 25
- solve,matrix.csr-method
 - (SparseM.solve), 25
- SparseM.hb, 19
- SparseM.image, 21
- SparseM.ontology, 22
- SparseM.ops, 24
- SparseM.solve, 25
- summary.mslm (slm.methods), 17
- summary.mslm-class, 27
- summary.slm (slm.methods), 17
- summary.slm-class, 28

- t,ANY-method (SparseM.ops), 24
- t,matrix.coo-method (SparseM.ops), 24
- t,matrix.csc-method (SparseM.ops), 24
- t,matrix.csr-method (SparseM.ops), 24
- triogramX, 28

- X (triogramX), 28