

Package ‘foto’

January 18, 2019

Title Fourier Transform Textural Ordination

Version 1.0.0

Description The Fourier Transform Textural Ordination method uses a principal component analysis on radially averaged two dimensional Fourier spectra to characterize image texture.

URL <https://github.com/khufkens/foto>

BugReports <https://github.com/khufkens/foto/issues>

Depends R (>= 3.4)

Imports raster, stats, grDevices

License AGPL-3

LazyData true

ByteCompile true

RoxygenNote 6.1.1

Suggests rgdal, knitr, rmarkdown, covr, testthat

VignetteBuilder knitr

NeedsCompilation no

Author Koen Hufkens [aut, cre],
Jonathan V. Solorzano [aut]

Maintainer Koen Hufkens <koen.hufkens@gmail.com>

Repository CRAN

Date/Publication 2019-01-17 23:01:04 UTC

R topics documented:

foto	2
normalize	3
rspectrum	3

Index

4

foto	<i>Calculates FOTO classification of texture</i>
-------------	--

Description

Note that the input matrix should be square or results will be discarded

Usage

```
foto(x, window_size = 61, method = "zones", plot = FALSE,
      norm_spec = TRUE)
```

Arguments

x	an image file, raster layer, stack or brick for multilayered images (RGB or otherwise) data are averaged to a single layer raster
window_size	a moving window size in pixels (default = 61 pixels)
method	zones (for discrete zones) or mw for a moving window approach
plot	plot output, boolean TRUE or FALSE
norm_spec	normalize radial spectrum, boolean TRUE or FALSE

Value

returns a radial spectrum for a moving window across a raster layer

See Also

[rspectrum](#)

Examples

```
# load demo data
r <- raster::raster(system.file("extdata", "yangambi.png", package = "foto",
                                mustWork = TRUE))

# classify pixels using zones (discrete steps)
output <- foto(r,
                plot = TRUE,
                window_size = 25,
                method = "zones")

# print data structure
print(names(output))
```

normalize	<i>Normalize a matrix or vector</i>
-----------	-------------------------------------

Description

Normalize values between 0 and 1, internal function only.

Usage

```
normalize(x)
```

Arguments

x	a matrix or vector
---	--------------------

Value

returns a normalized matrix or vector

rspectrum	<i>Calculates a radial spectrum</i>
-----------	-------------------------------------

Description

This is an internal function and not to be used stand-alone.

Usage

```
rspectrum(x, w, n = TRUE, env, ...)
```

Arguments

x	a square matrix
w	a moving window size
n	normalize, boolean TRUE or FALSE
env	local environment to evaluate
...	additional parameters to forward

Value

Returns a radial spectrum values for the image used in order to classify texture using a PCA (or other) analysis.

Index

- *Topic **foto**,
 - foto, [2](#)
 - normalize, [3](#)
 - rspectrum, [3](#)
- *Topic **normalization**
 - normalize, [3](#)
- *Topic **radial**
 - foto, [2](#)
 - normalize, [3](#)
 - rspectrum, [3](#)
- *Topic **spectrum**,
 - normalize, [3](#)
- *Topic **spectrum**
 - foto, [2](#)
 - rspectrum, [3](#)
- foto, [2](#)
- normalize, [3](#)
- rspectrum, [2, 3](#)