Package 'iIneq'

January 20, 2021

Type Package
Title Computing Individual Components of the Gini and the Theil Indices
Version 1.0.2
Date 2021-01-11
Author Tim Liao
Maintainer Tim Liao <tfliao@illinois.edu></tfliao@illinois.edu>
Description Computes individual contributions to the overall Gini and Theil's T and Theil's L measures and their decompositions by groups such as race, gender, national origin, with the three functions of iGini(), iTheiT(), and iTheilL(). For details, see Tim F. Liao (2019) <doi:10.1177 0049124119875961="">.</doi:10.1177>
License GPL-2
Depends R (>= 3.6.0), foreach(>= 1.4.8), parallel, doParallel(>= 1.0.15)
Encoding UTF-8
LazyData true
RoxygenNote 7.0.2
NeedsCompilation no
Repository CRAN
Date/Publication 2021-01-20 19:50:02 UTC
R topics documented:
iGini
Index

2 iGini

iGini	Individual decomposition of the Gini Inde	2X
iGini	Individual decomposition of the Gini Ir	ıde

Description

The function computes individual components of the Gini index and their group-based decompositions. It takes as input an outcome variable, a grouping variable, and an optional sampling weight. It returns a data matrix of three columns containg individual contributions and their between- and within-group components. Because iGini is computational insensive, parallel processing is recommended, and the number of cores can be specified.

Usage

```
iGini(x, g, w=rep(1,length(x)),core=1)
```

Arguments

x	Input continuous variable such as income.
g	A grouping variable containing integers, such gender coded 1 & 2.
W	An optional sampling weight variable.
core	An optional input for specifying the number of processing cores in your computer. When specified, you will need to have the doParallel package and the foreach package installed for conducting parallel processing to speed up the computation.

Value

The function outputs three variables, g.i, g.ikb, and g.ikw.

g.i	This variable gives the individual contribtions to the overall Gini index.
g.ikb	This variable provides for each individual component of the Gini its between-group subcomponent.
g.ikw	This variable provides for each individual component of the Gini its withingroup subcomponent. The g.ikb and g.ikw sum up to g.i for each i observation.

References

Tim F. Liao. 2019. "Individual Components of Three Inequality Measures for Analyzing Shapes of Inequality." *Sociological Methods & Research* Advance online publication. doi:10.1177/0049124119875961

Examples

```
data(ChickWeight)
attach(ChickWeight)
iGini.result <- iGini(weight,Diet,core=1)</pre>
```

iTheilL 3

iTheilL

Individual decomposition of Theil's L Index

Description

The function computes individual components of Theil's L index (or Theil's second measure) and their group-based decompositions. It takes as input an outcome variable, a grouping variable, and an optional sampling weight. It returns a data matrix of three columns containg individual contributions and their between- and within-group components.

Usage

```
iTheilL(x, g, w=rep(1,length(x)))
```

Arguments

- x Input continuous variable such as income.
- g A grouping variable containing integers, such gender coded 1 & 2.
- w An optional sampling weight variable.

Value

The function outputs three variables, g.i, g.ikb, and g.ikw.

- g. i This variable gives the individual contribtions to the overall Gini index.
- g. ikb This variable provides for each individual component of the Gini its between
 - group subcomponent.
- g.ikw This variable provides for each individual component of the Gini its withingroup subcomponent. The g.ikb and g.ikw sum up to g.i for each i observation.

References

Tim F. Liao. 2019. "Individual Components of Three Inequality Measures for Analyzing Shapes of Inequality." *Sociological Methods & Research* Advance online publication. doi:10.1177/0049124119875961

Examples

```
data(ChickWeight)
attach(ChickWeight)
iTheilL.result <- iTheilL(weight,Diet)</pre>
```

4 iTheilT

	_			_	_
i	Т	h٤	ıد	- 1	Т

Individual decomposition of Theil's T Index

Description

The function computes individual components of Theil's T index (or Theil's first measure) and their group-based decompositions. It takes as input an outcome variable, a grouping variable, and an optional sampling weight. It returns a data matrix of three columns containg individual contributions and their between- and within-group components.

Usage

```
iTheilT(x, g, w=rep(1,length(x)))
```

Arguments

	T		1 .
Y	Input confu	niioiis variable	such as income.
^	input contin	iluous vuiluoie	buch as miconic.

g A grouping variable containing integers, such gender coded 1 & 2.

w An optional sampling weight variable.

Value

The function outputs three variables, g.i, g.ikb, and g.ikw.

g.i	This variable gives the individual contribtions to the overall Gini index.
g.ikb	This variable provides for each individual component of the Gini its between-group subcomponent.
g.ikw	This variable provides for each individual component of the Gini its within-group subcomponent. The g.ikb and g.ikw sum up to g.i for each i observation.

References

Tim F. Liao. 2019. "Individual Components of Three Inequality Measures for Analyzing Shapes of Inequality." *Sociological Methods & Research* Advance online publication. doi:10.1177/0049124119875961

Examples

```
data(ChickWeight)
attach(ChickWeight)
iTheilT.result <- iTheilT(weight,Diet)</pre>
```

Index

iGini, 2 iTheilL, 3 iTheilT, 4