

Package ‘mappoly’

July 6, 2022

Type Package

Title Genetic Linkage Maps in Autopolyploids

Version 0.3.1

Maintainer Marcelo Mollinari <mmollin@ncsu.edu>

Description Construction of genetic maps in autopolyploid full-sib populations.

Uses pairwise recombination fraction estimation as the first source of information to sequentially position allelic variants in specific homologues. For situations where pairwise analysis has limited power, the algorithm relies on the multilocus likelihood obtained through a hidden Markov model (HMM). For more detail, please see Mollinari and Garcia (2019) <[doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)> and Mollinari et al. (2020) <[doi:10.1534/g3.119.400620](https://doi.org/10.1534/g3.119.400620)>.

License GPL-3

LazyData TRUE

LazyDataCompression xz

Depends R (>= 4.0.0)

Imports Rcpp (>= 0.12.6), RcppParallel, RCurl, fields, ggpibr, ggsci, rstudioapi, scatterplot3d, dplyr, crayon, cli, magrittr, reshape2, ggplot2, printr, dendextend, vcfR, zoo, plotly

LinkingTo Rcpp, RcppParallel

RoxigenNote 7.2.0

SystemRequirements C++11, GNU make

Encoding UTF-8

Suggests smacof, testthat, updog, fitPoly, polymapR, AGHmatrix, gatepoints, knitr, rmarkdown

URL <https://github.com/mmollina/MAPpoly>

BugReports <https://github.com/mmollina/MAPpoly/issues>

VignetteBuilder knitr

NeedsCompilation yes

Author Marcelo Mollinari [aut, cre] (<<https://orcid.org/0000-0002-7001-8498>>),
 Gabriel Gesteira [aut] (<<https://orcid.org/0000-0002-4106-7346>>),
 Guilhereme Pereira [ctb] (<<https://orcid.org/0000-0002-7106-8630>>),
 Augusto Garcia [ctb] (<<https://orcid.org/0000-0003-0634-3277>>),
 Zhao-Bang Zeng [ctb] (<<https://orcid.org/0000-0002-3115-1149>>),
 Katharine Preedy [ctb, cph] (MDS ordering algorithm),
 Robert Gentleman [cph] (C code for MLE optimization in
 src/pairwise_estimation.cpp),
 Ross Ihaka [cph] (C code for MLE optimization in
 src/pairwise_estimation.cpp),
 R Foundation [cph] (C code for MLE optimization in
 src/pairwise_estimation.cpp),
 R-core [cph] (C code for MLE optimization in
 src/pairwise_estimation.cpp)

Repository CRAN

Date/Publication 2022-07-06 09:30:12 UTC

R topics documented:

add_marker	4
cache_counts_twopt	6
calc_genoprob	8
calc_genoprob_dist	9
calc_genoprob_error	10
calc_genoprob_one_parent	11
calc_homologprob	13
calc_prefpair_profiles	14
check_data_sanity	15
compare_maps	15
drop_marker	16
elim_redundant	17
est_full_hmm_with_global_error	18
est_full_hmm_with_prior_prob	20
est_pairwise_rf	22
est_pairwise_rf2	24
est_rf_hmm	25
est_rf_hmm_sequential	28
export_data_to_polymapR	31
export_map_list	32
export_qtlpoly	33
extract_map	34
filter_individuals	34
filter_missing	35
filter_segregation	36
get_genomic_order	37
get_submap	37
get_tab_mrks	39

group_mappoly	40
hexafake	41
hexafake.geno.dist	42
import_data_from_polymapR	43
import_from_updog	44
import_phased_maplist_from_polymapR	46
loglike_hmm	47
make_mat_mappoly	48
make_pairs_mappoly	49
make_seq_mappoly	50
maps.hexafake	52
mds_mappoly	52
merge_datasets	54
merge_maps	56
plot.mappoly.homoprob	58
plot.mappoly.prefpair.profiles	59
plot_genome_vs_map	60
plot_GIC	61
plot_map_list	61
plot_mrk_info	62
poly_cross_simulate	63
print_mrk	65
read_fitpoly	65
read_geno	67
read_geno_csv	70
read_geno_prob	72
read_vcf	75
reest_rf	77
rev_map	78
rf_list_to_matrix	79
rf.snp_filter	81
segreg_poly	82
sim_homologous	83
solcap.dose.map	85
solcap.err.map	85
solcap.mds.map	86
solcap.prior.map	86
split_and_rephase	87
summary_maps	88
tetra.solcap	89
tetra.solcap.geno.dist	90
update_map	91
update_missing	91

`add_marker`*Add a single marker to a map*

Description

Creates a new map by adding a marker in a given position in a pre-built map.

Usage

```
add_marker(
  input.map,
  mrk,
  pos,
  rf.matrix,
  genoprob = NULL,
  phase.config = "best",
  tol = 0.001,
  r.test = NULL,
  verbose = TRUE
)
```

Arguments

<code>input.map</code>	an object of class <code>mappoly.map</code>
<code>mrk</code>	the name of the marker to be inserted
<code>pos</code>	the name of the marker after which the new marker should be added. One also can inform the numeric position (between markers) were the new marker should be added. To insert a marker at the beginning of a map, use <code>pos = 0</code>
<code>rf.matrix</code>	an object of class <code>mappoly.rf.matrix</code> containing the recombination fractions and the number of homologues sharing alleles between pairwise markers on <code>input.map</code> . It is important that <code>shared.alleles = TRUE</code> in function <code>rf_list_to_matrix</code> when computing <code>rf.matrix</code> .
<code>genoprob</code>	an object of class <code>mappoly.genoprob</code> containing the genotype probabilities for all marker positions on <code>input.map</code>
<code>phase.config</code>	which phase configuration should be used. "best" (default) will choose the maximum likelihood configuration
<code>tol</code>	the desired accuracy (default = 10e-04)
<code>r.test</code>	for internal use only
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Details

`add_marker` splits the input map into two sub-maps to the left and the right of the given position. Using the genotype probabilities, it computes the log-likelihood of all possible linkage phases under a two-point threshold inherited from function `rf_list_to_matrix`.

Value

A list of class `mappoly.map` with two elements:

i) info: a list containing information about the map, regardless of the linkage phase configuration:

<code>ploidy</code>	the ploidy level
<code>n.mrk</code>	number of markers
<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>mrk.names</code>	the names of markers in the map
<code>seq.dose.p1</code>	a vector containing the dosage in parent 1 for all markers in the map
<code>seq.dose.p2</code>	a vector containing the dosage in parent 2 for all markers in the map
<code>chrom</code>	a vector indicating the sequence (usually chromosome) each marker belongs as informed in the input file. If not available, <code>chrom</code> = NULL
<code>genome.pos</code>	physical position (usually in megabase) of the markers into the sequence
<code>seq.ref</code>	reference base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = NULL
<code>seq.alt</code>	alternative base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = NULL
<code>chisq.pval</code>	a vector containing p-values of the chi-squared test of Mendelian segregation for all markers in the map
<code>data.name</code>	name of the dataset of class <code>mappoly.data</code>
<code>ph.thres</code>	the LOD threshold used to define the linkage phase configurations to test

ii) a list of maps with possible linkage phase configuration. Each map in the list is also a list containing

<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>seq.rf</code>	a vector of size (<code>n.mrk</code> - 1) containing a sequence of recombination fraction between the adjacent markers in the map
<code>seq.ph</code>	linkage phase configuration for all markers in both parents
<code>loglike</code>	the hmm-based multipoint likelihood

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

Examples

```
sub.map <- get_submap(maps.hexafake[[1]], 1:20, reestimate.rf = FALSE)
plot(sub.map, mrk.names = TRUE)
s <- make_seq_mappoly(hexafake, sub.map$info$mrk.names)
tpt <- est_pairwise_rf(s)
rf.matrix <- rf_list_to_matrix(input.twopt = tpt,
```

```

        thresh.LOD.ph = 3,
        thresh.LOD.rf = 3,
        shared.alleles = TRUE)
##### Removing marker "M_1" (first) #####
mrk.to.remove <- "M_1"
input.map <- drop_marker(sub.map, mrk.to.remove)
plot(input.map, mrk.names = TRUE)
## Computing conditional probabilities using the resulting map
genoprob <- calc_genoprob(input.map)
res.add.M_1 <- add_marker(input.map = input.map,
                           mrk = "M_1",
                           pos = 0,
                           rf.matrix = rf.matrix,
                           genoprob = genoprob,
                           tol = 10e-4)
plot(res.add.M_1, mrk.names = TRUE)
best.phase <- res.add.M_1$maps[[1]]$seq.ph
names.id <- names(best.phase$P)
plot_compare_haplotypes(ploidy = 6,
                        hom.allele.p1 = best.phase$P[names.id],
                        hom.allele.q1 = best.phase$Q[names.id],
                        hom.allele.p2 = sub.map$maps[[1]]$seq.ph$P[names.id],
                        hom.allele.q2 = sub.map$maps[[1]]$seq.ph$Q[names.id])

##### Removing marker "M_10" (middle or last) #####
mrk.to.remove <- "M_10"
input.map <- drop_marker(sub.map, mrk.to.remove)
plot(input.map, mrk.names = TRUE)
# Computing conditional probabilities using the resulting map
genoprob <- calc_genoprob(input.map)
res.add.M_10 <- add_marker(input.map = input.map,
                            mrk = "M_10",
                            pos = "M_9",
                            rf.matrix = rf.matrix,
                            genoprob = genoprob,
                            tol = 10e-4)
plot(res.add.M_10, mrk.names = TRUE)
best.phase <- res.add.M_10$maps[[1]]$seq.ph
names.id <- names(best.phase$P)
plot_compare_haplotypes(ploidy = 6,
                        hom.allele.p1 = best.phase$P[names.id],
                        hom.allele.q1 = best.phase$Q[names.id],
                        hom.allele.p2 = sub.map$maps[[1]]$seq.ph$P[names.id],
                        hom.allele.q2 = sub.map$maps[[1]]$seq.ph$Q[names.id])

```

Description

Returns the frequency of each genotype for two-point reduction of dimensionality. The frequency is calculated for all pairwise combinations and for all possible linkage phase configurations.

Usage

```
cache_counts_twopt(
  input.seq,
  cached = FALSE,
  cache.prev = NULL,
  ncpus = 1L,
  verbose = TRUE,
  joint.prob = FALSE
)
```

Arguments

<code>input.seq</code>	an object of class <code>mappoly.sequence</code>
<code>cached</code>	If TRUE, access the counts for all linkage phase configurations in a internal file (default = FALSE)
<code>cache.prev</code>	an object of class <code>cache.info</code> containing pre-computed genotype frequencies, obtained with <code>cache_counts_twopt</code> (optional, default = NULL)
<code>ncpus</code>	Number of parallel processes to spawn (default = 1)
<code>verbose</code>	If TRUE (default), print the linkage phase configurations. If <code>cached</code> = TRUE, nothing is printed, since all linkage phase configurations will be cached.
<code>joint.prob</code>	If FALSE (default), returns the frequency of genotypes for transition probabilities (conditional probabilities). If TRUE returns the frequency for joint probabilities. The latter is especially important to compute the Fisher's Information for a pair of markers.

Value

An object of class `cache.info` which contains one (conditional probabilities) or two (both conditional and joint probabilities) lists. Each list contains all pairs of dosages between parents for all markers in the sequence. The names in each list are of the form 'A-B-C-D', where: A represents the dosage in parent 1, marker k; B represents the dosage in parent 1, marker k+1; C represents the dosage in parent 2, marker k; and D represents the dosage in parent 2, marker k+1. For each list, the frequencies were computed for all possible linkage phase configurations. The frequencies for each linkage phase configuration are distributed in matrices whose names represents the number of homologous chromosomes that share alleles. The rows on these matrices represents the dosages in markers k and k+1 for an individual in the offspring. See Table 3 of S3 Appendix in Mollinari and Garcia (2019) for an example.

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu> with updates by Gabriel Gesteira, <gabrielgesteira@usp.br>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:10.1534/g3.119.400378

Examples

```
all.mrk <- make_seq_mappoly(tetra.solcap, 1:20)
## local computation
counts <- cache_counts_twopt(all.mrk, ncpus = 1)
## load from internal file or web-stored counts (especially important for high ploidy levels)
counts.cached <- cache_counts_twopt(all.mrk, cached = TRUE)
```

calc_genoprob

Compute conditional probabilities of the genotypes

Description

Conditional genotype probabilities are calculated for each marker position and each individual given a map.

Usage

```
calc_genoprob(input.map, step = 0, phase.config = "best", verbose = TRUE)
```

Arguments

<code>input.map</code>	An object of class <code>mappoly.map</code>
<code>step</code>	Maximum distance (in cM) between positions at which the genotype probabilities are calculated, though for <code>step = 0</code> , probabilities are calculated only at the marker locations.
<code>phase.config</code>	which phase configuration should be used. "best" (default) will choose the phase configuration associated with the maximum likelihood
<code>verbose</code>	if <code>TRUE</code> (default), current progress is shown; if <code>FALSE</code> , no output is produced

Value

An object of class 'mappoly.genoprob' which has two elements: a tridimensional array containing the probabilities of all possible genotypes for each individual in each marker position; and the marker sequence with its recombination frequencies

Author(s)

Marcelo Molinari, <mmolin@ncsu.edu>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *G3: Genes, Genomes, Genetics*. doi:10.1534/g3.119.400378

Examples

```
## tetraploid example
probs.t <- calc_genoprob(input.map = solcap.dose.map[[1]],
                           verbose = TRUE)
probs.t
## displaying individual 1, 36 genotypic states
## (rows) across linkage group 1 (columns)
image(t(probs.t$probs[, , 1]))
```

calc_genoprob_dist	<i>Compute conditional probabilities of the genotypes using probability distribution of dosages</i>
--------------------	---

Description

Conditional genotype probabilities are calculated for each marker position and each individual given a map. In this function, the probabilities are not calculated between markers.

Usage

```
calc_genoprob_dist(
  input.map,
  dat.prob = NULL,
  phase.config = "best",
  verbose = TRUE
)
```

Arguments

input.map	An object of class <code>mappoly.map</code>
dat.prob	an object of class <code>mappoly.data</code> containing the probability distribution of the genotypes
phase.config	which phase configuration should be used. "best" (default) will choose the phase configuration with the maximum likelihood
verbose	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Value

An object of class 'mappoly.genoprob' which has two elements: a tridimensional array containing the probabilities of all possible genotypes for each individual in each marker position; and the marker sequence with its recombination frequencies

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. doi:10.1534/g3.119.400378

Examples

```
## tetraploid example
probs.t <- calc_genoprob_dist(input.map = solcap.prior.map[[1]],
                                dat.prob = tetra.solcap.geno.dist,
                                verbose = TRUE)

probs.t
## displaying individual 1, 36 genotypic states
## (rows) across linkage group 1 (columns)
image(t(probs.t$probs[, , 1]))
```

calc_genoprob_error *Compute conditional probabilities of the genotypes using global error*

Description

Conditional genotype probabilities are calculated for each marker position and each individual given a map.

Usage

```
calc_genoprob_error(
  input.map,
  step = 0,
  phase.config = "best",
  error = 0.01,
  th.prob = 0.95,
  restricted = TRUE,
  verbose = TRUE
)
```

Arguments

<code>input.map</code>	An object of class <code>mappoly.map</code>
<code>step</code>	Maximum distance (in cM) between positions at which the genotype probabilities are calculated, though for <code>step = 0</code> , probabilities are calculated only at the marker locations.

phase.config	which phase configuration should be used. "best" (default) will choose the maximum likelihood configuration
error	the assumed global error rate (default = 0.01)
th.prob	the threshold for using global error or genotype probability distribution contained in the dataset (default = 0.95)
restricted	if TRUE (default), restricts the prior to the possible classes under Mendelian non double-reduced segregation given the parental dosages
verbose	if TRUE (default), current progress is shown; if FALSE, no output is produced

Value

An object of class 'mappoly.genoprob' which has two elements: a tridimensional array containing the probabilities of all possible genotypes for each individual in each marker position; and the marker sequence with it's recombination frequencies

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *G3: Genes, Genomes, Genetics*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
probs.error <- calc_genoprob_error(input.map = solcap.err.map[[1]],
                                     error = 0.05,
                                     verbose = TRUE)
```

calc_genoprob_one_parent

Compute conditional probabilities of the genotype (one informative parent)

Description

Conditional genotype probabilities are calculated for each marker position and each individual given a map

Usage

```
calc_genoprob_one_parent(  
    input.map,  
    step = 0,  
    info.parent = 1,  
    uninfo.parent = 2,  
    global.err = 0,  
    phase.config = "best",  
    verbose = TRUE  
)
```

Arguments

<code>input.map</code>	An object of class <code>mappoly.map</code> (with exceptions)
<code>step</code>	Maximum distance (in cM) between positions at which the genotype probabilities are calculated, though for <code>step = 0</code> , probabilities are calculated only at the marker locations.
<code>info.parent</code>	index for informative parent
<code>uninfo.parent</code>	index for uninformative parent
<code>global.err</code>	the assumed global error rate (default = 0.0)
<code>phase.config</code>	which phase configuration should be used. "best" (default) will choose the phase configuration associated with the maximum likelihood
<code>verbose</code>	if TRUE (default), current progress is shown; if FALSE, no output is produced

Value

An object of class 'mappoly.genoprob' which has two elements: a tridimensional array containing the probabilities of all possible genotypes for each individual in each marker position; and the marker sequence with its recombination frequencies

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *G3: Genes, Genomes, Genetics*. doi:10.1534/g3.119.400378

Examples

```

            uninfo.parent = 2,
            tol = 10e-4)
plot(map1)
probs <- calc_genoprob_one_parent(input.map = map1,
                                    info.parent = 1,
                                    uninfo.parent = 2,
                                    step = 1)
probs
## displaying individual 1, 6 genotypic states
## (rows) across linkage group 1 (columns)
image(t(probs$probs[, , 2]))

```

calc_homologprob *Homolog probabilities*

Description

Compute homolog probabilities for all individuals in the full-sib population given a map and conditional genotype probabilities.

Usage

```
calc_homologprob(input.genoprops, verbose = TRUE)
```

Arguments

input.genoprops	an object of class <code>mappoly.genoprop</code>
verbose	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari M., Olukolu B. A., Pereira G. da S., Khan A., Gemenet D., Yencho G. C., Zeng Z-B. (2020), Unraveling the Hexaploid Sweetpotato Inheritance Using Ultra-Dense Multilocus Mapping, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400620](https://doi.org/10.1534/g3.119.400620)

Examples

```

## tetraploid example
w1 <- calc_genoprob(solcap.dose.map[[1]])
h.prob <- calc_homologprob(w1)
print(h.prob)
plot(h.prob, ind = 5, use.plotly = FALSE)

```

```

## using error modeling (removing noise)
w2 <- calc_genoprob_error(solcap.err.map[[1]])
h.prob2 <- calc_homologprob(w2)
print(h.prob2)
plot(h.prob2, ind = 5, use.plotly = FALSE)

```

calc_prefpair_profiles*Preferential pairing profiles***Description**

Given the genotype conditional probabilities for a map, this function computes the probability profiles for all possible homolog pairing configurations in both parents.

Usage

```
calc_prefpair_profiles(input.genoprobs, verbose = TRUE)
```

Arguments

<code>input.genoprobs</code>	an object of class <code>mappoly.genoprob</code>
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu> and Guilherme Pereira, <g.pereira@cgiar.org>

References

Mollinari M., Olukolu B. A., Pereira G. da S., Khan A., Gemenet D., Yencho G. C., Zeng Z-B. (2020), Unraveling the Hexaploid Sweetpotato Inheritance Using Ultra-Dense Multilocus Mapping, *G3: Genes, Genomes, Genetics*. [doi:10.1534/g3.119.400620](https://doi.org/10.1534/g3.119.400620)

Examples

```

## tetraploid example
w1 <- lapply(solcap.dose.map[1:12], calc_genoprob)
x1 <- calc_prefpair_profiles(w1)
print(x1)
plot(x1)

```

check_data_sanity	<i>Data sanity check</i>
-------------------	--------------------------

Description

Checks the consistency of a dataset

Usage

```
check_data_sanity(x)
```

Arguments

x	an object of class <code>mappoly.data</code>
---	--

Value

if consistent, returns 0. If not consistent, returns a vector with a number of tests, where TRUE indicates a failed test.

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:10.1534/g3.119.400378

Examples

```
check_data_sanity(tetra.solcap)
```

compare_maps	<i>Compare a list of maps</i>
--------------	-------------------------------

Description

Compare lengths, density, maximum gaps and log likelihoods in a list of maps. In order to make the maps comparable, the function uses the intersection of markers among maps.

Usage

```
compare_maps(...)
```

Arguments

... a list of objects of class mappoly.map

Value

A data frame where the lines correspond to the maps in the order provided in input list list

drop_marker *Remove markers from a map*

Description

This function creates a new map by removing markers from an existing one.

Usage

```
drop_marker(input.map, mrk, verbose = TRUE)
```

Arguments

input.map	an object of class mappoly.map
mrk	a vector containing markers to be removed from the input map, identified by their names or positions
verbose	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Value

an object of class mappoly.map

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

Examples

```
sub.map <- get_submap(maps.hexafake[[1]], 1:50, reestimate.rf = FALSE)
plot(sub.map, mrk.names = TRUE)
mrk.to.remove <- c("M_1", "M_23", "M_34")
red.map <- drop_marker(sub.map, mrk.to.remove)
plot(red.map, mrk.names = TRUE)
```

elim_redundant	<i>Eliminate redundant markers</i>
----------------	------------------------------------

Description

Eliminate markers with identical dosage information for all individuals.

Usage

```
elim_redundant(input.seq, data = NULL)
```

Arguments

input.seq	an object of class <code>mappoly.sequence</code>
data	name of the dataset that contains sequence markers (optional, default = <code>NULL</code>)

Value

An object of class `mappoly.unique.seq` which is a list containing the following components:

unique.seq	an object of class <code>mappoly.sequence</code> with the redundant markers removed
kept	a vector containing the name of the informative markers
eliminated	a vector containing the name of the non-informative (eliminated) markers

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>, with minor modifications by Gabriel Gesteira, <gabrielgesteira@usp.br>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
all.mrk <- make_seq_mappoly(hexafake, 'all')
red.mrk <- elim_redundant(all.mrk)
plot(red.mrk)
unique.mrks <- make_seq_mappoly(red.mrk)
```

est_full_hmm_with_global_error*Re-estimate genetic map given a global genotyping error***Description**

This function considers a global error when re-estimating a genetic map using Hidden Markov models. Since this function uses the whole transition space in the HMM, its computation can take a while, especially for hexaploid maps.

Usage

```
est_full_hmm_with_global_error(
  input.map,
  error = NULL,
  tol = 0.001,
  restricted = TRUE,
  th.prob = 0.95,
  verbose = FALSE
)
```

Arguments

<code>input.map</code>	an object of class <code>mappoly.map</code>
<code>error</code>	the assumed global error rate (default = <code>NULL</code>)
<code>tol</code>	the desired accuracy (default = <code>10e-04</code>)
<code>restricted</code>	if <code>TRUE</code> (default), restricts the prior to the possible classes under Mendelian, non double-reduced segregation given dosage of the parents
<code>th.prob</code>	the threshold for using global error or genotype probability distribution if present in the dataset (default = <code>0.95</code>)
<code>verbose</code>	if <code>TRUE</code> , current progress is shown; if <code>FALSE</code> (default), no output is produced

Value

A list of class `mappoly.map` with two elements:

i) `info`: a list containing information about the map, regardless of the linkage phase configuration:

<code>ploidy</code>	the ploidy level
<code>n.mrk</code>	number of markers
<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>mrk.names</code>	the names of markers in the map
<code>seq.dose.p1</code>	a vector containing the dosage in parent 1 for all markers in the map
<code>seq.dose.p2</code>	a vector containing the dosage in parent 2 for all markers in the map

chrom	a vector indicating the sequence (usually chromosome) each marker belongs as informed in the input file. If not available, chrom = NULL
genome.pos	physical position (usually in megabase) of the markers into the sequence
seq.ref	reference base used for each marker (i.e. A, T, C, G). If not available, seq.ref = NULL
seq.alt	alternative base used for each marker (i.e. A, T, C, G). If not available, seq.ref = NULL
chisq.pval	a vector containing p-values of the chi-squared test of Mendelian segregation for all markers in the map
data.name	name of the dataset of class mappoly.data
ph.thres	the LOD threshold used to define the linkage phase configurations to test
ii)	a list of maps with possible linkage phase configuration. Each map in the list is also a list containing
seq.num	a vector containing the (ordered) indices of markers in the map, according to the input file
seq.rf	a vector of size (n.mrk - 1) containing a sequence of recombination fraction between the adjacent markers in the map
seq.ph	linkage phase configuration for all markers in both parents
loglike	the hmm-based multipoint likelihood

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. doi:[10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
submap <- get_submap(solcap.dose.map[[1]], mrk.pos = 1:20, verbose = FALSE)
err.submap <- est_full_hmm_with_global_error(submap,
                                              error = 0.01,
                                              tol = 10e-4,
                                              verbose = TRUE)

err.submap
plot_map_list(list(dose = submap, err = err.submap),
              title = "estimation procedure")
```

est_full_hmm_with_prior_prob*Re-estimate genetic map using dosage.priorprobability distribution***Description**

This function considers dosage.priordistribution when re-estimating a genetic map using Hidden Markov models

Usage

```
est_full_hmm_with_prior_prob(
  input.map,
  dat.prob = NULL,
  phase.config = "best",
  tol = 0.001,
  verbose = FALSE
)
```

Arguments

<code>input.map</code>	an object of class <code>mappoly.map</code>
<code>dat.prob</code>	an object of class <code>mappoly.data</code> containing the probability distribution of the genotypes
<code>phase.config</code>	which phase configuration should be used. "best" (default) will choose the maximum likelihood configuration
<code>tol</code>	the desired accuracy (default = 10e-04)
<code>verbose</code>	if TRUE, current progress is shown; if FALSE (default), no output is produced

Value

A list of class `mappoly.map` with two elements:

i) info: a list containing information about the map, regardless of the linkage phase configuration:

<code>ploidy</code>	the ploidy level
<code>n.mrk</code>	number of markers
<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>mrk.names</code>	the names of markers in the map
<code>seq.dose.p1</code>	a vector containing the dosage in parent 1 for all markers in the map
<code>seq.dose.p2</code>	a vector containing the dosage in parent 2 for all markers in the map
<code>chrom</code>	a vector indicating the sequence (usually chromosome) each marker belongs as informed in the input file. If not available, <code>chrom</code> = NULL
<code>genome.pos</code>	physical position (usually in megabase) of the markers into the sequence

seq.ref	reference base used for each marker (i.e. A, T, C, G). If not available, seq.ref = NULL
seq.alt	alternative base used for each marker (i.e. A, T, C, G). If not available, seq.ref = NULL
chisq.pval	a vector containing p-values of the chi-squared test of Mendelian segregation for all markers in the map
data.name	name of the dataset of class mappoly.data
ph.thres	the LOD threshold used to define the linkage phase configurations to test
ii)	a list of maps with possible linkage phase configuration. Each map in the list is also a list containing
seq.num	a vector containing the (ordered) indices of markers in the map, according to the input file
seq.rf	a vector of size (n.mrk - 1) containing a sequence of recombination fraction between the adjacent markers in the map
seq.ph	linkage phase configuration for all markers in both parents
loglike	the hmm-based multipoint likelihood

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. doi:10.1534/g3.119.400378

Examples

```
submap <- get_submap(solcap.dose.map[[1]], mrk.pos = 1:20, verbose = FALSE)
prob.submap <- est_full_hmm_with_prior_prob(submap,
                                              dat.prob = tetra.solcap.geno.dist,
                                              tol = 10e-4,
                                              verbose = TRUE)
prob.submap
plot_map_list(list(dose = submap, prob = prob.submap),
              title = "estimation procedure")
```

<i>est_pairwise_rf</i>	<i>Pairwise two-point analysis</i>
------------------------	------------------------------------

Description

Performs the two-point pairwise analysis between all markers in a sequence. For each pair, the function estimates the recombination fraction for all possible linkage phase configurations and associated LOD Scores.

Usage

```
est_pairwise_rf(
  input.seq,
  count.cache = NULL,
  count.matrix = NULL,
  ncpus = 1L,
  mrk.pairs = NULL,
  n.batches = 1L,
  est.type = c("disc", "prob"),
  verbose = TRUE,
  memory.warning = TRUE,
  parallelization.type = c("PSOCK", "FORK"),
  tol = .Machine$double.eps^0.25
)
```

Arguments

<code>input.seq</code>	an object of class <code>mappoly.sequence</code>
<code>count.cache</code>	an object of class <code>cache.info</code> containing pre-computed genotype frequencies, obtained with <code>cache_counts_twopt</code> . If <code>NULL</code> (default), genotype frequencies are internally loaded.
<code>count.matrix</code>	similar to <code>count.cache</code> , but in matrix format. Mostly for internal use.
<code>ncpus</code>	Number of parallel processes (cores) to spawn (default = 1)
<code>mrk.pairs</code>	a matrix of dimensions $2 \times N$, containing N pairs of markers to be analyzed. If <code>NULL</code> (default), all pairs are considered
<code>n.batches</code>	deprecated. Not available on MAPpoly 0.3.0 or higher
<code>est.type</code>	Indicates whether to use the discrete ("disc") or the probabilistic ("prob") dosage scoring when estimating the two-point recombination fractions.
<code>verbose</code>	If <code>TRUE</code> (default), current progress is shown; if <code>FALSE</code> , no output is produced
<code>memory.warning</code>	if <code>TRUE</code> , prints a memory warning if the number of markers is greater than 10000 for ploidy levels up to 4, and 3000 for ploidy levels > 4.
<code>parallelization.type</code>	one of the supported cluster types. This should be either <code>PSOCK</code> (default) or <code>FORK</code> .
<code>tol</code>	the desired accuracy. See <code>optimize()</code> for details

Value

An object of class `mappoly.twopt` which is a list containing the following components:

<code>data.name</code>	name of the object of class <code>mappoly.data</code> with the raw data
<code>n.mrk</code>	number of markers in the sequence
<code>seq.num</code>	a vector containing the (ordered) indices of markers in the sequence, according to the input file
<code>pairwise</code>	a list of size <code>choose(length(input.seq\$seq.num), 2)</code> , each of them containing a matrix where the name of the rows have the form x-y, where x and y indicate how many homologues share the same allelic variant in parents P and Q, respectively (see Mollinari and Garcia, 2019 for notation). The first column indicates the LOD Score in relation to the most likely linkage phase configuration. The second column shows the estimated recombination fraction for each configuration, and the third indicates the LOD Score comparing the likelihood under no linkage ($r = 0.5$) with the estimated recombination fraction (evidence of linkage).

`chisq.pval.threshold` used to perform the segregation tests `chisq.pval`p-values associated with the performed segregation tests

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
## Tetraploid example (first 50 markers)
all.mrk <- make_seq_mappoly(tetra.solcap, 1:50)
red.mrk <- elim_redundant(all.mrk)
unique.mrks <- make_seq_mappoly(red.mrk)
all.pairs <- est_pairwise_rf(input.seq = unique.mrks,
                               ncpus = 1,
                               verbose = TRUE)

all.pairs
plot(all.pairs, 20, 21)
mat <- rf_list_to_matrix(all.pairs)
plot(mat)
```

est_pairwise_rf2 *Pairwise two-point analysis - RcppParallel version*

Description

Performs the two-point pairwise analysis between all markers in a sequence. For each pair, the function estimates the recombination fraction for all possible linkage phase configurations and associated LOD Scores.

Usage

```
est_pairwise_rf2(
  input.seq,
  ncpus = 1L,
  mrk.pairs = NULL,
  verbose = TRUE,
  tol = .Machine$double.eps^0.25
)
```

Arguments

<code>input.seq</code>	an object of class <code>mappoly.sequence</code>
<code>ncpus</code>	Number of parallel processes (cores) to spawn (default = 1)
<code>mrk.pairs</code>	a matrix of dimensions $2 \times N$, containing N pairs of markers to be analyzed. If <code>NULL</code> (default), all pairs are considered
<code>verbose</code>	If <code>TRUE</code> (default), current progress is shown; if <code>FALSE</code> , no output is produced
<code>tol</code>	the desired accuracy. See <code>optimize()</code> for details

Details

Differently from `est_pairwise_rf` this function returns only the values associated to the best linkage phase configuration.

Value

An object of class `mappoly.twopt2`

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
## Tetraploid example
all.mrk <- make_seq_mappoly(tetra.solcap, 100:200)
all.pairs <- est_pairwise_rf2(input.seq = all.mrk, ncpus = 2)
m <- rf_list_to_matrix(all.pairs)
plot(m, fact = 2)
```

est_rf_hmm

Multipoint analysis using Hidden Markov Models in autoployploids

Description

Performs the multipoint analysis proposed by *Molinari and Garcia (2019)* in a sequence of markers

Usage

```
est_rf_hmm(
  input.seq,
  input.ph = NULL,
  thres = 0.5,
  twopt = NULL,
  verbose = FALSE,
  tol = 1e-04,
  est.given.0.rf = FALSE,
  reestimate.single.ph.configuration = TRUE,
  high.prec = TRUE
)

## S3 method for class 'mappoly.map'
print(x, detailed = FALSE, ...)

## S3 method for class 'mappoly.map'
plot(
  x,
  left.lim = 0,
  right.lim = Inf,
  phase = TRUE,
  mrk.names = FALSE,
  cex = 1,
  config = "best",
  P = "Parent 1",
  Q = "Parent 2",
  xlim = NULL,
  ...
)
```

Arguments

input.seq	an object of class <code>mappoly.sequence</code>
input.ph	an object of class <code>two pts linkage.phases</code> . If not available (default = NULL), it will be computed
thres	LOD Score threshold used to determine if the linkage phases compared via two-point analysis should be considered. Smaller values will result in smaller number of linkage phase configurations to be evaluated by the multipoint algorithm.
twopt	an object of class <code>mappoly.twopt</code> containing two-point information
verbose	if TRUE, current progress is shown; if FALSE (default), no output is produced
tol	the desired accuracy (default = 1e-04)
est.given.0.rf	logical. If TRUE returns a map forcing all recombination fractions equals to 0 (1e-5, for internal use only. Default = FALSE)
reestimate.single.ph.configuration	logical. If TRUE returns a map without re-estimating the map parameters for cases where there is only one possible linkage phase configuration. This argument is intended to be used in a sequential map construction
high.prec	logical. If TRUE (default) uses high precision long double numbers in the HMM procedure
x	an object of the class <code>mappoly.map</code>
detailed	logical. if TRUE, prints the linkage phase configuration and the marker position for all maps. If FALSE (default), prints a map summary
...	currently ignored
left.lim	the left limit of the plot (in cM, default = 0).
right.lim	the right limit of the plot (in cM, default = Inf, i.e., will print the entire map)
phase	logical. If TRUE (default) plots the phase configuration for both parents
mrk.names	if TRUE, marker names are displayed (default = FALSE)
cex	The magnification to be used for marker names
config	should be 'best' or the position of the configuration to be plotted. If 'best', plot the configuration with the highest likelihood
P	a string containing the name of parent P
Q	a string containing the name of parent Q
xlim	range of the x-axis. If xlim = NULL (default) it uses the map range.

Details

This function first enumerates a set of linkage phase configurations based on two-point recombination fraction information using a threshold provided by the user (argument `thresh`). After that, for each configuration, it reconstructs the genetic map using the HMM approach described in Mollinari and Garcia (2019). As result, it returns the multipoint likelihood for each configuration in form of LOD Score comparing each configuration to the most likely one. It is recommended to use a small number of markers (e.g. 50 markers for hexaploids) since the possible linkage phase combinations bounded only by the two-point information can be huge. Also, it can be quite sensible to small changes in '`thresh`'. For a large number of markers, please see [est_rf_hmm_sequential](#).

Value

A list of class `mappoly.map` with two elements:

i) info: a list containing information about the map, regardless of the linkage phase configuration:

<code>ploidy</code>	the ploidy level
<code>n.mrk</code>	number of markers
<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>mrk.names</code>	the names of markers in the map
<code>seq.dose.p1</code>	a vector containing the dosage in parent 1 for all markers in the map
<code>seq.dose.p2</code>	a vector containing the dosage in parent 2 for all markers in the map
<code>chrom</code>	a vector indicating the sequence (usually chromosome) each marker belongs as informed in the input file. If not available, <code>chrom</code> = NULL
<code>genome.pos</code>	physical position (usually in megabase) of the markers into the sequence
<code>seq.ref</code>	reference base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = NULL
<code>seq.alt</code>	alternative base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = NULL
<code>chisq.pval</code>	a vector containing p-values of the chi-squared test of Mendelian segregation for all markers in the map
<code>data.name</code>	name of the dataset of class <code>mappoly.data</code>
<code>ph.thres</code>	the LOD threshold used to define the linkage phase configurations to test

ii) a list of maps with possible linkage phase configuration. Each map in the list is also a list containing

<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>seq.rf</code>	a vector of size (<code>n.mrk</code> - 1) containing a sequence of recombination fraction between the adjacent markers in the map
<code>seq.ph</code>	linkage phase configuration for all markers in both parents
<code>loglike</code>	the hmm-based multipoint likelihood

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. <https://doi.org/10.1534/g3.119.400378>

Examples

```

mrk.subset <- make_seq_mappoly(hexafake, 1:10)
red.mrk <- elim_redundant(mrk.subset)
unique.mrks <- make_seq_mappoly(red.mrk)
subset.pairs <- est_pairwise_rf(input.seq = unique.mrks,
                                    ncpus = 1,
                                    verbose = TRUE)

## Estimating subset map with a low tolerance for the E.M. procedure
## for CRAN testing purposes
subset.map <- est_rf_hmm(input.seq = unique.mrks,
                           thres = 2,
                           twopt = subset.pairs,
                           verbose = TRUE,
                           tol = 0.1,
                           est.given.θ.rf = FALSE)

subset.map
## linkage phase configuration with highest likelihood
plot(subset.map, mrk.names = TRUE, config = "best")
## the second one
plot(subset.map, mrk.names = TRUE, config = 2)

```

est_rf_hmm_sequential *Multipoint analysis using Hidden Markov Models: Sequential phase elimination*

Description

Performs the multipoint analysis proposed by *Molinari and Garcia (2019)* in a sequence of markers removing unlikely phases using sequential multipoint information.

Usage

```

est_rf_hmm_sequential(
  input.seq,
  twopt,
  start.set = 4,
  thres.twopt = 5,
  thres.hmm = 50,
  extend.tail = NULL,
  phase.number.limit = 20,
  sub.map.size.diff.limit = Inf,
  info.tail = TRUE,
  reestimate.single.ph.configuration = FALSE,
  tol = 0.1,
  tol.final = 0.001,
  verbose = TRUE,

```

```

detailed.verbose = FALSE,
high.prec = FALSE
)

```

Arguments

input.seq	an object of class <code>mappoly.sequence</code>
twopt	an object of class <code>mappoly.twopt</code> containing the two-point information
start.set	number of markers to start the phasing procedure (default = 4)
thres.twopt	the LOD threshold used to determine if the linkage phases compared via two-point analysis should be considered for the search space reduction (A.K.A. η in <i>Molinari and Garcia (2019)</i> , default = 5)
thres.hmm	the LOD threshold used to determine if the linkage phases compared via hmm analysis should be evaluated in the next round of marker inclusion (default = 50)
extend.tail	the length of the chain's tail that should be used to calculate the likelihood of the map. If NULL (default), the function uses all markers positioned. Even if <code>info.tail</code> = TRUE, it uses at least <code>extend.tail</code> as the tail length
phase.number.limit	the maximum number of linkage phases of the sub-maps defined by arguments <code>info.tail</code> and <code>extend.tail</code> . Default is 20. If the size exceeds this limit, the marker will not be inserted. If Inf, then it will insert all markers.
sub.map.size.diff.limit	the maximum accepted length difference between the current and the previous sub-map defined by arguments <code>info.tail</code> and <code>extend.tail</code> . If the size exceeds this limit, the marker will not be inserted. If NULL (default), then it will insert all markers.
info.tail	if TRUE (default), it uses the complete informative tail of the chain (i.e. number of markers where all homologous (<i>ploidyx2</i>) can be distinguished) to calculate the map likelihood
reestimate.single.ph.configuration	logical. If FALSE (default) returns a map without re-estimating the map parameters in cases where there are only one possible linkage phase configuration
tol	the desired accuracy during the sequential phase (default = 10e-02)
tol.final	the desired accuracy for the final map (default = 10e-04)
verbose	If TRUE (default), current progress is shown; if FALSE, no output is produced
detailed.verbose	If TRUE, the expansion of the current submap is shown;
high.prec	logical. If TRUE uses high precision (long double) numbers in the HMM procedure implemented in C++, which can take a long time to perform (default = FALSE)

Details

This function sequentially includes markers into a map given an ordered sequence. It uses two-point information to eliminate unlikely linkage phase configurations given `thres.twopt`. The search is made within a window of size `extend.tail`. For the remaining configurations, the HMM-based likelihood is computed and the ones that pass the HMM threshold (`thres.hmm`) are eliminated.

Value

A list of class `mappoly.map` with two elements:

i) info: a list containing information about the map, regardless of the linkage phase configuration:

<code>ploidy</code>	the ploidy level
<code>n.mrk</code>	number of markers
<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>mrk.names</code>	the names of markers in the map
<code>seq.dose.p1</code>	a vector containing the dosage in parent 1 for all markers in the map
<code>seq.dose.p2</code>	a vector containing the dosage in parent 2 for all markers in the map
<code>chrom</code>	a vector indicating the sequence (usually chromosome) each marker belongs as informed in the input file. If not available, <code>chrom</code> = NULL
<code>genome.pos</code>	physical position (usually in megabase) of the markers into the sequence
<code>seq.ref</code>	reference base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = NULL
<code>seq.alt</code>	alternative base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = NULL
<code>chisq.pval</code>	a vector containing p-values of the chi-squared test of Mendelian segregation for all markers in the map
<code>data.name</code>	name of the dataset of class <code>mappoly.data</code>
<code>ph.thres</code>	the LOD threshold used to define the linkage phase configurations to test

ii) a list of maps with possible linkage phase configuration. Each map in the list is also a list containing

<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>seq.rf</code>	a vector of size (<code>n.mrk</code> - 1) containing a sequence of recombination fraction between the adjacent markers in the map
<code>seq.ph</code>	linkage phase configuration for all markers in both parents
<code>loglike</code>	the hmm-based multipoint likelihood

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```

mrk.subset <- make_seq_mappoly(hexafake, 1:20)
red.mrk <- elim_redundant(mrk.subset)
unique.mrks <- make_seq_mappoly(red.mrk)
subset.pairs <- est_pairwise_rf(input.seq = unique.mrks,
                                    ncpus = 1,
                                    verbose = TRUE)
subset.map <- est_rf_hmm_sequential(input.seq = unique.mrks,
                                       thres.twopt = 5,
                                       thres.hmm = 10,
                                       extend.tail = 10,
                                       tol = 0.1,
                                       tol.final = 10e-3,
                                       phase.number.limit = 5,
                                       twopt = subset.pairs,
                                       verbose = TRUE)
print(subset.map, detailed = TRUE)
plot(subset.map)
plot(subset.map, left.lim = 0, right.lim = 1, mrk.names = TRUE)
plot(subset.map, phase = FALSE)

## Retrieving simulated linkage phase
ph.P <- maps.hexafake[[1]]$maps[[1]]$seq.ph$P
ph.Q <- maps.hexafake[[1]]$maps[[1]]$seq.ph$Q
## Estimated linkage phase
ph.P.est <- subset.map$maps[[1]]$seq.ph$P
ph.Q.est <- subset.map$maps[[1]]$seq.ph$Q
compare_haplotypes(ploidy = 6, h1 = ph.P[names(ph.P.est)], h2 = ph.P.est)
compare_haplotypes(ploidy = 6, h1 = ph.Q[names(ph.Q.est)], h2 = ph.Q.est)

```

export_data_to_polymapR

Export data to polymapR

Description

See examples at https://rpubs.com/mmollin/tetra_mappoly_vignette.

Usage

```
export_data_to_polymapR(data.in)
```

Arguments

data.in	an object of class mappoly.data
---------	---------------------------------

Value

```
a dosage matrix
```

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

export_map_list

Export a genetic map to a CSV file

Description

Function to export genetic linkage map(s) generated by MAPpoly. The map(s) should be passed as a single object or a list of objects of class `mappoly.map`.

Usage

```
export_map_list(map.list, file = "map_output.csv")
```

Arguments

<code>map.list</code>	A list of objects or a single object of class <code>mappoly.map</code>
<code>file</code>	either a character string naming a file or a connection open for writing. "" indicates output to the console.

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:10.1534/g3.119.400378

Examples

```
export_map_list(solcap.err.map[[1]], file = "")
```

export_qtlpoly	<i>Export to QTLpoly</i>
----------------	--------------------------

Description

Compute homolog probabilities for all individuals in the full-sib population given a map and conditional genotype probabilities, and exports the results to be used for QTL mapping in the QTLpoly package.

Usage

```
export_qtlpoly(input.genoprobs, verbose = TRUE)
```

Arguments

input.genoprobs	an object of class mappoly.genoprob
verbose	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari M., Olukolu B. A., Pereira G. da S., Khan A., Gemenet D., Yencho G. C., Zeng Z-B. (2020), Unraveling the Hexaploid Sweetpotato Inheritance Using Ultra-Dense Multilocus Mapping, _G3: Genes, Genomes, Genetics_. [doi:10.1534/g3.119.400620](https://doi.org/10.1534/g3.119.400620)

Examples

```
## tetraploid example
w1 <- calc_genoprob(solcap.dose.map[[1]])
h.prob <- export_qtlpoly(w1)
```

extract_map*Extract the maker position from an object of class 'mappoly.map'***Description**

Extract the maker position from an object of class 'mappoly.map'

Usage

```
extract_map(input.map, phase.config = "best")
```

Arguments

- | | |
|---------------------------|---|
| <code>input.map</code> | An object of class <code>mappoly.map</code> |
| <code>phase.config</code> | which phase configuration should be used. "best" (default) will choose the maximum likelihood configuration |

Examples

```
x <- maps.hexasfake[[1]]$info$genome.pos/1e6
y <- extract_map(maps.hexasfake[[1]])
plot(y~x, ylab = "Map position (cM)", xlab = "Genome Position (Mbp)")
```

filter_individuals*Filter contaminant individuals***Description**

This function removes individuals from the data set. Individuals can be user-defined or can be accessed via interactive kinship analysis.

Usage

```
filter_individuals(
  input.data,
  ind.to.remove = NULL,
  inter = TRUE,
  verbose = TRUE
)
```

Arguments

- | | |
|----------------------------|--|
| <code>input.data</code> | name of input object (class <code>mappoly.data</code>) |
| <code>ind.to.remove</code> | individuals to be removed. If <code>NULL</code> it opens an interactive graphic to proceed with the individual selection |
| <code>inter</code> | if <code>TRUE</code> , expects user-input to proceed with filtering |
| <code>verbose</code> | if <code>TRUE</code> (default), shows the filtered out individuals |

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

filter_missing *Filter missing genotypes*

Description

Excludes markers or individuals based on their proportion of missing data

Usage

```
filter_missing(  
  input.data,  
  type = c("marker", "individual"),  
  filter.thres = 0.2,  
  inter = TRUE  
)
```

Arguments

input.data	an object of class <code>mappoly.data</code>
type	one of the following options: ' <code>marker</code> ' filter out markers based on their percentage of missing data (default) ' <code>individual</code> ' filter out individuals based on their percentage of missing data Please notice that removing individuals with certain amount of data can change some marker parameters (such as depth), and can also change the estimated genotypes for other individuals. So be careful when removing individuals.
filter.thres	maximum percentage of missing data (default = 0.2)
inter	if TRUE, expects user-input to proceed with filtering

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

Examples

filter_segregation *Filter markers based on chi-square test*

Description

This function filter markers based on p-values of a chi-square test. The chi-square test assumes that markers follow the expected segregation patterns under Mendelian inheritance, random chromosome bivalent pairing and no double reduction.

Usage

```
filter_segregation(input.data, chisq.pval.thres = 1e-04, inter = TRUE)
```

Arguments

input.data	name of input object (class <code>mappoly.data</code>)
chisq.pval.thres	p-value threshold used for chi-square tests (default = 10e-05)
inter	if TRUE (default), plots distorted vs. non-distorted markers

Value

An object of class `mappoly.chitest.seq` which contains a list with the following components:

keep	markers that follow Mendelian segregation pattern
exclude	markers with distorted segregation
chisq.pval.thres	threshold p-value used for chi-square tests
data.name	input dataset used to perform the chi-square tests

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

Examples

```
mrks.chifilt <- filter_segregation(input.data = tetra.solcap,
                                      chisq.pval.thres = 0.05/tetra.solcap$n.mrk,
                                      inter = TRUE)
seq.init <- make_seq_mappoly(mrks.chifilt)
```

<code>get_genomic_order</code>	<i>Get the genomic position of markers in a sequence</i>
--------------------------------	--

Description

This functions gets the genomic position of markers in a sequence and return an ordered data frame with the name and position of each marker

Usage

```
get_genomic_order(input.seq, verbose = TRUE)

## S3 method for class 'mappoly.geno.ord'
print(x, ...)

## S3 method for class 'mappoly.geno.ord'
plot(x, ...)
```

Arguments

input.seq	a sequence object of class <code>mappoly.sequence</code>
verbose	if TRUE (default), the current progress is shown; if FALSE, no output is produced
x	an object of the class <code>mappoly.geno.ord</code>
...	currently ignored

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

Examples

```
s1 <- make_seq_mappoly(tetra.solcap, "all")
o1 <- get_genomic_order(s1)
plot(o1)
s.geno.ord <- make_seq_mappoly(o1)
```

<code>get_submap</code>	<i>Extract sub-map from map</i>
-------------------------	---------------------------------

Description

Given a pre-constructed map, it extracts a sub-map for a provided sequence of marker positions. Optionally, it can update the linkage phase configurations and respective recombination fractions.

Usage

```
get_submap(
  input.map,
  mrk.pos,
  phase.config = "best",
  reestimate.rf = TRUE,
  reestimate.phase = FALSE,
  thres.twopt = 5,
  thres.hmm = 3,
  extend.tail = 50,
  tol = 0.1,
  tol.final = 0.001,
  use.high.precision = FALSE,
  verbose = TRUE
)
```

Arguments

<code>input.map</code>	An object of class <code>mappoly.map</code>
<code>mrk.pos</code>	positions of the markers that should be considered in the new map. This can be in any order
<code>phase.config</code>	which phase configuration should be used. "best" (default) will choose the configuration associated with the maximum likelihood
<code>reestimate.rf</code>	logical. If TRUE (default) the recombination fractions between markers are re-estimated
<code>reestimate.phase</code>	logical. If TRUE, the linkage phase configurations are re-estimated (default = FALSE)
<code>thres.twopt</code>	the LOD threshold used to determine if the linkage phases compared via two-point analysis should be considered (default = 5)
<code>thres.hmm</code>	the threshold used to determine if the linkage phases compared via hmm analysis should be considered (default = 3)
<code>extend.tail</code>	the length of the tail of the chain that should be used to calculate the likelihood of the linkage phases. If <code>info.tail</code> = TRUE, the function uses at least <code>extend.tail</code> as the length of the tail (default = 50)
<code>tol</code>	the desired accuracy during the sequential phase (default = 0.1)
<code>tol.final</code>	the desired accuracy for the final map (default = 10e-04)
<code>use.high.precision</code>	logical. If TRUE uses high precision (long double) numbers in the HMM procedure implemented in C++, which can take a long time to perform (default = FALSE)
<code>verbose</code>	If TRUE (default), current progress is shown; if FALSE, no output is produced

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:10.1534/g3.119.400378

Examples

```
## selecting the six first markers in linkage group 1
## re-estimating the recombination fractions and linkage phases
submap1.lg1 <- get_submap(input.map = maps.hexafake[[1]],
                           mrk.pos = 1:6, verbose = TRUE,
                           reestimate.phase = TRUE,
                           tol.final = 10e-3)
## no recombination fraction re-estimation: first 20 markers
submap2.lg1 <- get_submap(input.map = maps.hexafake[[1]],
                           mrk.pos = 1:20, reestimate.rf = FALSE,
                           verbose = TRUE,
                           tol.final = 10e-3)
plot(maps.hexafake[[1]])
plot(submap1.lg1, mrk.names = TRUE, cex = .8)
plot(submap2.lg1, mrk.names = TRUE, cex = .8)
```

get_tab_mrks

Get table of dosage combinations

Description

Internal function

Usage

get_tab_mrks(x)

Arguments

x an object of class mappoly.map

Author(s)

Gabriel Gesteira, <gabrielgesteira@usp.br>

group_mappoly	<i>Assign markers to linkage groups</i>
---------------	---

Description

Identifies linkage groups of markers using the results of two-point (pairwise) analysis.

Usage

```
group_mappoly(
  input.mat,
  expected.groups = NULL,
  inter = TRUE,
  comp.mat = FALSE,
  LODweight = FALSE,
  verbose = TRUE
)
```

Arguments

<code>input.mat</code>	an object of class <code>mappoly.rf.matrix</code>
<code>expected.groups</code>	when available, inform the number of expected linkage groups (i.e. chromosomes) for the species
<code>inter</code>	if TRUE (default), plots a dendrogram highlighting the expected groups before continue
<code>comp.mat</code>	if TRUE, shows a comparison between the reference based and the linkage based grouping, if the chromosome information is available (default = FALSE)
<code>LODweight</code>	if TRUE, clusterization is weighted by the square of the LOD Score
<code>verbose</code>	logical. If TRUE (default), current progress is shown; if FALSE, no output is produced

Value

Returns an object of class `mappoly.group`, which is a list containing the following components:

<code>data.name</code>	the referred dataset name
<code>hc.snp</code>	a list containing information related to the UPGMA grouping method
<code>expected.groups</code>	the number of expected linkage groups
<code>groups.snp</code>	the groups to which each of the markers belong
<code>seq.vs.grouped.snp</code>	comparison between the genomic group information (when available) and the groups provided by <code>group_mappoly</code>
<code>chisq.pval.thres</code>	the threshold used on the segregation test when reading the dataset
<code>chisq.pval</code>	the p-values associated with the segregation test for all markers in the sequence

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. doi:10.1534/g3.119.400378

Examples

```
## Getting first 20 markers from two linkage groups
all.mrk <- make_seq_mappoly(hexafake, c(1:20,601:620))
red.mrk <- elim_redundant(all.mrk)
unique.mrks <- make_seq_mappoly(red.mrk)
counts <- cache_counts_twopt(unique.mrks, cached = TRUE)
all.pairs <- est_pairwise_rf(input.seq = unique.mrks,
                               count.cache = counts,
                               ncpus = 1,
                               verbose = TRUE)

## Full recombination fraction matrix
mat.full <- rf_list_to_matrix(input.twopt = all.pairs)
plot(mat.full, index = FALSE)

lgs <- group_mappoly(input.mat = mat.full,
                      expected.groups = 2,
                      inter = TRUE,
                      comp.mat = TRUE, #this data has physical information
                      verbose = TRUE)
lgs
plot(lgs)
```

hexafake

Simulated autohexaploid dataset.

Description

A dataset of a hypothetical autohexaploid full-sib population containing three homology groups

Usage

hexafake

Format

An object of class `mappoly.data` which contains a list with the following components:

ploidy ploidy level = 6
n.ind number individuals = 300
n.mrk total number of markers = 1500
ind.names the names of the individuals
mrk.names the names of the markers
dosage.p1 a vector containing the dosage in parent P for all n.mrk markers
dosage.p2 a vector containing the dosage in parent Q for all n.mrk markers
chrom a vector indicating the chromosome each marker belongs. Zero indicates that the marker was not assigned to any chromosome
genome.pos Physical position of the markers into the sequence
geno.dose a matrix containing the dosage for each markers (rows) for each individual (columns).
 Missing data are represented by `ploidy_level + 1 = 7`
n.phen There are no phenotypes in this simulation
phen There are no phenotypes in this simulation
chisq.pval vector containing p-values for all markers associated to the chi-square test for the expected segregation patterns under Mendelian segregation

`hexafake.geno.dist` *Simulated autohexaploid dataset with genotype probabilities.*

Description

A dataset of a hypothetical autohexaploid full-sib population containing three homology groups. This dataset contains the probability distribution of the genotypes and 2% of missing data, but is essentially the same dataset found in `hexafake`

Usage

`hexafake.geno.dist`

Format

An object of class `mappoly.data` which contains a list with the following components:

ploidy ploidy level = 6
n.ind number individuals = 300
n.mrk total number of markers = 1500
ind.names the names of the individuals
mrk.names the names of the markers

dosage.p1 a vector containing the dosage in parent P for all n.mrk markers
dosage.p2 a vector containing the dosage in parent Q for all n.mrk markers
chrom a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
genome.pos Physical position of the markers into the sequence
prob.thres = 0.95 probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than 'prob.thres' are considered as missing data for the dosage calling purposes
geno a data.frame containing the probability distribution for each combination of marker and offspring. The first two columns represent the marker and the offspring, respectively. The remaining elements represent the probability associated to each one of the possible dosages
geno.dose a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by ploidy_level + 1 = 7
n.phen There are no phenotypes in this simulation
phen There are no phenotypes in this simulation

```
import_data_from_polymapR
Import data from polymapR
```

Description

Function to import datasets from polymapR.

Usage

```
import_data_from_polymapR(
  input.data,
  ploidy,
  parent1 = "P1",
  parent2 = "P2",
  input.type = c("discrete", "probabilistic"),
  prob.thres = 0.95,
  pardose = NULL,
  offspring = NULL,
  filter.non.conforming = TRUE,
  verbose = TRUE
)
```

Arguments

input.data	a polymapR dataset
ploidy	the ploidy level
parent1	a character string containing the name (or pattern of genotype IDs) of parent 1

<code>parent2</code>	a character string containing the name (or pattern of genotype IDs) of parent 2
<code>input.type</code>	Indicates whether the input is discrete ("disc") or probabilistic ("prob")
<code>prob.thres</code>	threshold probability to assign a dosage to offspring. If the probability is smaller than <code>thresh.parent.geno</code> , the data point is converted to 'NA'.
<code>pardose</code>	matrix of dimensions (n.mrk x 3) containing the name of the markers in the first column, and the dosage of parents 1 and 2 in columns 2 and 3. (see <code>polymapR vignette</code>)
<code>offspring</code>	a character string containing the name (or pattern of genotype IDs) of the offspring individuals. If NULL (default) it considers all individuals as offsprings, except <code>parent1</code> and <code>parent2</code> .
<code>filter.non.conforming</code>	if TRUE exclude samples with non expected genotypes under no double reduction. Since markers were already filtered in <code>polymapR</code> , the default is FALSE.
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Details

See examples at https://rpubs.com/mmollin/tetra_mappoly_vignette.

Author(s)

Marcelo Mollinari <mmollin@ncsu.edu>

References

Bourke PM et al: (2019) PolymapR — linkage analysis and genetic map construction from F1 populations of outcrossing polyploids. *_Bioinformatics_* 34:3496–3502. [doi:10.1093/bioinformatics/bty1002](https://doi.org/10.1093/bioinformatics/bty1002)

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Description

Read objects with information related to genotype calling in polyploids. Currently this function supports output objects created with the `updog` (output of `multidog` function) package. This function creates an object of class `mappoly.data`

Usage

```
import_from_updog(
  object,
  prob.thres = 0.95,
  filter.non.conforming = TRUE,
  verbose = TRUE
)
```

Arguments

<code>object</code>	the name of the object of class <code>multidog</code>
<code>prob.thres</code>	probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than 'prob.thres' are considered as missing data for the dosage calling purposes
<code>filter.non.conforming</code>	if TRUE (default) exclude samples with non expected genotypes under random chromosome pairing and no double reduction
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Value

An object of class `mappoly.data` which contains a list with the following components:

<code>ploidy</code>	ploidy level
<code>n.ind</code>	number individuals
<code>n.mrk</code>	total number of markers
<code>ind.names</code>	the names of the individuals
<code>mrk.names</code>	the names of the markers
<code>dosage.p1</code>	a vector containing the dosage in parent P for all <code>n.mrk</code> markers
<code>dosage.p2</code>	a vector containing the dosage in parent Q for all <code>n.mrk</code> markers
<code>chrom</code>	a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
<code>genome.pos</code>	physical position of the markers into the sequence
<code>prob.thres</code>	probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than 'prob.thres' were considered as missing data in the 'geno.dose' matrix
<code>geno.dose</code>	a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by <code>ploidy_level + 1</code>
<code>geno</code>	a <code>data.frame</code> containing the probability distribution for each combination of marker and offspring. The first two columns represent the marker and the offspring, respectively. The remaining elements represent the probability associated to each one of the possible dosages. Missing data are converted from NA to the expected segregation ratio using function <code>segreg_poly</code>
<code>n.phen</code>	number of phenotypic traits

phen	a matrix containing the phenotypic data. The rows correspond to the traits and the columns correspond to the individuals
chisq.pval	a vector containing p-values related to the chi-squared test of Mendelian segregation performed for all markers

Author(s)

Gabriel Gesteira, <gabrielgesteira@usp.br>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. doi:[10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
if(requireNamespace("updog", quietly = TRUE)){
  library("updog")
  data("uitdewilligen")
  mout = multidog(refmat = t(uitdewilligen$refmat),
                  sizemat = t(uitdewilligen$sizemat),
                  ploidy = uitdewilligen$ploidy,
                  model = "f1",
                  p1_id = colnames(t(uitdewilligen$sizemat))[1],
                  p2_id = colnames(t(uitdewilligen$sizemat))[2],
                  nc = 2)
  mydata = import_from_updog(mout)
  mydata
  plot(mydata)
}
```

import_phased_maplist_from_polymapR
Import phased map list from polymapR

Description

Function to import phased map lists from polymapR

Usage

```
import_phased_maplist_from_polymapR(maplist, mappoly.data, ploidy = NULL)
```

Arguments

maplist	a list of phased maps obtained using function <code>create_phased_maplist</code> from package <code>polymapR</code>
mappoly.data	a dataset used to obtain <code>maplist</code> , converted into class <code>mappoly.data</code>
ploidy	the ploidy level

Details

See examples at https://rpubs.com/mmollin/tetra_mappoly_vignette.

Author(s)

Marcelo Mollinari <mmollin@ncsu.edu>

References

Bourke PM et al: (2019) PolymapR — linkage analysis and genetic map construction from F1 populations of outcrossing polyploids. *_Bioinformatics_* 34:3496–3502. doi:[10.1093/bioinformatics/bty1002](https://doi.org/10.1093/bioinformatics/bty1002)

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:[10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

loglike_hmm

Multipoint log-likelihood computation

Description

Update the multipoint log-likelihood of a given map using the method proposed by *Mollinari and Garcia (2019)*.

Usage

```
loglike_hmm(input.map, input.data = NULL, verbose = FALSE)
```

Arguments

input.map	An object of class <code>mappoly.map</code>
input.data	An object of class <code>mappoly.data</code> , which was used to generate <code>input.map</code>
verbose	If TRUE, map information is shown; if FALSE(default), no output is produced

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
hexa.map <- loglike_hmm(maps.hexafake[[1]])
hexa.map
```

make_mat_mappoly *Subset recombination fraction matrices*

Description

Get a subset of an object of class `mappoly.rf.matrix`, i.e. recombination fraction and LOD score matrices based in a sequence of markers.

Usage

```
make_mat_mappoly(input.mat, input.seq)
```

Arguments

- | | |
|------------------------|---|
| <code>input.mat</code> | an object of class <code>mappoly.rf.matrix</code> |
| <code>input.seq</code> | an object of class <code>mappoly.sequence</code> , with a sequence of markers contained in <code>input.mat</code> |

Value

an object of class `mappoly.rf.matrix`, which is a subset of '`input.mat`'. See `rf_list_to_matrix` for details

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
# sequence with 20 markers
mrk.seq <- make_seq_mappoly(hexafake, 1:20)
mrk.pairs <- est_pairwise_rf(input.seq = mrk.seq,
                               verbose = TRUE)
## Full recombination fraction matrix
mat <- rf_list_to_matrix(input.twopt = mrk.pairs)
plot(mat)
## Matrix subset
id <- make_seq_mappoly(hexafake, 1:10)
mat.sub <- make_mat_mappoly(mat, id)
plot(mat.sub)
```

make_pairs_mappoly *Subset pairwise recombination fractions*

Description

Get a subset of an object of class `mappoly.twopt` or `mappoly.twopt2` (i.e. recombination fraction) and LOD score statistics for all possible linkage phase combinations based on a sequence of markers.

Usage

```
make_pairs_mappoly(input.twopt, input.seq)
```

Arguments

- `input.twopt` an object of class `mappoly.twopt`
- `input.seq` an object of class `mappoly.sequence`, with a sequence of markers contained in `input.twopt`

Value

an object of class `mappoly.twopt` which is a subset of `input.twopt`. See `est_pairwise_rf` for details

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

- Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
## selecting some markers along the genome
some.mrk <- make_seq_mappoly(hexafake, seq(1, 1500, 30))
all.pairs <- est_pairwise_rf(input.seq = some.mrk)
mat.full <- rf_list_to_matrix(input.twopt = all.pairs)
plot(mat.full)

## selecting two-point information for chromosome 1
mrks.1 <- make_seq_mappoly(hexafake, names(which(some.mrk$chrom == 1)))
p1 <- make_pairs_mappoly(input.seq = mrks.1, input.twopt = all.pairs)
m1 <- rf_list_to_matrix(input.twopt = p1)
plot(m1, main.text = "LG1")
```

make_seq_mappoly *Create a sequence of markers*

Description

Makes a sequence of markers based on an object of another class.

Usage

```
make_seq_mappoly(input.obj, arg = NULL, data.name = NULL, genomic.info = NULL)

## S3 method for class 'mappoly.sequence'
print(x, ...)

## S3 method for class 'mappoly.sequence'
plot(x, ...)
```

Arguments

<code>input.obj</code>	an object of one of the following classes: <code>mappoly.data</code> , <code>mappoly.map</code> , <code>mappoly.group</code> , <code>mappoly.unique.seq</code> , <code>mappoly.pcmap</code> , <code>mappoly.pcmap3d</code> , or <code>mappoly.geno.ord</code>
<code>arg</code>	can be one of the following objects: i) a string 'all', resulting in a sequence with all markers in the raw data; ii) a string or a vector of strings 'seqx', where x is the sequence (x = 0 indicates unassigned markers); iii) a vector of integers specifying which markers comprise the sequence; iv) an integer representing linkage group if <code>input.object</code> has class <code>mappoly.group</code> ; or v) <code>NULL</code> if <code>input.object</code> has class <code>mappoly.pcmap</code> , <code>mappoly.pcmap3d</code> , <code>mappoly.unique.seq</code> , or <code>mappoly.geno.ord</code>
<code>data.name</code>	name of the object of class <code>mappoly.data</code>
<code>genomic.info</code>	optional argument applied for <code>mappoly.group</code> objects only. This argument can be <code>NULL</code> , or can hold the numeric combination of sequences from genomic information to be used when making the sequences. When <code>genomic.info = NULL</code> (default), the function returns a sequence containing all markers defined

by the grouping function. When `genomic.info = 1`, the function returns a sequence with markers that matched the intersection between grouping function and genomic information, considering the sequence from genomic information that holds the maximum number of markers matching the group; when `genomic.info = c(1, 2)`, the function returns a sequence with markers that matched the intersection between grouping function and genomic information, considering two sequences from genomic information that presented the maximum number of markers matching the group; and so on.

- x an object of the class `mappoly.sequence`
- ... currently ignored

Value

An object of class `mappoly.sequence`, which is a list containing the following components:

<code>seq.num</code>	a vector containing the (ordered) indices of markers in the sequence, according to the input file
<code>seq.phases</code>	a list with the linkage phases between markers in the sequence, in corresponding positions. -1 means that there are no defined linkage phases
<code>seq.rf</code>	a vector with the recombination frequencies between markers in the sequence. -1 means that there are no estimated recombination frequencies
<code>loglike</code>	log-likelihood of the corresponding linkage map
<code>data.name</code>	name of the object of class <code>mappoly.data</code> with the raw data
<code>twopt</code>	name of the object of class <code>mappoly.twopt</code> with the 2-point analyses. -1 means that the twopt estimates were not computed

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>, with modifications by Gabriel Gesteira, <gabrielgesteira@usp.br>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
all.mrk <- make_seq_mappoly(hexafake, 'all')
seq1.mrk <- make_seq_mappoly(hexafake, 'seq1')
plot(seq1.mrk)
some.mrk.pos <- c(1,4,28,32,45)
(some.mrk.1 <- make_seq_mappoly(hexafake, some.mrk.pos))
plot(some.mrk.1)
```

maps.hexafake	<i>Resulting maps from hexafake</i>
---------------	-------------------------------------

Description

A list containing three linkage groups estimated using the procedure available in [MAPpoly's tutorial](https://mmollina.github.io/MAPpoly/#estimating_the_map_for_a_given_order)

Usage

```
maps.hexafake
```

Format

A list containing three objects of class `mappoly.map`, each one representing one linkage group in the simulated data.

mds_mappoly	<i>Estimates loci position using Multidimensional Scaling</i>
-------------	---

Description

Estimates loci position using Multidimensional Scaling proposed by *Preedy and Hackett (2016)*. The code is an adaptation from the package `MDSmap`, available under GNU GENERAL PUBLIC LICENSE, Version 3, at <https://CRAN.R-project.org/package=MDSMap>

Usage

```
mds_mappoly(
  input.mat,
  p = NULL,
  n = NULL,
  ndim = 2,
  weight.exponent = 2,
  verbose = TRUE
)

## S3 method for class 'mappoly.pcmap'
print(x, ...)

## S3 method for class 'mappoly.pcmap3d'
print(x, ...)
```

Arguments

<code>input.mat</code>	an object of class <code>mappoly.input.matrix</code>
<code>p</code>	integer. The smoothing parameter for the principal curve. If NULL (default) this will be done using the leave-one-out cross validation
<code>n</code>	vector of integers or strings containing loci to be omitted from the analysis
<code>ndim</code>	number of dimensions to be considered in the multidimensional scaling procedure (default = 2)
<code>weight.exponent</code>	the exponent that should be used in the LOD score values to weight the MDS procedure (default = 2)
<code>verbose</code>	if TRUE (default), display information about the analysis
<code>x</code>	an object of class <code>mappoly.mds</code>
<code>...</code>	currently ignored

Value

A list containing:

<code>M</code>	the input distance map
<code>sm</code>	the unconstrained MDS results
<code>pc</code>	the principal curve results
<code>distmap</code>	a matrix of pairwise distances between loci where the columns are in the estimated order
<code>locimap</code>	a data frame of the loci containing the name and position of each locus in order of increasing distance
<code>length</code>	integer giving the total length of the segment
<code>removed</code>	a vector of the names of loci removed from the analysis
<code>scale</code>	the scaling factor from the MDS
<code>locikey</code>	a data frame showing the number associated with each locus name for interpreting the MDS configuration plot
<code>confplotno</code>	a data frame showing locus name associated with each number on the MDS configuration plots

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu> mostly adapted from MDSmap codes, written by Katharine F. Preedy, <katharine.preedy@bioss.ac.uk>

References

Preedy, K. F., & Hackett, C. A. (2016). A rapid marker ordering approach for high-density genetic linkage maps in experimental autotetraploid populations using multidimensional scaling. *Theoretical and Applied Genetics*, 129(11), 2117-2132. doi:10.1007/s0012201627618

Examples

```
if(requireNamespace("smacof", quietly = TRUE)){
  library("smacof")
  s1 <- make_seq_mappoly(hexafake, 1:20)
  t1 <- est_pairwise_rf(s1, ncpus = 1)
  m1 <- rf_list_to_matrix(t1)
  o1 <- get_genomic_order(s1)
  s.go <- make_seq_mappoly(o1)
  plot(m1, ord = s.go$seq.mrk.names)
  mds.ord <- mds_mappoly(m1)
  plot(mds.ord)
  so <- make_seq_mappoly(mds.ord)
  plot(m1, ord = so$seq.mrk.names)
  plot(so$seq.num ~ I(so$genome.pos/1e6),
       xlab = "Genome Position",
       ylab = "MDS position")
}
```

merge_datasets

Merge datasets

Description

This function merges two datasets of class `mappoly.data`. This can be useful when individuals of a population were genotyped using two or more techniques and have datasets in different files or formats. Please notice that the datasets should contain the same number of individuals and they must be represented identically in both datasets (e.g. `Ind_1` in both datasets, not `Ind_1` in one dataset and `ind_1` or `Ind.1` in the other).

Usage

```
merge_datasets(dat.1 = NULL, dat.2 = NULL)
```

Arguments

- `dat.1` the first dataset of class `mappoly.data` to be merged
- `dat.2` the second dataset of class `mappoly.data` to be merged (default = `NULL`); if `dat.2 = NULL`, the function returns `dat.1` only

Value

An object of class `mappoly.data` which contains all markers from both datasets. It will be a list with the following components:

- `ploidy` ploidy level

n.ind	number individuals
n.mrk	total number of markers
ind.names	the names of the individuals
mrk.names	the names of the markers
dosage.p1	a vector containing the dosage in parent P for all n.mrk markers
dosage.p2	a vector containing the dosage in parent Q for all n.mrk markers
chrom	a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
genome.pos	Physical position of the markers into the sequence
seq.ref	if one or both datasets originated from read_vcf, it keeps reference alleles from sequencing platform, otherwise is NULL
seq.alt	if one or both datasets originated from read_vcf, it keeps alternative alleles from sequencing platform, otherwise is NULL
all.mrk.depth	if one or both datasets originated from read_vcf, it keeps marker read depths from sequencing, otherwise is NULL
prob.thres	(unused field)
geno.dose	a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by ploidy_level + 1
geno	if both datasets contain genotype distribution information, the final object will contain 'geno'. This is set to NULL otherwise
nphen	(0)
phen	(NULL)
chisq.pval	a vector containing p-values related to the chi-squared test of Mendelian segregation performed for all markers in both datasets
kept	if elim.redundant = TRUE when reading any dataset, holds all non-redundant markers
elim.correspondence	if elim.redundant = TRUE when reading any dataset, holds all non-redundant markers and its equivalence to the redundant ones

Author(s)

Gabriel Gesteira, <gabrielgesteira@usp.br>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```

## Loading a subset of SNPs from chromosomes 3 and 12 of sweetpotato dataset
## (SNPs anchored to Ipomoea trifida genome)
dat <- NULL
for(i in c(3, 12)){
  cat("Loading chromosome", i, "...\\n")
  tempfl <- tempfile(pattern = paste0("ch", i), fileext = ".vcf.gz")
  x <- "https://github.com/mmollina/MAopoly_vignettes/raw/master/data/sweet_sample_ch"
  address <- paste0(x, i, ".vcf.gz")
  download.file(url = address, destfile = tempfl)
  dattemp <- read_vcf(file = tempfl, parent.1 = "PARENT1", parent.2 = "PARENT2",
                       ploidy = 6, verbose = FALSE)
  dat <- merge_datasets(dat, dattemp)
  cat("\\n")
}
dat
plot(dat)

```

merge_maps

Merge two maps

Description

Estimates the linkage phase and recombination fraction between pre-built maps and creates a new map by merging them.

Usage

```

merge_maps(
  map.list,
  twopt,
  thres.twopt = 10,
  genoprob.list = NULL,
  thres.hmm = "best",
  tol = 1e-04
)

```

Arguments

- | | |
|--------------------------|---|
| <code>map.list</code> | a list of objects of class <code>mappoly.map</code> to be merged. |
| <code>twopt</code> | an object of class <code>mappoly.twopt</code> containing the two-point information for all pairs of markers present in the original maps |
| <code>thres.twopt</code> | the threshold used to determine if the linkage phases compared via two-point analysis should be considered for the search space reduction (default = 3) |

<code>genoprob.list</code>	a list of objects of class <code>mappoly.genoprob</code> containing the genotype probabilities for the maps to be merged. If <code>NULL</code> (default), the probabilities are computed.
<code>thres.hmm</code>	the threshold used to determine which linkage phase configurations should be returned when merging two maps. If "best" (default), returns only the best linkage phase configuration. NOTE: if merging multiple maps, it always uses the "best" linkage phase configuration at each block insertion.
<code>tol</code>	the desired accuracy (default = <code>10e-04</code>)

Details

`merge_maps` uses two-point information, under a given LOD threshold, to reduce the linkage phase search space. The remaining linkage phases are tested using the genotype probabilities.

Value

A list of class `mappoly.map` with two elements:

- i) info: a list containing information about the map, regardless of the linkage phase configuration:

<code>ploidy</code>	the ploidy level
<code>n.mrk</code>	number of markers
<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>mrk.names</code>	the names of markers in the map
<code>seq.dose.p1</code>	a vector containing the dosage in parent 1 for all markers in the map
<code>seq.dose.p2</code>	a vector containing the dosage in parent 2 for all markers in the map
<code>chrom</code>	a vector indicating the sequence (usually chromosome) each marker belongs as informed in the input file. If not available, <code>chrom</code> = <code>NULL</code>
<code>genome.pos</code>	physical position (usually in megabase) of the markers into the sequence
<code>seq.ref</code>	reference base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = <code>NULL</code>
<code>seq.alt</code>	alternative base used for each marker (i.e. A, T, C, G). If not available, <code>seq.ref</code> = <code>NULL</code>
<code>chisq.pval</code>	a vector containing p-values of the chi-squared test of Mendelian segregation for all markers in the map
<code>data.name</code>	name of the dataset of class <code>mappoly.data</code>
<code>ph.thres</code>	the LOD threshold used to define the linkage phase configurations to test

- ii) a list of maps with possible linkage phase configuration. Each map in the list is also a list containing

<code>seq.num</code>	a vector containing the (ordered) indices of markers in the map, according to the input file
<code>seq.rf</code>	a vector of size (<code>n.mrk</code> - 1) containing a sequence of recombination fraction between the adjacent markers in the map
<code>seq.ph</code>	linkage phase configuration for all markers in both parents
<code>loglike</code>	the hmm-based multipoint likelihood

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

Examples

```
#### Tetraploid example #####
map1 <- get_submap(solcap.dose.map[[1]], 1:5)
map2 <- get_submap(solcap.dose.map[[1]], 6:15)
map3 <- get_submap(solcap.dose.map[[1]], 16:30)
full.map <- get_submap(solcap.dose.map[[1]], 1:30)
s <- make_seq_mappoly(tetra.solcap, full.map$maps[[1]]$seq.num)
twopt <- est_pairwise_rf(input.seq = s)
merged.maps <- merge_maps(map.list = list(map1, map2, map3),
                           twopt = twopt,
                           thres.twopt = 3)
plot(merged.maps, mrk.names = TRUE)
plot(full.map, mrk.names = TRUE)
best.phase <- merged.maps$maps[[1]]$seq.ph
names.id <- names(best.phase$P)
compare_haplotypes(ploidy = 4, best.phase$P[names.id],
                    full.map$maps[[1]]$seq.ph$P[names.id])
compare_haplotypes(ploidy = 4, best.phase$Q[names.id],
                    full.map$maps[[1]]$seq.ph$Q[names.id])
```

plot.mappoly.homoprob *Plots mappoly.homoprob*

Description

Plots mappoly.homoprob

Usage

```
## S3 method for class 'mappoly.homoprob'
plot(
  x,
  stack = FALSE,
  lg = NULL,
  ind = NULL,
  use.plotly = TRUE,
  verbose = TRUE,
  ...
)
```

Arguments

x	an object of class <code>mappoly.homoprob</code>
stack	logical. If TRUE, probability profiles of all homologues are stacked in the plot (default = FALSE)
lg	indicates which linkage group should be plotted. If NULL (default), it plots the first linkage group. If "all", it plots all linkage groups
ind	indicates which individuals should be plotted. It can be the position of the individuals in the dataset or its name. If NULL (default), the function plots the first individual
use.plotly	if TRUE (default), it uses plotly interactive graphic
verbose	if TRUE (default), the current progress is shown; if FALSE, no output is produced
...	unused arguments

`plot.mappoly.prefpair.profiles`

Plots mappoly.prefpair.profiles

Description

Plots `mappoly.prefpair.profiles`

Usage

```
## S3 method for class 'mappoly.prefpair.profiles'
plot(
  x,
  type = c("pair.configs", "hom.pairs"),
  min.y.prof = 0,
  max.y.prof = 1,
  thresh = 0.01,
  P1 = "P1",
  P2 = "P2",
  ...
)
```

Arguments

x	an object of class <code>mappoly.prefpair.profiles</code>
type	a character string indicating which type of graphic is plotted: "pair.configs" (default) plots the preferential pairing profile for the pairing configurations or "hom.pairs" plots the preferential pairing profile for the homolog pairs
min.y.prof	lower bound for y axis on the probability profile graphic (default = 0)
max.y.prof	upper bound for y axis on the probability profile graphic (default = 1)

thresh	threshold for chi-square test (default = 0.01)
P1	a string containing the name of parent P1
P2	a string containing the name of parent P2
...	unused arguments

plot_genome_vs_map *Physical versus genetic distance*

Description

This function plots scatterplot(s) of physical distance (in Mbp) versus the genetic distance (in cM). Map(s) should be passed as a single object or a list of objects of class `mappoly.map`.

Usage

```
plot_genome_vs_map(map.list, phase.config = "best", same.ch.lg = FALSE)
```

Arguments

map.list	A list or a single object of class <code>mappoly.map</code>
phase.config	A vector containing which phase configuration should be plotted. If 'best' (default), plots the configuration with the highest likelihood for all elements in 'map.list'
same.ch.lg	Logical. If TRUE displays only the scatterplots between the chromosomes and linkage groups with the same number. Default is FALSE.

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
plot_genome_vs_map(solcap.mds.map, same.ch.lg = TRUE)
```

plot_GIC	<i>Genotypic information content</i>
----------	--------------------------------------

Description

This function plots the genotypic information content given an object of class `mappoly.homoprob`.

Usage

```
plot_GIC(hprobs, P = "P1", Q = "P2")
```

Arguments

- | | |
|--------|--|
| hprobs | an object of class <code>mappoly.homoprob</code> |
| P | a string containing the name of parent P |
| Q | a string containing the name of parent Q |

Examples

```
w <- lapply(solcap.err.map[1:3], calc_genoprob)
h.prob <- calc_homologprob(w)
plot_GIC(h.prob)
```

plot_map_list	<i>Plot a genetic map</i>
---------------	---------------------------

Description

This function plots a genetic linkage map(s) generated by MAPpoly. The map(s) should be passed as a single object or a list of objects of class `mappoly.map`.

Usage

```
plot_map_list(
  map.list,
  horiz = TRUE,
  col = "lightgray",
  title = "Linkage group"
)
```

Arguments

<code>map.list</code>	A list of objects or a single object of class <code>mappoly.map</code>
<code>horiz</code>	logical. If FALSE, the maps are plotted vertically with the first map to the left. If TRUE (default), the maps are plotted horizontally with the first at the bottom
<code>col</code>	a vector of colors for the bars or bar components (default = 'lightgrey') ggstyle produces maps using the default ggplot color palette
<code>title</code>	a title (string) for the maps (default = 'Linkage group')

Value

A `data.frame` object containing the name of the markers and their genetic position

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *G3: Genes, Genomes, Genetics*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
## hexafake map
plot_map_list(maps.hexafake, horiz = FALSE)
plot_map_list(maps.hexafake, col = c("#999999", "#E69F00", "#56B4E9"))

## solcap map
plot_map_list(solcap.dose.map, col = "ggstyle")
```

`plot_mrk_info` *Plot marker information*

Description

Plots summary statistics for a given marker

Usage

```
plot_mrk_info(input.data, mrk)
```

Arguments

<code>input.data</code>	an object of class <code>mappoly.data</code>
<code>mrk</code>	marker name or position in the dataset

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:10.1534/g3.119.400378

Examples

```
plot_mrk_info(tetra.solcap.geno.dist, 2680)
plot_mrk_info(tetra.solcap.geno.dist, "solcap.snp_c2_23828")
```

poly_cross_simulate *Simulate an autopolyploid full-sib population*

Description

Simulate an autopolyploid full-sib population with one or two informative parents under random chromosome segregation.

Usage

```
poly_cross_simulate(
  ploidy,
  rf.vec,
  n.mrk,
  n.ind,
  hom.allele,
  draw = FALSE,
  file = "output.pdf",
  seed = NULL,
  width = 12,
  height = 6,
  prob.P = NULL,
  prob.Q = NULL
)
```

Arguments

ploidy	ploidy level. Must be an even number
rf.vec	vector containing the recombination fractions between adjacent markers. If a single recombination fraction is provided, it is repeated $n.mrk - 1$ times
n.mrk	number of markers

<code>n.ind</code>	number of individuals in the offspring
<code>hom.allele</code>	a list containing the linkage phase information for both parents
<code>draw</code>	if TRUE, draws a graphical representation of the parental map, including the linkage phase configuration, in a pdf output (default = FALSE)
<code>file</code>	name of the output file. It is ignored if <code>draw</code> = TRUE
<code>seed</code>	random number generator seed (default = NULL)
<code>width</code>	the width of the graphics region in inches (default = 12)
<code>height</code>	the height of the graphics region in inches (default = 6)
<code>prob.P</code>	a vector indicating the proportion of preferential pairing in parent P (currently ignored)
<code>prob.Q</code>	a vector indicating the proportion of preferential pairing in parent Q (currently ignored)

Details

`hom.allele.p` and `hom.allele.q` are lists of vectors containing linkage phase configurations. Each vector contains the numbers of the homologous chromosomes in which the alleles are located. For instance, a vector containing (1, 3, 4) means that the marker has three doses located in the chromosomes 1, 3 and 4. For zero doses, use 0. For more sophisticated simulations, we strongly recommend using PedigreeSim V2.0 <https://github.com/PBR/pedigreeSim>

Value

an object of class `mappoly.data`. See [read_genotype](#) for more information

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
h.temp <- sim_homologous(ploidy = 6, n.mrk = 20, max.d = 3, max.ph = 3, seed = 123)
fake.poly.dat <- poly_cross_simulate(ploidy = 6, rf.vec = .05, n.mrk = 20,
                                         n.ind = 200, h.temp, seed = 123)
plot(fake.poly.dat)
```

print_mrk	<i>Summary of a set of markers</i>
-----------	------------------------------------

Description

Returns information related to a given set of markers

Usage

```
print_mrk(input.data, mrks)
```

Arguments

input.data	an object 'mappoly.data'
mrks	marker sequence index (integer vector)

Examples

```
print_mrk(tetra.solcap.geno.dist, 1:5)
print_mrk(hexafake, 256)
```

read_fitpoly	<i>Data Input in fitPoly format</i>
--------------	-------------------------------------

Description

Reads an external data file generated as output of [saveMarkerModels](#). This function creates an object of class mappoly.data.

Usage

```
read_fitpoly(
  file.in,
  ploidy,
  parent1,
  parent2,
  offspring = NULL,
  filter.non.conforming = TRUE,
  elim.redundant = TRUE,
  parent.geno = c("joint", "max"),
  thresh.parent.geno = 0.95,
  prob.thres = 0.95,
  file.type = c("table", "csv"),
  verbose = TRUE
)
```

Arguments

<code>file.in</code>	a character string with the name of (or full path to) the input file
<code>ploidy</code>	the ploidy level
<code>parent1</code>	a character string containing the name (or pattern of genotype IDs) of parent 1
<code>parent2</code>	a character string containing the name (or pattern of genotype IDs) of parent 2
<code>offspring</code>	a character string containing the name (or pattern of genotype IDs) of the offspring individuals. If NULL (default) it considers all individuals as offsprings, except <code>parent1</code> and <code>parent2</code> .
<code>filter.non.conforming</code>	if TRUE (default) converts data points with unexpected genotypes (i.e. no double reduction) to 'NA'. See function <code>segreg_poly</code> for information on expected classes and their respective frequencies.
<code>elim.redundant</code>	logical. If TRUE (default), removes redundant markers during map construction, keeping them annotated to in order to include them in the final map.
<code>parent.geno</code>	indicates whether to use the joint probability 'joint' (default) or the maximum probability of multiple replicates (if available) to assign dosage to parents. If there is one observation per parent, both options will yield the same results.
<code>thresh.parent.geno</code>	threshold probability to assign a dosage to parents. If the probability is smaller than <code>thresh.parent.geno</code> , the marker is discarded.
<code>prob.thres</code>	threshold probability to assign a dosage to offspring. If the probability is smaller than <code>prob.thres</code> , the data point is converted to 'NA'.
<code>file.type</code>	indicates whether the characters in the input file are separated by 'white spaces' ("table") or by commas ("csv").
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Value

An object of class `mappoly.data` which contains a list with the following components:

<code>ploidy</code>	ploidy level
<code>n.ind</code>	number individuals
<code>n.mrk</code>	total number of markers
<code>ind.names</code>	the names of the individuals
<code>mrk.names</code>	the names of the markers
<code>dosage.p1</code>	a vector containing the dosage in parent P for all <code>n.mrk</code> markers
<code>dosage.p2</code>	a vector containing the dosage in parent Q for all <code>n.mrk</code> markers
<code>chrom</code>	a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
<code>genome.pos</code>	Physical position of the markers into the sequence
<code>seq.ref</code>	NULL (unused in this type of data)
<code>seq.alt</code>	NULL (unused in this type of data)

```

all.mrk.depth    NULL (unused in this type of data)
geno.dose        a matrix containing the dosage for each markers (rows) for each individual
                  (columns). Missing data are represented by ploidy_level + 1
n.phen           number of phenotypic traits
phen              a matrix containing the phenotypic data. The rows correspond to the traits and
                  the columns correspond to the individuals
kept              if elim.redundant = TRUE, holds all non-redundant markers
elim.correspondence
                  if elim.redundant = TRUE, holds all non-redundant markers and its equivalence
                  to the redundant ones

```

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Voorrips, R.E., Gort, G. & Vosman, B. (2011) Genotype calling in tetraploid species from bi-allelic marker data using mixture models. *BMC Bioinformatics*. doi:10.1186/1471-2105-12-172

Examples

```

#### Tetraploid Example
ft <- "https://raw.githubusercontent.com/mmollina/MAppoly_vignettes/master/data/fitpoly.dat"
tempfl <- tempfile()
download.file(ft, destfile = tempfl)
fitpoly.dat <- read_fitpoly(file.in = tempfl, ploidy = 4,
                             parent1 = "P1", parent2 = "P2",
                             verbose = TRUE)
print(fitpoly.dat, detailed = TRUE)
plot(fitpoly.dat)
plot_mrk_info(fitpoly.dat, 37)

```

Description

Reads an external data file. The format of the file is described in the Details section. This function creates an object of class `mappoly.data`

Usage

```
read_geno(
  file.in,
  filter.non.conforming = TRUE,
  elim.redundant = TRUE,
  verbose = TRUE
)

## S3 method for class 'mappoly.data'
print(x, detailed = FALSE, ...)

## S3 method for class 'mappoly.data'
plot(x, thresh.line = 1e-05, ...)
```

Arguments

<code>file.in</code>	a character string with the name of (or full path to) the input file which contains the data to be read
<code>filter.non.conforming</code>	if TRUE (default) converts data points with unexpected genotypes (i.e. no double reduction) to 'NA'. See function <code>segreg_poly</code> for information on expected classes and their respective frequencies.
<code>elim.redundant</code>	logical. If TRUE (default), removes redundant markers during map construction, keeping them annotated to export to the final map.
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced
<code>x</code>	an object of class <code>mappoly.data</code>
<code>detailed</code>	if available, print the number of markers per sequence (default = FALSE)
<code>...</code>	currently ignored
<code>thresh.line</code>	position of a threshold line for p values of the segregation test (default = 10e-06)

Details

The first line of the input file contains the string `ploidy` followed by the ploidy level of the parents. The second and third lines contain the strings `n.ind` and `n.mrk` followed by the number of individuals in the dataset and the total number of markers, respectively. Lines number 4 and 5 contain the strings `mrk.names` and `ind.names` followed by a sequence of the names of the markers and the name of the individuals, respectively. Lines 6 and 7 contain the strings `dosageP` and `dosageQ` followed by a sequence of numbers containing the dosage of all markers in parent P and Q. Line 8, contains the string `seq` followed by a sequence of integer numbers indicating the chromosome each marker belongs. It can be any 'a priori' information regarding the physical distance between markers. For example, these numbers could refer to chromosomes, scaffolds or even contigs, in which the markers are positioned. If this information is not available for a particular marker, NA should be used. If this information is not available for any of the markers, the string `seq` should be followed by a single NA. Line number 9 contains the string `seqpos` followed by the physical position of the markers into the sequence. The physical position can be given in any unity of physical genomic distance (base pairs, for instance). However, the user should be able to make decisions based on these values, such as the occurrence of crossing overs, etc. Line number 10 should contain

the string nphen followed by the number of phenotypic traits. Line number 11 is skipped (Usually used as a spacer). The next elements are strings containing the name of the phenotypic trait with no space characters followed by the phenotypic values. The number of lines should be the same number of phenotypic traits. NA represents missing values. The line number 12 + nphen is skipped. Finally, the last element is a table containing the dosage for each marker (rows) for each individual (columns). NA represents missing values.

Value

An object of class `mappoly.data` which contains a list with the following components:

<code>ploidy</code>	ploidy level
<code>n.ind</code>	number individuals
<code>n.mrk</code>	total number of markers
<code>ind.names</code>	the names of the individuals
<code>mrk.names</code>	the names of the markers
<code>dosage.p1</code>	a vector containing the dosage in parent P for all <code>n.mrk</code> markers
<code>dosage.p2</code>	a vector containing the dosage in parent Q for all <code>n.mrk</code> markers
<code>chrom</code>	a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
<code>genome.pos</code>	Physical position of the markers into the sequence
<code>seq.ref</code>	NULL (unused in this type of data)
<code>seq.alt</code>	NULL (unused in this type of data)
<code>all.mrk.depth</code>	NULL (unused in this type of data)
<code>geno.dose</code>	a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by <code>ploidy_level + 1</code>
<code>n.phen</code>	number of phenotypic traits
<code>phen</code>	a matrix containing the phenotypic data. The rows correspond to the traits and the columns correspond to the individuals
<code>kept</code>	if <code>elim.redundant = TRUE</code> , holds all non-redundant markers
<code>elim.correspondence</code>	if <code>elim.redundant = TRUE</code> , holds all non-redundant markers and its equivalence to the redundant ones

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

- Mollinari M., Olukolu B. A., Pereira G. da S., Khan A., Gemenet D., Yencho G. C., Zeng Z-B. (2020), Unraveling the Hexaploid Sweetpotato Inheritance Using Ultra-Dense Multilocus Mapping, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400620](https://doi.org/10.1534/g3.119.400620)
- Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
#### Tetraploid Example
f11 = "https://raw.githubusercontent.com/mmollina/MAOppoly_vignettes/master/data/SolCAP_dosage"
tempfl <- tempfile()
download.file(f11, destfile = tempfl)
SolCAP.dose <- read_geno(file.in = tempfl)
print(SolCAP.dose, detailed = TRUE)
plot(SolCAP.dose)
```

read_geno_csv

Data Input in CSV format

Description

Reads an external comma-separated values (CSV) data file. The format of the file is described in the Details section. This function creates an object of class `mappoly.data`.

Usage

```
read_geno_csv(
  file.in,
  ploidy,
  filter.non.conforming = TRUE,
  elim.redundant = TRUE,
  verbose = TRUE
)
```

Arguments

<code>file.in</code>	a character string with the name of (or full path to) the input file containing the data to be read
<code>ploidy</code>	the ploidy level
<code>filter.non.conforming</code>	if TRUE (default) converts data points with unexpected genotypes (i.e. no double reduction) to 'NA'. See function <code>segreg_poly</code> for information on expected classes and their respective frequencies.
<code>elim.redundant</code>	logical. If TRUE (default), removes redundant markers during map construction, keeping them annotated to export to the final map.
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Details

This is an alternative and a somewhat more straightforward version of the function `read_geno`. The input is a standard CSV file where the rows represent the markers, except for the first row which is used as a header. The first five columns contain the marker names, the dosage in parents 1 and 2, the chromosome information (i.e. chromosome, scaffold, contig, etc) and the position of the marker within the sequence. The remaining columns contain the dosage of the full-sib population. A tetraploid example of such file can be found in the Examples section.

Value

An object of class `mappoly.data` which contains a list with the following components:

<code>ploidy</code>	ploidy level
<code>n.ind</code>	number individuals
<code>n.mrk</code>	total number of markers
<code>ind.names</code>	the names of the individuals
<code>mrk.names</code>	the names of the markers
<code>dosage.p1</code>	a vector containing the dosage in parent P for all <code>n.mrk</code> markers
<code>dosage.p2</code>	a vector containing the dosage in parent Q for all <code>n.mrk</code> markers
<code>chrom</code>	a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
<code>genome.pos</code>	Physical position of the markers into the sequence
<code>seq.ref</code>	NULL (unused in this type of data)
<code>seq.alt</code>	NULL (unused in this type of data)
<code>all.mrk.depth</code>	NULL (unused in this type of data)
<code>geno.dose</code>	a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by <code>ploidy_level + 1</code>
<code>n.phen</code>	number of phenotypic traits
<code>phen</code>	a matrix containing the phenotypic data. The rows correspond to the traits and the columns correspond to the individuals
<code>kept</code>	if <code>elim.redundant = TRUE</code> , holds all non-redundant markers
<code>elim.correspondence</code>	if <code>elim.redundant = TRUE</code> , holds all non-redundant markers and its equivalence to the redundant ones

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>, with minor changes by Gabriel Gesteira, <gabrielgesteira@usp.br>

References

- Molinari M., Olukolu B. A., Pereira G. da S., Khan A., Gemenet D., Yencho G. C., Zeng Z-B. (2020), Unraveling the Hexaploid Sweetpotato Inheritance Using Ultra-Dense Multilocus Mapping, _G3: Genes, Genomes, Genetics_. doi:10.1534/g3.119.400620
- Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. doi:10.1534/g3.119.400378

Examples

```
#### Tetraploid Example
ft = "https://raw.githubusercontent.com/mmollina/MAPpoly_vignettes/master/data/tetra_solcap.csv"
tempfl <- tempfile()
download.file(ft, destfile = tempfl)
SolCAP.dose <- read_geno_csv(file.in = tempfl, ploidy = 4)
print(SolCAP.dose, detailed = TRUE)
plot(SolCAP.dose)
```

read_geno_prob *Data Input*

Description

Reads an external data file. The format of the file is described in the Details section. This function creates an object of class `mappoly.data`

Usage

```
read_geno_prob(
  file.in,
  prob.thres = 0.95,
  filter.non.conforming = TRUE,
  elim.redundant = TRUE,
  verbose = TRUE
)
```

Arguments

- | | |
|-------------------------|--|
| <code>file.in</code> | a character string with the name of (or full path to) the input file which contains the data to be read |
| <code>prob.thres</code> | probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than <code>prob.thres</code> are considered as missing data for the dosage calling purposes (default = 0.95) |

<code>filter.non.conforming</code>	if TRUE (default) converts data points with unexpected genotypes (i.e. no double reduction) to 'NA'. See function <code>segreg_poly</code> for information on expected classes and their respective frequencies.
<code>elim.redundant</code>	logical. If TRUE (default), removes redundant markers during map construction, keeping them annotated to export to the final map.
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Details

The first line of the input file contains the string `ploidy` followed by the ploidy level of the parents. The second and third lines contains the strings `n.ind` and `n.mrk` followed by the number of individuals in the dataset and the total number of markers, respectively. Lines number 4 and 5 contain the string `mrk.names` and `ind.names` followed by a sequence of the names of the markers and the name of the individuals, respectively. Lines 6 and 7 contain the strings `dosageP` and `dosageQ` followed by a sequence of numbers containing the dosage of all markers in parent P and Q. Line 8, contains the string `seq` followed by a sequence of integer numbers indicating the chromosome each marker belongs. It can be any 'a priori' information regarding the physical distance between markers. For example, these numbers could refer to chromosomes, scaffolds or even contigs, in which the markers are positioned. If this information is not available for a particular marker, NA should be used. If this information is not available for any of the markers, the string `seq` should be followed by a single NA. Line number 9 contains the string `seqpos` followed by the physical position of the markers into the sequence. The physical position can be given in any unity of physical genomic distance (base pairs, for instance). However, the user should be able to make decisions based on these values, such as the occurrence of crossing overs, etc. Line number 10 should contain the string `nphen` followed by the number of phenotypic traits. Line number 11 is skipped (Usually used as a spacer). The next elements are strings containing the name of the phenotypic trait with no space characters followed by the phenotypic values. The number of lines should be the same number of phenotypic traits. NA represents missing values. The line number $12 + nphen$ is skipped. Finally, the last element is a table containing the probability distribution for each combination of marker and offspring. The first two columns represent the marker and the offspring, respectively. The remaining elements represent the probability associated with each one of the possible dosages. NA represents missing data.

Value

an object of class `mappoly.data` which contains a list with the following components:

<code>ploidy</code>	ploidy level
<code>n.ind</code>	number individuals
<code>n.mrk</code>	total number of markers
<code>ind.names</code>	the names of the individuals
<code>mrk.names</code>	the names of the markers
<code>dosage.p1</code>	a vector containing the dosage in parent P for all <code>n.mrk</code> markers
<code>dosage.p2</code>	a vector containing the dosage in parent Q for all <code>n.mrk</code> markers
<code>chrom</code>	a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
<code>genome.pos</code>	physical position of the markers into the sequence

seq.ref	NULL (unused in this type of data)
seq.alt	NULL (unused in this type of data)
all.mrk.depth	NULL (unused in this type of data)
prob.thres	probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than 'prob.thres' were considered as missing data in the 'geno.dose' matrix
geno.dose	a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by ploidy_level + 1
geno	a data.frame containing the probability distribution for each combination of marker and offspring. The first two columns represent the marker and the offspring, respectively. The remaining elements represent the probability associated to each one of the possible dosages. Missing data are converted from NA to the expected segregation ratio using function segreg_poly
n.phen	number of phenotypic traits
phen	a matrix containing the phenotypic data. The rows correspond to the traits and the columns correspond to the individuals
chisq.pval	a vector containing p-values related to the chi-squared test of Mendelian segregation performed for all markers
kept	if elim.redundant = TRUE, holds all non-redundant markers
elim.correspondence	if elim.redundant = TRUE, holds all non-redundant markers and its equivalence to the redundant ones

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

- Mollinari M., Olukolu B. A., Pereira G. da S., Khan A., Gemenet D., Yencho G. C., Zeng Z-B. (2020), Unraveling the Hexaploid Sweetpotato Inheritance Using Ultra-Dense Multilocus Mapping, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400620](https://doi.org/10.1534/g3.119.400620)
- Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
#### Tetraploid Example
ft = "https://raw.githubusercontent.com/mmollina/MAPoly_vignettes/master/data/hexa_sample"
tempfl <- tempfile()
download.file(ft, destfile = tempfl)
SolCAP.dose.prob <- read_geno_prob(file.in = tempfl)
print(SolCAP.dose.prob, detailed = TRUE)
plot(SolCAP.dose.prob)
```

read_vcf*Data Input VCF*

Description

Reads an external VCF file and creates an object of class `mappoly.data`

Usage

```
read_vcf(
  file.in,
  parent.1,
  parent.2,
  ploidy = NA,
  filter.non.conforming = TRUE,
  thresh.line = 0.05,
  min.gt.depth = 0,
  min.av.depth = 0,
  max.missing = 1,
  elim.redundant = TRUE,
  verbose = TRUE,
  read.geno.prob = FALSE,
  prob.thres = 0.95
)
```

Arguments

<code>file.in</code>	a character string with the name of (or full path to) the input file which contains the data (VCF format)
<code>parent.1</code>	a character string containing the name of parent 1
<code>parent.2</code>	a character string containing the name of parent 2
<code>ploidy</code>	the species ploidy (optional, it will be automatically detected)
<code>filter.non.conforming</code>	if TRUE (default) converts data points with unexpected genotypes (i.e. no double reduction) to 'NA'. See function <code>segreg_poly</code> for information on expected classes and their respective frequencies.
<code>thresh.line</code>	threshold used for p-values on segregation test (default = 0.05)
<code>min.gt.depth</code>	minimum genotype depth to keep information. If the genotype depth is below <code>min.gt.depth</code> , it will be replaced with NA (default = 0)
<code>min.av.depth</code>	minimum average depth to keep markers (default = 0)
<code>max.missing</code>	maximum proportion of missing data to keep markers (range = 0-1; default = 1)
<code>elim.redundant</code>	logical. If TRUE (default), removes redundant markers during map construction, keeping them annotated to export to the final map.
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

<code>read.genotype.prob</code>	If genotypic probabilities are available (PL field), generates a probability-based dataframe (default = FALSE).
<code>prob.thres</code>	probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than <code>prob.thres</code> are considered as missing data for the dosage calling purposes (default = 0.95)

Details

This function can handle .vcf files versions 4.0 or higher. The ploidy can be automatically detected, but it is highly recommended that you inform it to check for mismatches. All individual and marker names will be kept as they are in the .vcf file.

Value

An object of class `mappoly.data` which contains a list with the following components:

<code>ploidy</code>	ploidy level
<code>n.ind</code>	number individuals
<code>n.mrk</code>	total number of markers
<code>ind.names</code>	the names of the individuals
<code>mrk.names</code>	the names of the markers
<code>dosage.p1</code>	a vector containing the dosage in parent P for all <code>n.mrk</code> markers
<code>dosage.p2</code>	a vector containing the dosage in parent Q for all <code>n.mrk</code> markers
<code>chrom</code>	a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence
<code>genome.pos</code>	Physical position of the markers into the sequence
<code>seq.ref</code>	Reference base used for each marker (i.e. A, T, C, G)
<code>seq.alt</code>	Alternative base used for each marker (i.e. A, T, C, G)
<code>prob.thres</code>	(unused field)
<code>geno.dose</code>	a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by <code>ploidy_level + 1</code>
<code>geno</code>	a dataframe containing all genotypic probabilities columns for each marker and individual combination (rows). Missing data are represented by <code>ploidy_level + 1</code>
<code>nphen</code>	(unused field)
<code>phen</code>	(unused field)
<code>all.mrk.depth</code>	DP information for all markers on VCF file
<code>chisq.pval</code>	a vector containing p-values related to the chi-squared test of Mendelian segregation performed for all markers
<code>kept</code>	if <code>elim.redundant = TRUE</code> , holds all non-redundant markers
<code>elim.correspondence</code>	if <code>elim.redundant = TRUE</code> , holds all non-redundant markers and its equivalence to the redundant ones

Author(s)

Gabriel Gesteira, <gabrielgesteira@usp.br>

References

- Mollinari M., Olukolu B. A., Pereira G. da S., Khan A., Gemenet D., Yencho G. C., Zeng Z-B. (2020), Unraveling the Hexaploid Sweetpotato Inheritance Using Ultra-Dense Multilocus Mapping, _G3: Genes, Genomes, Genetics_. doi:10.1534/g3.119.400620
- Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, _G3: Genes, Genomes, Genetics_. doi:10.1534/g3.119.400378

Examples

```
## Hexaploid sweetpotato: Subset of chromosome 3
f1 = "https://github.com/mmollina/MAPpoly_vignettes/raw/master/data/sweet_sample_ch3.vcf.gz"
tempf1 <- tempfile(pattern = 'chr3_', fileext = '.vcf.gz')
download.file(f1, destfile = tempf1)
dat.dose.vcf = read_vcf(file = tempf1, parent.1 = "PARENT1", parent.2 = "PARENT2")
print(dat.dose.vcf)
plot(dat.dose.vcf)
```

reest_rf

*Re-estimate the recombination fractions in a genetic map***Description**

This function re-estimates the recombination fractions between all markers in a given map.

Usage

```
reest_rf(
  input.map,
  input.mat = NULL,
  tol = 0.01,
  phase.config = "all",
  method = c("hmm", "ols", "wMDS_to_1D_pc"),
  weight = TRUE,
  verbose = TRUE,
  high.prec = FALSE,
  max.rf.to.break.EM = 0.5,
  input.mds = NULL
)
```

Arguments

<code>input.map</code>	An object of class <code>mappoly.map</code>
<code>input.mat</code>	An object of class <code>mappoly.rf.matrix</code>
<code>tol</code>	tolerance for determining convergence (default = 10e-03)
<code>phase.config</code>	which phase configuration should be used. "best" (default) will choose the maximum likelihood configuration
<code>method</code>	indicates whether to use 'hmm' (Hidden Markov Models), 'ols' (Ordinary Least Squares) or 'wMDS_to_1D_pc' (weighted MDS followed by fitting a one dimensional principal curve) to re-estimate the recombination fractions.
<code>weight</code>	if TRUE (default), it uses the LOD scores to perform a weighted regression when the Ordinary Least Squares is chosen
<code>verbose</code>	if TRUE (default), current progress is shown; if FALSE, no output is produced
<code>high.prec</code>	logical. If TRUE uses high precision (long double) numbers in the HMM procedure implemented in C++, which can take a long time to perform (default = FALSE)
<code>max.rf.to.break.EM</code>	for internal use only.
<code>input.mds</code>	An object of class <code>mappoly.map</code>

Value

An updated object of class `mappoly.pcmap` whose order was used in the `input.map`

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:[10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Stam P (1993) Construction of integrated genetic-linkage maps by means of a new computer package: Joinmap. *_Plant J_* 3:739–744 doi:[10.1111/j.1365313X.1993.00739.x](https://doi.org/10.1111/j.1365313X.1993.00739.x)

`rev_map`*Reverse map***Description**

Provides the reverse of a given map.

Usage

```
rev_map(input.map)
```

Arguments

<code>input.map</code>	an object of class <code>mappoly.map</code>
------------------------	---

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

Examples

```
plot_genome_vs_map(solcap.mds.map[[1]])
plot_genome_vs_map(rev_map(solcap.mds.map[[1]]))
```

rf_list_to_matrix *Recombination fraction list to matrix*

Description

Transforms the recombination fraction list contained in an object of class `mappoly.twopt` or `mappoly.twopt2` into a recombination fraction matrix

Usage

```
rf_list_to_matrix(
  input.twopt,
  thresh.LOD.ph = 0,
  thresh.LOD.rf = 0,
  thresh.rf = 0.5,
  ncpus = 1L,
  shared.alleles = FALSE,
  verbose = TRUE
)

## S3 method for class 'mappoly.rf.matrix'
print(x, ...)

## S3 method for class 'mappoly.rf.matrix'
plot(
  x,
  type = c("rf", "lod"),
  ord = NULL,
  rem = NULL,
  main.text = NULL,
  index = FALSE,
  fact = 1,
  ...
)
```

Arguments

<code>input.twopt</code>	an object of class <code>mappoly.twopt</code> or <code>mappoly.twopt2</code>
<code>thresh.LOD.ph</code>	LOD score threshold for linkage phase configurations (default = 0)
<code>thresh.LOD.rf</code>	LOD score threshold for recombination fractions (default = 0)
<code>thresh.rf</code>	the threshold used for recombination fraction filtering (default = 0.5)
<code>ncpus</code>	number of parallel processes (i.e. cores) to spawn (default = 1)
<code>shared.alleles</code>	if TRUE, computes two matrices (for both parents) indicating the number of homologues that share alleles (default = FALSE)
<code>verbose</code>	if TRUE (default), current progress is shown; if FALSE, no output is produced
<code>x</code>	an object of class <code>mappoly.rf.matrix</code>
<code>...</code>	currently ignored
<code>type</code>	type of matrix that should be printed. Can be one of the following: "rf", for recombination fraction or "lod" for LOD Score
<code>ord</code>	the order in which the markers should be plotted (default = NULL)
<code>rem</code>	which markers should be removed from the heatmap (default = NULL)
<code>main.text</code>	a character string as the title of the heatmap (default = NULL)
<code>index</code>	logical should the name of the markers be printed in the diagonal of the heatmap? (default = FALSE)
<code>fact</code>	positive integer. factor expressed as number of cells to be aggregated (default = 1, no aggregation)

Details

`thresh_LOD_ph` should be set in order to only select recombination fractions that have LOD scores associated to the linkage phase configuration higher than `thresh_LOD_ph` when compared to the second most likely linkage phase configuration.

Value

A list containing two matrices. The first one contains the filtered recombination fraction and the second one contains the information matrix

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```

all.mrk <- make_seq_mappoly(hexafake, 1:20)
red.mrk <- elim_redundant(all.mrk)
unique.mrks <- make_seq_mappoly(red.mrk)
all.pairs <- est_pairwise_rf(input.seq = unique.mrks,
                               ncpus = 1,
                               verbose = TRUE)

## Full recombination fraction matrix
mat.full <- rf_list_to_matrix(input.twopt = all.pairs)
plot(mat.full)
plot(mat.full, type = "lod")

```

rf.snp.filter

Remove markers that do not meet a LOD criteria

Description

Remove markers that do not meet a LOD and recombination fraction criteria for at least a percentage of the pairwise marker combinations. It also removes markers with strong evidence of linkage across the whole linkage group (false positive).

Usage

```

rf.snp.filter(
  input.twopt,
  thresh.LOD.ph = 5,
  thresh.LOD.rf = 5,
  thresh.rf = 0.15,
  probs = c(0.05, 1),
  ncpus = 1L,
  diagnostic.plot = TRUE,
  breaks = 100
)

```

Arguments

input.twopt	an object of class mappoly.twopt
thresh.LOD.ph	LOD score threshold for linkage phase configuration (default = 5)
thresh.LOD.rf	LOD score threshold for recombination fraction (default = 5)
thresh.rf	threshold for recombination fractions (default = 0.15)
probs	indicates the probability corresponding to the filtering quantiles. (default = c(0.05, 1))
ncpus	number of parallel processes (i.e. cores) to spawn (default = 1)
diagnostic.plot	if TRUE produces a diagnostic plot
breaks	number of cells for the histogram

Details

`thresh.LOD.ph` should be set in order to only select recombination fractions that have LOD scores associated to the linkage phase configuration higher than `thresh_LOD_ph` when compared to the second most likely linkage phase configuration. That action usually eliminates markers that are unlinked to the set of analyzed markers.

Value

A filtered object of class `mappoly.sequence`. See [make_seq_mappoly](#) for details

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu> with updates by Gabriel Gesteira, <gabrielgosteira@usp.br>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. [doi:10.1534/g3.119.400378](https://doi.org/10.1534/g3.119.400378)

Examples

```
all.mrk <- make_seq_mappoly(hexafake, 1:20)
red.mrk <- elim_redundant(all.mrk)
unique.mrks <- make_seq_mappoly(red.mrk)
all.pairs <- est_pairwise_rf(input.seq = unique.mrks,
                               ncpus = 1,
                               verbose = TRUE)

## Full recombination fraction matrix
mat.full <- rf_list_to_matrix(input.twopt = all.pairs)
plot(mat.full)

## Removing disruptive SNPs
tpt.filt <- rf.snp_filter(all.pairs, 2, 2, 0.07, probs = c(0.15, 1))
p1.filt <- make_pairs_mappoly(input.seq = tpt.filt, input.twopt = all.pairs)
m1.filt <- rf_list_to_matrix(input.twopt = p1.filt)
plot(mat.full, main.text = "LG1")
plot(m1.filt, main.text = "LG1.filt")
```

Description

Computes the polysomic segregation frequency given a ploidy level and the dosage of the locus in both parents. It does not consider double reduction.

Usage

```
segreg_poly(ploidy, dP, dQ)
```

Arguments

ploidy	the ploidy level
dP	the dosage in parent P
dQ	the dosage in parent Q

Value

a vector containing the expected segregation frequency for all possible genotypic classes.

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Mollinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:10.1534/g3.119.400378

Serang O, Mollinari M, Garcia AAF (2012) Efficient Exact Maximum a Posteriori Computation for Bayesian SNP Genotyping in Polyploids. *_PLoS ONE_* 7(2): e30906.

Examples

```
# autohexaploid with two and three doses in parents P and Q,  
# respectively  
seg <- segreg_poly(ploidy = 6, dP = 2, dQ = 3)  
barplot(seg, las = 2)
```

sim_homologous *Simulate homology groups*

Description

Simulate two homology groups (one for each parent) and their linkage phase configuration.

Usage

```
sim_homologous(
  ploidy,
  n.mrk,
  min.d = 0,
  max.d = ploidy + 1,
  prob.dose = NULL,
  max.ph,
  restriction = TRUE,
  seed = NULL
)
```

Arguments

ploidy	ploidy level. Must be an even number
n.mrk	number of markers
min.d	minimum dosage to be simulated (default = 0)
max.d	maximum dosage to be simulated (default = ploidy + 1)
prob.dose	a vector indicating the proportion of markers for different dosage to be simulated (default = NULL)
max.ph	maximum phase difference
restriction	if TRUE (default), avoid cases where it is impossible to estimate recombination fraction and/or linkage phases via two-point analysis
seed	random number generator seed

Details

This function prevents the simulation of linkage phase configurations which are impossible to estimate via two point methods

Value

a list containing the following components:

hom.allele.p	a list of vectors containing linkage phase configurations. Each vector contains the numbers of the homologous chromosomes in which the alleles are located. For instance, a vector containing (1, 3, 4) means that the marker has three doses located in the chromosomes 1, 3 and 4. For zero doses, use 0
p	contains the indices of the starting positions of the dosages, considering that the vectors contained in p are concatenated. Markers with no doses (zero doses are also considered)
hom.allele.q	Analogously to hom.allele.p
q	Analogously to p

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *G3: Genes, Genomes, Genetics*. doi:10.1534/g3.119.400378

Examples

```
h.temp <- sim_homologous(ploidy = 6, n.mrk = 20, max.d = 3, max.ph = 3,  
seed = 123)
```

solcap.dose.map *Resulting maps from tetra.solcap*

Description

A list containing 12 linkage groups estimated using genomic order and dosage call

Usage

```
solcap.dose.map
```

Format

A list containing 12 objects of class `mappoly.map`, each one representing one linkage group in the `tetra.solcap` dataset.

solcap.err.map *Resulting maps from tetra.solcap*

Description

A list containing 12 linkage groups estimated using genomic order, dosage call and global calling error

Usage

```
solcap.err.map
```

Format

A list containing 12 objects of class `mappoly.map`, each one representing one linkage group in the `tetra.solcap` dataset.

`solcap.mds.map` *Resulting maps from [tetra.solcap](#)*

Description

A list containing 12 linkage groups estimated using [mds_mappoly](#) order and dosage call

Usage

`solcap.mds.map`

Format

A list containing 12 objects of class [mappoly.map](#), each one representing one linkage group in the [tetra.solcap](#) dataset.

`solcap.prior.map` *Resulting maps from [tetra.solcap.geno.dist](#)*

Description

A list containing 12 linkage groups estimated using genomic order and prior probability distribution

Usage

`solcap.prior.map`

Format

A list containing 12 objects of class [mappoly.map](#), each one representing one linkage group in the [tetra.solcap.geno.dist](#) dataset.

<code>split_and_rephase</code>	<i>Divides map in sub-maps and re-phase them</i>
--------------------------------	--

Description

The function splits the input map in sub-maps given a distance threshold of neighboring markers and evaluates alternative phases between the sub-maps.

Usage

```
split_and_rephase(
  input.map,
  twopt,
  gap.threshold = 5,
  size.rem.cluster = 1,
  phase.config = "best",
  tol.final = 0.001,
  verbose = TRUE
)
```

Arguments

<code>input.map</code>	an object of class <code>mappoly.map</code>
<code>twopt</code>	an object of class <code>mappoly.twopt</code> containing the two-point information for the markers contained in <code>input.map</code>
<code>gap.threshold</code>	distance threshold of neighboring markers where the map should be spitted. The default value is 5 cM
<code>size.rem.cluster</code>	the size of the marker cluster (in number of markers) from which the cluster should be removed. The default value is 1
<code>phase.config</code>	which phase configuration should be used. "best" (default) will choose the maximum likelihood phase configuration
<code>tol.final</code>	the desired accuracy for the final map (default = 10e-04)
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Value

An object of class `mappoly.map`

Author(s)

Marcelo Mollinari, <mmollin@ncsu.edu>

References

Molinari, M., and Garcia, A. A. F. (2019) Linkage analysis and haplotype phasing in experimental autopolyploid populations with high ploidy level using hidden Markov models, *_G3: Genes, Genomes, Genetics_*. doi:10.1534/g3.119.400378

Examples

```
map <- get_submap(solcap.dose.map[[1]], 1:20, verbose = FALSE)
tpt <- est_pairwise_rf(make_seq_mappoly(map))
new.map <- split_and_rephase(map, tpt, 1, 1)
map
new.map
plot_map_list(list(old.map = map, new.map = new.map), col = "ggstyle")
```

summary_maps

Summary maps

Description

This function generates a brief summary table of a list of `mappoly.map` objects

Usage

```
summary_maps(map.list, verbose = TRUE)
```

Arguments

<code>map.list</code>	a list of objects of class <code>mappoly.map</code>
<code>verbose</code>	if TRUE (default), the current progress is shown; if FALSE, no output is produced

Value

a data frame containing a brief summary of all maps contained in `map.list`

Author(s)

Gabriel Gesteira, <gabrielgesteira@usp.br>

Examples

```
tetra.sum <- summary_maps(solcap.err.map)
tetra.sum
```

tetra.solcap*Autotetraploid potato dataset.*

Description

A dataset of the B2721 population which derived from a cross between two tetraploid potato varieties: Atlantic × B1829-5. The population comprises 160 offsprings genotyped with the SolCAP Infinium 8303 potato array. The original data set can be found in [The Solanaceae Coordinated Agricultural Project (SolCAP) webpage](http://solcap.msu.edu/potato_infinium.shtml) The dataset also contains the genomic order of the SNPs from the *Solanum tuberosum* genome version 4.03. The genotype calling was performed using the fitPoly R package.

Usage

```
tetra.solcap
```

Format

An object of class `mappoly.data` which contains a list with the following components:

ploidy ploidy level = 4

n.ind number individuals = 160

n.mrk total number of markers = 4017

ind.names the names of the individuals

mrk.names the names of the markers

dosage.p1 a vector containing the dosage in parent P for all `n.mrk` markers

dosage.p2 a vector containing the dosage in parent Q for all `n.mrk` markers

chrom a vector indicating the chromosome each marker belongs. Zero indicates that the marker was not assigned to any sequence

genome.pos Physical position of the markers into the sequence

geno.dose a matrix containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by `ploidy_level + 1 = 5`

n.phen There are no phenotypes in this simulation

phen There are no phenotypes in this simulation

chisq.pval vector containing p-values for all markers associated to the chi-square test for the expected segregation patterns under Mendelian segregation

tetra.solcap.geno.dist*Autotetraploid potato dataset with genotype probabilities.*

Description

A dataset of the B2721 population which derived from a cross between two tetraploid potato varieties: Atlantic × B1829-5. The population comprises 160 offsprings genotyped with the SolCAP Infinium 8303 potato array. The original data set can be found in [The Solanaceae Coordinated Agricultural Project (SolCAP) webpage](http://solcap.msu.edu/potato_infinium.shtml) The dataset also contains the genomic order of the SNPs from the *Solanum tuberosum* genome version 4.03. The genotype calling was performed using the fitPoly R package. Although this dataset contains the probability distribution of the genotypes, it is essentially the same dataset found in [tetra.solcap](#)

Usage

```
tetra.solcap.geno.dist
```

Format

An object of class `mappoly.data` which contains a list with the following components:

ploidy ploidy level = 4

n.ind number individuals = 160

n.mrk total number of markers = 4017

ind.names the names of the individuals

mrk.names the names of the markers

dosage.p1 a vector containing the dosage in parent P for all `n.mrk` markers

dosage.p2 a vector containing the dosage in parent Q for all `n.mrk` markers

chrom a vector indicating which sequence each marker belongs. Zero indicates that the marker was not assigned to any sequence

genome.pos Physical position of the markers into the sequence

prob.thres = 0.95 probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than 'prob.thres' are considered as missing data for the dosage calling purposes

geno a `data.frame` containing the probability distribution for each combination of marker and offspring. The first two columns represent the marker and the offspring, respectively. The remaining elements represent the probability associated to each one of the possible dosages

geno.dose a `matrix` containing the dosage for each markers (rows) for each individual (columns). Missing data are represented by `ploidy_level + 1 = 5`

n.phen There are no phenotypes in this simulation

phen There are no phenotypes in this simulation

update_map

Update map

Description

This function takes an object of class `mappoly.map` and checks for removed redundant markers in the original dataset. Once redundant markers are found, they are re-added to the map in their respective equivalent positions and another HMM round is performed.

Usage

```
update_map(input.maps, verbose = TRUE)
```

Arguments

<code>input.maps</code>	a single map or a list of maps of class <code>mappoly.map</code>
<code>verbose</code>	if TRUE (default), shows information about each update process

Value

an updated map (or list of maps) of class `mappoly.map`, containing the original map(s) plus redundant markers

Author(s)

Gabriel Gesteira, <gabrielgesteira@usp.br>

Examples

```
orig.map <- solcap.err.map
up.map <- lapply(solcap.err.map, update_map)
summary_maps(orig.map)
summary_maps(up.map)
```

update_missing

Update missing information

Description

Updates the missing data in the dosage matrix of an object of class `mappoly.data` given a new probability threshold

Usage

```
update_missing(input.data, prob.thres = 0.95)
```

Arguments

- input.data an object of class `mappoly.data`
prob.thres probability threshold to associate a marker call to a dosage. Markers with maximum genotype probability smaller than 'prob.thres' are considered as missing data for the dosage calling purposes

Author(s)

Marcelo Mollinari, <mmolin@ncsu.edu>

Examples

```
data.updated = update_missing(hexafake.geno.dist, prob.thres = 0.5)
print(hexafake.geno.dist)
print(data.updated)
```

Index

* **analysis**
 cache_counts_twopt, 6

* **datasets**
 hexafake, 41
 hexafake.geno.dist, 42
 maps.hexafake, 52
 solcap.dose.map, 85
 solcap.err.map, 85
 solcap.mds.map, 86
 solcap.prior.map, 86
 tetra.solcap, 89
 tetra.solcap.geno.dist, 90

* **two-point**
 cache_counts_twopt, 6

add_marker, 4

cache_counts_twopt, 6, 7, 22
calc_genoprob, 8
calc_genoprob_dist, 9
calc_genoprob_error, 10
calc_genoprob_one_parent, 11
calc_homologprob, 13
calc_prefpair_profiles, 14
check_data_sanity, 15
compare_maps, 15

drop_marker, 16

elim_redundant, 17
est_full_hmm_with_global_error, 18
est_full_hmm_with_prior_prob, 20
est_pairwise_rf, 22, 49
est_pairwise_rf2, 24
est_rf_hmm, 25
est_rf_hmm_sequential, 26, 28
export_data_to_polymapR, 31
export_map_list, 32
export_qtlpoly, 33
extract_map, 34

filter_individuals, 34
filter_missing, 35
filter_segregation, 36

get_genomic_order, 37
get_submap, 37
get_tab_mrks, 39
group_mappoly, 40

hexafake, 41, 42, 52
hexafake.geno.dist, 42

import_data_from_polymapR, 43
import_from_updog, 44
import_phased_maplist_from_polymapR, 46

loglike_hmm, 47

make_mat_mappoly, 48
make_pairs_mappoly, 49
make_seq_mappoly, 50, 82
maps.hexafake, 52
mds_mappoly, 52, 86
merge_datasets, 54
merge_maps, 56

plot.mappoly.data (read_geno), 67
plot.mappoly.geno.ord
 (get_genomic_order), 37
plot.mappoly.homoprob, 58
plot.mappoly.map (est_rf_hmm), 25
plot.mappoly.prefpair.profiles, 59
plot.mappoly.rf.matrix
 (rf_list_to_matrix), 79
plot.mappoly.sequence
 (make_seq_mappoly), 50
plot_genome_vs_map, 60
plot_GIC, 61
plot_map_list, 61
plot_mrk_info, 62

poly_cross_simulate, 63
print.mappoly.data (read_geno), 67
print.mappoly.geno.ord
 (get_genomic_order), 37
print.mappoly.map (est_rf_hmm), 25
print.mappoly.pcmap (mds_mappoly), 52
print.mappoly.pcmap3d (mds_mappoly), 52
print.mappoly.rf.matrix
 (rf_list_to_matrix), 79
print.mappoly.sequence
 (make_seq_mappoly), 50
print_mrk, 65

read_fitpoly, 65
read_geno, 64, 67, 71
read_geno_csv, 70
read_geno_prob, 72
read_vcf, 75
reest_rf, 77
rev_map, 78
rf_list_to_matrix, 4, 48, 79
rf.snp.filter, 81

saveMarkerModels, 65
segreg_poly, 45, 66, 68, 70, 73–75, 82
sim_homologous, 83
solcap.dose.map, 85
solcap.err.map, 85
solcap.mds.map, 86
solcap.prior.map, 86
split_and_rephase, 87
summary_maps, 88

tetra.solcap, 85, 86, 89, 90
tetra.solcap.geno.dist, 86, 90

update_map, 91
update_missing, 91