

Package ‘rxode2’

May 17, 2022

Version 2.0.7

Title Facilities for Simulating from ODE-Based Models

Maintainer Matthew L. Fidler <matthew.fidler@gmail.com>

Depends R (>= 4.0.0)

Suggests Matrix, DT, covr, crayon, curl, data.table (>= 1.12.4), digest, dplyr (>= 0.8.0), ggrepel, gridExtra, htmltools, knitr, learnr, microbenchmark, nlme, remotes, rlang, rmarkdown, scales, shiny, stringi, symengine, testthat, tidyr, usethis, vdiffR (>= 1.0), withr, xgxr, pillar, tibble, units (>= 0.6-0), rconnect, devtools, patchwork, nlmixr2data

Imports PreciseSums (>= 0.3), Rcpp (>= 0.12.3), assertthat, backports, checkmate, cli (>= 2.0.0), dparser (>= 0.1.8), ggplot2, inline, lotri (>= 0.4.0), magrittr, memoise, methods, rex, qs, sys, tools, utils

Description Facilities for running simulations from ordinary differential equation ('ODE') models, such as pharmacometrics and other compartmental models. A compilation manager translates the ODE model into C, compiles it, and dynamically loads the object code into R for improved computational efficiency. An event table object facilitates the specification of complex dosing regimens (optional) and sampling schedules. NB: The use of this package requires both C and Fortran compilers, for details on their use with R please see Section 6.3, Appendix A, and Appendix D in the "R Administration and Installation" manual. Also the code is mostly released under GPL. The 'VODE' and 'LSODA' are in the public domain. The information is available in the inst/COPYRIGHTS.

BugReports <https://github.com/nlmixr2/rxode2/issues/>

NeedsCompilation yes

VignetteBuilder knitr

License GPL (>= 3)

URL <https://nlmixr2.github.io/rxode2/>,
<https://github.com/nlmixr2/rxode2/>

RoxygenNote 7.1.2

Biarch true

LinkingTo dparser (>= 1.3.1-0), PreciseSums (>= 0.3), RcppEigen (>= 0.3.3.3.0), RcppArmadillo (>= 0.9.300.2.0), sitmo, StanHeaders (>= 2.21.0), BH

Encoding UTF-8

LazyData true

Language en-US

Config/testthat/edition 3

Author Matthew L. Fidler [aut, cre] (<<https://orcid.org/0000-0001-8538-6691>>),
 Melissa Hallow [aut],
 Wenping Wang [aut],
 Zufar Mulyukov [ctb],
 Alan Hindmarsh [ctb],
 Awad H. Al-Mohy [ctb],
 Matt Dowle [ctb],
 Cleve Moler [ctb],
 David Cooley [ctb],
 Drew Schmidt [ctb],
 Arun Srinivasan [ctb],
 Ernst Hairer [ctb],
 Gerhard Wanner [ctb],
 Goro Fuji [ctb],
 Hadley Wickham [ctb],
 Jack Dongarra [ctb],
 Linda Petzold [ctb],
 Martin Maechler [ctb],
 Matteo Fasiolo [ctb],
 Morwenn [ctb],
 Nicholas J. Higham [ctb],
 Roger B. Sidje [ctb],
 Simon Frost [ctb],
 Kevin Ushey [ctb],
 Yu Feng [ctb]

Repository CRAN

Date/Publication 2022-05-17 17:50:02 UTC

R topics documented:

.copyUi	5
.handleSingleErrTypeNormOrTFoeciBase	6
.modelHandleModelLines	6
.quoteCallInfoLines	7
.rxLinCmtGen	8
.rxWithOptions	9

.rxWithWd	9
add.dosing	10
add.sampling	13
as.et	15
assertRxUi	16
cvPost	18
erf	21
et	21
etExpand	26
etRbind	27
etRep	30
etSeq	33
eventTable	36
gammap	38
gammapDer	39
gammapInv	39
gammaq	40
gammaqInv	41
genShinyApp.template	42
getRxThreads	44
ini.rxUi	45
logit	46
lowergamma	48
model.function	49
phi	50
plot.rxSolve	51
probit	51
rinvchisq	52
rxAllowUnload	53
rxAppendModel	54
rxAssignControlValue	55
rxAssignPtr	56
rxbeta	56
rxbinom	57
rxcauchy	59
rxCbindStudyIndividual	60
rxchisq	61
rxClean	63
rxCompile	63
rxControlUpdateSens	65
rxCreateCache	66
rxD	67
rxDelete	68
rxDerived	68
rxDfdy	70
rxEvid	71
rxexp	72
rxf	73

rxFun	74
rxgamma	76
rxgeom	77
rxGetControl	79
rxGetLin	79
rxGetrxode2	80
rxGetSeed	81
rxHtml	82
rxIndLinState	82
rxIndLinStrategy	83
rxIndLin_	83
rxInv	84
rxIsCurrent	85
rxLhs	85
rxLock	86
rxNorm	86
rxnorm	87
rxode2	88
rxOptExpr	96
rxord	97
rxParams	98
rxPkg	100
rxpois	101
rxPp	102
rxPreferredDistributionName	104
rxProgress	105
rxRandNV	106
rxRateDur	107
rxRemoveControl	107
rxRename	108
rxReservedKeywords	109
rxRmvn	109
rxS	112
rxSetControl	113
rxSetCovariateNamesForPiping	113
rxSetIni0	115
rxSetProd	115
rxSetProgressBar	116
rxSetSeed	116
rxSetSum	118
rxShiny	118
rxSimThetaOmega	120
rxSolve	123
rxStack	136
rxState	137
rxSumProdModel	138
rxSupportedFuns	138
rxSuppressMsg	139

rxSymInvChol	140
rxSyncOptions	141
rxSyntaxFunctions	141
rxT	142
rxTempDir	143
rxTheme	143
rxToSE	144
rxTrans	145
rxUiGet.cmtLines	146
rxunif	148
rxUnloadAll	150
rxUse	150
rxValidate	151
rxweibull	151
rxWinSetup	153
rxWithSeed	153
stat_amt	154
stat_cens	157
summary.rxode2	158
update.rxUi	159
uppergamma	159

Index **161**

.copyUi *This copies the rxode2 UI object so it can be modified*

Description

This copies the rxode2 UI object so it can be modified

Usage

.copyUi(ui)

Arguments

ui Original UI object

Value

Copied UI object

Author(s)

Matthew L. Fidler

```
.handleSingleErrTypeNormOrTFoeciBase
```

Handle the single error for normal or t distributions

Description

Handle the single error for normal or t distributions

Usage

```
.handleSingleErrTypeNormOrTFoeciBase(env, pred1)
```

Arguments

env	Environment for the parsed model
pred1	The data.frame of the current error

Value

A list of the lines added. The lines will contain

- rx_yj_ which is an integer that corresponds to the transformation type.
- rx_lambda_ is the transformation lambda
- rx_low_ The lower boundary of the transformation
- rx_hi_ The upper boundary of the transformation
- rx_pred_f_ The prediction function
- rx_pred_ The transformed prediction function
- rx_r_ The transformed variance

Author(s)

Matthew Fidler

```
.modelHandleModelLines
```

Handle model lines

Description

Handle model lines

Usage

```
.modelHandleModellines(  
  modellines,  
  rxui,  
  modifyIni = FALSE,  
  append = FALSE,  
  auto = TRUE,  
  envir  
)
```

Arguments

modellines	The model lines that are being considered
rxui	The rxode2 UI object
modifyIni	Should the ini() be considered
append	This is a boolean to determine if the lines are appended in piping. The possible values for this is: <ul style="list-style-type: none">• TRUE which is when the lines are appended to the model instead of replaced (default)• FALSE when the lines are replaced in the model• NA is when the lines are pre-pended to the model instead of replaced
auto	This boolean tells if piping automatically selects the parameters should be characterized as a population parameter, between subject variability, or a covariate. When TRUE this automatic selection occurs. When FALSE this automatic selection is turned off and everything is added as a covariate (which can be promoted to a parameter with the ini statement). By default this is TRUE, but it can be changed by options(rxode2.autoVarPiping=FALSE).
envir	Environment for evaluation

Value

New UI

Author(s)

Matthew L. Fidler

.quoteCallInfoLines *Returns quoted call information*

Description

Returns quoted call information

Usage

```
.quoteCallInfoLines(callInfo, envir = parent.frame())
```

Arguments

callInfo	Call information
envir	Environment for evaluation (if needed)

Value

Quote call information. for name=expression, change to name<-expression in quoted call list. For expressions that are within brackets ie {}, unlist the brackets as if they were called in one single sequence.

Author(s)

Matthew L. Fidler

.rxLinCmtGen

Internal function to generate the model variables for a linCmt() model

Description

Internal function to generate the model variables for a linCmt() model

Usage

```
.rxLinCmtGen(lenState, vars)
```

Arguments

lenState	Length of the state
vars	Variables in the model

Value

Model variables of expanded linCmt model

Author(s)

Matthew L. Fidler

.rxWithOptions *Temporarily set options then restore them while running code*

Description

Temporarily set options then restore them while running code

Usage

```
.rxWithOptions(ops, code)
```

Arguments

ops list of options that will be temporarily set for the code
code The code to run during the sink

Value

value of code

Examples

```
.rxWithOptions(list(digits = 21), {  
  print(pi)  
})  
  
print(pi)
```

.rxWithWd *Temporarily set options then restore them while running code*

Description

Temporarily set options then restore them while running code

Usage

```
.rxWithWd(wd, code)
```

Arguments

wd working directory to temporarily set the system to while evaluating the code
code The code to run during the sink

Value

value of code

Examples

```
.rxWithWd(tempdir(), {
  getwd()
})

getwd()
```

 add.dosing

Add dosing to eventTable

Description

This adds a dosing event to the event table. This is provided for piping syntax through magrittr. It can also be accessed by eventTable\$add.dosing(...)

Usage

```
add.dosing(
  eventTable,
  dose,
  nbr.doses = 1L,
  dosing.interval = 24,
  dosing.to = 1L,
  rate = NULL,
  amount.units = NA_character_,
  start.time = 0,
  do.sampling = FALSE,
  time.units = NA_character_,
  ...
)
```

Arguments

eventTable	eventTable object; When accessed from object it would be eventTable\$
dose	numeric scalar, dose amount in amount.units;
nbr.doses	integer, number of doses;
dosing.interval	required numeric scalar, time between doses in time.units, defaults to 24 of time.units="hours";
dosing.to	integer, compartment the dose goes into (first compartment by default);
rate	for infusions, the rate of infusion (default is NULL, for bolus dosing);

amount.units	optional string indicating the dosing units. Defaults to NA to indicate as per the original EventTable definition.
start.time	required dosing start time;
do.sampling	logical, should observation sampling records be added at the dosing times? Defaults to FALSE.
time.units	optional string indicating the time units. Defaults to "hours" to indicate as per the original EventTable definition.
...	Other parameters passed to <code>et()</code> .

Value

eventTable with updated dosing (note the event table will be updated anyway)

Author(s)

Matthew L. Fidler

Matthew L Fidler, Wenping Wang

References

Wang W, Hallow K, James D (2015). "A Tutorial on rxode2: Simulating Differential Equation Pharmacometric Models in R." *CPT: Pharmacometrics & Systems Pharmacology*, 5(1), 3-10. ISSN 2163-8306, <URL: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4728294/>>.

See Also

[eventTable](#), [add.sampling](#), [add.dosing](#), [et](#), [etRep](#), [etRbind](#), [rxode2](#)

Examples

```
library(rxode2)
library(units)

## Model from rxode2 tutorial
mod1 <-rxode2({
  KA=2.94E-01;
  CL=1.86E+01;
  V2=4.02E+01;
  Q=1.05E+01;
  V3=2.97E+02;
  Kin=1;
  Kout=1;
  EC50=200;
  C2 = centr/V2;
  C3 = peri/V3;
  d/dt(depot) =-KA*depot;
  d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3;
```

```

      d/dt(peri) =          Q*C2 - Q*C3;
      d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
    });

## These are making the more complex regimens of the rxode2 tutorial

## bid for 5 days
bid <- et(timeUnits="hr") %>%
  et(amt=10000,ii=12,until=set_units(5, "days"))

## qd for 5 days
qd <- et(timeUnits="hr") %>%
  et(amt=20000,ii=24,until=set_units(5, "days"))

## bid for 5 days followed by qd for 5 days

et <- seq(bid,qd) %>% et(seq(0,11*24,length.out=100));

bidQd <- rxSolve(mod1, et)

plot(bidQd, C2)

## Now Infusion for 5 days followed by oral for 5 days

## note you can dose to a named compartment instead of using the compartment number
infusion <- et(timeUnits = "hr") %>%
  et(amt=10000, rate=5000, ii=24, until=set_units(5, "days"), cmt="centr")

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(5, "days"), cmt="depot")

et <- seq(infusion,qd)

infusionQd <- rxSolve(mod1, et)

plot(infusionQd, C2)

## 2wk-on, 1wk-off

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- seq(qd, set_units(1,"weeks"), qd) %>%
  add.sampling(set_units(seq(0, 5.5,by=0.005),weeks))

wkOnOff <- rxSolve(mod1, et)

plot(wkOnOff, C2)

## You can also repeat the cycle easily with the rep function

qd <-et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

```

```
et <- etRep(qd, times=4, wait=set_units(1,"weeks")) %>%
  add.sampling(set_units(seq(0, 12.5,by=0.005),weeks))

repCycle4 <- rxSolve(mod1, et)

plot(repCycle4, C2)
```

add.sampling	<i>Add sampling to eventTable</i>
--------------	-----------------------------------

Description

This adds a dosing event to the event table. This is provided for piping syntax through magrittr. It can also be accessed by `eventTable$add.sampling()`

Usage

```
add.sampling(eventTable, time, time.units = NA)
```

Arguments

<code>eventTable</code>	An eventTable object. When accessed from object it would be <code>eventTable\$</code>
<code>time</code>	a vector of time values (in <code>time.units</code>).
<code>time.units</code>	an optional string specifying the time units. Defaults to the units specified when the EventTable was initialized.

Value

eventTable with updated sampling. (Note the event table will be updated even if you don't reassign the eventTable)

Author(s)

Matthew L Fidler, Wenping Wang

References

Wang W, Hallow K, James D (2015). "A Tutorial on rxode2: Simulating Differential Equation Pharmacometric Models in R." *CPT: Pharmacometrics & Systems Pharmacology*, 5(1), 3-10. ISSN 2163-8306, <URL: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4728294/>>.

See Also

[eventTable](#), [add.sampling](#), [add.dosing](#), [et](#), [etRep](#), [etRbind](#), [rxode2](#)

Examples

```

library(rxode2)
library(units)

## Model from rxode2 tutorial
mod1 <-rxode2({
  KA=2.94E-01;
  CL=1.86E+01;
  V2=4.02E+01;
  Q=1.05E+01;
  V3=2.97E+02;
  Kin=1;
  Kout=1;
  EC50=200;
  C2 = centr/V2;
  C3 = peri/V3;
  d/dt(depot) =-KA*depot;
  d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3;
  d/dt(peri) = Q*C2 - Q*C3;
  d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
});

## These are making the more complex regimens of the rxode2 tutorial

## bid for 5 days
bid <- et(timeUnits="hr") %>%
  et(amt=10000,ii=12,until=set_units(5, "days"))

## qd for 5 days
qd <- et(timeUnits="hr") %>%
  et(amt=20000,ii=24,until=set_units(5, "days"))

## bid for 5 days followed by qd for 5 days

et <- seq(bid,qd) %>% et(seq(0,11*24,length.out=100));

bidQd <- rxSolve(mod1, et)

plot(bidQd, C2)

## Now Infusion for 5 days followed by oral for 5 days

## note you can dose to a named compartment instead of using the compartment number
infusion <- et(timeUnits = "hr") %>%
  et(amt=10000, rate=5000, ii=24, until=set_units(5, "days"), cmt="centr")

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(5, "days"), cmt="depot")

```

```

et <- seq(infusion,qd)

infusionQd <- rxSolve(mod1, et)

plot(infusionQd, C2)

## 2wk-on, 1wk-off

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- seq(qd, set_units(1,"weeks"), qd) %>%
  add.sampling(set_units(seq(0, 5.5,by=0.005),weeks))

wkOnOff <- rxSolve(mod1, et)

plot(wkOnOff, C2)

## You can also repeat the cycle easily with the rep function

qd <-et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- etRep(qd, times=4, wait=set_units(1,"weeks")) %>%
  add.sampling(set_units(seq(0, 12.5,by=0.005),weeks))

repCycle4 <- rxSolve(mod1, et)

plot(repCycle4, C2)

```

as.et

Coerce object to data.frame

Description

Coerce object to data.frame

Usage

```
as.et(x, ...)
```

```
## Default S3 method:
as.et(x, ...)
```

Arguments

x	Object to coerce to et.
...	Other parameters

Value

An event table

assertRxUi	<i>Assert properties of the rxUi models</i>
------------	---

Description

Assert properties of the rxUi models

Usage

```
assertRxUi(model, extra = "", .var.name = .vname(model))
assertRxUiPrediction(model, extra = "", .var.name = .vname(model))
assertRxUiSingleEndpoint(model, extra = "", .var.name = .vname(model))
assertRxUiTransformNormal(model, extra = "", .var.name = .vname(model))
assertRxUiNormal(model, extra = "", .var.name = .vname(model))
assertRxUiMuRefOnly(model, extra = "", .var.name = .vname(model))
assertRxUiEstimatedResiduals(model, extra = "", .var.name = .vname(model))
assertRxUiPopulationOnly(model, extra = "", .var.name = .vname(model))
assertRxUiMixedOnly(model, extra = "", .var.name = .vname(model))
assertRxUiRandomOnIdOnly(model, extra = "", .var.name = .vname(model))
```

Arguments

model	Model to check
extra	Extra text to append to the error message (like "for focei")
.var.name	[character(1)] Name of the checked object to print in assertions. Defaults to the heuristic implemented in vname .

Details

These functions have different types of assertions

- `assertRxUi` – Make sure this is a proper rxode2 model (if not throw error)
- `assertRxUiSingleEndpoint` – Make sure the rxode2 model is only a single endpoint model (if not throw error)

- `assertRxUiTransformNormal` – This needs to be a normal or transformably normal residual distribution
- `assertRxUiNormal` – This needs to be a normal residual distribution
- `assertRxUiEstimatedResiduals` – This makes sure that the residual error parameter are estimated (not modeled).
- `assertRxUiPopulationOnly` – This makes sure the model is the population only model (no mixed effects)
- `assertRxUiMixedOnly` – This makes sure the model is a mixed effect model (not a population effect)
- `assertRxUiPrediction` – This makes sure the model has predictions
- `assertRxUiMuRefOnly` – This make sure that all the parameters are mu-referenced
- `assertRxUiRandomOnIdOnly` – This makes sure there is only random effects at the ID level

Value

the rxUi model

Author(s)

Matthew L. Fidler

Examples

```
one.cmt <- function() {
  ini({
    ## You may label each parameter with a comment
    tka <- 0.45 # Ka
    tcl <- log(c(0, 2.7, 100)) # Log Cl
    ## This works with interactive models
    ## You may also label the preceding line with label("label text")
    tv <- 3.45; label("log V")
    ## the label("Label name") works with all models
    eta.ka ~ 0.6
    eta.cl ~ 0.3
    eta.v ~ 0.1
    add.sd <- 0.7
  })
  model({
    ka <- exp(tka + eta.ka)
    cl <- exp(tcl + eta.cl)
    v <- exp(tv + eta.v)
    linCmt() ~ add(add.sd)
  })
}

assertRxUi(one.cmt)
# assertRxUi(rnorm) # will fail
```

```
assertRxUiSingleEndpoint(one.cmt)
```

cvPost	<i>Sample a covariance Matrix from the Posterior Inverse Wishart distribution.</i>
--------	--

Description

Note this Inverse wishart rescaled to match the original scale of the covariance matrix.

Usage

```
cvPost(
  nu,
  omega,
  n = 1L,
  omegaIsChol = FALSE,
  returnChol = FALSE,
  type = c("invWishart", "lkj", "separation"),
  diagXformType = c("log", "identity", "variance", "nlmixrSqrt", "nlmixrLog",
    "nlmixrIdentity")
)
```

Arguments

nu	Degrees of Freedom (Number of Observations) for covariance matrix simulation.
omega	Either the estimate of covariance matrix or the estimated standard deviations in matrix form each row forming the standard deviation simulated values
n	Number of Matrices to sample. By default this is 1. This is only useful when omega is a matrix. Otherwise it is determined by the number of rows in the input omega matrix of standard deviations
omegaIsChol	is an indicator of if the omega matrix is in the Cholesky decomposition. This is only used when codetype="invWishart"
returnChol	Return the Cholesky decomposition of the covariance matrix sample. This is only used when codetype="invWishart"
type	The type of covariance posterior that is being simulated. This can be: <ul style="list-style-type: none"> • <code>invWishart</code> The posterior is an inverse wishart; This allows for correlations between parameters to be modeled. All the uncertainty in the parameter is captured in the degrees of freedom parameter. • <code>lkj</code> The posterior separates the standard deviation estimates (modeled outside and provided in the omega argument) and the correlation estimates. The correlation estimate is simulated with the <code>rLKJ1()</code>. This simulation uses the relationship $\eta = (\nu - 1) / 2$. This is relationship based on the proof of

the relationship between the restricted LKJ-distribution and inverse wishart distribution (XXXXXX). Once the correlation posterior is calculated, the estimated standard deviations are then combined with the simulated correlation matrix to create the covariance matrix.

- `separation` Like the `lkj` option, this separates out the estimation of the correlation and standard deviation. Instead of using the LKJ distribution to simulate the correlation, it simulates the inverse wishart of the identity matrix and converts the result to a correlation matrix. This correlation matrix is then used with the standard deviation to calculate the simulated covariance matrix.

`diagXformType` Diagonal transformation type. These could be:

- `log` The standard deviations are log transformed, so the actual standard deviations are $\exp(\omega)$
- `identity` The standard deviations are not transformed. The standard deviations are not transformed; They should be positive.
- `variance` The variances are specified in the ω matrix; They are transformed into standard deviations.
- `nlmixrSqrt` These standard deviations come from an `nlmixr` ω matrix where $\text{diag}(\text{chol}(\text{inv}(\omega))) = x^2$
- `nlmixrLog` These standard deviations come from a `nlmixr` ω matrix where $\text{diag}(\text{chol}(\text{solve}(\omega))) = \exp(x)$
- `nlmixrIdentity` These standard deviations come from a `nlmixr` ω matrix where $\text{diag}(\text{chol}(\text{solve}(\omega))) = x$

The `nlmixr` transformations only make sense when there is no off-diagonal correlations modeled.

Details

If your covariance matrix is a 1x1 matrix, this uses an scaled inverse chi-squared which is equivalent to the Inverse Wishart distribution in the uni-directional case.

In general, the `separation` strategy is preferred for diagonal matrices. If the dimension of the matrix is below 10, `lkj` is numerically faster than `separation` method. However, the `lkj` method has densities too close to zero (XXXX) when the dimension is above 10. In that case, though computationally more expensive `separation` method performs better.

For matrices with modeled covariances, the easiest method to use is the inverse Wishart which allows the simulation of correlation matrices (XXXX). This method is more well suited for well behaved matrices, that is the variance components are not too low or too high. When modeling non-linear mixed effects modeling matrices with too high or low variances are considered sub-optimal in describing a system. With these rules in mind, it is reasonable to use the inverse Wishart.

Value

a matrix (n=1) or a list of matrices (n > 1)

Author(s)

Matthew L.Fidler & Wenping Wang

References

Alvarez I, Niemi J and Simpson M. (2014) *Bayesian Inference for a Covariance Matrix*. Conference on Applied Statistics in Agriculture. <https://newprairiepress.org/cgi/viewcontent.cgi?article=1004&context=agstatconference>

Wangl Z, Wu Y, and Chu H. (2018) *On Equivalence of the LKJ distribution and the restricted Wishart distribution*. arXiv:1809.04746

Examples

```
## Sample a single covariance.
draw1 <- cvPost(3, matrix(c(1, .3, .3, 1), 2, 2))

## Sample 3 covariances
set.seed(42)
draw3 <- cvPost(3, matrix(c(1, .3, .3, 1), 2, 2), n = 3)

## Sample 3 covariances, but return the cholesky decomposition
set.seed(42)
draw3c <- cvPost(3, matrix(c(1, .3, .3, 1), 2, 2), n = 3, returnChol = TRUE)

## Sample 3 covariances with lognormal standard deviations via LKJ
## correlation sample
cvPost(3, sapply(1:3, function(...) {
  rnorm(10)
}), type = "lkj")

## or return cholesky decomposition
cvPost(3, sapply(1:3, function(...) {
  rnorm(10)
}),
type = "lkj",
returnChol = TRUE
)

## Sample 3 covariances with lognormal standard deviations via separation
## strategy using inverse Wishart correlation sample
cvPost(3, sapply(1:3, function(...) {
  rnorm(10)
}), type = "separation")

## or returning the cholesky decomposition
cvPost(3, sapply(1:3, function(...) {
  rnorm(10)
}),
type = "separation",
returnChol = TRUE
)
```

erf *Error function*

Description

Error function

Usage

erf(x)

Arguments

x vector or real values

Value

erf of x

Author(s)

Matthew L. Fidler

Examples

```
erf(1.0)
```

et *Event Table Function*

Description

Event Table Function

Usage

```
et(x, ..., envir = parent.frame())
```

```
## S3 method for class 'rxode2'  
et(x, ..., envir = parent.frame())
```

```
## S3 method for class 'rxSolve'  
et(x, ..., envir = parent.frame())
```

```
## S3 method for class 'rxParams'  
et(x, ..., envir = parent.frame())
```

```
## Default S3 method:
et(
  x,
  ...,
  time,
  amt,
  evid,
  cmt,
  ii,
  addl,
  ss,
  rate,
  dur,
  until,
  id,
  amountUnits,
  timeUnits,
  addSampling,
  envir = parent.frame(),
  by = NULL,
  length.out = NULL
)
```

Arguments

x	This is the first argument supplied to the event table. This is named to allow et to be used in a pipe-line with arbitrary objects.
...	Times or event tables. They can also be one of the named arguments below.
envir	the environment in which expr is to be evaluated. May also be NULL, a list, a data frame, a pairlist or an integer as specified to sys.call .
time	Time is the time of the dose or the sampling times. This can also be unspecified and is determined by the object type (list or numeric/integer).
amt	Amount of the dose. If specified, this assumes a dosing record, instead of a sampling record.
evid	Event ID; This can be:

Numeric Value	Description
0	An observation. This can also be specified as <code>evid=obs</code>
1	A dose observation. This can also be specified as <code>evid=dose</code>
2	A non-dose event. This can also be specified as <code>evid=other</code>
3	A reset event. This can also be specified as <code>evid=reset</code> .
4	Dose and reset event. This can also be specified as <code>evid=doseReset</code> or <code>evid=resetDose</code>

Note a reset event resets all the compartment values to zero and turns off all infusions.

cmt Compartment name or number. If a number, this is an integer starting at 1. Negative compartments turn off a compartment. If the compartment is a name, the compartment name is changed to the correct state/compartment number before running the simulation. For a compartment named "-cmt" the compartment is turned off.

Can also specify `cmt` as `dosing.to`,
`dose.to`, `doseTo`, `dosingTo`, and
`state`.

ii When specifying a dose, this is the inter-dose interval for **ss**, **addl** and **until** options (described below).

addl The number of additional doses at a inter-dose interval after one dose.

ss Steady state flag; It can be one of:

Value	Description
0	This dose is not a steady state dose
1	This dose is a steady state dose with the between/inter-dose interval of ii
2	Superposition steady state

When **ss=2** the steady state dose that uses the super-position principle to allow more complex steady states, like 10 mg in the morning and 20 mg at night, or dosing at 8 am 12 pm and 8 pm instead of every 12 hours. Since it uses the super positioning principle, it only makes sense when you know the kinetics are linear.

All other values of **SS** are currently invalid.

rate When positive, this is the rate of infusion. Otherwise:

Value	Description
0	No infusion is on this record
-1	Modeled rate (in <code>rxode2:rate(cmt) =</code>); Can be <code>et(rate=model)</code> .
-2	Modeled duration (in <code>rxode2: dur(cmt) =</code>); Can be <code>et(dur=model)</code> or <code>et(rate=dur)</code> .

When a modeled bioavailability is applied to positive rates ($rate > 0$), the duration of infusion is changed. This is because the data specify the rate and amount, the only thing that modeled bioavailability can affect is duration.

If instead you want the modeled bioavailability to increase the rate of infusion instead of the duration of infusion, specify the **dur** instead or model the duration with **rate=2**.

dur Duration of infusion. When **amt** and **dur** are specified the rate is calculated from the two data items. When **dur** is specified instead of **rate**, the bioavailability changes will increase rate instead of duration.

until This is the time until the dosing should end. It can be an easier way to figure out how many additional doses are needed over your sampling period.

id A integer vector of IDs to add or remove from the event table. If the event table

	is identical for each ID, then you may expand it to include all the IDs in this vector. All the negative IDs in this vector will be removed.
amountUnits	The units for the dosing records (amt)
timeUnits	The units for the time records (time)
addSampling	This is a boolean indicating if a sampling time should be added at the same time as a dosing time. By default this is FALSE.
by	When there are no observations in the event table, this is the amount to increment for the observations between from and to.
length.out	The number of observations to create if there isn't any observations in the event table. By default this is 200.

Value

A new event table

Author(s)

Matthew L Fidler, Wenping Wang

References

Wang W, Hallow K, James D (2015). "A Tutorial on rxode2: Simulating Differential Equation Pharmacometric Models in R." *CPT: Pharmacometrics & Systems Pharmacology*, 5(1), 3-10. ISSN 2163-8306, <URL: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4728294/>>.

See Also

[eventTable](#), [add.sampling](#), [add.dosing](#), [et](#), [etRep](#), [etRbind](#), [rxode2](#)

Examples

```
library(rxode2)
library(units)

## Model from rxode2 tutorial
mod1 <-rxode2({
  KA=2.94E-01;
  CL=1.86E+01;
  V2=4.02E+01;
  Q=1.05E+01;
  V3=2.97E+02;
  Kin=1;
  Kout=1;
  EC50=200;
  C2 = centr/V2;
  C3 = peri/V3;
  d/dt(depot) =-KA*depot;
```



```

    d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3;
    d/dt(peri) = Q*C2 - Q*C3;
    d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
  });

## These are making the more complex regimens of the rxode2 tutorial

## bid for 5 days
bid <- et(timeUnits="hr") %>%
  et(amt=10000,ii=12,until=set_units(5, "days"))

## qd for 5 days
qd <- et(timeUnits="hr") %>%
  et(amt=20000,ii=24,until=set_units(5, "days"))

## bid for 5 days followed by qd for 5 days

et <- seq(bid,qd) %>% et(seq(0,11*24,length.out=100));

bidQd <- rxSolve(mod1, et)

plot(bidQd, C2)

## Now Infusion for 5 days followed by oral for 5 days

## note you can dose to a named compartment instead of using the compartment number
infusion <- et(timeUnits = "hr") %>%
  et(amt=10000, rate=5000, ii=24, until=set_units(5, "days"), cmt="centr")

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(5, "days"), cmt="depot")

et <- seq(infusion,qd)

infusionQd <- rxSolve(mod1, et)

plot(infusionQd, C2)

## 2wk-on, 1wk-off

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- seq(qd, set_units(1,"weeks"), qd) %>%
  add.sampling(set_units(seq(0, 5.5,by=0.005),weeks))

wkOnOff <- rxSolve(mod1, et)

plot(wkOnOff, C2)

## You can also repeat the cycle easily with the rep function

qd <-et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

```

```
et <- etRep(qd, times=4, wait=set_units(1,"weeks")) %>%
  add.sampling(set_units(seq(0, 12.5,by=0.005),weeks))

repCycle4 <- rxSolve(mod1, et)

plot(repCycle4, C2)
```

etExpand

Expand additional doses

Description

Expand additional doses

Usage

```
etExpand(et)
```

Arguments

et Event table to expand additional doses for.

Value

New event table with addl doses expanded

Author(s)

Matthew Fidler

Examples

```
ev <- et(amt = 3, ii = 24, until = 240)
print(ev)
etExpand(ev) # expands event table, but doesn't modify it

print(ev)

ev$expand() ## Expands the current event table and saves it in ev
```

etRbind

Combining event tables

Description

Combining event tables

Usage

```
etRbind(
  ...,
  samples = c("use", "clear"),
  waitII = c("smart", "+ii"),
  id = c("merge", "unique")
)

## S3 method for class 'rxEt'
rbind(..., deparse.level = 1)
```

Arguments

...	The event tables and optionally time between event tables, called waiting times in this help document.
samples	How to handle samples when repeating an event table. The options are: <ul style="list-style-type: none"> • "clear" Clear sampling records before combining the datasets • "use" Use the sampling records when combining the datasets
waitII	This determines how waiting times between events are handled. The options are: <ul style="list-style-type: none"> • "smart" This "smart" handling of waiting times is the default option. In this case, if the waiting time is above the last observed inter-dose interval in the first combined event table, then the actual time between doses is given by the wait time. If it is smaller than the last observed inter-dose interval, the time between event tables is given by the inter-dose interval + the waiting time between event tables. • "+ii" In this case, the wait time is added to the inter-dose interval no matter the length of the wait time or inter-dose interval
id	This is how rbind will handle IDs. There are two different types of options: <ul style="list-style-type: none"> • merge with id="merge", the IDs are merged together, overlapping IDs would be merged into a single event table. • unique with id="unique", the IDs will be renumbered so that the IDs in all the event tables are not overlapping.
deparse.level	The deparse.level of a traditional rbind is ignored.

Value

An event table

Author(s)

Matthew L Fidler

Matthew L Fidler, Wenping Wang

References

Wang W, Hallow K, James D (2015). "A Tutorial on rxode2: Simulating Differential Equation Pharmacometric Models in R." *CPT: Pharmacometrics & Systems Pharmacology*, 5(1), 3-10. ISSN 2163-8306, <URL: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4728294/>>.

See Also

[eventTable](#), [add.sampling](#), [add.dosing](#), [et](#), [etRep](#), [etRbind](#), [rxode2](#)

Examples

```
library(rxode2)
library(units)

## Model from rxode2 tutorial
mod1 <-rxode2({
  KA=2.94E-01;
  CL=1.86E+01;
  V2=4.02E+01;
  Q=1.05E+01;
  V3=2.97E+02;
  Kin=1;
  Kout=1;
  EC50=200;
  C2 = centr/V2;
  C3 = peri/V3;
  d/dt(depot) =-KA*depot;
  d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3;
  d/dt(peri) = Q*C2 - Q*C3;
  d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
});

## These are making the more complex regimens of the rxode2 tutorial

## bid for 5 days
bid <- et(timeUnits="hr") %>%
  et(amt=10000,ii=12,until=set_units(5, "days"))

## qd for 5 days
```

```
qd <- et(timeUnits="hr") %>%
  et(amt=20000,ii=24,until=set_units(5, "days"))

## bid for 5 days followed by qd for 5 days

et <- seq(bid,qd) %>% et(seq(0,11*24,length.out=100));

bidQd <- rxSolve(mod1, et)

plot(bidQd, C2)

## Now Infusion for 5 days followed by oral for 5 days

## note you can dose to a named compartment instead of using the compartment number
infusion <- et(timeUnits = "hr") %>%
  et(amt=10000, rate=5000, ii=24, until=set_units(5, "days"), cmt="centr")

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(5, "days"), cmt="depot")

et <- seq(infusion,qd)

infusionQd <- rxSolve(mod1, et)

plot(infusionQd, C2)

## 2wk-on, 1wk-off

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- seq(qd, set_units(1,"weeks"), qd) %>%
  add.sampling(set_units(seq(0, 5.5,by=0.005),weeks))

wkOnOff <- rxSolve(mod1, et)

plot(wkOnOff, C2)

## You can also repeat the cycle easily with the rep function

qd <-et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- etRep(qd, times=4, wait=set_units(1,"weeks")) %>%
  add.sampling(set_units(seq(0, 12.5,by=0.005),weeks))

repCycle4 <- rxSolve(mod1, et)

plot(repCycle4, C2)
```

etRep

Repeat an rxode2 event table

Description

Repeat an rxode2 event table

Usage

```
etRep(
  x,
  times = 1,
  length.out = NA,
  each = NA,
  n = NULL,
  wait = 0,
  id = integer(0),
  samples = c("clear", "use"),
  waitII = c("smart", "+ii"),
  ii = 24
)

## S3 method for class 'rxEt'
rep(x, ...)
```

Arguments

x	An rxode2 event table
times	Number of times to repeat the event table
length.out	Invalid with rxode2 event tables, will throw an error if used.
each	Invalid with rxode2 event tables, will throw an error if used.
n	The number of times to repeat the event table. Overrides times.
wait	Waiting time between each repeated event table. By default there is no waiting, or wait=0
id	A integer vector of IDs to add or remove from the event table. If the event table is identical for each ID, then you may expand it to include all the IDs in this vector. All the negative IDs in this vector will be removed.
samples	How to handle samples when repeating an event table. The options are: <ul style="list-style-type: none"> • "clear" Clear sampling records before combining the datasets • "use" Use the sampling records when combining the datasets
waitII	This determines how waiting times between events are handled. The options are:

- "smart" This "smart" handling of waiting times is the default option. In this case, if the waiting time is above the last observed inter-dose interval in the first combined event table, then the actual time between doses is given by the wait time. If it is smaller than the last observed inter-dose interval, the time between event tables is given by the inter-dose interval + the waiting time between event tables.
 - "+i i" In this case, the wait time is added to the inter-dose interval no matter the length of the wait time or inter-dose interval
- ii When specifying a dose, this is the inter-dose interval for `ss`, `add1` and `until` options (described below).
- ... Times or event tables. They can also be one of the named arguments below.

Value

An event table

Author(s)

Matthew L Fidler, Wenping Wang

References

Wang W, Hallow K, James D (2015). "A Tutorial on rxode2: Simulating Differential Equation Pharmacometric Models in R." *CPT: Pharmacometrics & Systems Pharmacology*, 5(1), 3-10. ISSN 2163-8306, <URL: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4728294/>>.

See Also

[eventTable](#), [add.sampling](#), [add.dosing](#), [et](#), [etRep](#), [etRbind](#), [rxode2](#)

Examples

```
library(rxode2)
library(units)

## Model from rxode2 tutorial
mod1 <-rxode2({
  KA=2.94E-01;
  CL=1.86E+01;
  V2=4.02E+01;
  Q=1.05E+01;
  V3=2.97E+02;
  Kin=1;
  Kout=1;
  EC50=200;
  C2 = centr/V2;
  C3 = peri/V3;
```

```

d/dt(depot) =-KA*depot;
d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3;
d/dt(peri) = Q*C2 - Q*C3;
d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
});

## These are making the more complex regimens of the rxode2 tutorial

## bid for 5 days
bid <- et(timeUnits="hr") %>%
  et(amt=10000,ii=12,until=set_units(5, "days"))

## qd for 5 days
qd <- et(timeUnits="hr") %>%
  et(amt=20000,ii=24,until=set_units(5, "days"))

## bid for 5 days followed by qd for 5 days

et <- seq(bid,qd) %>% et(seq(0,11*24,length.out=100));

bidQd <- rxSolve(mod1, et)

plot(bidQd, C2)

## Now Infusion for 5 days followed by oral for 5 days

## note you can dose to a named compartment instead of using the compartment number
infusion <- et(timeUnits = "hr") %>%
  et(amt=10000, rate=5000, ii=24, until=set_units(5, "days"), cmt="centr")

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(5, "days"), cmt="depot")

et <- seq(infusion,qd)

infusionQd <- rxSolve(mod1, et)

plot(infusionQd, C2)

## 2wk-on, 1wk-off

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- seq(qd, set_units(1,"weeks"), qd) %>%
  add.sampling(set_units(seq(0, 5.5,by=0.005),weeks))

wkOnOff <- rxSolve(mod1, et)

plot(wkOnOff, C2)

## You can also repeat the cycle easily with the rep function

```



```

qd <-et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- etRep(qd, times=4, wait=set_units(1,"weeks")) %>%
  add.sampling(set_units(seq(0, 12.5,by=0.005),weeks))

repCycle4 <- rxSolve(mod1, et)

plot(repCycle4, C2)

```

etSeq *Sequence of event tables*

Description

This combines a sequence of event tables.

Usage

```

etSeq(..., samples = c("clear", "use"), waitII = c("smart", "+ii"), ii = 24)

## S3 method for class 'rxEt'
seq(...)

```

Arguments

...	The event tables and optionally time between event tables, called waiting times in this help document.
samples	How to handle samples when repeating an event table. The options are: <ul style="list-style-type: none"> • "clear" Clear sampling records before combining the datasets • "use" Use the sampling records when combining the datasets
waitII	This determines how waiting times between events are handled. The options are: <ul style="list-style-type: none"> • "smart" This "smart" handling of waiting times is the default option. In this case, if the waiting time is above the last observed inter-dose interval in the first combined event table, then the actual time between doses is given by the wait time. If it is smaller than the last observed inter-dose interval, the time between event tables is given by the inter-dose interval + the waiting time between event tables. • "+ii" In this case, the wait time is added to the inter-dose interval no matter the length of the wait time or inter-dose interval
ii	If there was no inter-dose intervals found in the event table, assume that the interdose interval is given by this ii value. By default this is 24.

Details

This sequences all the event tables in added in the argument list By default when combining the event tables the offset is at least by the last inter-dose interval in the prior event table (or *i*). If you separate any of the event tables by a number, the event tables will be separated at least the wait time defined by that number or the last inter-dose interval.

Value

An event table

Author(s)

Matthew L Fidler, Wenping Wang

References

Wang W, Hallow K, James D (2015). "A Tutorial on rxode2: Simulating Differential Equation Pharmacometric Models in R." *CPT: Pharmacometrics & Systems Pharmacology*, 5(1), 3-10. ISSN 2163-8306, <URL: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4728294/>>.

See Also

[eventTable](#), [add.sampling](#), [add.dosing](#), [et](#), [etRep](#), [etRbind](#), [rxode2](#)

Examples

```
library(rxode2)
library(units)

## Model from rxode2 tutorial
mod1 <-rxode2({
  KA=2.94E-01;
  CL=1.86E+01;
  V2=4.02E+01;
  Q=1.05E+01;
  V3=2.97E+02;
  Kin=1;
  Kout=1;
  EC50=200;
  C2 = centr/V2;
  C3 = peri/V3;
  d/dt(depot) =-KA*depot;
  d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3;
  d/dt(peri) = Q*C2 - Q*C3;
  d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
});

## These are making the more complex regimens of the rxode2 tutorial
```

```

## bid for 5 days
bid <- et(timeUnits="hr") %>%
  et(amt=10000,ii=12,until=set_units(5, "days"))

## qd for 5 days
qd <- et(timeUnits="hr") %>%
  et(amt=20000,ii=24,until=set_units(5, "days"))

## bid for 5 days followed by qd for 5 days

et <- seq(bid,qd) %>% et(seq(0,11*24,length.out=100));

bidQd <- rxSolve(mod1, et)

plot(bidQd, C2)

## Now Infusion for 5 days followed by oral for 5 days

## note you can dose to a named compartment instead of using the compartment number
infusion <- et(timeUnits = "hr") %>%
  et(amt=10000, rate=5000, ii=24, until=set_units(5, "days"), cmt="centr")

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(5, "days"), cmt="depot")

et <- seq(infusion,qd)

infusionQd <- rxSolve(mod1, et)

plot(infusionQd, C2)

## 2wk-on, 1wk-off

qd <- et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- seq(qd, set_units(1,"weeks"), qd) %>%
  add.sampling(set_units(seq(0, 5.5,by=0.005),weeks))

wkOnOff <- rxSolve(mod1, et)

plot(wkOnOff, C2)

## You can also repeat the cycle easily with the rep function

qd <-et(timeUnits = "hr") %>% et(amt=10000, ii=24, until=set_units(2, "weeks"), cmt="depot")

et <- etRep(qd, times=4, wait=set_units(1,"weeks")) %>%
  add.sampling(set_units(seq(0, 12.5,by=0.005),weeks))

repCycle4 <- rxSolve(mod1, et)

```

```
plot(repCycle4, C2)
```

eventTable	<i>Create an event table object</i>
------------	-------------------------------------

Description

Initializes an object of class 'EventTable' with methods for adding and querying dosing and observation records

Usage

```
eventTable(amount.units = NA, time.units = NA)
```

Arguments

`amount.units` string denoting the amount dosing units, e.g., "mg", "ug". Default to NA to denote unspecified units. It could also be a solved rxode2 object. In that case, `eventTable(obj)` returns the eventTable that was used to solve the rxode2 object.

`time.units` string denoting the time units, e.g., "hours", "days". Default to "hours".
 An eventTable is an object that consists of a data.frame storing ordered time-stamped events of an (unspecified) PK/PD dynamic system, units (strings) for dosing and time records, plus a list of functions to add and extract event records. Currently, events can be of two types: dosing events that represent inputs to the system and sampling time events that represent observations of the system with 'amount.units' and 'time.units', respectively.

Value

A modified data.frame with the following accessible functions:

- `get.EventTable()` returns the current event table
- `add.dosing()` adds dosing records to the event table.
- `get.dosing()` returns a data.frame of dosing records.
- `clear.dosing()` clears or deletes all dosing from event table
- `add.sampling()` adds sampling time observation records to the event table.
- `get.sampling()` returns a data.frame of sampled observation records.
- `clear.sampling()` removes all sampling from event table.
- `get.obs.rec()` returns a logical vector indicating whether each event record represents an observation or not.
- `get.nobs()` returns the number of observation (not dosing) records.
- `get.units()` returns a two-element character vector with the dosing and time units, respectively

- `copy()` makes a copy of the current event table. To create a copy of an event table object use `qd2 <- qd$copy()`
- `expand()` Expands the event table for multi-subject solving. This is done by `qd$expand(400)` for a 400 subject data expansion

Author(s)

Matthew Fidler, Melissa Hallow and Wenping Wang

See Also

[et\(\)](#), [rxode2\(\)](#)

Examples

```
# create dosing and observation (sampling) events
# QD 50mg dosing, 5 days followed by 25mg 5 days
#
qd <- eventTable(amount.units = "mg", time.units = "days")
#
qd$add.dosing(dose = 50, nbr.doses = 5, dosing.interval = 1, do.sampling = FALSE)
#
# sample the system's drug amounts hourly the first day, then every 12 hours
# for the next 4 days
qd$add.sampling(seq(from = 0, to = 1, by = 1 / 24))
qd$add.sampling(seq(from = 1, to = 5, by = 12 / 24))
#
# print(qd$get.dosing())      # table of dosing records
print(qd$get.nobs()) # number of observation (not dosing) records
#
# BID dosing, 5 days
bid <- eventTable("mg", "days") # only dosing
bid$add.dosing(
  dose = 10000, nbr.doses = 2 * 5,
  dosing.interval = 12, do.sampling = FALSE
)
#
# Use the copy() method to create a copy (clone) of an existing
# event table (simple assignments just create a new reference to
# the same event table object (closure)).
#
bid.ext <- bid$copy() # three-day extension for a 2nd cohort
bid.ext$add.dosing(
  dose = 5000, nbr.doses = 2 * 3,
  start.time = 120, dosing.interval = 12, do.sampling = FALSE
)

# You can also use the Piping operator to create a table

qd2 <- eventTable(amount.units = "mg", time.units = "days") %>%
  add.dosing(dose = 50, nbr.doses = 5, dosing.interval = 1, do.sampling = FALSE) %>%
  add.sampling(seq(from = 0, to = 1, by = 1 / 24)) %>%
```

```
  add.sampling(seq(from = 1, to = 5, by = 12 / 24))
# print(qd2$get.dosing())      # table of dosing records
print(qd2$get.nobs()) # number of observation (not dosing) records

# Note that piping with %>% will update the original table.

qd3 <- qd2 %>% add.sampling(seq(from = 5, to = 10, by = 6 / 24))
print(qd2$get.nobs())
print(qd3$get.nobs())
```

gammap

Gammap: normalized lower incomplete gamma function

Description

This is the `gamma_p` from the boost library

Usage

```
gammap(a, z)
```

Arguments

a	The numeric 'a' parameter in the normalized lower incomplete gamma
z	The numeric 'z' parameter in the normalized lower incomplete gamma

Details

The gamma p function is given by:

$$\text{gammap} = \text{lowergamma}(a, z) / \text{gamma}(a)$$

Value

gammap results

Author(s)

Matthew L. Fidler

Examples

```
gammap(1, 3)
gammap(1:3, 3)
gammap(1, 1:3)
```

gammapDer	<i>gammapDer: derivative of gammap</i>
-----------	--

Description

This is the `gamma_p_derivative` from the boost library

Usage

```
gammapDer(a, z)
```

Arguments

a	The numeric 'a' parameter in the upper incomplete gamma
z	The numeric 'z' parameter in the upper incomplete gamma

Value

lowergamma results

Author(s)

Matthew L. Fidler

Examples

```
gammapDer(1:3, 3)
```

```
gammapDer(1, 1:3)
```

gammapInv	<i>gammapInv and gammapInva: Inverses of normalized gammap function</i>
-----------	---

Description

`gammapInv` and `gammapInva`: Inverses of normalized gammap function

Usage

```
gammapInv(a, p)
```

```
gammapInva(x, p)
```

Arguments

a	The numeric 'a' parameter in the upper incomplete gamma
p	The numeric 'p' parameter in the upper incomplete gamma
x	The numeric 'x' parameter in the upper incomplete gamma

Details

With the equation:

$$p = \text{gammap}(a, x)$$

The 'gammapInv' function returns a value 'x' that satisfies the equation above

The 'gammapInva' function returns a value 'q' that satisfies the equation above

NOTE: gammapInva is slow

Value

inverse gammap results

Author(s)

Matthew L. Fidler

Examples

```
gammapInv(1:3, 0.5)
gammapInv(1, 1:3 / 3.1)
gammapInv(1:3, 1:3 / 3.1)
gammapInva(1:3, 1:3 / 3.1)
```

gammaq

Gammaq: normalized upper incomplete gamma function

Description

This is the gamma_q from the boost library

Usage

```
gammaq(a, z)
```

Arguments

a	The numeric 'a' parameter in the normalized upper incomplete gamma
z	The numeric 'z' parameter in the normalized upper incomplete gamma

Details

The gamma q function is given by:

$$\text{gammaq} = \text{uppergamma}(a, z)/\text{gamma}(a)$$

Value

gammaq results

Author(s)

Matthew L. Fidler

Examples

```
gammaq(1, 3)
gammaq(1:3, 3)
gammaq(1, 1:3)
```

gammaqInv	<i>gammaqInv and gammaqInva: Inverses of normalized gammaq function</i>
-----------	---

Description

gammaqInv and gammaqInva: Inverses of normalized gammaq function

Usage

```
gammaqInv(a, q)
```

```
gammaqInva(x, q)
```

Arguments

a	The numeric 'a' parameter in the upper incomplete gamma
q	The numeric 'q' parameter in the upper incomplete gamma
x	The numeric 'x' parameter in the upper incomplete gamma

Details

With the equation:

$$q = \text{gammaq}(a, x)$$

The 'gammaqInv' function returns a value 'x' that satisfies the equation above

The 'gammaqInva' function returns a value 'a' that satisfies the equation above

NOTE: gammaqInva is slow

Value

inverse gammaq results

Author(s)

Matthew L. Fidler

Examples

```
gammaqInv(1:3, 0.5)
gammaqInv(1, 1:3 / 3)
gammaqInv(1:3, 1:3 / 3.1)
gammaqInva(1:3, 1:3 / 3.1)
```

genShinyApp.template *Generate an example (template) of a dosing regimen shiny app*

Description

Create a complete shiny application for exploring dosing regimens given a (hardcoded) PK/PD model.

Usage

```
genShinyApp.template(
  appDir = "shinyExample",
  verbose = TRUE,
  ODE.config = list(ode = "model", params = c(KA = 0.294), inits = c(eff = 1), method =
    "lsoda", atol = 1e-08, rtol = 1e-06)
)

write.template.server(appDir)

write.template.ui(appDir, statevars)
```

Arguments

appDir	a string with a directory where to store the shiny app, by default is "shinyExample". The directory appDir will be created if it does not exist.
verbose	logical specifying whether to write messages as the shiny app is generated. Defaults to TRUE.
ODE.config	model name compiled and list of parameters sent to <code>rxSolve()</code> .

`statevars` List of statevars passed to to the `write.template.ui()` function. This usually isn't called directly.

A PK/PD model is defined using `rxode2()`, and a set of parameters and initial values are defined. Then the appropriate R scripts for the shiny's user interface `ui.R` and the server logic `server.R` are created in the directory `appDir`.

The function evaluates the following PK/PD model by default:

```
C2 = centr/V2;
C3 = peri/V3;
d/dt(depot) = -KA*depot;
d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3;
d/dt(peri) = Q*C2 - Q*C3;
d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
```

This can be changed by the `ODE.config` parameter.

To launch the shiny app, simply issue the `runApp(appDir)` R command.

Value

None, these functions are used for their side effects.

Note

These functions create a simple, but working example of a dosing regimen simulation web application. Users may want to modify the code to experiment creating shiny applications for their specific `rxode2` models.

See Also

`rxode2()`, `eventTable()`, and the package **shiny** (<https://shiny.rstudio.com>).

Examples

```
# remove myapp when the example is complete
on.exit(unlink("myapp", recursive = TRUE, force = TRUE))
# create the shiny app example (template)
genShinyApp.template(appDir = "myapp")
# run the shiny app
if (requireNamespace("shiny", quietly=TRUE)) {
  library(shiny)
  # runApp("myapp") # Won't launch in environments without browsers
}
```

 getRxThreads

Get/Set the number of threads that rxode2 uses

Description

Get/Set the number of threads that rxode2 uses

Usage

```
getRxThreads(verbose = FALSE)
```

```
setRxThreads(threads = NULL, percent = NULL, throttle = NULL)
```

```
rxCores(verbose = FALSE)
```

Arguments

verbose	Display the value of relevant OpenMP settings
threads	NULL (default) rereads environment variables. 0 means to use all logical CPUs available. Otherwise a number ≥ 1
percent	If provided it should be a number between 2 and 100; the percentage of logical CPUs to use. By default on startup, 50 percent.
throttle	<p>2 (default) means that, roughly speaking, a single thread will be used when number subjects solved for is ≤ 2, 2 threads when the number of all points is ≤ 4, etc. The throttle is to speed up small data tasks (especially when repeated many times) by not incurring the overhead of managing multiple threads.</p> <p>The throttle will also suppress sorting which ID will be solved first when there are $(n_{\text{subject solved}}) * \text{throttle} \leq n_{\text{threads}}$. In rxode2 this sorting occurs to minimize the time for waiting for another thread to finish. If the last item solved is has a long solving time, all the other solving have to wait for that last costly solving to occur. If the items which are likely to take more time are solved first, this wait is less likely to have an impact on the overall solving time.</p> <p>In rxode2 the IDs are sorted by the individual number of solving points (largest first). It also has a C interface that allows these IDs to be resorted by total time spent solving the equation. This allows packages like nlmixr to sort by solving time if needed.</p> <p>Overall the the number of threads is throttled (restricted) for small tasks and sorting for IDs are suppressed.</p>

Value

number of threads that rxode2 uses

ini.rxUi	<i>Ini block for rxode2/nlmixr models</i>
----------	---

Description

The ini block controls initial conditions for 'theta' (fixed effects), 'omega' (random effects), and 'sigma' (residual error) elements of the model.

Usage

```
## S3 method for class 'rxUi'
ini(x, ..., envir = parent.frame())

## S3 method for class '`function`'
ini(x, ..., envir = parent.frame())

ini(x, ..., envir = parent.frame())

## Default S3 method:
ini(x, ...)
```

Arguments

x	expression
...	Other expressions for ini() function
envir	the environment in which unevaluated model expressions is to be evaluated. May also be NULL, a list, a data frame, a pairlist or an integer as specified to sys.call.

Details

'theta' and 'sigma' can be set using either <- or = such as tvCL <- 1 or equivalently tvCL = 1. 'omega' can be set with a ~.

Parameters can be named or unnamed (though named parameters are preferred). A named parameter is set using the name on the left of the assignment while unnamed parameters are set without an assignment operator. tvCL <- 1 would set a named parameter of tvCL to 1. Unnamed parameters are set using just the value, such as 1.

For some estimation methods, lower and upper bounds can be set for 'theta' and 'sigma' values. To set a lower and/or upper bound, use a vector of values. The vector is c(lower, estimate, upper). The vector may be given with just the estimate (c(estimate)), the lower bound and estimate (c(lower, estimate)), or all three (c(lower, estimate, upper)). To set an estimate and upper bound without a lower bound, set the lower bound to -Inf, c(-Inf, estimate, upper). When an estimation method does not support bounds, the bounds will be ignored with a warning.

'omega' values can be set as a single value or as the values of a lower-triangular matrix. The values may be set as either a variance-covariance matrix (the default) or as a correlation matrix for the off-diagonals with the standard deviations on the diagonals. Names may be set on the left side of the

\sim . To set a variance-covariance matrix with variance values of 2 and 3 and a covariance of -2.5 use $\sim c(2, 2.5, 3)$. To set the same matrix with names of `iivKa` and `iivCL`, use `iivKa + iivCL ~ c(2, 2.5, 3)`. To set a correlation matrix with standard deviations on the diagonal, use `cor()` like `iivKa + iivCL ~ cor(2, -0.5, 3)`.

Values may be fixed (and therefore not estimated) using either the name `fixed` at the end of the assignment or by calling `fixed()` as a function for the value to fix. For `'theta'` and `'sigma'`, either the estimate or the full definition (including lower and upper bounds) may be included in the fixed setting. For example, the following are all effectively equivalent to set a `'theta'` or `'sigma'` to a fixed value (because the lower and upper bounds are ignored for a fixed value): `tvCL <- fixed(1)`, `tvCL <- fixed(0, 1)`, `tvCL <- fixed(0, 1, 2)`, `tvCL <- c(0, fixed(1), 2)`, or `tvCL <- c(0, 1, fixed)`. For `'omega'` assignment, the full block or none of the block must be set as fixed. Examples of setting an `'omega'` value as fixed are: `iivKa ~ fixed(1)`, `iivKa + iivCL ~ fixed(1, 2, 3)`, or `iivKa + iivCL ~ c(1, 2, 3, fixed)`. Anywhere that `fixed` is used, `FIX`, `FIXED`, or `fix` may be used equivalently.

For any value, standard mathematical operators or functions may be used to define the value. For example, `exp(2)` and `24*30` may be used to define a value anywhere that a number can be used (e.g. lower bound, estimate, upper bound, variance, etc.).

Values may be labeled using the `label()` function after the assignment. Labels are used to make reporting easier by giving a human-readable description of the parameter, but the labels do not have any effect on estimation. The typical way to set a label so that the parameter `tvCL` has a label of "Typical Value of Clearance (L/hr)" is `tvCL <- 1; label("Typical Value of Clearance (L/hr)")`.

`rxode2/nlmixr2` will attempt to determine some back-transformations for the user. For example, `CL <- exp(tvCL)` will detect that `tvCL` must be back-transformed by `exp()` for easier interpretation. When you want to control the back-transformation, you can specify the back-transformation using `backTransform()` after the assignment. For example, to set the back-transformation to `exp()`, you can use `tvCL <- 1; backTransform(exp())`.

Value

Ini block

Author(s)

Matthew Fidler

logit

logit and inverse logit (expit) functions

Description

logit and inverse logit (expit) functions

Usage

```
logit(x, low = 0, high = 1)
```

```
expit(alpha, low = 0, high = 1)
```

```
logitNormInfo(mean = 0, sd = 1, low = 0, high = 1, abs.tol = 1e-06, ...)
```

```
probitNormInfo(mean = 0, sd = 1, low = 0, high = 1, abs.tol = 1e-06, ...)
```

Arguments

x	Input value(s) in range [low,high] to translate -Inf to Inf
low	Lowest value in the range
high	Highest value in the range
alpha	Infinite value(s) to translate to range of [low, high]
mean	logit-scale mean
sd	logit-scale standard deviation
abs.tol	absolute accuracy requested.
...	other parameters passed to integrate()

Details

logit is given by:

$$\text{logit}(p) = -\log(1/p-1)$$

where:

$$p = (x - \text{low}) / (\text{high} - \text{low})$$

expit is given by:

$$\text{expit}(p, \text{low}, \text{high}) = (\text{high} - \text{low}) / (1 + \exp(-\alpha)) + \text{low}$$

The `logitNormInfo()` gives the mean, variance and coefficient of variability on the untransformed scale.

Value

values from logit and expit

Examples

```
logit(0.25)
```

```
expit(-1.09)
```

```
logitNormInfo(logit(0.25), sd = 0.1)
```

```
logitNormInfo(logit(1, 0, 10), sd = 1, low = 0, high = 10)
```

lowergamma

lowergamma: upper incomplete gamma function

Description

This is the `tgamma_lower` from the boost library

Usage

```
lowergamma(a, z)
```

Arguments

a	The numeric 'a' parameter in the upper incomplete gamma
z	The numeric 'z' parameter in the upper incomplete gamma

Details

The lowergamma function is given by:

$$\text{lowergamma}(a, z) = \int_0^z t^{a-1} \cdot e^{-t} dt$$

Value

lowergamma results

Author(s)

Matthew L. Fidler

Examples

```
lowergamma(1, 3)
```

```
lowergamma(1:3, 3)
```

```
lowergamma(1, 1:3)
```

model.function	<i>Model block for rxode2/nlmixr models</i>
----------------	---

Description

Model block for rxode2/nlmixr models

Usage

```
## S3 method for class '`function`'
model(x, ..., append = FALSE, auto = TRUE, envir = parent.frame())

## S3 method for class 'rxUi'
model(x, ..., append = FALSE, auto = TRUE, envir = parent.frame())

model(
  x,
  ...,
  append = FALSE,
  auto = getOption("rxode2.autoVarPiping", TRUE),
  envir = parent.frame()
)

## Default S3 method:
model(x, ..., append = FALSE, envir = parent.frame())
```

Arguments

x	model expression
...	Other arguments
append	This is a boolean to determine if the lines are appended in piping. The possible values for this is: <ul style="list-style-type: none"> • TRUE which is when the lines are appended to the model instead of replaced (default) • FALSE when the lines are replaced in the model • NA is when the lines are pre-pended to the model instead of replaced
auto	This boolean tells if piping automatically selects the parameters should be characterized as a population parameter, between subject variability, or a covariate. When TRUE this automatic selection occurs. When FALSE this automatic selection is turned off and everything is added as a covariate (which can be promoted to a parameter with the ini statement). By default this is TRUE, but it can be changed by options(rxode2.autoVarPiping=FALSE).
envir	the environment in which unevaluated model expressions is to be evaluated. May also be NULL, a list, a data frame, a pairlist or an integer as specified to sys.call.

Value

Model block with ini information included. ini must be called before model block

Author(s)

Matthew Fidler

phi

Cumulative distribution of standard normal

Description

Cumulative distribution of standard normal

Usage

phi(q)

Arguments

q vector of quantiles.

Value

cumulative distribution of standard normal distribution

Author(s)

Matthew Fidler

Examples

```
# phi is equivalent to pnorm(x)
phi(3)

# See
pnorm(3)

# This is provided for NONMEM-like compatibility in rxode2 models
```

plot.rxSolve	<i>Plot rxode2 objects</i>
--------------	----------------------------

Description

Plot rxode2 objects

Usage

```
## S3 method for class 'rxSolve'
plot(x, y, ..., log = "", xlab = "Time", ylab = "")

## S3 method for class 'rxSolveConfint1'
plot(x, y, ..., xlab = "Time", ylab = "", log = "")

## S3 method for class 'rxSolveConfint2'
plot(x, y, ..., xlab = "Time", ylab = "", log = "")
```

Arguments

x	rxode2 object to plot
y	Compartments or left-hand-side values to plot either as a bare name or as a character vector
...	Ignored
log	Should "" (neither x nor y), "x", "y", or "xy" (or "yx") be log-scale?
xlab, ylab	The x and y axis labels

Value

A ggplot2 object

See Also

Other rxode2 plotting: [rxTheme\(\)](#)

probit	<i>probit and inverse probit functions</i>
--------	--

Description

probit and inverse probit functions

Usage

```
probit(x, low = 0, high = 1)
```

```
probitInv(x, low = 0, high = 1)
```

Arguments

x	Input value(s) in range [low,high] to translate -Inf to Inf
low	Lowest value in the range
high	Highest value in the range

Value

values from probit, probitInv and probitNormInfo

Examples

```
probit(0.25)
```

```
probitInv(-0.674)
```

```
probitNormInfo(probit(0.25), sd = 0.1)
```

```
probitNormInfo(probit(1, 0, 10), sd = 1, low = 0, high = 10)
```

rinvchisq

Scaled Inverse Chi Squared distribution

Description

Scaled Inverse Chi Squared distribution

Usage

```
rinvchisq(n = 1L, nu = 1, scale = 1)
```

Arguments

n	Number of random samples
nu	degrees of freedom of inverse chi square
scale	Scale of inverse chi squared distribution (default is 1).

Value

a vector of inverse chi squared deviates.

Examples

```
rinvchisq(3, 4, 1) ## Scale = 1, degrees of freedom = 4  
rinvchisq(2, 4, 2) ## Scale = 2, degrees of freedom = 4
```

rxAllowUnload	<i>Allow unloading of dlls</i>
---------------	--------------------------------

Description

Allow unloading of dlls

Usage

```
rxAllowUnload(allow)
```

Arguments

allow boolean indicating if garbage collection will unload of rxode2 dlls.

Value

Boolean allow; called for side effects

Author(s)

Matthew Fidler

Examples

```
# Garbage collection will not unload un-used rxode2 dlls  
rxAllowUnload(FALSE);  
  
# Garbage collection will unload unused rxode2 dlls  
rxAllowUnload(TRUE);
```

rxAppendModel *Append two rxui models together*

Description

Append two rxui models together

Usage

```
rxAppendModel(model1, model2)
```

Arguments

model1	rxUi model 1
model2	rxUi model 2

Value

New model with both models appended together

Author(s)

Matthew L. Fidler

Examples

```
ocmt <- function() {
  ini({
    tka <- exp(0.45) # Ka
    tcl <- exp(1) # Cl
    tv <- exp(3.45); # log V
    ## the label("Label name") works with all models
    add.sd <- 0.7
  })
  model({
    ka <- tka
    cl <- tcl
    v <- tv
    d/dt(depot) = -ka * depot
    d/dt(center) = ka * depot - cl / v * center
    cp = center / v
    cp ~ add(add.sd)
  })
}

idr <- function() {
  ini({
    tkin <- log(1)
    tkout <- log(1)
  })
}
```

```
    tic50 <- log(10)
    gamma <- fix(1)
    idr.sd <- 1
  })
  model({
    kin <- exp(tkin)
    kout <- exp(tkout)
    ic50 <- exp(tic50)
    d/dt(eff) <- kin - kout*(1-ceff^gamma/(ic50^gamma+ceff^gamma))
    eff ~ add(idr.sd)
  })
}
```

rxAppendModel(ocmt %>% model(ceff=cp,append=TRUE), idr)

rxAssignControlValue *Assign Control Variable*

Description

Assign Control Variable

Usage

```
rxAssignControlValue(ui, option, value)
```

Arguments

ui	rxode2 ui function
option	Option name in the control to modify
value	Value of control to modify

Value

Nothing; called for the side effects

Author(s)

Matthew L. Fidler

rxAssignPtr	<i>Assign pointer based on model variables</i>
-------------	--

Description

Assign pointer based on model variables

Usage

```
rxAssignPtr(object = NULL)
```

Arguments

object rxode2 family of objects

Value

nothing, called for side effects

rxbeta	<i>Simulate beta variable from threefry generator</i>
--------	---

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxbeta(shape1, shape2, n = 1L, ncores = 1L)
```

Arguments

shape1	non-negative parameters of the Beta distribution.
shape2	non-negative parameters of the Beta distribution.
n	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with rxSetSeed()

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

beta random deviates

Examples

```
## Use threefry engine

rxbeta(0.5, 0.5, n = 10) # with rxbeta you have to explicitly state n
rxbeta(5, 1, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxbeta(1, 3)

## This example uses `rxbeta` directly in the model

rx <- rxode2({
  a <- rxbeta(2, 2)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxbinom

Simulate Binomial variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxbinom(size, prob, n = 1L, ncores = 1L)
```

Arguments

size	number of trials (zero or more).
prob	probability of success on each trial.
n	number of observations. If length(n) > 1, the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with rxSetSeed()

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

binomial random deviates

Examples

```
## Use threefry engine

rxbinom(10, 0.9, n = 10) # with rxbinom you have to explicitly state n
rxbinom(3, 0.5, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxbinom(4, 0.7)

## This example uses `rxbinom` directly in the model

rx <- rxode2({
  a <- rxbinom(1, 0.5)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

 rxcauchy

Simulate Cauchy variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxcauchy(location = 0, scale = 1, n = 1L, ncores = 1L)
```

Arguments

location	location and scale parameters.
scale	location and scale parameters.
n	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with `rxSetSeed()`

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

Cauchy random deviates

Examples

```
## Use threefry engine

rxcauchy(0, 1, n = 10) # with rxcauchy you have to explicitly state n
rxcauchy(0.5, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxcauchy(3)

## This example uses `rxcauchy` directly in the model

rx <- rxode2({
  a <- rxcauchy(2)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxCbindStudyIndividual

Bind the study parameters and individual parameters

Description

Bind the study parameters and individual parameters

Usage

```
rxCbindStudyIndividual(studyParameters, individualParameters)
```

Arguments

studyParameters

These are the study parameters, often can be generated by sampling from a population. This can be either a matrix or a data frame

individualParameters

A data frame of individual parameters

Value

Data frame that can be used in rxode2 simulations

Author(s)

Matthew Fidler

Examples

```

# Function for covering coefficient of covariance into a variance
lognCv <- function(x){log((x/100)^2+1)}

set.seed(32)

nSub <- 100
nStud <- 10

#define theta
theta <- c(lka=log(0.5), # log ka
          lCl=log(5), # log Cl
          lV=log(300) # log V
          )

#define theta Matrix
thetaMat <- lotri(lCl ~ lognCv(5),
                 lV ~ lognCv(5),
                 lka ~ lognCv(5))

nev <- nSub*nStud

ev1 <- data.frame(COV1=rnorm(nev,50,30),COV2=rnorm(nev,75,10),
                 COV3=sample(c(1.0,2.0),nev,replace=TRUE))

tmat <-rxRmvn(nStud, theta[dimnames(thetaMat)[[1]]], thetaMat)

rxCbindStudyIndividual(tmat, ev1)

```

rxchisq

*Simulate chi-squared variable from threefry generator***Description**

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxchisq(df, n = 1L, ncores = 1L)
```

Arguments

df	degrees of freedom (non-negative, but can be non-integer).
n	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with `rxSetSeed()`

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

chi squared random deviates

Examples

```
## Use threefry engine

rxchisq(0.5, n = 10) # with rxchisq you have to explicitly state n
rxchisq(5, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxchisq(1)

## This example uses `rxchisq` directly in the model

rx <- rxode2({
  a <- rxchisq(2)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxClean	<i>Cleanup anonymous DLLs by unloading them</i>
---------	---

Description

This cleans up any rxode2 loaded DLLs

Usage

```
rxClean(wd)
```

Arguments

wd	What directory should be cleaned; (DEPRECATED), this no longer does anything. This unloads all rxode2 anonymous dlls.
----	--

Value

TRUE if successful

Author(s)

Matthew L. Fidler

rxCompile	<i>Compile a model if needed</i>
-----------	----------------------------------

Description

This is the compilation workhorse creating the rxode2 model DLL files.

Usage

```
rxCompile(  
  model,  
  dir,  
  prefix,  
  force = FALSE,  
  modName = NULL,  
  package = NULL,  
  ...  
)  
  
## S3 method for class 'rxModelVars'  
rxCompile(  
  model,  
  dir,  
  prefix,  
  force = FALSE,  
  modName = NULL,  
  package = NULL,  
  ...  
)
```

```

    model,
    dir = NULL,
    prefix = NULL,
    force = FALSE,
    modName = NULL,
    package = NULL,
    ...
)

## S3 method for class 'character'
rxCompile(
  model,
  dir = NULL,
  prefix = NULL,
  force = FALSE,
  modName = NULL,
  package = NULL,
  ...
)

## S3 method for class 'rxDll'
rxCompile(model, ...)

## S3 method for class 'rxode2'
rxCompile(model, ...)

```

Arguments

model	<p>This is the ODE model specification. It can be:</p> <ul style="list-style-type: none"> • a string containing the set of ordinary differential equations (ODE) and other expressions defining the changes in the dynamic system. • a file name where the ODE system equation is contained <p>An ODE expression enclosed in <code>\{\}</code> (see also the filename argument). For details, see the sections “Details” and rxode2 Syntax below.</p>
dir	<p>This is the model directory where the C file will be stored for compiling.</p> <p>If unspecified, the C code is stored in a temporary directory, then the model is compiled and moved to the current directory. Afterwards the C code is removed.</p> <p>If specified, the C code is stored in the specified directory and then compiled in that directory. The C code is not removed after the DLL is created in the same directory. This can be useful to debug the c-code outputs.</p>
prefix	<p>is a string indicating the prefix to use in the C based functions. If missing, it is calculated based on file name, or md5 of parsed model.</p>

force	is a boolean stating if the (re)compile should be forced if rxode2 detects that the models are the same as already generated.
modName	a string to be used as the model name. This string is used for naming various aspects of the computations, including generating C symbol names, dynamic libraries, etc. Therefore, it is necessary that modName consists of simple ASCII alphanumeric characters starting with a letter.
package	Package name for pre-compiled binaries.
...	Other arguments sent to the rxTrans() function.

Value

An `rxDll` object that has the following components

- `dllDLL` path
- `model` specification
- `.cA` function to call C code in the correct context from the DLL using the `.C()` function.
- `.callA` function to call C code in the correct context from the DLL using the `.Call()` function.
- `argsA` list of the arguments used to create the `rxDll` object.

Author(s)

Matthew L.Fidler

See Also

[rxode2\(\)](#)

`rxControlUpdateSens` *This updates the tolerances based on the sensitivity equations*

Description

This assumes the normal ODE equations are the first equations and the ODE is expanded by the forward sensitivities or other type of sensitivity (like adjoint)

Usage

```
rxControlUpdateSens(rxControl, sensCmt = NULL, ncmt = NULL)
```

Arguments

<code>rxControl</code>	Input list or <code>rxControl</code> type of list
<code>sensCmt</code>	Number of sensitivity compartments
<code>ncmt</code>	Number of compartments

Value

Updated rxControl where \$atol, \$rtol, \$ssAtol \$ssRtol are updated with different sensitivities for the normal ODEs (first) and a different sensitivity for the larger compartments (sensitivities).

Author(s)

Matthew L. Fidler

Examples

```
tmp <- rxControl()

tmp2 <- rxControlUpdateSens(tmp, 3, 6)

tmp2$atol
tmp2$rtol
tmp2$ssAtol
tmp2$ssRtol
```

rxCreateCache	<i>This will create the cache directory for rxode2 to save between sessions</i>
---------------	---

Description

When run, if the R_user_dir for rxode2's cache isn't present, create the cache

Usage

```
rxCreateCache()
```

Value

nothing

Author(s)

Matthew Fidler

`rxD`*Add to rxode2's derivative tables*

Description

Add to rxode2's derivative tables

Usage

```
rxD(name, derivatives)
```

Arguments

<code>name</code>	Function Name
<code>derivatives</code>	A list of functions. Each function takes the same number of arguments as the original function. The first function will construct the derivative with respect to the first argument; The second function will construct the derivative with respect to the second argument, and so on.

Value

nothing

Author(s)

Matthew Fidler

Examples

```
## Add an arbitrary list of derivative functions
## In this case the fun(x,y) is assumed to be 0.5*x^2+0.5*y^2

rxD("fun", list(
  function(x, y) {
    return(x)
  },
  function(x, y) {
    return(y)
  }
))
```

rxDelete	<i>Delete the DLL for the model</i>
----------	-------------------------------------

Description

This function deletes the DLL, but doesn't delete the model information in the object.

Usage

```
rxDelete(obj)
```

Arguments

obj	rxode2 family of objects
-----	--------------------------

Value

A boolean stating if the operation was successful.

Author(s)

Matthew L.Fidler

rxDerived	<i>Calculate derived parameters for the 1-, 2-, and 3- compartment linear models.</i>
-----------	---

Description

This calculates the derived parameters based on what is provided in a data frame or arguments

Usage

```
rxDerived(..., verbose = FALSE, digits = 0)
```

Arguments

...	The input can be: <ul style="list-style-type: none"> • A data frame with PK parameters in it; This should ideally be a data frame with one pk parameter per row since it will output a data frame with one PK parameter per row. • PK parameters as either a vector or a scalar
verbose	boolean that when TRUE provides a message about the detected pk parameters and the detected compartmental model. By default this is FALSE.
digits	represents the number of significant digits for the output; If the number is zero or below (default), do not round.

Value

Return a data.frame of derived PK parameters for a 1-, 2-, or 3-compartment linear model given provided clearances and volumes based on the inferred model type.

The model parameters that will be provided in the data frame are:

- vc: Central Volume (for 1-, 2- and 3- compartment models)
- kel: First-order elimination rate (for 1-, 2-, and 3-compartment models)
- k12: First-order rate of transfer from central to first peripheral compartment; (for 2- and 3-compartment models)
- k21: First-order rate of transfer from first peripheral to central compartment, (for 2- and 3-compartment models)
- k13: First-order rate of transfer from central to second peripheral compartment; (3-compartment model)
- k31: First-order rate of transfer from second peripheral to central compartment (3-compartment model)
- vp: Peripheral Volume (for 2- and 3- compartment models)
- vp2: Peripheral Volume for 3rd compartment (3- compartment model)
- vss: Volume of distribution at steady state; (1-, 2-, and 3-compartment models)
- t12alpha: $t_{1/2,\alpha}$; (1-, 2-, and 3-compartment models)
- t12beta: $t_{1/2,\beta}$; (2- and 3-compartment models)
- t12gamma: $t_{1/2,\gamma}$; (3-compartment model)
- alpha: α ; (1-, 2-, and 3-compartment models)
- beta: β ; (2- and 3-compartment models)
- gamma: β ; (3-compartment model)
- A: true A; (1-, 2-, and 3-compartment models)
- B: true B; (2- and 3-compartment models)
- C: true C; (3-compartment model)
- fracA: fractional A; (1-, 2-, and 3-compartment models)
- fracB: fractional B; (2- and 3-compartment models)
- fracC: fractional C; (3-compartment model)

Author(s)

Matthew Fidler and documentation from Justin Wilkins, <justin.wilkins@occams.com>

References

Shafer S. L. CONVERT.XLS

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics: Concepts and Applications (4th). Clipping Williams & Wilkins, Philadelphia, 2010.

Examples

```
## Note that rxode2 parses the names to figure out the best PK parameter
params <- rxDerived(cl = 29.4, v = 23.4, Vp = 114, vp2 = 4614, q = 270, q2 = 73)

## That is why this gives the same results as the value before
params <- rxDerived(CL = 29.4, V1 = 23.4, V2 = 114, V3 = 4614, Q2 = 270, Q3 = 73)

## You may also use micro-constants alpha/beta etc.
params <- rxDerived(k12 = 0.1, k21 = 0.2, k13 = 0.3, k31 = 0.4, kel = 10, v = 10)

## or you can mix vectors and scalars
params <- rxDerived(CL = 29.4, V = 1:3)

## If you want, you can round to a number of significant digits
## with the `digits` argument:
params <- rxDerived(CL = 29.4, V = 1:3, digits = 2)
```

rxDfdy

Jacobian and parameter derivatives

Description

Return Jacobian and parameter derivatives

Usage

```
rxDfdy(obj)
```

Arguments

obj rxode2 family of objects

Value

A list of the jacobian parameters defined in this rxode2 object.

Author(s)

Matthew L. Fidler

See Also

Other Query model information: [rxInits\(\)](#), [rxLhs\(\)](#), [rxModelVars\(\)](#), [rxParams\(\)](#), [rxState\(\)](#)

`rxEvid`*EVID formatting for tibble and other places.*

Description

This is to make an EVID more readable by non pharmacometricians. It displays what each means and allows it to be displayed in a tibble.

Usage

```
rxEvid(x)

as.rxEvid(x)

## S3 method for class 'rxEvid'
c(x, ...)

## S3 method for class 'rxEvid'
x[...]

## S3 method for class 'rxEvid'
as.character(x, ...)

## S3 method for class 'rxEvid'
x[[...]]

## S3 method for class 'rxRateDur'
c(x, ...)

## S3 method for class 'rxEvid'
format(x, ...)

## S3 method for class 'rxRateDur'
format(x, ...)

## S3 method for class 'rxEvid'
print(x, ...)
```

Arguments

<code>x</code>	Item to be converted to a rxode2 EVID specification.
<code>...</code>	Other parameters

Value

rxEvid specification

Examples

```
rxEvid(1:7)
```

```
rxexp
```

Simulate exponential variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxexp(rate, n = 1L, ncores = 1L)
```

Arguments

rate	vector of rates.
n	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with `rxSetSeed()`

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

exponential random deviates

Examples

```
## Use threefry engine

rxexp(0.5, n = 10) # with rxexp you have to explicitly state n
rxexp(5, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxexp(1)

## This example uses `rxexp` directly in the model

rx <- rxode2({
  a <- rxexp(2)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

 rx

Simulate F variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rx(df1, df2, n = 1L, ncores = 1L)
```

Arguments

df1	degrees of freedom. Inf is allowed.
df2	degrees of freedom. Inf is allowed.
n	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with rxSetSeed()

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

f random deviates

Examples

```
## Use threefry engine

rxf(0.5, 0.5, n = 10) # with rxf you have to explicitly state n
rxf(5, 1, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxf(1, 3)

## This example uses `rxf` directly in the model

rx <- rxode2({
  a <- rxf(2, 2)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxFun

Add user function to rxode2

Description

This adds a user function to rxode2 that can be called. If needed, these functions can be differentiated by numerical differences or by adding the derivatives to rxode2's internal derivative table with [rxD\(\)](#)

Usage

```
rxFun(name, args, cCode)
```

```
rxRmFun(name)
```

Arguments

name	This gives the name of the user function
args	This gives the arguments of the user function
cCode	This is the C-code for the new function

Value

nothing

Author(s)

Matthew L. Fidler

Examples

```
## Right now rxode2 is not aware of the function f
## Therefore it cannot translate it to symengine or
## Compile a model with it.

try(rxode2("a=fun(a,b,c)"))

## Note for this approach to work, it cannot interfere with C
## function names or reserved rxode2 special terms. Therefore
## f(x) would not work since f is an alias for bioavailability.

fun <- "
double fun(double a, double b, double c) {
  return a*a+b*a+c;
}
" ## C-code for function

rxFun("fun", c("a", "b", "c"), fun) ## Added function

## Now rxode2 knows how to translate this function to symengine

rxToSE("fun(a,b,c)")

## And will take a central difference when calculating derivatives

rxFromSE("Derivative(fun(a,b,c),a)")

## Of course, you could specify the derivative table manually
rxD("fun", list(
  function(a, b, c) {
```

```

    paste0("2*", a, "+", b)
  },
  function(a, b, c) {
    return(a)
  },
  function(a, b, c) {
    return("0.0")
  }
))

rxFromSE("Derivative(fun(a,b,c),a)")

# You can also remove the functions by `rxRmFun`
rxRmFun("fun")

```

 rxgamma

Simulate gamma variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxgamma(shape, rate = 1/scale, scale = 1, n = 1L, ncores = 1L)
```

Arguments

shape	shape and scale parameters. Must be positive, scale strictly.
rate	an alternative way to specify the scale.
scale	shape and scale parameters. Must be positive, scale strictly.
n	number of observations. If length(n) > 1, the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with rxSetSeed()

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

gamma random deviates

Examples

```
## Use threefry engine

rxgamma(0.5, n = 10) # with rxgamma you have to explicitly state n
rxgamma(5, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxgamma(1)

## This example uses `rxbeta` directly in the model

rx <- rxode2({
  a <- rxgamma(2)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxgeom

Simulate geometric variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxgeom(prob, n = 1L, ncores = 1L)
```

Arguments

prob	probability of success in each trial. $0 < \text{prob} \leq 1$.
n	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with rxSetSeed()

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

geometric random deviates

Examples

```
## Use threefry engine

rxgeom(0.5, n = 10) # with rxgeom you have to explicitly state n
rxgeom(0.25, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxgeom(0.75)

## This example uses `rxgeom` directly in the model

rx <- rxode2({
  a <- rxgeom(0.24)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxGetControl	<i>rxGetControl option from ui</i>
--------------	------------------------------------

Description

rxGetControl option from ui

Usage

```
rxGetControl(ui, option, default)
```

Arguments

ui	rxode2 ui object
option	Option to get
default	Default value

Value

Option (if present) or default value

Author(s)

Matthew L. Fidler

rxGetLin	<i>Get the linear compartment model true function</i>
----------	---

Description

Get the linear compartment model true function

Usage

```
rxGetLin(  
  model,  
  linCmtSens = c("linCmtA", "linCmtB", "linCmtC"),  
  verbose = FALSE  
)
```

Arguments

model	This is the ODE model specification. It can be: <ul style="list-style-type: none"> • a string containing the set of ordinary differential equations (ODE) and other expressions defining the changes in the dynamic system. • a file name where the ODE system equation is contained An ODE expression enclosed in <code>\{\}</code> (see also the <code>filename</code> argument). For details, see the sections “Details” and <code>rxode2 Syntax</code> below.
linCmtSens	The method to calculate the <code>linCmt()</code> solutions
verbose	When TRUE be verbose with the linear compartmental model

Value

model with `linCmt()` replaced with `linCmtA()`

Author(s)

Matthew Fidler

rxGetrxode2

Get rxode2 model from object

Description

Get `rxode2` model from object

Usage

```
rxGetrxode2(obj)
```

Arguments

obj	<code>rxode2</code> family of objects
-----	---------------------------------------

Value

`rxode2` model

`rxGetSeed`*Get the rxode2 seed*

Description

Get the rxode2 seed

Usage

```
rxGetSeed()
```

Value

rxode2 seed state or -1 when the seed isn't set

See Also

`rxSetSeed`, `rxWithSeed`, `rxWithPreserveSeed`

Examples

```
# without setting seed

rxGetSeed()
# Now set the seed
rxSetSeed(42)

rxGetSeed()

rxnorm()

rxGetSeed()

# don't use the rxode2 seed again

rxSetSeed(-1)

rxGetSeed()

rxnorm()

rxGetSeed()
```

rxHtml	<i>Format rxSolve and related objects as html.</i>
--------	--

Description

Format rxSolve and related objects as html.

Usage

```
rxHtml(x, ...)
```

```
## S3 method for class 'rxSolve'
```

```
rxHtml(x, ...)
```

Arguments

x	rxode2 object
...	Extra arguments sent to kable

Value

html code for rxSolve object

Author(s)

Matthew L. Fidler

rxIndLinState	<i>Set the preferred factoring by state</i>
---------------	---

Description

Set the preferred factoring by state

Usage

```
rxIndLinState(preferred = NULL)
```

Arguments

preferred	A list of each state's preferred factorization
-----------	--

Value

Nothing

Author(s)

Matthew Fidler

rxIndLinStrategy	<i>This sets the inductive linearization strategy for matrix building</i>
------------------	---

Description

When there is more than one state in a ODE that cannot be separated this specifies how it is incorporated into the matrix exponential.

Usage

```
rxIndLinStrategy(strategy = c("curState", "split"))
```

Arguments

strategy	The strategy for inductive linearization matrix building
----------	--

- `curState` Prefer parameterizing in terms of the current state, followed by the first state observed in the term.
- `split` Split the parameterization between all states in the term by dividing each by the number of states in the term and then adding a matrix term for each state.

Value

Nothing

Author(s)

Matthew L. Fidler

rxIndLin_	<i>Inductive linearization solver</i>
-----------	---------------------------------------

Description

Inductive linearization solver

Arguments

cSub	= Current subject number
op	• rxode2 solving options
tp	• Prior time point/time zeor
yp	• Prior state; vector size = neq; Final state is updated here
tf	• Final Time
InfusionRate	= Rates of each comparment; vector size = neq
on	Indicator for if the compartment is "on"
cache	0 = no Cache When doIndLin == 0, cache > 0 = nInf-1
ME	the rxode2 matrix exponential function
IndF	The rxode2 Inductive Linearization function F

Value

Returns a status for solving

1 = Successful solve

-1 = Maximum number of iterations reached when doing inductive linearization

 rxInv

Invert matrix using RcppArmadillo.

Description

Invert matrix using RcppArmadillo.

Usage

```
rxInv(matrix)
```

Arguments

matrix matrix to be inverted.

Value

inverse or pseudo inverse of matrix.

rxIsCurrent	<i>Checks if the rxode2 object was built with the current build</i>
-------------	---

Description

Checks if the rxode2 object was built with the current build

Usage

```
rxIsCurrent(obj)
```

Arguments

obj rxode2 family of objects

Value

boolean indicating if this was built with current rxode2

rxLhs	<i>Left handed Variables</i>
-------	------------------------------

Description

This returns the model calculated variables

Usage

```
rxLhs(obj)
```

Arguments

obj rxode2 family of objects

Value

a character vector listing the calculated parameters

Author(s)

Matthew L.Fidler

See Also

[rxode2](#)

Other Query model information: [rxDfdy\(\)](#), [rxInits\(\)](#), [rxModelVars\(\)](#), [rxParams\(\)](#), [rxState\(\)](#)

rxLock	<i>Lock/unlocking of rxode2 dll file</i>
--------	--

Description

Lock/unlocking of rxode2 dll file

Usage

rxLock(obj)

rxUnlock(obj)

Arguments

obj A rxode2 family of objects

Value

nothing; called for side effects

rxNorm	<i>Get the normalized model</i>
--------	---------------------------------

Description

This get the syntax preferred model for processing

Usage

rxNorm(obj, condition = NULL, removeInis, removeJac, removeSens)

Arguments

obj	rxode2 family of objects
condition	Character string of a logical condition to use for subsetting the normalized model. When missing, and a condition is not set via rxCondition, return the whole code with all the conditional settings intact. When a condition is set with rxCondition, use that condition.
removeInis	A boolean indicating if parameter initialization will be removed from the model
removeJac	A boolean indicating if the Jacobians will be removed.
removeSens	A boolean indicating if the sensitivities will be removed.

Value

Normalized Normal syntax (no comments)

Author(s)

Matthew L. Fidler

rxnorm	<i>Simulate random normal variable from threefry/vandercorput generator</i>
--------	---

Description

Simulate random normal variable from threefry/vandercorput generator

Usage

```
rxnorm(mean = 0, sd = 1, n = 1L, ncores = 1L)
```

```
rxnormV(mean = 0, sd = 1, n = 1L, ncores = 1L)
```

Arguments

mean	vector of means.
sd	vector of standard deviations.
n	number of observations
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vandercorput generator

Value

normal random number deviates

Examples

```
## Use threefry engine

rxnorm(n = 10) # with rxnorm you have to explicitly state n
rxnorm(n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxnorm(2, 3) ## The first 2 arguments are the mean and standard deviation

## This example uses `rxnorm` directly in the model

rx <- rxode2({
  a <- rxnorm()
})
```

```
et <- et(1, id = 1:2)

s <- rxSolve(rx, et)

## Use vandercompt generator

rxnormV(n = 10) # with rxnorm you have to explicitly state n
rxnormV(n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxnormV(2, 3) ## The first 2 arguments are the mean and standard deviation

## This example uses `rxnormV` directly in the model

rx <- rxode2({
  a <- rxnormV()
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxode2

Create an ODE-based model specification

Description

Create a dynamic ODE-based model object suitably for translation into fast C code

Usage

```
rxode2(
  model,
  modName = basename(wd),
  wd = getwd(),
  filename = NULL,
  extraC = NULL,
  debug = FALSE,
  calcJac = NULL,
  calcSens = NULL,
  collapseModel = FALSE,
  package = NULL,
  ...,
  linCmtSens = c("linCmtA", "linCmtB", "linCmtC"),
  indLin = FALSE,
  verbose = FALSE
)
```



```

RxODE(
  model,
  modName = basename(wd),
  wd = getwd(),
  filename = NULL,
  extraC = NULL,
  debug = FALSE,
  calcJac = NULL,
  calcSens = NULL,
  collapseModel = FALSE,
  package = NULL,
  ...,
  linCmtSens = c("linCmtA", "linCmtB", "linCmtC"),
  indLin = FALSE,
  verbose = FALSE
)

rxode(
  model,
  modName = basename(wd),
  wd = getwd(),
  filename = NULL,
  extraC = NULL,
  debug = FALSE,
  calcJac = NULL,
  calcSens = NULL,
  collapseModel = FALSE,
  package = NULL,
  ...,
  linCmtSens = c("linCmtA", "linCmtB", "linCmtC"),
  indLin = FALSE,
  verbose = FALSE
)

```

Arguments

model	<p>This is the ODE model specification. It can be:</p> <ul style="list-style-type: none"> • a string containing the set of ordinary differential equations (ODE) and other expressions defining the changes in the dynamic system. • a file name where the ODE system equation is contained <p>An ODE expression enclosed in <code>\{\}</code> (see also the <code>filename</code> argument). For details, see the sections “Details” and <code>rxode2 Syntax</code> below.</p>
modName	<p>a string to be used as the model name. This string is used for naming various aspects of the computations, including generating C symbol names, dynamic libraries, etc. Therefore, it is necessary that <code>modName</code> consists of simple ASCII alphanumeric characters starting with a letter.</p>

wd	character string with a working directory where to create a subdirectory according to modName. When specified, a subdirectory named after the “modName.d” will be created and populated with a C file, a dynamic loading library, plus various other working files. If missing, the files are created (and removed) in the temporary directory, and the rxode2 DLL for the model is created in the current directory named rx_????_platform, for example rx_129f8f97fb94a87ca49ca8d8afe691e1e_i386.dll
filename	A file name or connection object where the ODE-based model specification resides. Only one of model or filename may be specified.
extraC	Extra c code to include in the model. This can be useful to specify functions in the model. These C functions should usually take double precision arguments, and return double precision values.
debug	is a boolean indicating if the executable should be compiled with verbose debugging information turned on.
calcJac	boolean indicating if rxode2 will calculate the Jacobian according to the specified ODEs.
calcSens	boolean indicating if rxode2 will calculate the sensitivities according to the specified ODEs.
collapseModel	boolean indicating if rxode2 will remove all LHS variables when calculating sensitivities.
package	Package name for pre-compiled binaries.
...	ignored arguments.
linCmtSens	The method to calculate the linCmt() solutions
indLin	Calculate inductive linearization matrices and compile with inductive linearization support.
verbose	When TRUE be verbose with the linear compartmental model

Details

The Rx in the name rxode2 is meant to suggest the abbreviation Rx for a medical prescription, and thus to suggest the package emphasis on pharmacometrics modeling, including pharmacokinetics (PK), pharmacodynamics (PD), disease progression, drug-disease modeling, etc.

The ODE-based model specification may be coded inside a character string or in a text file, see Section *rxode2 Syntax* below for coding details. An internal rxode2 compilation manager object translates the ODE system into C, compiles it, and dynamically loads the object code into the current R session. The call to rxode2 produces an object of class rxode2 which consists of a list-like structure (environment) with various member functions (see Section *Value* below).

For evaluating rxode2 models, two types of inputs may be provided: a required set of time points for querying the state of the ODE system and an optional set of doses (input amounts). These inputs are combined into a single *event table* object created with the function `eventTable()` or `et()`.

An rxode2 model specification consists of one or more statements optionally terminated by semicolons ; and optional comments (comments are delimited by # and an end-of-line).

A block of statements is a set of statements delimited by curly braces, { ... }.

Statements can be either assignments, conditional if/else if/else, while loops (can be exited by break), special statements, or printing statements (for debugging/testing)

Assignment statements can be:

- **simple** assignments, where the left hand is an identifier (i.e., variable)
- special **time-derivative** assignments, where the left hand specifies the change of the amount in the corresponding state variable (compartment) with respect to time e.g., $d/dt(\text{depot})$:
- special **initial-condition** assignments where the left hand specifies the compartment of the initial condition being specified, e.g. $\text{depot}(0) = 0$
- special model event changes including **bioavailability** ($f(\text{depot})=1$), **lag time** ($\text{alag}(\text{depot})=0$), **modeled rate** ($\text{rate}(\text{depot})=2$) and **modeled duration** ($\text{dur}(\text{depot})=2$). An example of these model features and the event specification for the modeled infusions the rxode2 data specification is found in [rxode2 events vignette](#).
- special **change point syntax, or model times**. These model times are specified by $\text{mtime}(\text{var})=\text{time}$
- special **Jacobian-derivative** assignments, where the left hand specifies the change in the compartment ode with respect to a variable. For example, if $d/dt(y) = dy$, then a Jacobian for this compartment can be specified as $df(y)/dy(dy) = 1$. There may be some advantage to obtaining the solution or specifying the Jacobian for very stiff ODE systems. However, for the few stiff systems we tried with LSODA, this actually slightly slowed down the solving.

Note that assignment can be done by $=$, $<-$ or \sim .

When assigning with the \sim operator, the **simple assignments** and **time-derivative** assignments will not be output.

Special statements can be:

- **Compartment declaration statements**, which can change the default dosing compartment and the assumed compartment number(s) as well as add extra compartment names at the end (useful for multiple-endpoint nlmixr models); These are specified by `cmt(compartmentName)`
- **Parameter declaration statements**, which can make sure the input parameters are in a certain order instead of ordering the parameters by the order they are parsed. This is useful for keeping the parameter order the same when using 2 different ODE models. These are specified by `param(par1, par2, ...)`

An example model is shown below:

```
# simple assignment
C2 = centr/V2;

# time-derivative assignment
d/dt(centr) = F*KA*depot - CL*C2 - Q*C2 + Q*C3;
```

Expressions in assignment and if statements can be numeric or logical.

Numeric expressions can include the following numeric operators $+$, $-$, $*$, $/$, $^$ and those mathematical functions defined in the C or the R math libraries (e.g., `fabs`, `exp`, `log`, `sin`, `abs`).

You may also access the R's functions in the [R math libraries](#), like `lgammafn` for the log gamma function.

The rxode2 syntax is case-sensitive, i.e., ABC is different than abc, Abc, ABc, etc.

Identifiers:

Like R, Identifiers (variable names) may consist of one or more alphanumeric, underscore `_` or period `.` characters, but the first character cannot be a digit or underscore `_`.

Identifiers in a model specification can refer to:

- State variables in the dynamic system (e.g., compartments in a pharmacokinetics model).
- Implied input variable, `t` (time), `tlast` (last time point), and `podo` (oral dose, in the undocumented case of absorption transit models).
- Special constants like `pi` or **R's predefined constants**.
- Model parameters (e.g., `ka` rate of absorption, `CL` clearance, etc.)
- Others, as created by assignments as part of the model specification; these are referred as *LHS* (left-hand side) variable.

Currently, the rxode2 modeling language only recognizes system state variables and “parameters”, thus, any values that need to be passed from R to the ODE model (e.g., `age`) should be either passed in the `params` argument of the integrator function `rxSolve()` or be in the supplied event data-set.

There are certain variable names that are in the rxode2 event tables. To avoid confusion, the following event table-related items cannot be assigned, or used as a state but can be accessed in the rxode2 code:

- `cmt`
- `dvid`
- `addl`
- `ss`
- `rate`
- `id`

However the following variables are cannot be used in a model specification:

- `evid`
- `ii`

Sometimes rxode2 generates variables that are fed back to rxode2. Similarly, `nlmixr` generates some variables that are used in `nlmixr` estimation and simulation. These variables start with the either the `rx` or `nlmixr` prefixes. To avoid any problems, it is suggested to not use these variables starting with either the `rx` or `nlmixr` prefixes.

Logical Operators:

Logical operators support the standard R operators `==`, `!=`, `>=`, `<=`, `>` and `<`. Like R these can be in `if()` or `while()` statements, `ifelse()` expressions. Additionally they can be in a standard assignment. For instance, the following is valid:

```
cov1 = covm*(sexf == "female") + covm*(sexf != "female")
```

Notice that you can also use character expressions in comparisons. This convenience comes at a cost since character comparisons are slower than numeric expressions. Unlike R, `as.numeric` or `as.integer` for these logical statements is not only not needed, but will cause a syntax error if you try to use the function.

Value

An object (environment) of class `rxode2` (see Chambers and Temple Lang (2001)) consisting of the following list of strings and functions:

- * ``model`` a character string holding the source model specification.
- * ``get.modelVars`` a function that returns a list with 3 character vectors, ``params``, ``state``, and ``lhs`` of variable names used in the model specification. These will be output when the model is computed (i.e., the ODE solved by integration).
- * ``solve``{this function solves (integrates) the ODE. This is done by passing the code to `[rxSolve()]`. This is as if you called ``rxSolve(rxode2object, ...)``, but returns a matrix instead of a `rxSolve` object.

``params``: a numeric named vector with values for every parameter in the ODE system; the names must correspond to the parameter identifiers used in the ODE specification;

``events``: an ``eventTable`` object describing the input (e.g., doses) to the dynamic system and observation sampling time points (see `[eventTable()]`);

``inits``: a vector of initial values of the state variables (e.g., amounts in each compartment), and the order in this vector must be the same as the state variables (e.g., PK/PD compartments);

``stiff``: a logical (``TRUE`` by default) indicating whether the ODE system is stiff or not.

For stiff ODE systems (``stiff = TRUE``), ``rxode2`` uses the LSODA (Livermore Solver for Ordinary Differential Equations) Fortran package, which implements an automatic method switching for stiff and non-stiff problems along the integration interval, authored by Hindmarsh and Petzold (2003).

For non-stiff systems (``stiff = FALSE``), ``rxode2`` uses ``DOP853``, an explicit Runge-Kutta method of order 8(5, 3) of Dormand and Prince as implemented in C by Hairer and Wanner (1993).

``trans_abs``: a logical (``FALSE`` by default) indicating whether to fit a transit absorption term (TODO: need further documentation and example);

``atol``: a numeric absolute tolerance (1e-08 by default);

``rtol``: a numeric relative tolerance (1e-06 by default).e

The output of `\dQuote{solve}` is a matrix with as many rows as there are sampled time points and as many columns as system variables (as defined by the ODEs and additional assignments in the `rxode2` model code).}

- * ``isValid`` a function that (naively) checks for model validity, namely that the C object code reflects the latest model specification.
- * ``version`` a string with the version of the ``rxode2`` object (not the package).
- * ``dynLoad`` a function with one ``force = FALSE`` argument that dynamically loads the object code if needed.
- * ``dynUnload`` a function with no argument that unloads the model object code.
- * ``delete`` removes all created model files, including C and DLL files. The model object is no longer valid and should be removed, e.g., ``rm(m1)``.
- * ``run`` deprecated, use ``solve``.
- * ``get.index`` deprecated.
- * ``getObj`` internal (not user callable) function.

Author(s)

Melissa Hallow, Wenping Wang and Matthew Fidler

References

- Chamber, J. M. and Temple Lang, D. (2001) *Object Oriented Programming in R*. R News, Vol. 1, No. 3, September 2001. https://cran.r-project.org/doc/Rnews/Rnews_2001-3.pdf.
- Hindmarsh, A. C. *ODEPACK, A Systematized Collection of ODE Solvers*. Scientific Computing, R. S. Stepleman et al. (Eds.), North-Holland, Amsterdam, 1983, pp. 55-64.
- Petzold, L. R. *Automatic Selection of Methods for Solving Stiff and Nonstiff Systems of Ordinary Differential Equations*. Siam J. Sci. Stat. Comput. 4 (1983), pp. 136-148.
- Hairer, E., Norsett, S. P., and Wanner, G. *Solving ordinary differential equations I, nonstiff problems*. 2nd edition, Springer Series in Computational Mathematics, Springer-Verlag (1993).
- Plevyak, J. `dparser`, <http://dparser.sourceforge.net>. Web. 12 Oct. 2015.

See Also

[eventTable\(\)](#), [et\(\)](#), [add.sampling\(\)](#), [add.dosing\(\)](#)

Examples

```
# Step 1 - Create a model specification
ode <- "
# A 4-compartment model, 3 PK and a PD (effect) compartment
# (notice state variable names 'depot', 'centr', 'peri', 'eff')

C2 = centr/V2;
C3 = peri/V3;
d/dt(depota) = -KA*depota;
d/dt(centra) = KA*depota - CL*C2 - Q*C2 + Q*C3;
```

```

      d/dt(peri) =          Q*C2 - Q*C3;
      d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff;
    ,,

m1 <- rxode(model = ode)
print(m1)

# Step 2 - Create the model input as an EventTable,
# including dosing and observation (sampling) events

# QD (once daily) dosing for 5 days.

qd <- eventTable(amount.units = "ug", time.units = "hours")
qd$add.dosing(dose = 10000, nbr.doses = 5, dosing.interval = 24)

# Sample the system hourly during the first day, every 8 hours
# then after

qd$add.sampling(0:24)
qd$add.sampling(seq(from = 24 + 8, to = 5 * 24, by = 8))

# Step 3 - set starting parameter estimates and initial
# values of the state

theta <-
  c(
    KA = .291, CL = 18.6,
    V2 = 40.2, Q = 10.5, V3 = 297.0,
    Kin = 1.0, Kout = 1.0, EC50 = 200.0
  )

# init state variable
inits <- c(0, 0, 0, 1)
# Step 4 - Fit the model to the data

qd.cp <- m1$solve(theta, events = qd, inits)

head(qd.cp)

# This returns a matrix. Note that you can also
# solve using name initial values. For example:

inits <- c(eff = 1)
qd.cp <- solve(m1, theta, events = qd, inits)
print(qd.cp)

plot(qd.cp)

# You can also directly simulate from a nlmixr model
f <- function() {
  ini({
    KA <- .291
    CL <- 18.6
  })
}

```

```

V2 <- 40.2
Q <- 10.5
V3 <- 297.0
Kin <- 1.0
Kout <- 1.0
EC50 <- 200.0
})
model({
  # A 4-compartment model, 3 PK and a PD (effect) compartment
  # (notice state variable names 'depot', 'centr', 'peri', 'eff')
  C2 <- centr/V2
  C3 <- peri/V3
  d/dt(depot) <- -KA*depot
  d/dt(centr) <- KA*depot - CL*C2 - Q*C2 + Q*C3
  d/dt(peri) <- Q*C2 - Q*C3
  d/dt(eff) <- Kin - Kout*(1-C2/(EC50+C2))*eff
  eff(0) <- 1
})
}

u <- f()

# this pre-compiles and displays the simulation model
u$simulationModel

qd.cp <-solve(u, qd)

print(qd.cp)

```

rxOptExpr

Optimize rxode2 for computer evaluation

Description

This optimizes rxode2 code for computer evaluation by only calculating redundant expressions once.

Usage

```
rxOptExpr(x, msg = "model")
```

Arguments

x	rxode2 model that can be accessed by rxNorm
msg	This is the name of type of object that rxode2 is optimizing that will in the message when optimizing. For example "model" will produce the following message while optimizing the model: finding duplicate expressions in model...

Value

Optimized rxode2 model text. The order and type lhs and state variables is maintained while the evaluation is sped up. While parameters names are maintained, their order may be modified.

Author(s)

Matthew L. Fidler

rxord	<i>Simulate ordinal value</i>
-------	-------------------------------

Description

Simulate ordinal value

Usage

```
rxord(...)
```

Arguments

... the probabilities to be simulated. These should sum up to a number below one.

Details

The values entered into the 'rxord' simulation will simulate the probability of falling each group. If it falls outside of the specified probabilities, it will simulate the group (number of probabilities specified + 1)

Value

A number from 1 to the (number of probabilities specified + 1)

Author(s)

Matthew L. Fidler

Examples

```
# This will give values 1, and 2
rxord(0.5)
rxord(0.5)
rxord(0.5)
rxord(0.5)

# This will give values 1, 2 and 3
rxord(0.3, 0.3)
rxord(0.3, 0.3)
```

```
rxord(0.3, 0.3)
```

```
rxParams
```

```
Parameters specified by the model
```

Description

This returns the model's parameters that are required to solve the ODE system, and can be used to pipe parameters into an rxode2 solve

Usage

```
rxParams(obj, ...)

## S3 method for class 'rxode2'
rxParams(
  obj,
  constants = TRUE,
  ...,
  params = NULL,
  inits = NULL,
  iCov = NULL,
  keep = NULL,
  thetaMat = NULL,
  omega = NULL,
  dfSub = NULL,
  sigma = NULL,
  dfObs = NULL,
  nSub = NULL,
  nStud = NULL
)

## S3 method for class 'rxSolve'
rxParams(
  obj,
  constants = TRUE,
  ...,
  params = NULL,
  inits = NULL,
  iCov = NULL,
  keep = NULL,
  thetaMat = NULL,
  omega = NULL,
  dfSub = NULL,
  sigma = NULL,
  dfObs = NULL,
```

```

    nSub = NULL,
    nStud = NULL
  )

## S3 method for class 'rxEt'
rxParams(
  obj,
  ...,
  params = NULL,
  inits = NULL,
  iCov = NULL,
  keep = NULL,
  thetaMat = NULL,
  omega = NULL,
  dfSub = NULL,
  sigma = NULL,
  dfObs = NULL,
  nSub = NULL,
  nStud = NULL
)

rxParam(obj, ...)

```

Arguments

obj	rxode2 family of objects
...	Other arguments including scaling factors for each compartment. This includes S# = numeric will scale a compartment # by a dividing the compartment amount by the scale factor, like NONMEM.
constants	is a boolean indicting if constants should be included in the list of parameters. Currently rxode2 parses constants into variables in case you wish to change them without recompiling the rxode2 model.
params	a numeric named vector with values for every parameter in the ODE system; the names must correspond to the parameter identifiers used in the ODE specification;
inits	a vector of initial values of the state variables (e.g., amounts in each compartment), and the order in this vector must be the same as the state variables (e.g., PK/PD compartments);
iCov	A data frame of individual non-time varying covariates to combine with the events dataset by merge.
keep	Columns to keep from either the input dataset or the iCov dataset. With the iCov dataset, the column is kept once per line. For the input dataset, if any records are added to the data LOCF (Last Observation Carried forward) imputation is performed.
thetaMat	Named theta matrix.
omega	Estimate of Covariance matrix. When omega is a list, assume it is a block matrix and convert it to a full matrix for simulations. When omega is NA and you are

using it with a rxode2 ui model, the between subject variability described by the omega matrix are set to zero.

dfSub	Degrees of freedom to sample the between subject variability matrix from the inverse Wishart distribution (scaled) or scaled inverse chi squared distribution.
sigma	Named sigma covariance or Cholesky decomposition of a covariance matrix. The names of the columns indicate parameters that are simulated. These are simulated for every observation in the solved system. When sigma is NA and you are using it with a rxode2 ui model, the unexplained variability described by the sigma matrix are set to zero.
dfObs	Degrees of freedom to sample the unexplained variability matrix from the inverse Wishart distribution (scaled) or scaled inverse chi squared distribution.
nSub	Number between subject variabilities (ETAs) simulated for every realization of the parameters.
nStud	Number virtual studies to characterize uncertainty in estimated parameters.

Value

When extracting the parameters from an rxode2 model, a character vector listing the parameters in the model.

Author(s)

Matthew L.Fidler

See Also

Other Query model information: `rxDfdy()`, `rxInits()`, `rxLhs()`, `rxModelVars()`, `rxState()`

rxPkg

Creates a package from compiled rxode2 models

Description

Creates a package from compiled rxode2 models

Usage

```
rxPkg(
  ...,
  package,
  wd = getwd(),
  action = c("install", "build", "binary", "create"),
  license = c("gpl3", "lgpl", "mit", "agpl3"),
  name = "Firstname Lastname",
  fields = list()
)
```

Arguments

...	Models to build a package from
package	String of the package name to create
wd	character string with a working directory where to create a subdirectory according to modName. When specified, a subdirectory named after the “modName.d” will be created and populated with a C file, a dynamic loading library, plus various other working files. If missing, the files are created (and removed) in the temporary directory, and the rxode2 DLL for the model is created in the current directory named rx_????_platform, for example rx_129f8f97fb94a87ca49ca8dafe691e1e_i386.dll
action	Type of action to take after package is created
license	is the type of license for the package.
name	Full name of author
fields	A named list of fields to add to DESCRIPTION, potentially overriding default values. See use_description() for how you can set personalized defaults using package options.

Value

this function returns nothing and is used for its side effects

Author(s)

Matthew Fidler

rxpois

Simulate random Poisson variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxpois(lambda, n = 1L, ncores = 1L)
```

Arguments

lambda	vector of (non-negative) means.
n	number of random values to return.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with rxSetSeed()

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

poission random number deviates

Examples

```
## Use threefry engine

rxpois(lambda = 3, n = 10) # with rxpois you have to explicitly state n
rxpois(lambda = 3, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxpois(4) ## The first arguments are the lambda parameter

## This example uses `rxpois` directly in the model

rx <- rxode2({
  a <- rxpois(3)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

 rxPp

Simulate a from a Poisson process

Description

Simulate a from a Poisson process

Usage

```

rxPp(
  n,
  lambda,
  gamma = 1,
  prob = NULL,
  t0 = 0,
  tmax = Inf,
  randomOrder = FALSE
)

```

Arguments

n	Number of time points to simulate in the Poisson process
lambda	Rate of Poisson process
gamma	Asymmetry rate of Poisson process. When gamma=1.0, this simulates a homogenous Poisson process. When gamma<1.0, the Poisson process has more events early, when gamma > 1.0, the Poisson process has more events late in the process. When gamma is non-zero, the tmax should not be infinite but indicate the end of the Poisson process to be simulated. In most pharamcometric cases, this will be the end of the study. Internally this uses a rate of: $l(t) = \text{lambda} \gamma (t/t_{\text{max}})^{\gamma-1}$
prob	When specified, this is a probability function with one argument, time, that gives the probability that a Poisson time t is accepted as a rejection time.
t0	the starting time of the Poisson process
tmax	the maximum time of the Poisson process
randomOrder	when TRUE randomize the order of the Poisson events. By default (FALSE) it returns the Poisson process is in order of how the events occurred.

Value

This returns a vector of the Poisson process times; If the dropout is \geq tmax, then all the rest of the times are = tmax to indicate the dropout is equal to or after tmax.

Author(s)

Matthew Fidler

Examples

```

## Sample homogenous Poisson process of rate 1/10
rxPp(10, 1 / 10)

## Sample inhomogenous Poisson rate of 1/10

```

```
rxPp(10, 1 / 10, gamma = 2, tmax = 100)

## Typically the Poisson process times are in a sequential order,
## using randomOrder gives the Poisson process in random order

rxPp(10, 1 / 10, gamma = 2, tmax = 10, randomOrder = TRUE)

## This uses an arbitrary function to sample a non-homogenous Poisson process

rxPp(10, 1 / 10, prob = function(x) {
  1 / x
})
```

rxPreferredDistributionName

Change distribution name to the preferred distribution name term

Description

This is determined by the internal preferred condition name list `.errIdenticalDists`

Usage

```
rxPreferredDistributionName(dist)
```

Arguments

dist This is the input distribution

Value

Preferred distribution term

Author(s)

Matthew Fidler

Examples

```
rxPreferredDistributionName("dnorm")

rxPreferredDistributionName("add")

# can be vectorized

rxPreferredDistributionName(c("add", "dnorm"))
```

rxProgress *rxode2 progress bar functions*

Description

rxProgress sets up the progress bar

Usage

```
rxProgress(num, core = 0L)
rxTick()
rxProgressStop(clear = TRUE)
rxProgressAbort(error = "Aborted calculation")
```

Arguments

num	Tot number of operations to track
core	Number of cores to show. If below 1, don't show number of cores
clear	Boolean telling if you should clear the progress bar after completion (as if it wasn't displayed). By default this is TRUE
error	With rxProgressAbort this is the error that is displayed

Details

rxTick is a progress bar tick
rxProgressStop stop progress bar
rxProgressAbort shows an abort if rxProgressStop wasn't called.

Value

All return NULL invisibly.

Author(s)

Matthew L. Fidler

Examples

```
f <- function() {
  on.exit({
    rxProgressAbort()
  })
  rxProgress(100)
  for (i in 1:100) {
```

```
    rxTick()  
    Sys.sleep(1 / 100)  
  }  
  rxProgressStop()  
}  
  
f()
```

rxRandNV

Create a random "normal" matrix using vandercorput generator

Description

Create a random "normal" matrix using vandercorput generator

Usage

```
rxRandNV(nrow = 1, ncol = 1)
```

Arguments

nrow	Number of rows
ncol	Number of Columns

Value

Matrix of random numbers

Author(s)

Matthew Fidler

Examples

```
rxRandNV(1, 1)  
rxRandNV(3, 2)
```

rxRateDur	<i>Creates a rxRateDur object</i>
-----------	-----------------------------------

Description

This is primarily to display information about rate

Usage

```
rxRateDur(x)

## S3 method for class 'rxRateDur'
x[...]

as.rxRateDur(x)

## S3 method for class 'rxRateDur'
as.character(x, ...)

## S3 method for class 'rxRateDur'
x[[...]]
```

Arguments

x	rxRateDur data
...	Other parameters

Value

rxRateDur object

rxRemoveControl	<i>rxRemoveControl options for UI object</i>
-----------------	--

Description

rxRemoveControl options for UI object

Usage

```
rxRemoveControl(ui)
```

Arguments

ui	rxode2 ui object
----	------------------

Value

Nothing, called for side effects

Author(s)

Matthew L. Fidler

rxRename

Rename items inside of a rxode2 ui model

Description

rxRename() changes the names of individual variables, lhs, and ode states using new_name = old_name syntax

Usage

```
rxRename(.data, ..., envir = parent.frame())
```

```
rename.rxUi(.data, ...)
```

```
rename.function(.data, ...)
```

Arguments

.data	rxode2 ui function, named data to be consistent with dplyr::rename()
...	rename items
envir	Environment for evaluation

Value

New model with items renamed

Author(s)

Matthew L. Fidler

Examples

```
ocmt <- function() {
  ini({
    tka <- exp(0.45) # Ka
    tcl <- exp(1) # Cl
    ## This works with interactive models
    ## You may also label the preceding line with label("label text")
    tv <- exp(3.45) # log V
    ## the label("Label name") works with all models
  })
}
```

```

    add.sd <- 0.7
  })
model({
  ka <- tka
  cl <- tc1
  v <- tv
  d/dt(depot) = -ka * depot
  d/dt(center) = ka * depot - cl / v * center
  cp = center / v
  cp ~ add(add.sd)
})
}

ocmt %>% rxRename(cpParent=cp)

```

rxReservedKeywords	<i>A list and description of Rode supported reserved keywords</i>
--------------------	---

Description

A list and description of Rode supported reserved keywords

Usage

```
rxReservedKeywords
```

Format

A data frame with 3 columns and 98 or more rows

Reserved Name Reserved Keyword Name

Meaning Reserved Keyword Meaning

Alias Keyword Alias

rxRmvn	<i>Simulate from a (truncated) multivariate normal</i>
--------	--

Description

This is simulated with the fast, thread-safe threefry simulator and can use multiple cores to generate the random deviates.

Usage

```

rxRmvn(
  n,
  mu = NULL,
  sigma,
  lower = -Inf,
  upper = Inf,
  ncores = 1,
  isChol = FALSE,
  keepNames = TRUE,
  a = 0.4,
  tol = 2.05,
  nlTol = 1e-10,
  nlMaxiter = 100L
)

```

Arguments

n	Number of random row vectors to be simulated OR the matrix to use for simulation (faster).
mu	mean vector
sigma	Covariance matrix for multivariate normal or a list of covariance matrices. If a list of covariance matrix, each matrix will simulate n matrices and combine them to a full matrix
lower	is a vector of the lower bound for the truncated multivariate norm
upper	is a vector of the upper bound for the truncated multivariate norm
ncores	Number of cores used in the simulation
isChol	A boolean indicating if sigma is a cholesky decomposition of the covariance matrix.
keepNames	Keep the names from either the mean or covariance matrix.
a	threshold for switching between methods; They can be tuned for maximum speed; There are three cases that are considered: case 1: $a < l < u$ case 2: $l < u < -a$ case 3: otherwise where l =lower and u = upper
tol	When case 3 is used from the above possibilities, the tol value controls the acceptance rejection and inverse-transformation; When $\text{abs}(u-l) > \text{tol}$, uses accept-reject from randn
nlTol	Tolerance for newton line-search
nlMaxiter	Maximum iterations for newton line-search

Value

If `n==integer` (default) the output is an $(n \times d)$ matrix where the i -th row is the i -th simulated vector.

If `is.matrix(n)` then the random vector are store in `n`, which is provided by the user, and the function returns NULL invisibly.

Author(s)

Matthew Fidler, Zdravko Botev and some from Matteo Fasiolo

References

John K. Salmon, Mark A. Moraes, Ron O. Dror, and David E. Shaw (2011). Parallel Random Numbers: As Easy as 1, 2, 3. D. E. Shaw Research, New York, NY 10036, USA.

The thread safe multivariate normal was inspired from the `mvnfast` package by Matteo Fasiolo <https://CRAN.R-project.org/package=mvnfast>

The concept of the truncated multivariate normal was taken from Zdravko Botev Botev (2017) [doi:10.1111/rssb.12162](https://doi.org/10.1111/rssb.12162) and Botev and L'Ecuyer (2015) [doi:10.1109/WSC.2015.7408180](https://doi.org/10.1109/WSC.2015.7408180) and converted to thread safe simulation;

Examples

```
## From mvnfast
## Unlike mvnfast, uses threefry simulation

d <- 5
mu <- 1:d

# Creating covariance matrix
tmp <- matrix(rnorm(d^2), d, d)
mcov <- tcrossprod(tmp, tmp)

set.seed(414)
rxRmvn(4, 1:d, mcov)

set.seed(414)
rxRmvn(4, 1:d, mcov)

set.seed(414)
rxRmvn(4, 1:d, mcov, ncores = 2) # r.v. generated on the second core are different

##### Here we create the matrix that will hold the simulated
# random variables upfront.
A <- matrix(NA, 4, d)
class(A) <- "numeric" # This is important. We need the elements of A to be of class "numeric".

set.seed(414)
rxRmvn(A, 1:d, mcov, ncores = 2) # This returns NULL ...
```

```
A # ... but the result is here

## You can also simulate from a truncated normal:

rxRmvn(10, 1:d, mcov, lower = 1:d - 1, upper = 1:d + 1)

# You can also simulate from different matrices (if they match
# dimensions) by using a list of matrices.

matL <- lapply(1:4, function(...) {
  tmp <- matrix(rnorm(d^2), d, d)
  tcrossprod(tmp, tmp)
})

rxRmvn(4, setNames(1:d, paste0("a", 1:d)), matL)
```

rxS

Load a model into a symengine environment

Description

Load a model into a symengine environment

Usage

```
rxS(x, doConst = TRUE, promoteLinSens = FALSE)
```

Arguments

`x` rxode2 object

`doConst` Load constants into the environment as well.

`promoteLinSens` Promote solved linear compartment systems to sensitivity-based solutions.

Value

rxode2/symengine environment

Author(s)

Matthew Fidler

rxSetControl	<i>rxSetControl options for UI object</i>
--------------	---

Description

rxSetControl options for UI object

Usage

```
rxSetControl(ui, control)
```

Arguments

ui	rxode2 ui object
control	Default value

Value

Nothing, called for side effects

Author(s)

Matthew L. Fidler

rxSetCovariateNamesForPiping	<i>Assign covariates for piping</i>
------------------------------	-------------------------------------

Description

Assign covariates for piping

Usage

```
rxSetCovariateNamesForPiping(covariates = NULL)
```

Arguments

covariates	NULL (for no covariates), or the list of covariates. nlmixr uses this function to set covariates if you pipe from a nlmixr fit.
------------	---

Value

Nothing, called for side effects

Author(s)

Matthew L. Fidler

Examples

```
# First set the name of known covariates
# Note this is case sensitive

rxSetCovariateNamesForPiping(c("WT", "HT", "TC"))

one.compartment <- function() {
  ini({
    tka <- 0.45 ; label("Log Ka")
    tc1 <- 1 ; label("Log Cl")
    tv <- 3.45 ; label("Log V")
    eta.ka ~ 0.6
    eta.cl ~ 0.3
    eta.v ~ 0.1
    add.err <- 0.7
  })
  model({
    ka <- exp(tka + eta.ka)
    cl <- exp(tc1 + eta.cl)
    v <- exp(tv + eta.v)
    d / dt(depot) <- -ka * depot
    d/dt(depot) <- -ka * depot
    d / dt(center) <- ka * depot - cl / v * center
    cp <- center / v
    cp ~ add(add.err)
  })
}

# now TC is detected as a covariate instead of a population parameter

one.compartment %>%
  model({ka <- exp(tka + eta.ka + TC * cov_C)})

# You can turn it off by simply adding it back

rxSetCovariateNamesForPiping()

one.compartment %>%
  model({ka <- exp(tka + eta.ka + TC * cov_C)})

# The covariates you set with `rxSetCovariateNamesForPiping()`
# are turned off every time you solve (or fit in nlmixr)
```

rxSetIni0	<i>Set Initial conditions to time zero instead of the first observed/dosed time</i>
-----------	---

Description

Set Initial conditions to time zero instead of the first observed/dosed time

Usage

```
rxSetIni0(ini0 = TRUE)
```

Arguments

ini0	When TRUE (default), set initial conditions to time zero. Otherwise the initial conditions are the first observed time.
------	---

Value

the boolean ini0, though this is called for its side effects

rxSetProd	<i>Defunct setting of product</i>
-----------	-----------------------------------

Description

Defunct setting of product

Usage

```
rxSetProd(type = c("long double", "double", "logify"))
```

Arguments

type	used to be type of product
------	----------------------------

Value

nothing

rxSetProgressBar *Set timing for progress bar*

Description

Set timing for progress bar

Usage

```
rxSetProgressBar(seconds = 1)
```

Arguments

seconds This sets the number of seconds that need to elapse before drawing the next segment of the progress bar. When this is zero or below this turns off the progress bar.

Value

nothing, used for side effects

Author(s)

Matthew Fidler

rxSetSeed *Set the parallel seed for rxode2 random number generation*

Description

This sets the seed for the rxode2 parallel random number generation. If set, then whenever a seed is set for the threefry or vandercorput simulation engine, it will use this seed, increment for the number of seeds and continue with the sequence the next time the random number generator is called.

Usage

```
rxSetSeed(seed)
```

Arguments

seed An integer that represents the rxode2 parallel and internal random number generator seed. When positive, use this seed for random number generation and increment and reseed any parallel or new engines that are being called. When negative, turn off the rxode2 seed and generate a seed from the R's uniform random number generator. Best practice is to set this seed.

Details

In contrast, when this is not called, the time that the vandercorput or threefry simulation engines are seeded it comes from a uniform random number generated from the standard R random seed. This may cause a duplicate seed based on the R seed state. This means that there could be correlations between simulations that do not exist. This will avoid the birthday problem picking exactly the same seed using the seed state of the R random number generator. The more times the seed is called, the more likely this becomes.

Value

Nothing, called for its side effects

Author(s)

Matthew Fidler

References

JD Cook. (2016). Random number generator seed mistakes. <https://tinyurl.com/m62v3kv9>

See Also

rxGetSeed, rxWithSeed, rxWithPreserveSeed

Examples

```
rxSetSeed(42)

# seed with generator 42
rxnorm()

# Use R's random number generator
rnorm(1)

rxSetSeed(42)

# reproduces the same number
rxnorm()

# But R's random number is not the same

rnorm(1)

# If we reset this to use the R's seed
# (internally rxode2 uses a uniform random number to span seeds)
# This can lead to duplicate sequences and seeds

rxSetSeed(-1)

# Now set seed works for both.
```

```
# This is not recommended, but illustrates the different types of
# seeds that can be generated.
```

```
set.seed(42)
```

```
rxnorm()
```

```
rnorm(1)
```

```
set.seed(42)
```

```
rxnorm()
```

```
rnorm(1)
```

rxSetSum

Defunct setting of sum

Description

Defunct setting of sum

Usage

```
rxSetSum(type = c("pairwise", "fsum", "kahan", "neumaier", "c"))
```

Arguments

type used to be type of product

Value

nothing

rxShiny

Use Shiny to help develop an rxode2 model

Description

Use Shiny to help develop an rxode2 model

Usage

```

rxShiny(
  object,
  params = NULL,
  events = NULL,
  inits = NULL,
  ...,
  data = data.frame()
)

## S3 method for class 'rxSolve'
rxShiny(
  object,
  params = NULL,
  events = NULL,
  inits = NULL,
  ...,
  data = data.frame()
)

## Default S3 method:
rxShiny(
  object = NULL,
  params = NULL,
  events = NULL,
  inits = NULL,
  ...,
  data = data.frame()
)

```

Arguments

<code>object</code>	A rxode2 family of objects. If not supplied a 2-compartment indirect effect model is used. If it is supplied, use the model associated with the rxode2 object for the model exploration.
<code>params</code>	Initial parameters for model
<code>events</code>	Event information (currently ignored)
<code>inits</code>	Initial estimates for model
<code>...</code>	Other arguments passed to rxShiny. Currently doesn't do anything.
<code>data</code>	Any data that you would like to plot. If the data has a <code>time</code> variable as well as a compartment or calculated variable that matches the rxode2 model, the data will be added to the plot of a specific compartment or calculated variable.

Value

Nothing; Starts a shiny server

Author(s)

Zufar Mulyukov and Matthew L. Fidler

 rxSimThetaOmega

Simulate Parameters from a Theta/Omega specification

Description

Simulate Parameters from a Theta/Omega specification

Usage

```
rxSimThetaOmega(
  params = NULL,
  omega = NULL,
  omegaDf = NULL,
  omegaLower = as.numeric(c(R_NegInf)),
  omegaUpper = as.numeric(c(R_PosInf)),
  omegaIsChol = FALSE,
  omegaSeparation = "auto",
  omegaXform = 1L,
  nSub = 1L,
  thetaMat = NULL,
  thetaLower = as.numeric(c(R_NegInf)),
  thetaUpper = as.numeric(c(R_PosInf)),
  thetaDf = NULL,
  thetaIsChol = FALSE,
  nStud = 1L,
  sigma = NULL,
  sigmaLower = as.numeric(c(R_NegInf)),
  sigmaUpper = as.numeric(c(R_PosInf)),
  sigmaDf = NULL,
  sigmaIsChol = FALSE,
  sigmaSeparation = "auto",
  sigmaXform = 1L,
  nCoresRV = 1L,
  nObs = 1L,
  dfSub = 0,
  dfObs = 0,
  simSubjects = TRUE,
  simVariability = as.logical(c(NA_LOGICAL))
)
```

Arguments

params Named Vector of rxode2 model parameters

omega	Estimate of Covariance matrix. When omega is a list, assume it is a block matrix and convert it to a full matrix for simulations. When omega is NA and you are using it with a rxode2 ui model, the between subject variability described by the omega matrix are set to zero.
omegaDf	The degrees of freedom of a t-distribution for simulation. By default this is NULL which is equivalent to Inf degrees, or to simulate from a normal distribution instead of a t-distribution.
omegaLower	Lower bounds for simulated ETAs (by default -Inf)
omegaUpper	Upper bounds for simulated ETAs (by default Inf)
omegaIsChol	Indicates if the omega supplied is a Cholesky decomposed matrix instead of the traditional symmetric matrix.
omegaSeparation	<p>Omega separation strategy</p> <p>Tells the type of separation strategy when simulating covariance with parameter uncertainty with standard deviations modeled in the thetaMat matrix.</p> <ul style="list-style-type: none"> • "lkj" simulates the correlation matrix from the rLKJ1 matrix with the distribution parameter eta equal to the degrees of freedom nu by (nu-1)/2 • "separation" simulates from the identity inverse Wishart covariance matrix with nu degrees of freedom. This is then converted to a covariance matrix and augmented with the modeled standard deviations. While computationally more complex than the "lkj" prior, it performs better when the covariance matrix size is greater or equal to 10 • "auto" chooses "lkj" when the dimension of the matrix is less than 10 and "separation" when greater than equal to 10.
omegaXform	<p>When taking omega values from the thetaMat simulations (using the separation strategy for covariance simulation), how should the thetaMat values be turned into standard deviation values:</p> <ul style="list-style-type: none"> • identity This is when standard deviation values are directly modeled by the params and thetaMat matrix • variance This is when the params and thetaMat simulates the variance that are directly modeled by the thetaMat matrix • log This is when the params and thetaMat simulates log(sd) • nlmixrSqrt This is when the params and thetaMat simulates the inverse cholesky decomposed matrix with the x^2 modeled along the diagonal. This only works with a diagonal matrix. • nlmixrLog This is when the params and thetaMat simulates the inverse cholesky decomposed matrix with the $\exp(x^2)$ along the diagonal. This only works with a diagonal matrix. • nlmixrIdentity This is when the params and thetaMat simulates the inverse cholesky decomposed matrix. This only works with a diagonal matrix.
nSub	Number between subject variabilities (ETAs) simulated for every realization of the parameters.
thetaMat	Named theta matrix.

thetaLower	Lower bounds for simulated population parameter variability (by default -Inf)
thetaUpper	Upper bounds for simulated population unexplained variability (by default Inf)
thetaDf	The degrees of freedom of a t-distribution for simulation. By default this is NULL which is equivalent to Inf degrees, or to simulate from a normal distribution instead of a t-distribution.
thetaIsChol	Indicates if the theta supplied is a Cholesky decomposed matrix instead of the traditional symmetric matrix.
nStud	Number virtual studies to characterize uncertainty in estimated parameters.
sigma	Named sigma covariance or Cholesky decomposition of a covariance matrix. The names of the columns indicate parameters that are simulated. These are simulated for every observation in the solved system. When sigma is NA and you are using it with a rxode2 ui model, the unexplained variability described by the sigma matrix are set to zero.
sigmaLower	Lower bounds for simulated unexplained variability (by default -Inf)
sigmaUpper	Upper bounds for simulated unexplained variability (by default Inf)
sigmaDf	Degrees of freedom of the sigma t-distribution. By default it is equivalent to Inf, or a normal distribution.
sigmaIsChol	Boolean indicating if the sigma is in the Cholesky decomposition instead of a symmetric covariance
sigmaSeparation	<p>separation strategy for sigma;</p> <p>Tells the type of separation strategy when simulating covariance with parameter uncertainty with standard deviations modeled in the thetaMat matrix.</p> <ul style="list-style-type: none"> • "lkj" simulates the correlation matrix from the rLKJ1 matrix with the distribution parameter eta equal to the degrees of freedom nu by (nu-1)/2 • "separation" simulates from the identity inverse Wishart covariance matrix with nu degrees of freedom. This is then converted to a covariance matrix and augmented with the modeled standard deviations. While computationally more complex than the "lkj" prior, it performs better when the covariance matrix size is greater or equal to 10 • "auto" chooses "lkj" when the dimension of the matrix is less than 10 and "separation" when greater than equal to 10.
sigmaXform	<p>When taking sigma values from the thetaMat simulations (using the separation strategy for covariance simulation), how should the thetaMat values be turned into standard deviation values:</p> <ul style="list-style-type: none"> • identity This is when standard deviation values are directly modeled by the params and thetaMat matrix • variance This is when the params and thetaMat simulates the variance that are directly modeled by the thetaMat matrix • log This is when the params and thetaMat simulates log(sd) • nlmixrSqrt This is when the params and thetaMat simulates the inverse cholesky decomposed matrix with the x^2 modeled along the diagonal. This only works with a diagonal matrix.

- `nlmixrLog` This is when the `params` and `thetaMat` simulates the inverse cholesky decomposed matrix with the $\exp(x^2)$ along the diagonal. This only works with a diagonal matrix.
- `nlmixrIdentity` This is when the `params` and `thetaMat` simulates the inverse cholesky decomposed matrix. This only works with a diagonal matrix.

<code>nCoresRV</code>	Number of cores used for the simulation of the sigma variables. By default this is 1. To reproduce the results you need to run on the same platform with the same number of cores. This is the reason this is set to be one, regardless of what the number of cores are used in threaded ODE solving.
<code>nObs</code>	Number of observations to simulate (with sigma matrix)
<code>dfSub</code>	Degrees of freedom to sample the between subject variability matrix from the inverse Wishart distribution (scaled) or scaled inverse chi squared distribution.
<code>dfObs</code>	Degrees of freedom to sample the unexplained variability matrix from the inverse Wishart distribution (scaled) or scaled inverse chi squared distribution.
<code>simSubjects</code>	boolean indicated <code>rxode2</code> should simulate subjects in studies (TRUE, default) or studies (FALSE)
<code>simVariability</code>	determines if the variability is simulated. When NA (default) this is determined by the solver.

Value

a data frame with the simulated subjects

Author(s)

Matthew L.Fidler

rxSolve

Solving & Simulation of a ODE/solved system (a options) equation

Description

This uses `rxode2` family of objects, file, or model specification to solve a ODE system. There are many options for a solved `rxode2` model, the first are the required object, and events with the some-times optional `params` and `inits`.

Usage

```
rxSolve(
  object,
  params = NULL,
  events = NULL,
  inits = NULL,
  scale = NULL,
```

```
method = c("liblsoda", "lsoda", "dop853", "indLin"),
sigdig = NULL,
atol = 1e-08,
rtol = 1e-06,
maxsteps = 70000L,
hmin = 0,
hmax = NA_real_,
hmaxSd = 0,
hini = 0,
maxordn = 12L,
maxords = 5L,
...,
cores,
covsInterpolation = c("locf", "linear", "nocb", "midpoint"),
addCov = TRUE,
sigma = NULL,
sigmaDf = NULL,
sigmaLower = -Inf,
sigmaUpper = Inf,
nCoresRV = 1L,
sigmaIsChol = FALSE,
sigmaSeparation = c("auto", "lkj", "separation"),
sigmaXform = c("identity", "variance", "log", "nlmixrSqrt", "nlmixrLog",
  "nlmixrIdentity"),
nDisplayProgress = 10000L,
amountUnits = NA_character_,
timeUnits = "hours",
theta = NULL,
thetaLower = -Inf,
thetaUpper = Inf,
eta = NULL,
addDosing = FALSE,
stateTrim = Inf,
updateObject = FALSE,
omega = NULL,
omegaDf = NULL,
omegaIsChol = FALSE,
omegaSeparation = c("auto", "lkj", "separation"),
omegaXform = c("variance", "identity", "log", "nlmixrSqrt", "nlmixrLog",
  "nlmixrIdentity"),
omegaLower = -Inf,
omegaUpper = Inf,
nSub = 1L,
thetaMat = NULL,
thetaDf = NULL,
thetaIsChol = FALSE,
nStud = 1L,
dfSub = 0,
```

```

dfObs = 0,
returnType = c("rxSolve", "matrix", "data.frame", "data.frame.TBS", "data.table",
  "tbl", "tibble"),
seed = NULL,
nsim = NULL,
minSS = 10L,
maxSS = 1000L,
infSSstep = 12,
strictSS = TRUE,
istateReset = TRUE,
subsetNonmem = TRUE,
maxAtolRtolFactor = 0.1,
from = NULL,
to = NULL,
by = NULL,
length.out = NULL,
iCov = NULL,
keep = NULL,
indLinPhiTol = 1e-07,
indLinPhiM = 0L,
indLinMatExpType = c("expokit", "Al-Mohy", "arma"),
indLinMatExpOrder = 6L,
drop = NULL,
idFactor = TRUE,
mxhnil = 0,
hmxi = 0,
warnIdSort = TRUE,
warnDrop = TRUE,
ssAtol = 1e-08,
ssRtol = 1e-06,
safeZero = TRUE,
sumType = c("pairwise", "fsum", "kahan", "neumaier", "c"),
prodType = c("long double", "double", "logify"),
sensType = c("advan", "autodiff", "forward", "central"),
linDiff = c(tlag = 1.5e-05, f = 1.5e-05, rate = 1.5e-05, dur = 1.5e-05, tlag2 =
  1.5e-05, f2 = 1.5e-05, rate2 = 1.5e-05, dur2 = 1.5e-05),
linDiffCentral = c(tlag = TRUE, f = TRUE, rate = TRUE, dur = TRUE, tlag2 = TRUE, f2 =
  TRUE, rate2 = TRUE, dur2 = TRUE),
resample = NULL,
resampleID = TRUE,
maxwhile = 1e+05,
atolSens = 1e-08,
rtolSens = 1e-06,
ssAtolSens = 1e-08,
ssRtolSens = 1e-06,
simVariability = NA
)

```

```
## S3 method for class ``function``
rxSolve(
  object,
  params = NULL,
  events = NULL,
  inits = NULL,
  ...,
  theta = NULL,
  eta = NULL
)

## S3 method for class 'rxUi'
rxSolve(
  object,
  params = NULL,
  events = NULL,
  inits = NULL,
  ...,
  theta = NULL,
  eta = NULL
)

## S3 method for class 'nlmixr2FitData'
rxSolve(
  object,
  params = NULL,
  events = NULL,
  inits = NULL,
  ...,
  theta = NULL,
  eta = NULL
)

## S3 method for class 'nlmixr2FitCore'
rxSolve(
  object,
  params = NULL,
  events = NULL,
  inits = NULL,
  ...,
  theta = NULL,
  eta = NULL
)

## Default S3 method:
rxSolve(
  object,
  params = NULL,
```

```
    events = NULL,  
    inits = NULL,  
    ...,  
    theta = NULL,  
    eta = NULL  
  )  
  
## S3 method for class 'rxSolve'  
update(object, ...)  
  
## S3 method for class 'rxode2'  
predict(object, ...)  
  
## S3 method for class 'rxSolve'  
predict(object, ...)  
  
## S3 method for class 'rxEt'  
predict(object, ...)  
  
## S3 method for class 'rxParams'  
predict(object, ...)  
  
## S3 method for class 'rxode2'  
simulate(object, nsim = 1L, seed = NULL, ...)  
  
## S3 method for class 'rxSolve'  
simulate(object, nsim = 1L, seed = NULL, ...)  
  
## S3 method for class 'rxParams'  
simulate(object, nsim = 1L, seed = NULL, ...)  
  
## S3 method for class 'rxSolve'  
solve(a, b, ...)  
  
## S3 method for class 'rxUi'  
solve(a, b, ...)  
  
## S3 method for class 'rxode2'  
solve(a, b, ...)  
  
## S3 method for class 'rxParams'  
solve(a, b, ...)  
  
## S3 method for class 'rxEt'  
solve(a, b, ...)  
  
rxControl(..., params = NULL, events = NULL, inits = NULL)
```

Arguments

object	is either a rxode2 family of objects, or a file-name with a rxode2 model specification, or a string with a rxode2 model specification.
params	a numeric named vector with values for every parameter in the ODE system; the names must correspond to the parameter identifiers used in the ODE specification;
events	an eventTable object describing the input (e.g., doses) to the dynamic system and observation sampling time points (see eventTable());
inits	a vector of initial values of the state variables (e.g., amounts in each compartment), and the order in this vector must be the same as the state variables (e.g., PK/PD compartments);
scale	a numeric named vector with scaling for ode parameters of the system. The names must correspond to the parameter identifiers in the ODE specification. Each of the ODE variables will be divided by the scaling factor. For example <code>scale=c(center=2)</code> will divide the center ODE variable by 2.
method	The method for solving ODEs. Currently this supports: <ul style="list-style-type: none"> • "liblsoda" thread safe lsoda. This supports parallel thread-based solving, and ignores user Jacobian specification. • "lsoda" – LSODA solver. Does not support parallel thread-based solving, but allows user Jacobian specification. • "dop853" – DOP853 solver. Does not support parallel thread-based solving nor user Jacobian specification • "indLin" – Solving through inductive linearization. The rxode2 dll must be setup specially to use this solving routine.
sigdig	Specifies the "significant digits" that the ode solving requests. When specified this controls the relative and absolute tolerances of the ODE solvers. By default the tolerance is $0.5 \times 10^{(-\text{sigdig}-2)}$ for regular ODEs. For the sensitivity equations and steady-state solutions the default is $0.5 \times 10^{(-\text{sigdig}-1.5)}$ (sensitivity changes only applicable for liblsoda). By default this is unspecified (NULL) and uses the standard <code>atol/rtol</code> .
atol	a numeric absolute tolerance ($1e-8$ by default) used by the ODE solver to determine if a good solution has been achieved; This is also used in the solved linear model to check if prior doses do not add anything to the solution.
rtol	a numeric relative tolerance ($1e-6$ by default) used by the ODE solver to determine if a good solution has been achieved. This is also used in the solved linear model to check if prior doses do not add anything to the solution.
maxsteps	maximum number of (internally defined) steps allowed during one call to the solver. (5000 by default)
hmin	The minimum absolute step size allowed. The default value is 0.
hmax	The maximum absolute step size allowed. When <code>hmax=NA</code> (default), uses the average difference + <code>hmaxSd*sd</code> in times and sampling events. The <code>hmaxSd</code> is a user specified parameter and which defaults to zero. When <code>hmax=NULL</code> rxode2 uses the maximum difference in times in your sampling and events. The value 0 is equivalent to infinite maximum absolute step size.

hmaxSd	The number of standard deviations of the time difference to add to hmax. The default is 0
hini	The step size to be attempted on the first step. The default value is determined by the solver (when $hini = 0$)
maxordn	The maximum order to be allowed for the nonstiff (Adams) method. The default is 12. It can be between 1 and 12.
maxords	The maximum order to be allowed for the stiff (BDF) method. The default value is 5. This can be between 1 and 5.
...	Other arguments including scaling factors for each compartment. This includes $S\# = numeric$ will scale a compartment # by a dividing the compartment amount by the scale factor, like NONMEM.
cores	Number of cores used in parallel ODE solving. This is equivalent to calling setRxThreads()
covsInterpolation	<p>specifies the interpolation method for time-varying covariates. When solving ODEs it often samples times outside the sampling time specified in events. When this happens, the time varying covariates are interpolated. Currently this can be:</p> <ul style="list-style-type: none"> • "linear" interpolation, which interpolates the covariate by solving the line between the observed covariates and extrapolating the new covariate value. • "constant" – Last observation carried forward (the default). • "NOCB" – Next Observation Carried Backward. This is the same method that NONMEM uses. • "midpoint" Last observation carried forward to midpoint; Next observation carried backward to midpoint.
addCov	A boolean indicating if covariates should be added to the output matrix or data frame. By default this is disabled.
sigma	Named sigma covariance or Cholesky decomposition of a covariance matrix. The names of the columns indicate parameters that are simulated. These are simulated for every observation in the solved system. When sigma is NA and you are using it with a rxode2 ui model, the unexplained variability described by the sigma matrix are set to zero.
sigmaDf	Degrees of freedom of the sigma t-distribution. By default it is equivalent to Inf, or a normal distribution.
sigmaLower	Lower bounds for simulated unexplained variability (by default -Inf)
sigmaUpper	Upper bounds for simulated unexplained variability (by default Inf)
nCoresRV	Number of cores used for the simulation of the sigma variables. By default this is 1. To reproduce the results you need to run on the same platform with the same number of cores. This is the reason this is set to be one, regardless of what the number of cores are used in threaded ODE solving.
sigmaIsChol	Boolean indicating if the sigma is in the Cholesky decomposition instead of a symmetric covariance

sigmaSeparation	<p>separation strategy for sigma;</p> <p>Tells the type of separation strategy when simulating covariance with parameter uncertainty with standard deviations modeled in the thetaMat matrix.</p> <ul style="list-style-type: none"> • "lkj" simulates the correlation matrix from the rLKJ1 matrix with the distribution parameter eta equal to the degrees of freedom nu by (nu-1)/2 • "separation" simulates from the identity inverse Wishart covariance matrix with nu degrees of freedom. This is then converted to a covariance matrix and augmented with the modeled standard deviations. While computationally more complex than the "lkj" prior, it performs better when the covariance matrix size is greater or equal to 10 • "auto" chooses "lkj" when the dimension of the matrix is less than 10 and "separation" when greater than equal to 10.
sigmaXform	<p>When taking sigma values from the thetaMat simulations (using the separation strategy for covariance simulation), how should the thetaMat values be turned into standard deviation values:</p> <ul style="list-style-type: none"> • identity This is when standard deviation values are directly modeled by the params and thetaMat matrix • variance This is when the params and thetaMat simulates the variance that are directly modeled by the thetaMat matrix • log This is when the params and thetaMat simulates log(sd) • nlmixrSqrt This is when the params and thetaMat simulates the inverse cholesky decomposed matrix with the x^2 modeled along the diagonal. This only works with a diagonal matrix. • nlmixrLog This is when the params and thetaMat simulates the inverse cholesky decomposed matrix with the exp(x^2) along the diagonal. This only works with a diagonal matrix. • nlmixrIdentity This is when the params and thetaMat simulates the inverse cholesky decomposed matrix. This only works with a diagonal matrix.
nDisplayProgress	<p>An integer indicating the minimum number of c-based solves before a progress bar is shown. By default this is 10,000.</p>
amountUnits	<p>This supplies the dose units of a data frame supplied instead of an event table. This is for importing the data as an rxode2 event table.</p>
timeUnits	<p>This supplies the time units of a data frame supplied instead of an event table. This is for importing the data as an rxode2 event table.</p>
theta	<p>A vector of parameters that will be named THETA\[#\] and added to parameters</p>
thetaLower	<p>Lower bounds for simulated population parameter variability (by default -Inf)</p>
thetaUpper	<p>Upper bounds for simulated population unexplained variability (by default Inf)</p>
eta	<p>A vector of parameters that will be named ETA\[#\] and added to parameters</p>
addDosing	<p>Boolean indicating if the solve should add rxode2 EVID and related columns. This will also include dosing information and estimates at the doses. By default, rxode2 only includes estimates at the observations. (default FALSE). When</p>

addDosing is NULL, only include EVID=0 on solve and exclude any model-times or EVID=2. If addDosing is NA the classic rxode2 EVID events are returned. When addDosing is TRUE add the event information in NONMEM-style format; If subsetNonmem=FALSE rxode2 will also include extra event types (EVID) for ending infusion and modeled times:

- EVID=-1 when the modeled rate infusions are turned off (matches rate=-1)
- EVID=-2 When the modeled duration infusions are turned off (matches rate=-2)
- EVID=-10 When the specified rate infusions are turned off (matches rate>0)
- EVID=-20 When the specified dur infusions are turned off (matches dur>0)
- EVID=101, 102, 103, . . . Modeled time where 101 is the first model time, 102 is the second etc.

stateTrim	When amounts/concentrations in one of the states are above this value, trim them to be this value. By default Inf. Also trims to -stateTrim for large negative amounts/concentrations. If you want to trim between a range say $c(0, 2000000)$ you may specify 2 values with a lower and upper range to make sure all state values are in the reasonable range.
updateObject	This is an internally used flag to update the rxode2 solved object (when supplying an rxode2 solved object) as well as returning a new object. You probably should not modify it's FALSE default unless you are willing to have unexpected results.
omega	Estimate of Covariance matrix. When omega is a list, assume it is a block matrix and convert it to a full matrix for simulations. When omega is NA and you are using it with a rxode2 ui model, the between subject variability described by the omega matrix are set to zero.
omegaDf	The degrees of freedom of a t-distribution for simulation. By default this is NULL which is equivalent to Inf degrees, or to simulate from a normal distribution instead of a t-distribution.
omegaIsChol	Indicates if the omega supplied is a Cholesky decomposed matrix instead of the traditional symmetric matrix.
omegaSeparation	Omega separation strategy Tells the type of separation strategy when simulating covariance with parameter uncertainty with standard deviations modeled in the thetaMat matrix. <ul style="list-style-type: none"> • "lkj" simulates the correlation matrix from the rLKJ1 matrix with the distribution parameter eta equal to the degrees of freedom nu by $(nu-1)/2$ • "separation" simulates from the identity inverse Wishart covariance matrix with nu degrees of freedom. This is then converted to a covariance matrix and augmented with the modeled standard deviations. While computationally more complex than the "lkj" prior, it performs better when the covariance matrix size is greater or equal to 10 • "auto" chooses "lkj" when the dimension of the matrix is less than 10 and "separation" when greater than equal to 10.
omegaXform	When taking omega values from the thetaMat simulations (using the separation strategy for covariance simulation), how should the thetaMat values be turned into standard deviation values:

	<ul style="list-style-type: none"> • <code>identity</code> This is when standard deviation values are directly modeled by the <code>params</code> and <code>thetaMat</code> matrix • <code>variance</code> This is when the <code>params</code> and <code>thetaMat</code> simulates the variance that are directly modeled by the <code>thetaMat</code> matrix • <code>log</code> This is when the <code>params</code> and <code>thetaMat</code> simulates $\log(\text{sd})$ • <code>nlmixrSqrt</code> This is when the <code>params</code> and <code>thetaMat</code> simulates the inverse cholesky decomposed matrix with the x^2 modeled along the diagonal. This only works with a diagonal matrix. • <code>nlmixrLog</code> This is when the <code>params</code> and <code>thetaMat</code> simulates the inverse cholesky decomposed matrix with the $\exp(x^2)$ along the diagonal. This only works with a diagonal matrix. • <code>nlmixrIdentity</code> This is when the <code>params</code> and <code>thetaMat</code> simulates the inverse cholesky decomposed matrix. This only works with a diagonal matrix.
<code>omegaLower</code>	Lower bounds for simulated ETAs (by default <code>-Inf</code>)
<code>omegaUpper</code>	Upper bounds for simulated ETAs (by default <code>Inf</code>)
<code>nSub</code>	Number between subject variabilities (ETAs) simulated for every realization of the parameters.
<code>thetaMat</code>	Named theta matrix.
<code>thetaDf</code>	The degrees of freedom of a t-distribution for simulation. By default this is <code>NULL</code> which is equivalent to <code>Inf</code> degrees, or to simulate from a normal distribution instead of a t-distribution.
<code>thetaIsChol</code>	Indicates if the theta supplied is a Cholesky decomposed matrix instead of the traditional symmetric matrix.
<code>nStud</code>	Number virtual studies to characterize uncertainty in estimated parameters.
<code>dfSub</code>	Degrees of freedom to sample the between subject variability matrix from the inverse Wishart distribution (scaled) or scaled inverse chi squared distribution.
<code>dfObs</code>	Degrees of freedom to sample the unexplained variability matrix from the inverse Wishart distribution (scaled) or scaled inverse chi squared distribution.
<code>returnType</code>	<p>This tells what type of object is returned. The currently supported types are:</p> <ul style="list-style-type: none"> • <code>"rxSolve"</code> (default) will return a reactive data frame that can change easily change different pieces of the solve and update the data frame. This is the currently standard solving method in <code>rxode2</code>, is used for <code>rxSolve(object, ...)</code>, <code>solve(object, ...)</code>, • <code>"data.frame"</code> – returns a plain, non-reactive data frame; Currently very slightly faster than <code>returnType="matrix"</code> • <code>"matrix"</code> – returns a plain matrix with column names attached to the solved object. This is what is used <code>object\$run</code> as well as <code>object\$solve</code> • <code>"data.table"</code> – returns a <code>data.table</code>; The <code>data.table</code> is created by reference (ie <code>setDt()</code>), which should be fast. • <code>"tbl"</code> or <code>"tibble"</code> returns a tibble format.
<code>seed</code>	an object specifying if and how the random number generator should be initialized

nsim	represents the number of simulations. For rxode2, if you supply single subject event tables (created with [eventTable()])
minSS	Minimum number of iterations for a steady-state dose
maxSS	Maximum number of iterations for a steady-state dose
infSSstep	Step size for determining if a constant infusion has reached steady state. By default this is large value, 12.
strictSS	Boolean indicating if a strict steady-state is required. If a strict steady-state is (TRUE) required then at least minSS doses are administered and the total number of steady states doses will continue until maxSS is reached, or atol and rtol for every compartment have been reached. However, if ODE solving problems occur after the minSS has been reached the whole subject is considered an invalid solve. If strictSS is FALSE then as long as minSS has been reached the last good solve before ODE solving problems occur is considered the steady state, even though either atol, rtol or maxSS have not been achieved.
istateReset	When TRUE, reset the ISTATE variable to 1 for lsoda and liblsoda with doses, like deSolve; When FALSE, do not reset the ISTATE variable with doses.
subsetNonmem	subset to NONMEM compatible EVIDs only. By default TRUE.
maxAtolRtolFactor	The maximum atol/rtol that FOCEi and other routines may adjust to. By default 0.1
from	When there is no observations in the event table, start observations at this value. By default this is zero.
to	When there is no observations in the event table, end observations at this value. By default this is 24 + maximum dose time.
by	When there are no observations in the event table, this is the amount to increment for the observations between from and to.
length.out	The number of observations to create if there isn't any observations in the event table. By default this is 200.
iCov	A data frame of individual non-time varying covariates to combine with the events dataset by merge.
keep	Columns to keep from either the input dataset or the iCov dataset. With the iCov dataset, the column is kept once per line. For the input dataset, if any records are added to the data LOCF (Last Observation Carried forward) imputation is performed.
indLinPhiTol	the requested accuracy tolerance on exponential matrix.
indLinPhiM	the maximum size for the Krylov basis
indLinMatExpType	This is them matrix exponential type that is use for rxode2. Currently the following are supported: <ul style="list-style-type: none"> • Al-Mohy Uses the exponential matrix method of Al-Mohy Higham (2009) • arma Use the exponential matrix from RcppArmadillo • expokit Use the exponential matrix from Roger B. Sidje (1998)

indLinMatExpOrder	an integer, the order of approximation to be used, for the Al-Mohy and expokit values. The best value for this depends on machine precision (and slightly on the matrix). We use 6 as a default.
drop	Columns to drop from the output
idFactor	This boolean indicates if original ID values should be maintained. This changes the default sequentially ordered ID to a factor with the original ID values in the original dataset. By default this is enabled.
mxhnil	maximum number of messages printed (per problem) warning that $T + H = T$ on a step ($H =$ step size). This must be positive to result in a non-default value. The default value is 0 (or infinite).
hmxi	inverse of the maximum absolute value of H to be used. $hmxi = 0.0$ is allowed and corresponds to an infinite $hmax1$ (default). $hmin$ and $hmxi$ may be changed at any time, but with
warnIdSort	Warn if the ID is not present and rxode2 assumes the order of the parameters/ $iCov$ are the same as the order of the parameters in the input dataset.
warnDrop	Warn if column(s) were supposed to be dropped, but were not present.
ssAtol	Steady state atol convergence factor. Can be a vector based on each state.
ssRtol	Steady state rtol convergence factor. Can be a vector based on each state.
safeZero	Use safe zero divide and log routines. By default this is turned on but you may turn it off if you wish.
sumType	Sum type to use for <code>sum()</code> in rxode2 code blocks. pairwise uses the pairwise sum (fast, default) fsum uses the PreciseSum package's fsum function (most accurate) kahan uses Kahan correction neumaier uses Neumaier correction c uses no correction: default/native summing
prodType	Product to use for <code>prod()</code> in rxode2 blocks long double converts to long double, performs the multiplication and then converts back. double uses the standard double scale for multiplication.
sensType	Sensitivity type for <code>linCmt()</code> model: advan Use the direct advan solutions autodiff Use the autodiff advan solutions forward Use forward difference solutions central Use central differences
linDiff	This gives the linear difference amount for all the types of linear compartment model parameters where sensitivities are not calculated. The named components of this numeric vector are: <ul style="list-style-type: none"> • "lag" Central compartment lag • "f" Central compartment bioavailability • "rate" Central compartment modeled rate • "dur" Central compartment modeled duration

- "lag2" Depot compartment lag
- "f2" Depot compartment bioavailability
- "rate2" Depot compartment modeled rate
- "dur2" Depot compartment modeled duration

linDiffCentral	This gives the which parameters use central differences for the linear compartment model parameters. The are the same components as linDiff
resample	A character vector of model variables to resample from the input dataset; This sampling is done with replacement. When NULL or FALSE no resampling is done. When TRUE resampling is done on all covariates in the input dataset
resampleID	boolean representing if the resampling should be done on an individual basis TRUE (ie. a whole patient is selected) or each covariate is resampled independent of the subject identifier FALSE. When resampleID=TRUE correlations of parameters are retained, where as when resampleID=FALSE ignores patient covariate correlations. Hence the default is resampleID=TRUE.
maxwhile	represents the maximum times a while loop is evaluated before exiting. By default this is 100000
atolSens	Sensitivity atol, can be different than atol with liblsoda. This allows a less accurate solve for gradients (if desired)
rtolSens	Sensitivity rtol, can be different than rtol with liblsoda. This allows a less accurate solve for gradients (if desired)
ssAtolSens	Sensitivity absolute tolerance (atol) for calculating if steady state has been achieved for sensitivity compartments.
ssRtolSens	Sensitivity relative tolerance (rtol) for calculating if steady state has been achieved for sensitivity compartments.
simVariability	determines if the variability is simulated. When NA (default) this is determined by the solver.
a	when using solve(), this is equivalent to the object argument. If you specify object later in the argument list it overwrites this parameter.
b	when using solve(), this is equivalent to the params argument. If you specify params as a named argument, this overwrites the output

Details

The rest of the document focus on the different ODE solving methods, followed by the core solving method's options, rxode2 event handling options, rxode2's numerical stability options, rxode2's output options, and finally internal rxode2 options or compatibility options.

Value

An "rxSolve" solve object that stores the solved value in a special data.frame or other type as determined by returnType. By default this has as many rows as there are sampled time points and as many columns as system variables (as defined by the ODEs and additional assignments in the rxode2 model code). It also stores information about the call to allow dynamic updating of the solved object.

The operations for the object are similar to a data-frame, but expand the \$ and [""] access operators and assignment operators to resolve based on different parameter values, initial conditions, solver parameters, or events (by updating the time variable).

You can call the `eventTable()` methods on the solved object to update the event table and resolve the system of equations.

Author(s)

Matthew Fidler, Melissa Hallow and Wenping Wang

References

"New Scaling and Squaring Algorithm for the Matrix Exponential", by Awad H. Al-Mohy and Nicholas J. Higham, August 2009

Roger B. Sidje (1998). EXPOKIT: Software package for computing matrix exponentials. *ACM - Transactions on Mathematical Software* 24(1), 130-156.

Hindmarsh, A. C. *ODEPACK, A Systematized Collection of ODE Solvers*. Scientific Computing, R. S. Stepleman et al. (Eds.), North-Holland, Amsterdam, 1983, pp. 55-64.

Petzold, L. R. *Automatic Selection of Methods for Solving Stiff and Nonstiff Systems of Ordinary Differential Equations*. *Siam J. Sci. Stat. Comput.* 4 (1983), pp. 136-148.

Hairer, E., Norsett, S. P., and Wanner, G. *Solving ordinary differential equations I, nonstiff problems*. 2nd edition, Springer Series in Computational Mathematics, Springer-Verlag (1993).

See Also

[rxode2\(\)](#)

rxStack

Stack a solved object for things like ggplot

Description

Stack a solved object for things like ggplot

Usage

```
rxStack(Data, vars = NULL)
```

Arguments

Data	is a rxode2 object to be stacked.
vars	Variables to include in stacked data; By default this is all the variables when vars is NULL.

Value

Stacked data with value and trt, where value is the values and trt is the state and lhs variables.

Author(s)

Matthew Fidler

rxState

State variables

Description

This returns the model's compartments or states.

Usage

```
rxState(obj = NULL, state = NULL)
```

Arguments

obj	rxode2 family of objects
state	is a string indicating the state or compartment that you would like to lookup.

Value

If state is missing, return a character vector of all the states.

If state is a string, return the compartment number of the named state.

Author(s)

Matthew L.Fidler

See Also

[rxode2\(\)](#)

Other Query model information: [rxDfdy\(\)](#), [rxInits\(\)](#), [rxLhs\(\)](#), [rxModelVars\(\)](#), [rxParams\(\)](#)

rxSumProdModel	<i>Recast model in terms of sum/prod</i>
----------------	--

Description

Recast model in terms of sum/prod

Usage

```
rxSumProdModel(model, expand = FALSE, sum = TRUE, prod = TRUE)
```

Arguments

model	rxode2 model
expand	Boolean indicating if the expression is expanded.
sum	Use sum(...)
prod	Use prod(...)

Value

model string with prod(.) and sum(.) for all these operations.

Author(s)

Matthew L. Fidler

rxSupportedFuns	<i>Get list of supported functions</i>
-----------------	--

Description

Get list of supported functions

Usage

```
rxSupportedFuns()
```

Value

list of supported functions in rxode2

Examples

```
rxSupportedFuns()
```

rxSuppressMsg	<i>Respect suppress messages</i>
---------------	----------------------------------

Description

This turns on the silent Rprintf in C when suppressMessages() is turned on. This makes the Rprintf act like messages in R, they can be suppressed with suppressMessages()

Usage

```
rxSuppressMsg()
```

Value

Nothing

Author(s)

Matthew Fidler

Examples

```
# rxSuppressMsg() is called with rxode2()

# Note the errors are output to the console

try(rxode2("d/dt(matt)=/3"), silent = TRUE)

# When using suppressMessages, the output is suppressed

suppressMessages(try(rxode2("d/dt(matt)=/3"), silent = TRUE))

# In rxode2, we use Rprintf so that interrupted threads do not crash R
# if there is a user interrupt. This isn't captured by R's messages, but
# This interface allows the `suppressMessages()` to suppress the C printing
# as well

# If you want to suppress messages from rxode2 in other packages, you can use
# this function
```

rxSymInvChol

*Get Omega⁻¹ and derivatives***Description**Get Omega⁻¹ and derivatives**Usage**

```
rxSymInvChol(
  invObjOrMatrix,
  theta = NULL,
  type = "cholOmegaInv",
  thetaNumber = 0L
)
```

Arguments

- | | |
|----------------|---|
| invObjOrMatrix | Object for inverse-type calculations. If this is a matrix, setup the object for inversion <code>rxSymInvCholCreate()</code> with the default arguments and return a reactive s3 object. Otherwise, use the inversion object to calculate the requested derivative/inverse. |
| theta | Thetas to be used for calculation. If missing (NULL), a special s3 class is created and returned to access Omega ⁻¹ objects as needed and cache them based on the theta that is used. |
| type | The type of object. Currently the following types are supported: <ul style="list-style-type: none"> • cholOmegaInv gives the Cholesky decomposition of the Omega Inverse matrix. • omegaInv gives the Omega Inverse matrix. • d(omegaInv) gives the d(Omega⁻¹) with respect to the theta parameter specified in thetaNumber. • d(D) gives the d(diagonal(Omega⁻¹)) with respect to the theta parameter specified in the thetaNumber parameter |
| thetaNumber | For types d(omegaInv) and d(D), the theta number that the derivative is taken against. This must be positive from 1 to the number of thetas defining the Omega matrix. |

Value

Matrix based on parameters or environment with all the matrixes calculated in variables omega, omegaInv, dOmega, dOmegaInv.

Author(s)

Matthew L. Fidler

rxSyncOptions	<i>Sync options with rxode2 variables</i>
---------------	---

Description

Accessing rxode2 options via `getOption` slows down solving. This allows the options to be synced with variables.

Usage

```
rxSyncOptions(setDefaults = c("none", "permissive", "strict"))
```

Arguments

<code>setDefaults</code>	This will setup rxode2's default solving options with the following options: <ul style="list-style-type: none"> • "none" leave the options alone • "permissive" This is a permissive option set similar to R language specifications. • "strict" This is a strict option set similar to the original rxode2(). It requires semicolons at the end of lines and equals for assignment
--------------------------	--

Value

nothing; called for side effects

Author(s)

Matthew L. Fidler

rxSyntaxFunctions	<i>A list and description of Rode supported syntax functions</i>
-------------------	--

Description

A list and description of Rode supported syntax functions

Usage

```
rxSyntaxFunctions
```

Format

A data frame with 3 columns and 98 or more rows

Function Reserved function Name

Description Description of function

Aliases Function Aliases

`rxt`*Simulate student t variable from threefry generator*

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the `sitmo` threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxt(df, n = 1L, ncores = 1L)
```

Arguments

<code>df</code>	degrees of freedom (> 0 , maybe non-integer). <code>df = Inf</code> is allowed.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
<code>ncores</code>	Number of cores for the simulation <code>rxnorm</code> simulates using the threefry <code>sitmo</code> generator; <code>rxnormV</code> uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the `rxode2` environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the `rxode2` engine with `rxSetSeed()`

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

t-distribution random numbers

Examples

```
## Use threefry engine

rxt(df = 3, n = 10) # with rxt you have to explicitly state n
rxt(df = 3, n = 10, ncores = 2) # You can parallelize the simulation using openMP
```

```
rx(4) ## The first argument is the df parameter

## This example uses `rxt` directly in the model

rx <- rxode2({
  a <- rxt(3)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxTempDir*Get the rxode2 temporary directory*

Description

Get the rxode2 temporary directory

Usage

```
rxTempDir()
```

Value

rxode2 temporary directory.

rxTheme*rxTheme is the ggplot2 theme for rxode2 plots*

Description

rxTheme is the ggplot2 theme for rxode2 plots

Usage

```
rxTheme(
  base_size = 11,
  base_family = "",
  base_line_size = base_size/22,
  base_rect_size = base_size/22,
  grid = TRUE
)
```

Arguments

base_size	base font size, given in pts.
base_family	base font family
base_line_size	base size for line elements
base_rect_size	base size for rect elements
grid	a Boolean indicating if the grid is on (TRUE) or off (FALSE). This could also be a character indicating x or y.

Value

ggplot2 theme used in rxode2

See Also

Other rxode2 plotting: [plot.rxSolve\(\)](#)

 rxToSE

rxode2 to symengine environment

Description

rxode2 to symengine environment

Usage

```
rxToSE(x, envir = NULL, progress = FALSE, promoteLinSens = TRUE)
```

```
.rxToSE(x, envir = NULL, progress = FALSE)
```

```
rxFromSE(x, unknownDerivatives = c("forward", "central", "error"))
```

```
.rxFromSE(x)
```

Arguments

x	expression
envir	default is NULL; Environment to put symengine variables in.
progress	shows progress bar if true.
promoteLinSens	Promote solved linear compartment systems to sensitivity-based solutions.
unknownDerivatives	<p>When handling derivatives from unknown functions, the translator will translate into different types of numeric derivatives. The currently supported methods are:</p> <ul style="list-style-type: none"> - `forward` for forward differences - `central` for central differences - `error` for throwing an error for unknown derivatives

Value

An rxode2 symengine environment

Author(s)

Matthew L. Fidler

rxTrans

Translate the model to C code if needed

Description

This function translates the model to C code, if needed

Usage

```
rxTrans(  
  model,  
  modelPrefix = "",  
  md5 = "",  
  modName = NULL,  
  modVars = FALSE,  
  ...  
)  
  
## Default S3 method:  
rxTrans(  
  model,  
  modelPrefix = "",  
  md5 = "",  
  modName = NULL,  
  modVars = FALSE,  
  ...  
)  
  
## S3 method for class 'character'  
rxTrans(  
  model,  
  modelPrefix = "",  
  md5 = "",  
  modName = NULL,  
  modVars = FALSE,  
  ...  
)
```

Arguments

model	This is the ODE model specification. It can be: <ul style="list-style-type: none"> • a string containing the set of ordinary differential equations (ODE) and other expressions defining the changes in the dynamic system. • a file name where the ODE system equation is contained An ODE expression enclosed in <code>\{\}</code> (see also the <code>filename</code> argument). For details, see the sections “Details” and <code>rxode2 Syntax</code> below.
modelPrefix	Prefix of the model functions that will be compiled to make sure that multiple <code>rxode2</code> objects can coexist in the same R session.
md5	Is the md5 of the model before parsing, and is used to embed the md5 into DLL, and then provide for functions like <code>rxModelVars()</code> .
modName	a string to be used as the model name. This string is used for naming various aspects of the computations, including generating C symbol names, dynamic libraries, etc. Therefore, it is necessary that <code>modName</code> consists of simple ASCII alphanumeric characters starting with a letter.
modVars	returns the model variables instead of the named vector of translated properties.
...	Ignored parameters.

Value

a named vector of translated model properties including what type of jacobian is specified, the C function prefixes, as well as the C functions names to be called through the compiled model.

Author(s)

Matthew L.Fidler

See Also

`rxode2()`, `rxCompile()`.

rxUiGet.cmtLines

S3 for getting information from UI model

Description

S3 for getting information from UI model

Usage

```
## S3 method for class 'cmtLines'
rxUiGet(x, ...)

## S3 method for class 'dvidLine'
rxUiGet(x, ...)

## S3 method for class 'paramsLine'
rxUiGet(x, ...)

## S3 method for class 'simulationSigma'
rxUiGet(x, ...)

## S3 method for class 'simulationModel'
rxUiGet(x, ...)

rxUiGet(x, ...)

## S3 method for class 'theta'
rxUiGet(x, ...)

## S3 method for class 'lstChr'
rxUiGet(x, ...)

## S3 method for class 'omega'
rxUiGet(x, ...)

## S3 method for class 'funTxt'
rxUiGet(x, ...)

## S3 method for class 'allCovs'
rxUiGet(x, ...)

## S3 method for class 'muRefTable'
rxUiGet(x, ...)

## S3 method for class 'multipleEndpoint'
rxUiGet(x, ...)

## S3 method for class 'funPrint'
rxUiGet(x, ...)

## S3 method for class 'fun'
rxUiGet(x, ...)

## S3 method for class 'md5'
rxUiGet(x, ...)
```

```
## S3 method for class 'ini'  
rxUiGet(x, ...)  
  
## S3 method for class 'iniFun'  
rxUiGet(x, ...)  
  
## S3 method for class 'modelFun'  
rxUiGet(x, ...)  
  
## S3 method for class 'modelDesc'  
rxUiGet(x, ...)  
  
## S3 method for class 'thetaLower'  
rxUiGet(x, ...)  
  
## S3 method for class 'thetaUpper'  
rxUiGet(x, ...)  
  
## Default S3 method:  
rxUiGet(x, ...)
```

Arguments

x	list of (UIenvironment, exact). UI environment is the parsed function for rxode2. exact is a boolean that says if an exact match is required.
...	Other arguments

Value

value that was requested from the UI object

Author(s)

Matthew Fidler

rxunif

Simulate uniform variable from threefry generator

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxunif(min = 0, max = 1, n = 1L, ncores = 1L)
```

Arguments

min	lower and upper limits of the distribution. Must be finite.
max	lower and upper limits of the distribution. Must be finite.
n	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with `rxSetSeed()`

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

uniform random numbers

Examples

```
## Use threefry engine

rxunif(min = 0, max = 4, n = 10) # with rxunif you have to explicitly state n
rxunif(min = 0, max = 4, n = 10, ncores = 2) # You can parallelize the simulation using openMP

rxunif()

## This example uses `rxunif` directly in the model

rx <- rxode2({
  a <- rxunif(0, 3)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

rxUnloadAll	<i>Unloads all rxode2 compiled DLLs</i>
-------------	---

Description

Unloads all rxode2 compiled DLLs

Usage

```
rxUnloadAll()
```

Value

List of rxode2 dlls still loaded

boolean of if all rxode2 dlls have been unloaded

Examples

```
print(rxUnloadAll())
```

rxUse	<i>Use model object in your package</i>
-------	---

Description

Use model object in your package

Usage

```
rxUse(obj, overwrite = TRUE, compress = "bzip2", internal = FALSE)
```

Arguments

obj	model to save.
overwrite	By default, <code>use_data()</code> will not overwrite existing files. If you really want to do so, set this to TRUE.
compress	Choose the type of compression used by <code>save()</code> . Should be one of "gzip", "bzip2", or "xz".
internal	If this is run internally. By default this is FALSE

Value

Nothing; This is used for its side effects and shouldn't be called by a user

rxValidate	<i>Validate rxode2 This allows easy validation/qualification of nlmixr by running the testing suite on your system.</i>
------------	---

Description

Validate rxode2 This allows easy validation/qualification of nlmixr by running the testing suite on your system.

Usage

```
rxValidate(type = NULL, skipOnCran = TRUE)
```

```
rxTest(type = NULL, skipOnCran = TRUE)
```

Arguments

type	Type of test or filter of test type, When this is an expression, evaluate the contents, respecting skipOnCran
skipOnCran	when TRUE skip the test on CRAN.

Value

nothing

Author(s)

Matthew L. Fidler

rxweibull	<i>Simulate Weibull variable from threefry generator</i>
-----------	--

Description

Care should be taken with this method not to encounter the birthday problem, described <https://www.johndcook.com/blog/2016/01/29/random-number-generator-seed-mistakes/>. Since the sitmo threefry, this currently generates one random deviate from the uniform distribution to seed the engine threefry and then run the code.

Usage

```
rxweibull(shape, scale = 1, n = 1L, ncores = 1L)
```

Arguments

shape	shape and scale parameters, the latter defaulting to 1.
scale	shape and scale parameters, the latter defaulting to 1.
n	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required.
ncores	Number of cores for the simulation rxnorm simulates using the threefry sitmo generator; rxnormV uses the vander-corput generator

Details

Therefore, a simple call to the random number generated followed by a second call to random number generated may have identical seeds. As the number of random number generator calls are increased the probability that the birthday problem will increase.

The key to avoid this problem is to either run all simulations in the rxode2 environment once (therefore one seed or series of seeds for the whole simulation), pre-generate all random variables used for the simulation, or seed the rxode2 engine with `rxSetSeed()`

Also care should be made that the computer you will be running on can run the same number of cores as you are running so they can reproduce your results.

Value

Weibull random deviates

Examples

```
## Use threefry engine

# with rxweibull you have to explicitly state n
rxweibull(shape = 1, scale = 4, n = 10)

# You can parallelize the simulation using openMP
rxweibull(shape = 1, scale = 4, n = 10, ncores = 2)

rxweibull(3)

## This example uses `rxweibull` directly in the model

rx <- rxode2({
  a <- rxweibull(1, 3)
})

et <- et(1, id = 1:2)

s <- rxSolve(rx, et)
```

`rxWinSetup`*Setup Windows components for rxode2*

Description

Setup Windows components for rxode2

Usage

```
rxWinSetup(rm.rtools = TRUE)
```

Arguments

`rm.rtools` Remove the Rtools from the current path specs.

Value

nothing, used for its side effects

Author(s)

Matthew L. Fidler

`rxWithSeed`*Preserved seed and possibly set the seed*

Description

Preserved seed and possibly set the seed

Usage

```
rxWithSeed(  
  seed,  
  code,  
  rxseed = rxGetSeed(),  
  kind = "default",  
  normal.kind = "default",  
  sample.kind = "default"  
)  
  
rxWithPreserveSeed(code)
```

Arguments

seed	R seed to use for the session
code	Is the code to evaluate
rxseed	is the rxode2 seed that is being preserved
kind	character or NULL. If kind is a character string, set R's RNG to the kind desired. Use "default" to return to the R default. See 'Details' for the interpretation of NULL.
normal.kind	character string or NULL. If it is a character string, set the method of Normal generation. Use "default" to return to the R default. NULL makes no change.
sample.kind	character string or NULL. If it is a character string, set the method of discrete uniform generation (used in sample , for instance). Use "default" to return to the R default. NULL makes no change.

Value

returns whatever the code is returning

See Also

rxGetSeed, rxSetSeed

Examples

```
rxGetSeed()
rxWithSeed(1, {
  print(rxGetSeed())
  rxnorm()
  print(rxGetSeed())
  rxnorm()
}, rxseed=3)
```

stat_amt

Dosing/Amt geom/stat

Description

This is a dosing geom that shows the vertical lines where a dose occurs

Usage

```

stat_amt(
  mapping = NULL,
  data = NULL,
  position = "identity",
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)

geom_amt(
  mapping = NULL,
  data = NULL,
  position = "identity",
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)

```

Arguments

mapping	Set of aesthetic mappings created by <code>aes()</code> or <code>aes_()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to <code>ggplot()</code> . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See <code>fortify()</code> for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code> , and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>).
position	Position adjustment, either as a string, or the result of a call to a position adjustment function.
show.legend	logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .
...	Other arguments passed on to <code>layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired <code>geom/stat</code> .

Details

Requires the following aesthetics:

- x representing the x values, usually time
- amt representing the dosing values; They are missing or zero when no dose is given

Value

This returns a stat_amt in context of a ggplot2 plot

Examples

```
library(rxode2)
library(units)

## Model from RxODE tutorial
mod1 <-rxode2({
  KA=2.94E-01
  CL=1.86E+01
  V2=4.02E+01
  Q=1.05E+01
  V3=2.97E+02
  Kin=1
  Kout=1
  EC50=200
  C2 = centr/V2
  C3 = peri/V3
  d/dt(depot) =-KA*depot
  d/dt(centr) = KA*depot - CL*C2 - Q*C2 + Q*C3
  d/dt(peri) = Q*C2 - Q*C3
  d/dt(eff) = Kin - Kout*(1-C2/(EC50+C2))*eff
})

## These are making the more complex regimens of the rxode2 tutorial

## bid for 5 days
bid <- et(timeUnits="hr") %>%
  et(amt=10000,ii=12,until=set_units(5, "days"))

## qd for 5 days
qd <- et(timeUnits="hr") %>%
  et(amt=20000,ii=24,until=set_units(5, "days"))

## bid for 5 days followed by qd for 5 days
et <- seq(bid,qd) %>% et(seq(0,11*24,length.out=100));

bidQd <- rxSolve(mod1, et, addDosing=TRUE)

# by default dotted and under-stated
```

```
plot(bidQd, C2) + geom_amt(aes(amt=amt))

# of course you can make it a bit more visible

plot(bidQd, C2) + geom_amt(aes(amt=amt), col="red", lty=1, size=1.2)
```

stat_cens

Censoring geom/stat

Description

This is a censoring geom that shows the left or right censoring specified in the `nlmixr` input data-set or fit

Usage

```
stat_cens(
  mapping = NULL,
  data = NULL,
  position = "identity",
  show.legend = NA,
  inherit.aes = TRUE,
  width = 0.01,
  ...
)
```

```
geom_cens(
  mapping = NULL,
  data = NULL,
  position = "identity",
  show.legend = NA,
  inherit.aes = TRUE,
  width = 0.01,
  ...
)
```

Arguments

mapping	Set of aesthetic mappings created by <code>aes()</code> or <code>aes_()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to <code>ggplot()</code> . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See <code>fortify()</code> for which variables will be created.

A function will be called with a single argument, the plot data. The return value must be a `data.frame`, and will be used as the layer data. A function can be created from a formula (e.g. `~ head(.x, 10)`).

<code>position</code>	Position adjustment, either as a string, or the result of a call to a position adjustment function.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .
<code>width</code>	represents the width (in \ censoring box
<code>...</code>	Other arguments passed on to <code>layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired <code>geom/stat</code> .

Details

Requires the following aesthetics:

- `x` Represents the independent variable, often the time scale
- `y` represents the dependent variable
- `CENS` for the censoring information; (-1 right censored, 0 no censoring or 1 left censoring)
- `LIMIT` which represents the corresponding limit ()

Will add boxes representing the areas of the fit that were censored.

Value

This returns a `ggplot2` stat

<code>summary.rxode2</code>	<i>Print expanded information about the rxode2 object.</i>
-----------------------------	--

Description

This prints the expanded information about the `rxode2` object.

Usage

```
## S3 method for class 'rxode2'
summary(object, ...)
```

Arguments

<code>object</code>	<code>rxode2</code> object
<code>...</code>	Ignored parameters

Value

object is returned

Author(s)

Matthew L.Fidler

update.rxUi	<i>Update for rxUi</i>
-------------	------------------------

Description

Update for rxUi

Usage

```
## S3 method for class 'rxUi'
update(object, ..., envir = parent.frame())
```

Arguments

object	rxode2 UI object
...	Lines to update
envir	Environment for evaluating ini() style calls

Value

a new rxode2 updated UI object

uppergamma	<i>uppergamma: upper incomplete gamma function</i>
------------	--

Description

This is the tgamma from the boost library

Usage

```
uppergamma(a, z)
```

Arguments

a	The numeric 'a' parameter in the upper incomplete gamma
z	The numeric 'z' parameter in the upper incomplete gamma

Details

The uppergamma function is given by:

$$\text{uppergamma}(a, z) = \int_z^{\infty} t^{a-1} \cdot e^{-t} dt$$

Value

uppergamma results

Author(s)

Matthew L. Fidler

Examples

uppergamma(1, 3)

uppergamma(1:3, 3)

uppergamma(1, 1:3)

Index

- * **Internal**
 - plot.rxSolve, 51
- * **Nonlinear regression**
 - eventTable, 36
 - rxode2, 88
- * **ODE models**
 - rxode2, 88
- * **Ordinary differential equations**
 - rxode2, 88
- * **PK/PD**
 - genShinyApp.template, 42
- * **Pharmacodynamics (PD)**
 - eventTable, 36
 - rxode2, 88
- * **Pharmacokinetics (PK)**
 - eventTable, 36
 - rxode2, 88
- * **Query model information**
 - rxDfdy, 70
 - rxLhs, 85
 - rxParams, 98
 - rxState, 137
- * **datasets**
 - rxReservedKeywords, 109
 - rxSyntaxFunctions, 141
- * **data**
 - eventTable, 36
- * **models**
 - eventTable, 36
 - rxode2, 88
- * **nonlinear**
 - genShinyApp.template, 42
 - rxode2, 88
- * **ordinary differential equations**
 - eventTable, 36
- * **pharmacometrics**
 - genShinyApp.template, 42
- * **rxode2 plotting**
 - plot.rxSolve, 51
 - rxTheme, 143
- * **simulation**
 - genShinyApp.template, 42
 - .C(), 65
 - .Call(), 65
 - .copyUi, 5
 - .handleSingleErrTypeNormOrTFocciBase, 6
 - .modelHandleModelLines, 6
 - .quoteCallInfoLines, 7
 - .rxFromSE (rxToSE), 144
 - .rxLinCmtGen, 8
 - .rxToSE (rxToSE), 144
 - .rxWithOptions, 9
 - .rxWithWd, 9
 - [.rxEvid (rxEvid), 71
 - [.rxRateDur (rxRateDur), 107
 - [[.rxEvid (rxEvid), 71
 - [[.rxRateDur (rxRateDur), 107
 - add.dosing, 10, 11, 13, 24, 28, 31, 34
 - add.dosing(), 36, 94
 - add.sampling, 11, 13, 13, 24, 28, 31, 34
 - add.sampling(), 36, 94
 - aes(), 155, 157
 - aes_(), 155, 157
 - as.character.rxEvid (rxEvid), 71
 - as.character.rxRateDur (rxRateDur), 107
 - as.et, 15
 - as.rxEvid (rxEvid), 71
 - as.rxRateDur (rxRateDur), 107
 - assertRxUi, 16
 - assertRxUiEstimatedResiduals (assertRxUi), 16
 - assertRxUiMixedOnly (assertRxUi), 16
 - assertRxUiMuRefOnly (assertRxUi), 16
 - assertRxUiNormal (assertRxUi), 16
 - assertRxUiPopulationOnly (assertRxUi), 16
 - assertRxUiPrediction (assertRxUi), 16

- assertRxUiRandomOnIdOnly (assertRxUi), 16
- assertRxUiSingleEndpoint (assertRxUi), 16
- assertRxUiTransformNormal (assertRxUi), 16

- borders(), 155, 158

- c.rxEvid (rxEvid), 71
- c.rxRateDur (rxEvid), 71
- cvPost, 18

- environment, 22
- erf, 21
- et, 11, 13, 21, 24, 28, 31, 34
- et(), 11, 37, 90, 94
- etExpand, 26
- etRbind, 11, 13, 24, 27, 28, 31, 34
- etRep, 11, 13, 24, 28, 30, 31, 34
- etSeq, 33
- eventTable, 11, 13, 24, 28, 31, 34, 36
- eventTable(), 43, 90, 94, 128, 136
- expit (logit), 46

- format.rxEvid (rxEvid), 71
- format.rxRateDur (rxEvid), 71
- fortify(), 155, 157

- gammap, 38
- gammapDer, 39
- gammapInv, 39
- gammapInva (gammapInv), 39
- gammaq, 40
- gammaqInv, 41
- gammaqInva (gammaqInv), 41
- genShinyApp.template, 42
- geom_amt (stat_amt), 154
- geom_cens (stat_cens), 157
- getRxThreads, 44
- ggplot(), 155, 157

- ini (ini.rxUi), 45
- ini.rxUi, 45

- layer(), 155, 158
- logit, 46
- logitNormInfo (logit), 46
- lowergamma, 48

- model (model.function), 49
- model.function, 49

- phi, 50
- plot.rxSolve, 51, 144
- plot.rxSolveConfint1 (plot.rxSolve), 51
- plot.rxSolveConfint2 (plot.rxSolve), 51
- predict.rxEt (rxSolve), 123
- predict.rxode2 (rxSolve), 123
- predict.rxParams (rxSolve), 123
- predict.rxSolve (rxSolve), 123
- print.rxEvid (rxEvid), 71
- probit, 51
- probitInv (probit), 51
- probitNormInfo (logit), 46

- rbind.rxEt (etRbind), 27
- rename.function (rxRename), 108
- rename.rxUi (rxRename), 108
- rep.rxEt (etRep), 30
- rinvchisq, 52
- rLKJ1(), 18
- rxAllowUnload, 53
- rxAppendModel, 54
- rxAssignControlValue, 55
- rxAssignPtr, 56
- rxbeta, 56
- rxbinom, 57
- rxcauchy, 59
- rxCbindStudyIndividual, 60
- rxchisq, 61
- rxClean, 63
- rxCompile, 63
- rxCompile(), 146
- rxControl (rxSolve), 123
- rxControlUpdateSens, 65
- rxCores (getRxThreads), 44
- rxCreateCache, 66
- rxD, 67
- rxD(), 74
- rxDelete, 68
- rxDerived, 68
- rxDfdy, 70, 85, 100, 137
- rxEvid, 71
- rxexp, 72
- rxf, 73
- rxFromSE (rxToSE), 144
- rxFun, 74
- rxgamma, 76

rxgeom, 77
 rxGetControl, 79
 rxGetLin, 79
 rxGetrxode2, 80
 rxGetSeed, 81
 rxHtml, 82
 rxIndLin_, 83
 rxIndLinState, 82
 rxIndLinStrategy, 83
 rxInits, 70, 85, 100, 137
 rxInv, 84
 rxIsCurrent, 85
 rxLhs, 70, 85, 100, 137
 rxLock, 86
 rxModelVars, 70, 85, 100, 137
 rxModelVars(), 146
 rxNorm, 86
 rxnorm, 87
 rxnormV (rxnorm), 87
 RxODE (rxode2), 88
 rxode (rxode2), 88
 rxode2, 11, 13, 24, 28, 31, 34, 85, 88
 rxode2(), 37, 43, 65, 136, 137, 146
 rxOptExpr, 96
 rxord, 97
 rxParam (rxParams), 98
 rxParams, 70, 85, 98, 137
 rxPkg, 100
 rxpois, 101
 rxPp, 102
 rxPreferredDistributionName, 104
 rxProgress, 105
 rxProgressAbort (rxProgress), 105
 rxProgressStop (rxProgress), 105
 rxRandNV, 106
 rxRateDur, 107
 rxRemoveControl, 107
 rxRename, 108
 rxReservedKeywords, 109
 rxRmFun (rxFun), 74
 rxRmvn, 109
 rxS, 112
 rxSetControl, 113
 rxSetCovariateNamesForPiping, 113
 rxSetIni0, 115
 rxSetProd, 115
 rxSetProgressBar, 116
 rxSetSeed, 116
 rxSetSum, 118
 rxShiny, 118
 rxSimThetaOmega, 120
 rxSolve, 123
 rxSolve(), 42
 rxStack, 136
 rxState, 70, 85, 100, 137
 rxSumProdModel, 138
 rxSupportedFuns, 138
 rxSuppressMsg, 139
 rxSymInvChol, 140
 rxSymInvCholCreate(), 140
 rxSyncOptions, 141
 rxSyntaxFunctions, 141
 rxt, 142
 rxTempDir, 143
 rxTest (rxValidate), 151
 rxTheme, 51, 143
 rxTick (rxProgress), 105
 rxToSE, 144
 rxTrans, 145
 rxTrans(), 65
 rxUiGet (rxUiGet.cmtLines), 146
 rxUiGet.cmtLines, 146
 rxunif, 148
 rxUnloadAll, 150
 rxUnlock (rxLock), 86
 rxUse, 150
 rxValidate, 151
 rxweibull, 151
 rxWinSetup, 153
 rxWithPreserveSeed (rxWithSeed), 153
 rxWithSeed, 153

 sample, 154
 save(), 150
 seq.rxEt (etSeq), 33
 setRxThreads (getRxThreads), 44
 setRxThreads(), 129
 simulate.rxode2 (rxSolve), 123
 simulate.rxParams (rxSolve), 123
 simulate.rxSolve (rxSolve), 123
 solve.rxEt (rxSolve), 123
 solve.rxode2 (rxSolve), 123
 solve.rxParams (rxSolve), 123
 solve.rxSolve (rxSolve), 123
 solve.rxEt (rxSolve), 123
 solve.rxEt (rxSolve), 123
 solve.rxEt (rxSolve), 123
 solve.rxEt (rxSolve), 123
 stat_amt, 154
 stat_cens, 157

summary.rxode2, [158](#)
sys.call, [22](#)

update.rxSolve (rxSolve), [123](#)
update.rxUi, [159](#)
uppergamma, [159](#)
use_description(), [101](#)

vname, [16](#)

write.template.server
 (genShinyApp.template), [42](#)
write.template.ui
 (genShinyApp.template), [42](#)
write.template.ui(), [43](#)