

Package ‘sabre’

June 3, 2021

Version 0.4.0

Title Spatial Association Between Regionalizations

Description Calculates a degree of spatial association between regionalizations or categorical maps using the information-theoretical V-measure (Nowosad and Stepinski (2018) <[doi:10.1080/13658816.2018.1511794](https://doi.org/10.1080/13658816.2018.1511794)>). It also offers an R implementation of the MapCurve method (Hargrove et al. (2006) <[doi:10.1007/s10109-006-0025-x](https://doi.org/10.1007/s10109-006-0025-x)>).

License MIT + file LICENSE

Encoding UTF-8

LazyData true

ByteCompile true

Suggests testthat, covr, knitr, rmarkdown, methods

RoxygenNote 7.1.1

Depends R (>= 3.3.0)

Imports dplyr, entropy, raster, rlang, sf, tibble, tidyr

Enhances stars, terra

VignetteBuilder knitr

URL <https://nowosad.github.io/sabre/>

BugReports <https://github.com/Nowosad/sabre/issues>

NeedsCompilation no

Author Jakub Nowosad [aut, cre] (<<https://orcid.org/0000-0002-1057-3721>>),
Tomasz Stepinski [aut],
Space Informatics Lab [cph]

Maintainer Jakub Nowosad <nowosad.jakub@gmail.com>

Repository CRAN

Date/Publication 2021-06-03 12:40:02 UTC

R topics documented:

eco_us	2
mapcurves	2
mapcurves_calc	3
partitions1	5
partitions2	5
regions1	6
regions2	6
vmeasure	7
vmeasure_calc	8

Index	10
--------------	-----------

eco_us	<i>Ecoregions of the United States</i>
--------	--

Description

Bailey's Ecoregions of the Conterminous United States

Usage

eco_us

Format

An object of class `sf` (inherits from `data.frame`) with 330 rows and 5 columns.

Source

<https://www.sciencebase.gov/catalog/item/54244abde4b037b608f9e23d>

mapcurves	<i>Mapcurves</i>
-----------	------------------

Description

Mapcurves: a quantitative method for comparing categorical maps.

Usage

mapcurves(x, y, z = NULL)

Arguments

x	A numeric vector, representing a categorical values.
y	A numeric vector, representing a categorical values.
z	A numeric matrix. The goodness of fit (GOF) value for each pair of classes in x and y. By default this argument is set to NULL, and the value of z is calculated based on x and y.

Value

A list with two elements:

- "ref_map" - the map to be used as reference ("x" or "y")
- "gof" - the Mapcurves's goodness of fit value

References

Hargrove, William W., Forrest M. Hoffman, and Paul F. Hessburg. "Mapcurves: a quantitative method for comparing categorical maps." *Journal of Geographical Systems* 8.2 (2006): 187.

Examples

```
set.seed(2018-03-21)
A = floor(matrix(runif(100, 0, 9), 10))
B = floor(matrix(runif(100, 0, 9), 10))
mapcurves(A, B)
```

mapcurves_calc

Mapcurves calculation

Description

It calculates the Mapcurves's goodness-of-fit (GOF)

Usage

```
mapcurves_calc(x, y, x_name, y_name, precision = NULL)

## S3 method for class 'sf'
mapcurves_calc(x, y, x_name, y_name, precision = NULL)

## S3 method for class 'stars'
mapcurves_calc(x, y, x_name = NULL, y_name = NULL, precision = NULL)

## S3 method for class 'SpatRaster'
mapcurves_calc(x, y, x_name = NULL, y_name = NULL, precision = NULL)

## S3 method for class 'RasterLayer'
mapcurves_calc(x, y, x_name = NULL, y_name = NULL, precision = NULL)
```

Arguments

x	An object of class <code>sf</code> with a POLYGON or MULTIPOLYGON geometry type or a spatial raster object of class <code>RasterLayer</code> , <code>SpatRaster</code> , or <code>stars</code> .
y	An object of class <code>sf</code> with a POLYGON or MULTIPOLYGON geometry type or a spatial raster object of class <code>RasterLayer</code> , <code>SpatRaster</code> , or <code>stars</code> .
x_name	A name of the column with regions/clusters names.
y_name	A name of the column with regions/clusters names.
precision	numeric, or object of class <code>units</code> with distance units (but see details); see st_as_binary for how to do this.

Value

A list with four elements:

- "map1" - the `sf` object containing the first map used for calculation of GOF
- "map2" - the `sf` object containing the second map used for calculation of GOF
- "ref_map" - the map used as a reference ("x" or "y")
- "gof" - the Mapcurves's goodness of fit value

References

Hargrove, William W., Forrest M. Hoffman, and Paul F. Hessburg. "Mapcurves: a quantitative method for comparing categorical maps." *Journal of Geographical Systems* 8.2 (2006): 187.

Examples

```
library(sf)
data("regions1")
data("regions2")

mc = mapcurves_calc(x = regions1, y = regions2, x_name = z, y_name = z)
mc

plot(mc$map1)
plot(mc$map2)

library(raster)
data("partitions1")
data("partitions2")
mc2 = mapcurves_calc(x = partitions1, y = partitions2)
mc2

plot(mc2$map1)
plot(mc2$map2)
```

partitions1

Red regionalization (raster version)

Description

Raster data of the red regionalization used in Figure 1 of Stepinski and Nowosad (2018)

Usage

partitions1

Format

An object of class RasterLayer of dimension 8 x 10 x 1.

References

Nowosad, Jakub, and Tomasz F. Stepinski. "Spatial association between regionalizations using the information-theoretical V-measure." *International Journal of Geographical Information Science* (2018). <https://doi.org/10.1080/13658816.2018.1511794>

partitions2

Blue regionalization (raster version)

Description

Raster data of the blue regionalization used in Figure 1 of Stepinski and Nowosad (2018)

Usage

partitions2

Format

An object of class RasterLayer of dimension 8 x 10 x 1.

References

Nowosad, Jakub, and Tomasz F. Stepinski. "Spatial association between regionalizations using the information-theoretical V-measure." *International Journal of Geographical Information Science* (2018). <https://doi.org/10.1080/13658816.2018.1511794>

regions1

Red regionalization

Description

Data of the red regionalization used in Figure 1 of Stepinski and Nowosad (2018)

Usage

regions1

Format

An object of class sf (inherits from data.frame) with 4 rows and 2 columns.

References

Nowosad, Jakub, and Tomasz F. Stepinski. "Spatial association between regionalizations using the information-theoretical V-measure." *International Journal of Geographical Information Science* (2018). <https://doi.org/10.1080/13658816.2018.1511794>

regions2

Blue regionalization

Description

Data of the blue regionalization used in Figure 1 of Stepinski and Nowosad (2018)

Usage

regions2

Format

An object of class sf (inherits from data.frame) with 3 rows and 2 columns.

References

Nowosad, Jakub, and Tomasz F. Stepinski. "Spatial association between regionalizations using the information-theoretical V-measure." *International Journal of Geographical Information Science* (2018). <https://doi.org/10.1080/13658816.2018.1511794>

vmeasure

V-measure

Description

A conditional entropy-based external cluster evaluation measure.

Usage

```
vmeasure(x, y, z = NULL, B = 1)
```

Arguments

x	A numeric vector, representing a categorical values.
y	A numeric vector, representing a categorical values.
z	A numeric matrix. A contingency table of the counts at each combination of categorical levels. By default this argument is set to NULL, and the value of z is calculated based on x and y.
B	A numeric value. If $B > 1$ then completeness is weighted more strongly than homogeneity, and if $B < 1$ then homogeneity is weighted more strongly than completeness. By default this value is 1.

Value

A list with three elements:

- "v_measure"
- "homogeneity"
- "completeness"

References

Rosenberg, Andrew, and Julia Hirschberg. "V-measure: A conditional entropy-based external cluster evaluation measure." Proceedings of the 2007 joint conference on empirical methods in natural language processing and computational natural language learning (EMNLP-CoNLL). 2007.

Examples

```
x = c(1, 1, 1, 2, 2, 3, 3, 3, 1, 1, 2, 2, 2, 3, 3)
y = c(rep(1, 5), rep(2, 5), rep(3, 5))
vmeasure(x, y)
```

vmeasure_calc	<i>V-measure calculation</i>
---------------	------------------------------

Description

It calculates a degree of spatial association between regionalizations using an information-theoretical measure called the V-measure

Usage

```
vmeasure_calc(x, y, x_name, y_name, B = 1, precision = NULL)

## S3 method for class 'sf'
vmeasure_calc(x, y, x_name, y_name, B = 1, precision = NULL)

## S3 method for class 'stars'
vmeasure_calc(x, y, x_name = NULL, y_name = NULL, B = 1, precision = NULL)

## S3 method for class 'SpatRaster'
vmeasure_calc(x, y, x_name = NULL, y_name = NULL, B = 1, precision = NULL)

## S3 method for class 'RasterLayer'
vmeasure_calc(x, y, x_name = NULL, y_name = NULL, B = 1, precision = NULL)
```

Arguments

x	An object of class <code>sf</code> with a POLYGON or MULTIPOLYGON geometry type or a spatial raster object of class <code>RasterLayer</code> , <code>SpatRaster</code> , or <code>stars</code> .
y	An object of class <code>sf</code> with a POLYGON or MULTIPOLYGON geometry type or a spatial raster object of class <code>RasterLayer</code> , <code>SpatRaster</code> , or <code>stars</code> .
x_name	A name of the column with regions/clusters names.
y_name	A name of the column with regions/clusters names.
B	A numeric value. If $B > 1$ then completeness is weighted more strongly than homogeneity, and if $B < 1$ then homogeneity is weighted more strongly than completeness. By default this value is 1.
precision	numeric, or object of class <code>units</code> with distance units (but see details); see st_as_binary for how to do this.

Value

A list with five elements:

- "map1" - the `sf` object containing the first preprocessed map used for calculation of GOF with two attributes - `map1` (name of the category) and `rih` (region inhomogeneity)
- "map2" - the `sf` object containing the second preprocessed map used for calculation of GOF with two attributes - `map1` (name of the category) and `rih` (region inhomogeneity)

- "v_measure"
- "homogeneity"
- "completeness"

References

Nowosad, Jakub, and Tomasz F. Stepinski. "Spatial association between regionalizations using the information-theoretical V-measure." *International Journal of Geographical Information Science* (2018). <https://doi.org/10.1080/13658816.2018.1511794>

Rosenberg, Andrew, and Julia Hirschberg. "V-measure: A conditional entropy-based external cluster evaluation measure." *Proceedings of the 2007 joint conference on empirical methods in natural language processing and computational natural language learning (EMNLP-CoNLL)*. 2007.

Examples

```
library(sf)
data("regions1")
data("regions2")
vm = vmeasure_calc(x = regions1, y = regions2, x_name = z, y_name = z)
vm
```

```
plot(vm$map1["rih"])
plot(vm$map2["rih"])
```

```
library(raster)
data("partitions1")
data("partitions2")
vm2 = vmeasure_calc(x = partitions1, y = partitions2)
vm2
```

```
plot(vm2$map1[["rih"]])
plot(vm2$map2[["rih"]])
```

Index

* datasets

- eco_us, 2
- partitions1, 5
- partitions2, 5
- regions1, 6
- regions2, 6

eco_us, 2

mapcurves, 2
mapcurves_calc, 3

partitions1, 5
partitions2, 5

regions1, 6
regions2, 6

st_as_binary, 4, 8

vmeasure, 7
vmeasure_calc, 8