

Package ‘sf’

July 14, 2022

Version 1.0-8

Title Simple Features for R

Description Support for simple features, a standardized way to encode spatial vector data. Binds to 'GDAL' for reading and writing data, to 'GEOS' for geometrical operations, and to 'PROJ' for projection conversions and datum transformations. Uses by default the 's2' package for spherical geometry operations on ellipsoidal (long/lat) coordinates.

License GPL-2 | MIT + file LICENSE

URL <https://r-spatial.github.io/sf/>, <https://github.com/r-spatial/sf/>

BugReports <https://github.com/r-spatial/sf/issues/>

Depends methods, R (>= 3.3.0)

Imports classInt (>= 0.4-1), DBI (>= 0.8), graphics, grDevices, grid, magrittr, Rcpp (>= 0.12.18), s2 (>= 1.0.7), stats, tools, units (>= 0.7-0), utils

Suggests blob, covr, dplyr (>= 0.8-3), ggplot2, knitr, lwgeom (>= 0.2-1), maps, mapview, Matrix, microbenchmark, odbc, pbapply, pillar, pool, raster, rlang, rmarkdown, RPostgres (>= 1.1.0), RPostgreSQL, RSQLite, sp (>= 1.2-4), spatstat (>= 2.0-1), spatstat.geom, spatstat.random, spatstat.linnet, spatstat.utils, stars (>= 0.2-0), terra, testthat, tibble (>= 1.4.1), tidyr (>= 1.2.0), tidyselect (>= 1.0.0), tmap (>= 2.0), vctrs, wk

LinkingTo Rcpp

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.1.2

SystemRequirements C++11, GDAL (>= 2.0.1), GEOS (>= 3.4.0), PROJ (>= 4.8.0), sqlite3

Collate 'RcppExports.R' 'init.R' 'crs.R' 'bbox.R' 'read.R' 'db.R'
'sfc.R' 'sfg.R' 'sf.R' 'bind.R' 'wkb.R' 'wkt.R' 'plot.R'
'geom-measures.R' 'geom-predicates.R' 'geom-transformers.R'

```
'transform.R' 'proj.R' 'sp.R' 'grid.R' 'arith.R' 'tidyverse.R'
'tidyverse-vctrs.R' 'cast_sfg.R' 'cast_sf.R' 'graticule.R'
'datasets.R' 'aggregate.R' 'agr.R' 'maps.R' 'join.R' 'sample.R'
'velid.R' 'collection_extract.R' 'jitter.R' 'sgbp.R'
'spatstat.R' 'stars.R' 'crop.R' 'gdal_utils.R' 'nearest.R'
'normalize.R' 'defunct.R' 'z_range.R' 'm_range.R'
'shift_longitude.R' 'make_grid.R' 's2.R' 'terra.R'
'geos-overlayng.R'
```

NeedsCompilation yes

Author Edzer Pebesma [aut, cre] (<<https://orcid.org/0000-0001-8049-7069>>),

Roger Bivand [ctb] (<<https://orcid.org/0000-0003-2392-6140>>),

Etienne Racine [ctb],

Michael Sumner [ctb],

Ian Cook [ctb],

Tim Keitt [ctb],

Robin Lovelace [ctb],

Hadley Wickham [ctb],

Jeroen Ooms [ctb] (<<https://orcid.org/0000-0002-4035-0289>>),

Kirill Müller [ctb],

Thomas Lin Pedersen [ctb],

Dan Baston [ctb],

Dewey Dunnington [ctb] (<<https://orcid.org/0000-0002-9415-4582>>)

Maintainer Edzer Pebesma <edzer.pebesma@uni-muenster.de>

Repository CRAN

Date/Publication 2022-07-14 11:40:02 UTC

R topics documented:

aggregate.sf	4
as	6
bind	7
dbDataType,PostgreSQLConnection,sf-method	8
dbWriteTable,PostgreSQLConnection,character,sf-method	8
db_drivers	10
extension_map	10
gdal	10
gdal_addo	14
gdal_utils	15
geos_binary_ops	16
geos_binary_pred	19
geos_combine	22
geos_measures	23
geos_query	25
geos_unary	26
internal	31
interpolate_aw	31

is_driver_available	32
is_driver_can	32
is_geometry_column	33
merge.sf	33
nc	34
Ops	34
plot	35
prefix_map	41
proj_tools	41
rawToHex	43
s2	43
sf	44
sf-defunct	46
sfc	47
sf_extSoftVersion	48
sf_project	49
sgbp	50
st	51
stars	53
st_agr	55
st_as_binary	56
st_as_grob	57
st_as_sf	57
st_as_sfc	60
st_as_text	63
st_bbox	64
st_cast	66
st_cast_sfc_default	69
st_collection_extract	69
st_coordinates	71
st_crop	72
st_crs	73
st_drivers	75
st_geometry	76
st_geometry_type	78
st_graticule	78
st_is	80
st_is_longlat	81
st_jitter	81
st_join	82
st_layers	84
st_line_sample	85
st_make_grid	86
st_m_range	87
st_nearest_feature	89
st_nearest_points	90
st_normalize	92
st_precision	92

st_read	93
st_relate	97
st_sample	98
st_shift_longitude	101
st_transform	102
st_viewport	105
st_write	106
st_zm	108
st_z_range	109
summary.sfc	111
tibble	111
tidyverse	112
transform.sf	118
valid	119
vctrs	120

Index	122
--------------	------------

aggregate.sf	<i>aggregate an sf object</i>
--------------	-------------------------------

Description

aggregate an sf object, possibly union-ing geometries

Usage

```
## S3 method for class 'sf'
aggregate(
  x,
  by,
  FUN,
  ...,
  do_union = TRUE,
  simplify = TRUE,
  join = st_intersects
)
```

Arguments

x	object of class sf
by	either a list of grouping vectors with length equal to nrow(x) (see aggregate), or an object of class sf or sfc with geometries that are used to generate groupings, using the binary predicate specified by the argument join
FUN	function passed on to aggregate , in case ids was specified and attributes need to be grouped
...	arguments passed on to FUN

do_union	logical; should grouped geometries be unioned using st_union ? See details.
simplify	logical; see aggregate
join	logical spatial predicate function to use if by is a simple features object or geometry; see st_join

Details

In case do_union is FALSE, aggregate will simply combine geometries using [c.sfg](#). When polygons sharing a boundary are combined, this leads to geometries that are invalid; see <https://github.com/r-spatial/sf/issues/681>.

Value

an sf object with aggregated attributes and geometries; additional grouping variables having the names of names(ids) or are named Group.i for ids[[i]]; see [aggregate](#).

Note

Does not work using the formula notation involving ~ defined in [aggregate](#).

Examples

```
m1 = cbind(c(0, 0, 1, 0), c(0, 1, 1, 0))
m2 = cbind(c(0, 1, 1, 0), c(0, 0, 1, 0))
pol = st_sf(st_polygon(list(m1)), st_polygon(list(m2)))
set.seed(1985)
d = data.frame(matrix(runif(15), ncol = 3))
p = st_as_sf(x = d, coords = 1:2)
plot(pol)
plot(p, add = TRUE)
(p_ag1 = aggregate(p, pol, mean))
plot(p_ag1) # geometry same as pol
# works when x overlaps multiple objects in 'by':
p_buff = st_buffer(p, 0.2)
plot(p_buff, add = TRUE)
(p_ag2 = aggregate(p_buff, pol, mean)) # increased mean of second
# with non-matching features
m3 = cbind(c(0, 0, -0.1, 0), c(0, 0.1, 0.1, 0))
pol = st_sf(st_polygon(list(m3)), st_polygon(list(m1)), st_polygon(list(m2)))
(p_ag3 = aggregate(p, pol, mean))
plot(p_ag3)
# In case we need to pass an argument to the join function:
(p_ag4 = aggregate(p, pol, mean,
  join = function(x, y) st_is_within_distance(x, y, dist = 0.3)))
```

as

Methods to coerce simple features to Spatial and Spatial*DataFrame objects*

Description

`as_Spatial()` allows to convert sf and sfc to Spatial*DataFrame and Spatial* for sp compatibility. You can also use `as(x, "Spatial")` To transform sp objects to sf and sfc with `as(x, "sf")`.

Usage

```
as_Spatial(from, cast = TRUE, IDs = paste0("ID", seq_along(from)))
```

Arguments

from	object of class sf, sfc_POINT, sfc_MULTIPOINT, sfc_LINESTRING, sfc_MULTILINESTRING, sfc_POLYGON, or sfc_MULTIPOLYGON.
cast	logical; if TRUE, <code>st_cast()</code> from before converting, so that e.g. GEOMETRY objects with a mix of POLYGON and MULTIPOLYGON are cast to MULTIPOLYGON.
IDs	character vector with IDs for the Spatial* geometries

Details

Package sp supports three dimensions for POINT and MULTIPOINT (SpatialPoint*). Other geometries must be two-dimensional (XY). Dimensions can be dropped using `st_zm()` with what = "M" or what = "ZM".

For converting simple features (i.e., sf objects) to their Spatial counterpart, use `as(obj, "Spatial")`

Value

geometry-only object deriving from Spatial, of the appropriate class

Examples

```
nc <- st_read(system.file("shape/nc.shp", package="sf"))
if (require(sp, quietly = TRUE)) {
  # convert to SpatialPolygonsDataFrame
  spdf <- as_Spatial(nc)
  # identical to
  spdf <- as(nc, "Spatial")
  # convert to SpatialPolygons
  as(st_geometry(nc), "Spatial")
  # back to sf
  as(spdf, "sf")
}
```

bind	<i>Bind rows (features) of sf objects</i>
------	---

Description

Bind rows (features) of sf objects
 Bind columns (variables) of sf objects

Usage

```
## S3 method for class 'sf'
rbind(..., deparse.level = 1)

## S3 method for class 'sf'
cbind(..., deparse.level = 1, sf_column_name = NULL)

st_bind_cols(...)
```

Arguments

... objects to bind; note that for the rbind and cbind methods, all objects have to be of class `sf`; see [dotsMethods](#)
`deparse.level` integer; see [rbind](#)
`sf_column_name` character; specifies active geometry; passed on to [st_sf](#)

Details

both `rbind` and `cbind` have non-standard method dispatch (see [cbind](#)): the `rbind` or `cbind` method for `sf` objects is only called when all arguments to be binded are of class `sf`.
 If you need to `cbind` e.g. a `data.frame` to an `sf`, use [data.frame](#) directly and use [st_sf](#) on its result, or use [bind_cols](#); see examples.
`st_bind_cols` is deprecated; use `cbind` instead.

Value

`cbind` called with multiple `sf` objects warns about multiple geometry columns present when the geometry column to use is not specified by using argument `sf_column_name`; see also [st_sf](#).

Examples

```
crs = st_crs(3857)
a = st_sf(a=1, geom = st_sfc(st_point(0:1)), crs = crs)
b = st_sf(a=1, geom = st_sfc(st_linestring(matrix(1:4,2))), crs = crs)
c = st_sf(a=4, geom = st_sfc(st_multilinestring(list(matrix(1:4,2)))), crs = crs)
rbind(a,b,c)
rbind(a,b)
```

```

rbind(a,b)
rbind(b,c)
cbind(a,b,c) # warns
if (require(dplyr, quietly = TRUE))
  dplyr::bind_cols(a,b)
c = st_sf(a=4, geomc = st_sfc(st_multilinestring(list(matrix(1:4,2)))), crs = crs)
cbind(a,b,c, sf_column_name = "geomc")
df = data.frame(x=3)
st_sf(data.frame(c, df))
if (require(dplyr, quietly = TRUE))
  dplyr::bind_cols(c, df)

```

dbDataType,PostgreSQLConnection,sf-method*Determine database type for R vector***Description**

Determine database type for R vector

Determine database type for R vector

Usage

```

## S4 method for signature 'PostgreSQLConnection,sf'
dbDataType(dbObj, obj)

## S4 method for signature 'DBIObject,sf'
dbDataType(dbObj, obj)

```

Arguments

dbObj	DBIObject driver or connection.
obj	Object to convert

dbWriteTable,PostgreSQLConnection,character,sf-method*Write sf object to Database***Description**

Write sf object to Database

Write sf object to Database

Usage

```
## S4 method for signature 'PostgreSQLConnection,character,sf'
dbWriteTable(
  conn,
  name,
  value,
  ...,
  row.names = FALSE,
  overwrite = FALSE,
  append = FALSE,
  field.types = NULL,
  binary = TRUE
)

## S4 method for signature 'DBIObject,character,sf'
dbWriteTable(
  conn,
  name,
  value,
  ...,
  row.names = FALSE,
  overwrite = FALSE,
  append = FALSE,
  field.types = NULL,
  binary = TRUE
)
```

Arguments

conn	DBIObject
name	character vector of names (table names, fields, keywords).
value	a data.frame.
...	placeholder for future use.
row.names	Add a <code>row.name</code> column, or a vector of length <code>nrow(obj)</code> containing <code>row.names</code> ; default FALSE.
overwrite	Will try to drop table before writing; default FALSE.
append	Append rows to existing table; default FALSE.
field.types	default NULL. Allows to override type conversion from R to PostgreSQL. See <code>dbDataType()</code> for details.
binary	Send geometries serialized as Well-Known Binary (WKB); if FALSE, uses Well-Known Text (WKT). Defaults to TRUE (WKB).

`db_drivers`

Drivers for which update should be TRUE by default

Description

Drivers for which update should be TRUE by default

Usage`db_drivers`**Format**

An object of class character of length 12.

`extension_map`

Map extension to driver

Description

Map extension to driver

Usage`extension_map`**Format**

An object of class list of length 26.

`gdal`

*functions to interact with gdal not meant to be called directly by users
(but e.g. by stars::read_stars)*

Description

functions to interact with gdal not meant to be called directly by users (but e.g. by stars::read_stars)

Usage

```
gdal_read(
  x,
  ...,
  options = character(0),
  driver = character(0),
  read_data = TRUE,
  NA_value = NA_real_,
  RasterIO_parameters = list()
)

gdal_write(
  x,
  ...,
  file,
  driver = "GTiff",
  options = character(0),
  type = "Float32",
  NA_value = NA_real_,
  geotransform,
  update = FALSE
)

gdal_inv_geotransform(gt)

gdal_crs(file, options = character(0))

gdal_metadata(
  file,
  domain_item = character(0),
  options = character(0),
  parse = TRUE
)

gdal_subdatasets(file, options = character(0), name = TRUE)

gdal_polygonize(
  x,
  mask = NULL,
  file = tempfile(),
  driver = "GTiff",
  use_integer = TRUE,
  geotransform,
  breaks = classInt::classIntervals(na.omit(as.vector(x[[1]])))$brks,
  use_contours = FALSE,
  contour_lines = FALSE,
  connect8 = FALSE,
  ...
)
```

```
)
gdal_rasterize(sf, x, gt, file, driver = "GTiff", options = character())
gdal_extract(f, pts, bilinear = FALSE)
gdal_read_mdim(file, array_name = character(0), options = character(0))
gdal_write_mdim(x, file, dimension_values, units)
gdal_create(f, nxy, values, crs, xlim, ylim)
```

Arguments

x	character vector, possibly of length larger than 1 when more than one raster is read
...	ignored
options	open options
driver	character; when empty vector, driver is auto-detected.
read_data	logical; if FALSE, only the imagery metadata is returned
NA_value	(double) non-NA value to use for missing values; if NA, when writing missing values are not specially flagged in output dataset, when reading the default (dataset) missing values are used (if present / set).
RasterIO_params	list with named parameters to GDAL's RasterIO; see the stars::read_stars documentation.
file	file name
type	gdal write type
geotransform	length 6 numeric vector with GDAL geotransform parameters.
update	logical; TRUE if in an existing raster file pixel values shall be updated.
gt	double vector of length 6
domain_item	character vector of length 0, 1 (with domain), or 2 (with domain and item); use "" for the default domain, use NA_character_ to query the domain names.
parse	logical; should metadata be parsed into a named list (TRUE) or returned as character data?
name	logical; retrieve name of subdataset? If FALSE, retrieve description
mask	stars object with NA mask (0 where NA), or NULL
use_integer	boolean; if TRUE, raster values are read as (and rounded to) unsigned 32-bit integers values; if FALSE they are read as 32-bit floating points numbers. The former is supposedly faster.
breaks	numeric vector with break values for contour polygons (or lines)
use_contours	logical;
contour_lines	logical;

connect8	logical; if TRUE use 8 connection algorithm, rather than 4
sf	object of class sf
f	character; file name
pts	points matrix
bilinear	logical; use bilinear interpolation, rather than nearest neighbor?
array_name	array name
dimension_values	list with dimension values
units	character; units names (udunits conform) corresponding to dimension_values
nxy	integer vector of length 2
values	fill value
crs	object of class crs
xlim	numeric
ylim	numeric

Details

These functions are exported for the single purpose of being used by package stars, they are not meant to be used directly and may change or disappear without prior notice or deprecation warnings.

gdal_inv_geotransform returns the inverse geotransform

gdal_crs reads coordinate reference system from GDAL data set

get_metadata gets metadata of a raster layer

gdal_subdatasets returns the subdatasets of a gdal dataset

Value

object of class crs, see [st_crs](#).

named list with metadata items

gdal_subdatasets returns a zero-length list if file does not have subdatasets, and else a named list with subdatasets.

Examples

```
## Not run:
f = system.file("tif/L7_ETMs.tif", package="stars")
f = system.file("nc/avhrr-only-v2.19810901.nc", package = "stars")
gdal_metadata(f)
gdal_metadata(f, NA_character_)
try(gdal_metadata(f, "wrongDomain"))
gdal_metadata(f, c("", "AREA_OR_POINT"))

## End(Not run)
```

gdal_addo*add or remove overviews to/from a raster image*

Description

add or remove overviews to/from a raster image

Usage

```
gdal_addo(  
  file,  
  overviews = c(2, 4, 8, 16),  
  method = "NEAREST",  
  layers = integer(0),  
  options = character(),  
  clean = FALSE,  
  read_only = FALSE  
)
```

Arguments

file	character; file name
overviews	integer; overview levels
method	character; method to create overview; one of: nearest, average, rms, gauss, cubic, cubicspline, lanczos, average_mp, average_magphase, mode
layers	integer; layers to create overviews for (default: all)
options	character; dataset opening options
clean	logical; if TRUE only remove overviews, do not add
read_only	logical; if TRUE, add overviews to another file with extension .ovr added to file

Value

TRUE, invisibly, on success

See Also

[gdal_utils](#) for access to other gdal utilities that have a C API

gdal_utils*Native interface to gdal utils*

Description

Native interface to gdal utils

Usage

```
gdal_utils(  
  util = "info",  
  source,  
  destination,  
  options = character(0),  
  quiet = !(util %in% c("info", "mdiminfo")),  
  processing = character(0),  
  colorfilename = character(0)  
)
```

Arguments

util	character; one of info, warp, rasterize, translate, vectortranslate (for ogr2ogr), buildvrt, demprocessing, nearblack, grid, mdiminfo and mdimtranslate (the last two requiring GDAL 3.1)
source	character; name of input layer(s); for warp, buildvrt or mdimtranslate this can be more than one
destination	character; name of output layer
options	character; options for the utility
quiet	logical; if TRUE, suppress printing the output for info and mdiminfo, and suppress printing progress
processing	character; processing options for demprocessing
colorfilename	character; name of color file for demprocessing (mandatory if processing="color-relief")

Value

info returns a character vector with the raster metadata; all other utils return (invisibly) a logical indicating success (i.e., TRUE); in case of failure, an error is raised.

See Also

[gdal_addo](#) for adding overlays to a raste file; [st_layers](#) to query geometry type(s) and crs from layers in a (vector) data source

Examples

```

if (sf_extSoftVersion()["GDAL"] > "2.1.0") {
  # info utils can be used to list information about a raster
  # dataset. More info: https://gdal.org/programs/gdalinfo.html
  in_file <- system.file("tif/geomatrix.tif", package = "sf")
  gdal_utils("info", in_file, options = c("-mm", "-proj4"))

  # vectortranslate utils can be used to convert simple features data between
  # file formats. More info: https://gdal.org/programs/ogr2ogr.html
  in_file <- system.file("shape/storms_xyz.shp", package="sf")
  out_file <- paste0(tempfile(), ".gpkg")
  gdal_utils(
    util = "vectortranslate",
    source = in_file,
    destination = out_file, # output format must be specified for GDAL < 2.3
    options = c("-f", "GPKG")
  )
  # The parameters can be specified as c("name") or c("name", "value"). The
  # vectortranslate utils can perform also various operations during the
  # conversion process. For example we can reproject the features during the
  # translation.
  gdal_utils(
    util = "vectortranslate",
    source = in_file,
    destination = out_file,
    options = c(
      "-f", "GPKG", # output file format for GDAL < 2.3
      "-s_srs", "EPSG:4326", # input file SRS
      "-t_srs", "EPSG:2264", # output file SRS
      "-overwrite"
    )
  )
  st_read(out_file)
  # The parameter s_srs had to be specified because, in this case, the in_file
  # has no associated SRS.
  st_read(in_file)
}

```

Description

Perform geometric set operations with simple feature geometry collections

Usage

```
st_intersection(x, y, ...)
```

```

## S3 method for class 'sfc'
st_intersection(x, y, ...)

## S3 method for class 'sf'
st_intersection(x, y, ...)

st_difference(x, y, ...)

## S3 method for class 'sfc'
st_difference(x, y, ...)

st_sym_difference(x, y, ...)

st_snap(x, y, tolerance)

```

Arguments

x	object of class sf, sfc or sfg
y	object of class sf, sfc or sfg
...	arguments passed on to s2_options
tolerance	tolerance values used for st_snap; numeric value or object of class units; may have tolerance values for each feature in x

Details

When using GEOS and not using s2, a spatial index is built on argument x; see <https://r-spatial.org/r/2017/06/22/spatial-index.html>. The reference for the STR tree algorithm is: Leutenegger, Scott T., Mario A. Lopez, and Jeffrey Edgington. "STR: A simple and efficient algorithm for R-tree packing." Data Engineering, 1997. Proceedings. 13th international conference on. IEEE, 1997. For the pdf, search Google Scholar.

When called with missing y, the sfc method for st_intersection returns all non-empty intersections of the geometries of x; an attribute idx contains a list-column with the indexes of contributing geometries.

when called with a missing y, the sf method for st_intersection returns an sf object with attributes taken from the contributing feature with lowest index; two fields are added: n.overlaps with the number of overlapping features in x, and a list-column origins with indexes of all overlapping features.

When st_difference is called with a single argument, overlapping areas are erased from geometries that are indexed at greater numbers in the argument to x; geometries that are empty or contained fully inside geometries with higher priority are removed entirely. The st_difference.sfc method with a single argument returns an object with an "idx" attribute with the original index for returned geometries.

st_snap snaps the vertices and segments of a geometry to another geometry's vertices. If y contains more than one geometry, its geometries are merged into a collection before snapping to that collection.

(from the GEOS docs:) "A snap distance tolerance is used to control where snapping is performed. Snapping one geometry to another can improve robustness for overlay operations by eliminating nearly-coincident edges (which cause problems during noding and intersection calculation). Too much snapping can result in invalid topology being created, so the number and location of snapped vertices is decided using heuristics to determine when it is safe to snap. This can result in some potential snaps being omitted, however."

Value

The intersection, difference or symmetric difference between two sets of geometries. The returned object has the same class as that of the first argument (x) with the non-empty geometries resulting from applying the operation to all geometry pairs in x and y. In case x is of class sf, the matching attributes of the original object(s) are added. The sfc geometry list-column returned carries an attribute idx, which is an n-by-2 matrix with every row the index of the corresponding entries of x and y, respectively.

Note

To find whether pairs of simple feature geometries intersect, use the function [st_intersects](#) instead of [st_intersection](#).

When using GEOS and not using s2 polygons contain their boundary. When using s2 this is determined by the model defaults of [s2_options](#), which can be overriden via the ... argument, e.g. model = "closed" to force DE-9IM compliant behaviour of polygons (and reproduce GEOS results).

See Also

[st_union](#) for the union of simple features collections; [intersect](#) and [setdiff](#) for the base R set operations.

Examples

```
set.seed(131)
library(sf)
m = rbind(c(0,0), c(1,0), c(1,1), c(0,1), c(0,0))
p = st_polygon(list(m))
n = 100
l = vector("list", n)
for (i in 1:n)
  l[[i]] = p + 10 * runif(2)
s = st_sfc(l)
plot(s, col = sf.colors(categorical = TRUE, alpha = .5))
title("overlapping squares")
d = st_difference(s) # sequential differences: s1, s2-s1, s3-s2-s1, ...
plot(d, col = sf.colors(categorical = TRUE, alpha = .5))
title("non-overlapping differences")
i = st_intersection(s) # all intersections
plot(i, col = sf.colors(categorical = TRUE, alpha = .5))
title("non-overlapping intersections")
summary(lengths(st_overlaps(s, s))) # includes self-counts!
summary(lengths(st_overlaps(d, d)))
summary(lengths(st_overlaps(i, i)))
```

```

sf = st_sf(s)
i = st_intersection(sf) # all intersections
plot(i[["n.overlaps"]])
summary(i$n.overlaps - lengths(i$origins))
# A helper function that erases all of y from x:
st_erase = function(x, y) st_difference(x, st_union(st_combine(y)))
poly = st_polygon(list(cbind(c(0, 0, 1, 1, 0), c(0, 1, 1, 0, 0))))
lines = st_multilinestring(list(
  cbind(c(0, 1), c(1, 1.05)),
  cbind(c(0, 1), c(0, -.05)),
  cbind(c(1, .95, 1), c(1.05, .5, -.05)))
))
snapped = st_snap(poly, lines, tolerance=.1)
plot(snapped, col='red')
plot(poly, border='green', add=TRUE)
plot(lines, lwd=2, col='blue', add=TRUE)

```

geos_binary_pred

*Geometric binary predicates on pairs of simple feature geometry sets***Description**

Geometric binary predicates on pairs of simple feature geometry sets

Usage

```

st_intersects(x, y, sparse = TRUE, ...)
st_disjoint(x, y = x, sparse = TRUE, prepared = TRUE)
st_touches(x, y, sparse = TRUE, prepared = TRUE, ...)
st_crosses(x, y, sparse = TRUE, prepared = TRUE, ...)
st_within(x, y, sparse = TRUE, prepared = TRUE, ...)
st_contains(x, y, sparse = TRUE, prepared = TRUE, ..., model = "open")
st_contains_properly(x, y, sparse = TRUE, prepared = TRUE, ...)
st_overlaps(x, y, sparse = TRUE, prepared = TRUE, ...)
st_equals(
  x,
  y,
  sparse = TRUE,
  prepared = FALSE,
  ...
)

```

```

retain_unique = FALSE,
remove_self = FALSE
)

st_covers(x, y, sparse = TRUE, prepared = TRUE, ..., model = "closed")

st_covered_by(x, y = x, sparse = TRUE, prepared = TRUE, ..., model = "closed")

st_equals_exact(x, y, par, sparse = TRUE, prepared = FALSE, ...)

st_is_within_distance(x, y = x, dist, sparse = TRUE, ...)

```

Arguments

x	object of class sf, sfc or sfg
y	object of class sf, sfc or sfg; if missing, x is used
sparse	logical; should a sparse index list be returned (TRUE) or a dense logical matrix? See below.
...	passed on to s2_options
prepared	logical; prepare geometry for x, before looping over y? See Details.
model	character; polygon/polyline model; one of "open", "semi-open" or "closed"; see Details.
retain_unique	logical; if TRUE (and y is missing) return only indexes of points larger than the current index; this can be used to select unique geometries, see examples. This argument can be used for all geometry predicates; see also distinct.sf to find records where geometries AND attributes are distinct.
remove_self	logical; if TRUE (and y is missing) return only indexes of geometries different from the current index; this can be used to omit self-intersections; see examples. This argument can be used for all geometry predicates
par	numeric; parameter used for "equals_exact" (margin);
dist	distance threshold; geometry indexes with distances smaller or equal to this value are returned; numeric value or units value having distance units.

Details

If prepared is TRUE, and x contains POINT geometries and y contains polygons, then the polygon geometries are prepared, rather than the points.

For most predicates, a spatial index is built on argument x; see <https://r-spatial.org/r/2017/06/22/spatial-index.html>. Specifically, st_intersects, st_disjoint, st_touches, st_crosses, st_within, st_contains, st_contains_properly, st_overlaps, st_equals, st_covers and st_covered_by all build spatial indexes for more efficient geometry calculations. st_relate, st_equals_exact, and do not; st_is_within_distance uses a spatial index for geographic coordinates when sf_use_s2() is true.

If y is missing, 'st_predicate(x, x)' is effectively called, and a square matrix is returned with diagonal elements 'st_predicate(x[i], x[i])'.

Sparse geometry binary predicate ([sgbp](#)) lists have the following attributes: `region.id` with the row.names of `x` (if any, else `1:n`), `ncol` with the number of features in `y`, and `predicate` with the name of the predicate used.

for model, see <https://github.com/r-spatial/s2/issues/32>

‘`st_contains_properly(A,B)`’ is true if `A` intersects `B`’s interior, but not its edges or exterior; `A` contains `A`, but `A` does not properly contain `A`.

See also `st_relate` and <https://en.wikipedia.org/wiki/DE-9IM> for a more detailed description of the underlying algorithms.

`st_equals_exact` returns true for two geometries of the same type and their vertices corresponding by index are equal up to a specified tolerance.

Value

If `sparse=FALSE`, `st_predicate` (with predicate e.g. “`intersects`”) returns a dense logical matrix with element `i, j` `TRUE` when `predicate(x[i], y[j])` (e.g., when geometry of feature `i` and `j` intersect); if `sparse=TRUE`, an object of class [sgbp](#) with a sparse list representation of the same matrix, with list element `i` an integer vector with all indices `j` for which `predicate(x[i], y[j])` is `TRUE` (and hence a zero-length integer vector if none of them is `TRUE`). From the dense matrix, one can find out if one or more elements intersect by `apply(mat, 1, any)`, and from the sparse list by `lengths(lst) > 0`, see examples below.

Note

For intersection on pairs of simple feature geometries, use the function `st_intersection` instead of `st_intersects`.

Examples

```
pts = st_sf(st_point(c(.5,.5)), st_point(c(1.5, 1.5)), st_point(c(2.5, 2.5)))
pol = st_polygon(list(rbind(c(0,0), c(2,0), c(2,2), c(0,2), c(0,0))))
(lst = st_intersects(pts, pol))
(mat = st_intersects(pts, pol, sparse = FALSE))
# which points fall inside a polygon?
apply(mat, 1, any)
lengths(lst) > 0
# which points fall inside the first polygon?
st_intersects(pol, pts)[[1]]
# remove duplicate geometries:
p1 = st_point(0:1)
p2 = st_point(2:1)
p = st_sf(a = letters[1:8], geom = st_sf(p1, p1, p2, p1, p1, p2, p2, p1))
st_equals(p)
st_equals(p, remove_self = TRUE)
(u = st_equals(p, retain_unique = TRUE))
# retain the records with unique geometries:
p[-unlist(u),]
```

geos_combine	<i>Combine or union feature geometries</i>
--------------	--

Description

Combine several feature geometries into one, without unioning or resolving internal boundaries

Usage

```
st_combine(x)

st_union(x, y, ..., by_feature = FALSE, is_coverage = FALSE)
```

Arguments

x	object of class sf, sfc or sfg
y	object of class sf, sfc or sfg (optional)
...	ignored
by_feature	logical; if TRUE, union each feature, if FALSE return a single feature that is the geometric union of the set of features
is_coverage	logical; if TRUE, use an optimized algorithm for features that form a polygonal coverage (have no overlaps)

Details

`st_combine` combines geometries without resolving borders, using [c.sfg](#) (analogous to [c](#) for ordinary vectors).

If `st_union` is called with a single argument, `x`, (with `y` missing) and `by_feature` is FALSE all geometries are unioned together and an sfg or single-geometry sfc object is returned. If `by_feature` is TRUE each feature geometry is unioned. This can for instance be used to resolve internal boundaries after polygons were combined using `st_combine`. If `y` is provided, all elements of `x` and `y` are unioned, pairwise (and `by_feature` is ignored). The former corresponds to `rgeos::gUnaryUnion`, the latter to `rgeos::gUnion`.

Unioning a set of overlapping polygons has the effect of merging the areas (i.e. the same effect as iteratively unioning all individual polygons together). Unioning a set of LineStrings has the effect of fully noding and dissolving the input linework. In this context "fully noded" means that there will be a node or endpoint in the output for every endpoint or line segment crossing in the input. "Dissolved" means that any duplicate (e.g. coincident) line segments or portions of line segments will be reduced to a single line segment in the output. Unioning a set of Points has the effect of merging all identical points (producing a set with no duplicates).

Value

`st_combine` returns a single, combined geometry, with no resolved boundaries; returned geometries may well be invalid.

If `y` is missing, `st_union(x)` returns a single geometry with resolved boundaries, else the geometries for all unioned pairs of `x[i]` and `y[j]`.

See Also

[st_intersection](#), [st_difference](#), [st_sym_difference](#)

Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
st_combine(nc)
plot(st_union(nc))
```

geos_measures

Compute geometric measurements

Description

Compute Euclidian or great circle distance between pairs of geometries; compute, the area or the length of a set of geometries.

Usage

```
st_area(x, ...)

## S3 method for class 'sfc'
st_area(x, ...)

st_length(x, ...)

st_distance(
  x,
  y,
  ...,
  dist_fun,
  by_element = FALSE,
  which = ifelse(isTRUE(st_is_longlat(x)), "Great Circle", "Euclidean"),
  par = 0,
  tolerance = 0
)
```

Arguments

x	object of class sf, sfc or sfg
...	passed on to s2_distance or s2_distance_matrix
y	object of class sf, sfc or sfg, defaults to x
dist_fun	deprecated
by_element	logical; if TRUE, return a vector with distance between the first elements of x and y, the second, etc. if FALSE, return the dense matrix with all pairwise distances.

which	character; for Cartesian coordinates only: one of Euclidean, Hausdorff or Frechet; for geodetic coordinates, great circle distances are computed; see details
par	for which equal to Hausdorff or Frechet, optionally use a value between 0 and 1 to densify the geometry
tolerance	ignored if <code>st_is_longlat(x)</code> is FALSE; otherwise, if set to a positive value, the first distance smaller than tolerance will be returned, and true distance may be smaller; this may speed up computation. In meters, or a units object convertible to meters.

Details

great circle distance calculations use by default spherical distances ([s2_distance](#) or [s2_distance_matrix](#)); if `sf_use_s2()` is FALSE, ellipsoidal distances are computed using [st_geod_distance](#) which uses function `geod_inverse` from `GeographicLib` (part of PROJ); see Karney, Charles FF, 2013, Algorithms for geodesics, *Journal of Geodesy* 87(1), 43–55

Value

If the coordinate reference system of `x` was set, these functions return values with unit of measurement; see [set_units](#).

`st_area` returns the area of a geometry, in the coordinate reference system used; in case `x` is in degrees longitude/latitude, [st_geod_area](#) is used for area calculation.

`st_length` returns the length of a LINESTRING or MULTILINESTRING geometry, using the coordinate reference system. POINT, MULTIPOINT, POLYGON or MULTIPOLYGON geometries return zero.

If `by_element` is FALSE `st_distance` returns a dense numeric matrix of dimension `length(x)` by `length(y)`; otherwise it returns a numeric vector of length `x` or `y`, the shorter one being recycled. Distances involving empty geometries are NA.

See Also

[st_dimension](#), [st_cast](#) to convert geometry types

Examples

```
b0 = st_polygon(list(rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,-1))))
b1 = b0 + 2
b2 = b0 + c(-0.2, 2)
x = st_sfc(b0, b1, b2)
st_area(x)
line = st_sfc(st_linestring(rbind(c(30,30), c(40,40))), crs = 4326)
st_length(line)

outer = matrix(c(0,0,10,0,10,10,0,10,0,0),ncol=2, byrow=TRUE)
hole1 = matrix(c(1,1,1,2,2,2,1,1,1),ncol=2, byrow=TRUE)
hole2 = matrix(c(5,5,5,6,6,6,5,5,5),ncol=2, byrow=TRUE)

poly = st_polygon(list(outer, hole1, hole2))
mpoly = st_multipolygon(list(
```

```

list(outer, hole1, hole2),
list(outer + 12, hole1 + 12)
))

st_length(st_sfc(poly, mpoly))
p = st_sfc(st_point(c(0,0)), st_point(c(0,1)), st_point(c(0,2)))
st_distance(p, p)
st_distance(p, p, by_element = TRUE)

```

geos_query

Dimension, simplicity, validity or is_empty queries on simple feature geometries

Description

Dimension, simplicity, validity or is_empty queries on simple feature geometries

Usage

```

st_dimension(x, NA_if_empty = TRUE)

st_is_simple(x)

st_is_empty(x)

```

Arguments

x	object of class sf, sfc or sfg
NA_if_empty	logical; if TRUE, return NA for empty geometries

Value

st_dimension returns a numeric vector with 0 for points, 1 for lines, 2 for surfaces, and, if NA_if_empty is TRUE, NA for empty geometries.

st_is_simple returns a logical vector, indicating for each geometry whether it is simple (e.g., not self-intersecting)

st_is_empty returns for each geometry whether it is empty

Examples

```

x = st_sfc(
  st_point(0:1),
  st_linestring(rbind(c(0,0),c(1,1))),
  st_polygon(list(rbind(c(0,0),c(1,0),c(0,1),c(0,0)))),
  st_multipoint(),
  st_linestring(),
  st_geometrycollection())
st_dimension(x)

```

```
st_dimension(x, FALSE)
ls = st_linestring(rbind(c(0,0), c(1,1), c(1,0), c(0,1)))
st_is_simple(st_sfc(ls, st_point(c(0,0))))
ls = st_linestring(rbind(c(0,0), c(1,1), c(1,0), c(0,1)))
st_is_empty(st_sfc(ls, st_point(), st_linestring()))
```

geos_unary*Geometric unary operations on simple feature geometry sets***Description**

Geometric unary operations on simple feature geometries. These are all generics, with methods for sfg, sfc and sf objects, returning an object of the same class. All operations work on a per-feature basis, ignoring all other features.

Usage

```
st_buffer(
  x,
  dist,
  nQuadSegs = 30,
  endCapStyle = "ROUND",
  joinStyle = "ROUND",
  mitreLimit = 1,
  singleSide = FALSE,
  ...
)

st_boundary(x)

st_convex_hull(x)

st_simplify(x, preserveTopology, dTolerance = 0)

st_triangulate(x, dTolerance = 0, bOnlyEdges = FALSE)

st_inscribed_circle(x, dTolerance, ...)

st_minimum_rotated_rectangle(x, ...)

st_voronoi(x, envelope, dTolerance = 0, bOnlyEdges = FALSE)

st_polygonize(x)

st_line_merge(x)

st_centroid(x, ..., of_largest_polygon = FALSE)
```

```

st_point_on_surface(x)

st_reverse(x)

st_node(x)

st_segmentize(x, dfMaxLength, ...)

```

Arguments

x	object of class sfg, sfc or sf
dist	numeric; buffer distance for all, or for each of the elements in x; in case dist is a units object, it should be convertible to arc_degree if x has geographic coordinates, and to st_crs(x)\$units otherwise
nQuadSegs	integer; number of segments per quadrant (fourth of a circle), for all or per-feature
endCapStyle	character; style of line ends, one of 'ROUND', 'FLAT', 'SQUARE'
joinStyle	character; style of line joins, one of 'ROUND', 'MITRE', 'BEVEL'
mitreLimit	numeric; limit of extension for a join if joinStyle 'MITRE' is used (default 1.0, minimum 0.0)
singleSide	logical; if TRUE, single-sided buffers are returned for linear geometries, in which case negative dist values give buffers on the right-hand side, positive on the left.
...	ignored
preserveTopology	logical; carry out topology preserving simplification? May be specified for each, or for all feature geometries. Note that topology is preserved only for single feature geometries, not for sets of them. If not specified (i.e. the default), then it is internally set equal to FALSE when the input data is specified with projected coordinates or sf_use_s2() returns FALSE. Ignored in all the other cases (with a warning when set equal to FALSE) since the function implicitly calls s2::s2_simplify which always preserve topological relationships (per single feature).
dTolerance	numeric; tolerance parameter, specified for all or for each feature geometry. If you run st_simplify, the input data is specified with long-lat coordinates and sf_use_s2() returns TRUE, then the value of dTolerance must be specified in meters.
bOnlyEdges	logical; if TRUE, return lines, else return polygons
envelope	object of class sfc or sfg containing a POLYGON with the envelope for a voronoi diagram; this only takes effect when it is larger than the default envelope, chosen when envelope is an empty polygon
of_largest_polygon	logical; for st_centroid: if TRUE, return centroid of the largest (sub)polygon of a MULTIPOLYGON rather than of the whole MULTIPOLYGON

`dfMaxLength` maximum length of a line segment. If `x` has geographical coordinates (long/lat), `dfMaxLength` is either a numeric expressed in meter, or an object of class `units` with length units `rad` or `degree`; segmentation in the long/lat case takes place along the great circle, using [st_geod_segmentize](#).

Details

`st_buffer` computes a buffer around this geometry/each geometry. If any of `endCapStyle`, `joinStyle`, or `mitreLimit` are set to non-default values ('ROUND', 'ROUND', 1.0 respectively) then the underlying 'buffer with style' GEOS function is used. See postgis.net/docs/ST_Buffer.html for details.

`st_boundary` returns the boundary of a geometry

`st_convex_hull` creates the convex hull of a set of points

`st_simplify` simplifies lines by removing vertices.

`st_triangulate` triangulates set of points (not constrained). `st_triangulate` requires GEOS version 3.4 or above

`st_inscribed_circle` returns the maximum inscribed circle for polygon geometries. For `st_inscribed_circle`, if `nQuadSegs` is 0 a 2-point LINESTRING is returned with the center point and a boundary point of every circle, otherwise a circle (buffer) is returned where `nQuadSegs` controls the number of points per quadrant to approximate the circle. `st_inscribed_circle` requires GEOS version 3.9 or above

`st_minimum_rotated_rectangle` returns the minimum rotated rectangular POLYGON which encloses the input geometry. The rectangle has width equal to the minimum diameter, and a longer length. If the convex hull of the input is degenerate (a line or point) a linestring or point is returned.

`st_voronoi` creates voronoi tessellation. `st_voronoi` requires GEOS version 3.5 or above

`st_polygonize` creates polygon from lines that form a closed ring. In case of `st_polygonize`, `x` must be an object of class `LINESTRING` or `MULTILINESTRING`, or an `sfc` geometry list-column object containing these

`st_line_merge` merges lines. In case of `st_line_merge`, `x` must be an object of class `MULTILINESTRING`, or an `sfc` geometry list-column object containing these

`st_centroid` gives the centroid of a geometry

`st_point_on_surface` returns a point guaranteed to be on the (multi)surface.

`st_reverse` reverses the nodes in a line

`st_node` adds nodes to linear geometries at intersections without a node, and only works on individual linear geometries

`st_segmentize` adds points to straight lines

Value

an object of the same class of `x`, with manipulated geometry.

Examples

```
## st_buffer, style options (taken from rgeos gBuffer)
l1 = st_as_sfc("LINESTRING(0 0,1 5,4 5,5 2,8 2,9 4,4 6.5)")
op = par(mfrow=c(2,3))
```

```

plot(st_buffer(l1, dist = 1, endCapStyle="ROUND"), reset = FALSE, main = "endCapStyle: ROUND")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, endCapStyle="FLAT"), reset = FALSE, main = "endCapStyle: FLAT")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, endCapStyle="SQUARE"), reset = FALSE, main = "endCapStyle: SQUARE")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, nQuadSegs=1), reset = FALSE, main = "nQuadSegs: 1")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, nQuadSegs=2), reset = FALSE, main = "nQuadSegs: 2")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, nQuadSegs= 5), reset = FALSE, main = "nQuadSegs: 5")
plot(l1,col='blue',add=TRUE)
par(op)

l2 = st_as_sfc("LINESTRING(0 0,1 5,3 2)")
op = par(mfrow = c(2, 3))
plot(st_buffer(l2, dist = 1, joinStyle="ROUND"), reset = FALSE, main = "joinStyle: ROUND")
plot(l2, col = 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE"), reset = FALSE, main = "joinStyle: MITRE")
plot(l2, col= 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="BEVEL"), reset = FALSE, main = "joinStyle: BEVEL")
plot(l2, col= 'blue', add=TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE" , mitreLimit=0.5), reset = FALSE,
     main = "mitreLimit: 0.5")
plot(l2, col = 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE",mitreLimit=1), reset = FALSE,
     main = "mitreLimit: 1")
plot(l2, col = 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE",mitreLimit=3), reset = FALSE,
     main = "mitreLimit: 3")
plot(l2, col = 'blue', add = TRUE)
par(op)
nc = st_read(system.file("shape/nc.shp", package="sf"))
nc_g = st_geometry(nc)
plot(st_convex_hull(nc_g))
plot(nc_g, border = grey(.5), add = TRUE)

# st_simplify examples:
op = par(mfrow = c(2, 3), mar = rep(0, 4))
plot(nc_g[1])
plot(st_simplify(nc_g[1], dTolerance = 1e3)) # 1000m
plot(st_simplify(nc_g[1], dTolerance = 5e3)) # 5000m
nc_g_planar = st_transform(nc_g, 2264) # planar coordinates, US foot
plot(nc_g_planar[1])
plot(st_simplify(nc_g_planar[1], dTolerance = 1e3)) # 1000 foot
plot(st_simplify(nc_g_planar[1], dTolerance = 5e3)) # 5000 foot
par(op)

if (compareVersion(sf_extSoftVersion()[[["GEOS"]]], "3.9.0") > -1) {
  nc_t = st_transform(nc, 'EPSG:2264')
  x = st_inscribed_circle(st_geometry(nc_t))
  plot(st_geometry(nc_t), asp = 1, col = grey(.9))
}

```

```

    plot(x, add = TRUE, col = '#ff9999')
}
set.seed(1)
x = st_multipoint(matrix(runif(10), , 2))
box = st_polygon(list(rbind(c(0, 0), c(1, 0), c(1, 1), c(0, 1), c(0, 0))))
if (compareVersion(sf_extSoftVersion()[["GEOS"]], "3.5.0") > -1) {
  v = st_sfc(st_voronoi(x, st_sfc(box)))
  plot(v, col = 0, border = 1, axes = TRUE)
  plot(box, add = TRUE, col = 0, border = 1) # a larger box is returned, as documented
  plot(x, add = TRUE, col = 'red', cex=2, pch=16)
  plot(st_intersection(st_cast(v), box)) # clip to smaller box
  plot(x, add = TRUE, col = 'red', cex=2, pch=16)
# matching Voronoi polygons to data points:
# https://github.com/r-spatial/sf/issues/1030
# generate 50 random unif points:
n = 100
pts = st_as_sf(data.frame(matrix(runif(n), , 2), id = 1:(n/2)), coords = c("X1", "X2"))
# compute Voronoi polygons:
polys = st_collection_extract(st_voronoi(do.call(c, st_geometry(pts))))
# match them to points:
pts$pols = polys[unlist(st_intersects(pts, polys))]
plot(pts["id"], pch = 16) # ID is color
plot(st_set_geometry(pts, "polys")["id"], xlim = c(0,1), ylim = c(0,1), reset = FALSE)
plot(st_geometry(pts), add = TRUE)
layout(matrix(1)) # reset plot layout
}
mls = st_multilinestring(list(matrix(c(0,0,0,1,1,1,0,0), , 2, byrow=TRUE)))
st_polygonize(st_sfc(mls))
mls = st_multilinestring(list(rbind(c(0,0), c(1,1)), rbind(c(2,0), c(1,1))))
st_line_merge(st_sfc(mls))
plot(nc_g, axes = TRUE)
plot(st_centroid(nc_g), add = TRUE, pch = 3, col = 'red')
mp = st_combine(st_buffer(st_sfc(lapply(1:3, function(x) st_point(c(x,x)))), 0.2 * 1:3))
plot(mp)
plot(st_centroid(mp), add = TRUE, col = 'red') # centroid of combined geometry
plot(st_centroid(mp, of_largest_polygon = TRUE), add = TRUE, col = 'blue', pch = 3)
plot(nc_g, axes = TRUE)
plot(st_point_on_surface(nc_g), add = TRUE, pch = 3, col = 'red')
if (compareVersion(sf_extSoftVersion()[["GEOS"]], "3.7.0") > -1) {
  st_reverse(st_linestring(rbind(c(1,1), c(2,2), c(3,3))))
}
(l = st_linestring(rbind(c(0,0), c(1,1), c(0,1), c(1,0), c(0,0))))
st_polygonize(st_node(l))
st_node(st_multilinestring(list(rbind(c(0,0), c(1,1), c(0,1), c(1,0), c(0,0)))))
sf = st_sf(a=1, geom=st_sfc(st_linestring(rbind(c(0,0),c(1,1)))), crs = 4326)
if (require(lwgeom, quietly = TRUE)) {
  seg = st_segmentize(sf, units::set_units(100, km))
  seg = st_segmentize(sf, units::set_units(0.01, rad))
  nrow(seg$geom[[1]])
}

```

internal*Internal functions*

Description

Internal functions

Usage

```
.stop_geos(msg)
```

Arguments

msg	error message
-----	---------------

interpolate_aw*Areal-weighted interpolation of polygon data*

Description

Areal-weighted interpolation of polygon data

Usage

```
st_interpolate_aw(x, to, extensive, ...)

## S3 method for class 'sf'
st_interpolate_aw(x, to, extensive, ..., keep_NA = FALSE)
```

Arguments

x	object of class sf, for which we want to aggregate attributes
to	object of class sf or sfc, with the target geometries
extensive	logical; if TRUE, the attribute variables are assumed to be spatially extensive (like population) and the sum is preserved, otherwise, spatially intensive (like population density) and the mean is preserved.
...	ignored
keep_NA	logical; if TRUE, return all features in to, if FALSE return only those with non-NA values (but with row.names the index corresponding to the feature in to)

Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
g = st_make_grid(nc, n = c(10, 5))
a1 = st_interpolate_aw(nc["BIR74"], g, extensive = FALSE)
sum(a1$BIR74) / sum(nc$BIR74) # not close to one: property is assumed spatially intensive
a2 = st_interpolate_aw(nc["BIR74"], g, extensive = TRUE)
# verify mass preservation (pycnochylactic) property:
sum(a2$BIR74) / sum(nc$BIR74)
a1$intensive = a1$BIR74
a1$extensive = a2$BIR74
plot(a1[c("intensive", "extensive")], key.pos = 4)
```

is_driver_available *Check if driver is available*

Description

Search through the driver table if driver is listed

Usage

```
is_driver_available(drv, drivers = st_drivers())
```

Arguments

drv	character. Name of driver
drivers	data.frame. Table containing driver names and support. Default is from st_drivers

is_driver_can *Check if a driver can perform an action*

Description

Search through the driver table to match a driver name with an action (e.g. "write") and check if the action is supported.

Usage

```
is_driver_can(drv, drivers = st_drivers(), operation = "write")
```

Arguments

drv	character. Name of driver
drivers	data.frame. Table containing driver names and support. Default is from st_drivers
operation	character. What action to check

is_geometry_column	<i>Check if the columns could be of a coercable type for sf</i>
--------------------	---

Description

Check if the columns could be of a coercable type for sf

Usage

```
is_geometry_column(con, x, classes = "")
```

Arguments

con	database connection
x	inherits data.frame
classes	classes inherited

merge.sf	<i>merge method for sf and data.frame object</i>
----------	--

Description

merge method for sf and data.frame object

Usage

```
## S3 method for class 'sf'  
merge(x, y, ...)
```

Arguments

x	object of class sf
y	object of class data.frame
...	arguments passed on to merge.data.frame

Examples

```
a = data.frame(a = 1:3, b = 5:7)  
st_geometry(a) = st_sf(st_point(c(0,0)), st_point(c(1,1)), st_point(c(2,2)))  
b = data.frame(x = c("a", "b", "c"), b = c(2,5,6))  
merge(a, b)  
merge(a, b, all = TRUE)
```

nc*North Carolina SIDS data*

Description

Sudden Infant Death Syndrome (SIDS) sample data for North Carolina counties, two time periods (1974-78 and 1979-84). The details of the columns can be found on the `seealso` URL, `spdep` package's vignette. Please note that, though this is basically the same as `nc.sids` dataset in `spData` package, `nc` only contains a subset of variables. The differences are also discussed on the vignette.

See Also

<https://r-spatial.github.io/spdep/articles/sids.html>

Ops*S3 Ops Group Generic Functions for simple feature geometries*

Description

S3 Ops Group Generic Functions for simple feature geometries

Usage

```
## S3 method for class 'sfg'
Ops(e1, e2)

## S3 method for class 'sfc'
Ops(e1, e2)
```

Arguments

e1	object of class <code>sfg</code> or <code>sfc</code>
e2	numeric, or object of class <code>sfg</code> ; in case <code>e1</code> is of class <code>sfc</code> also an object of class <code>sfc</code> is allowed

Details

in case `e2` is numeric, `+`, `-`, `*`, `/`,

If `e1` is of class `sfc`, and `e2` is a length 2 numeric, then it is considered a two-dimensional point (and if needed repeated as such) only for operations `+` and `-`, in other cases the individual numbers are repeated; see commented examples.

Value

object of class `sfg`

Examples

```

st_point(c(1,2,3)) + 4
st_point(c(1,2,3)) * 3 + 4
m = matrix(0, 2, 2)
diag(m) = c(1, 3)
# affine:
st_point(c(1,2)) * m + c(2,5)
# world in 0-360 range:
if (require(maps, quietly = TRUE)) {
  w = st_as_sf(map('world', plot = FALSE, fill = TRUE))
  w2 = (st_geometry(w) + c(360,90)) %% c(360) - c(0,90)
  w3 = st_wrap_dateline(st_set_crs(w2 - c(180,0), 4326)) + c(180,0)
  plot(st_set_crs(w3, 4326), axes = TRUE)
}
(mp <- st_point(c(1,2)) + st_point(c(3,4))) # MULTIPOINT (1 2, 3 4)
mp = st_point(c(3,4)) # POINT (1 2)
opar = par(mfrow = c(2,2), mar = c(0, 0, 1, 0))
a = st_buffer(st_point(c(0,0)), 2)
b = a + c(2, 0)
p = function(m) { plot(c(a,b)); plot(eval(parse(text=m)), col=grey(.9), add = TRUE); title(m) }
lapply(c('a | b', 'a / b', 'a & b', 'a %% b'), p)
par(opar)
sfc = st_sfc(st_point(0:1), st_point(2:3))
sfc + c(2,3) # added to EACH geometry
sfc * c(2,3) # first geometry multiplied by 2, second by 3
nc = st_transform(st_read(system.file("gpkg/nc.gpkg", package="sf")), 32119) # nc state plane, m
b = st_buffer(st_centroid(st_union(nc)), units::set_units(50, km)) # shoot a hole in nc:
plot(st_geometry(nc) / b, col = grey(.9))

```

plot

plot sf object

Description

plot one or more attributes of an sf object on a map Plot sf object

Usage

```

## S3 method for class 'sf'
plot(
  x,
  y,
  ...,
  main,
  pal = NULL,
  nbreaks = 10,
  breaks = "pretty",
  max.plot = if (is.null(n <- getOption("sf_max.plot"))) 9 else n,
  key.pos = get_key_pos(x, ...),

```

```
key.length = 0.618,
key.width = lcm(1.8),
reset = TRUE,
logz = FALSE,
extent = x,
xlim = st_bbox(extent)[c(1, 3)],
ylim = st_bbox(extent)[c(2, 4)]
)

get_key_pos(x, ...)

## S3 method for class 'sfc_POINT'
plot(
  x,
  y,
  ...,
  pch = 1,
  cex = 1,
  col = 1,
  bg = 0,
  lwd = 1,
  lty = 1,
  type = "p",
  add = FALSE
)

## S3 method for class 'sfc_MULTIPOINT'
plot(
  x,
  y,
  ...,
  pch = 1,
  cex = 1,
  col = 1,
  bg = 0,
  lwd = 1,
  lty = 1,
  type = "p",
  add = FALSE
)

## S3 method for class 'sfc_LINESTRING'
plot(x, y, ..., lty = 1, lwd = 1, col = 1, pch = 1, type = "l", add = FALSE)

## S3 method for class 'sfc_CIRCULARSTRING'
plot(x, y, ...)

## S3 method for class 'sfc_MULTILINESTRING'
```

```
plot(x, y, ..., lty = 1, lwd = 1, col = 1, pch = 1, type = "l", add = FALSE)

## S3 method for class 'sfc_POLYGON'
plot(
  x,
  y,
  ...,
  lty = 1,
  lwd = 1,
  col = NA,
  cex = 1,
  pch = NA,
  border = 1,
  add = FALSE,
  rule = "evenodd",
  xpd = par("xpd")
)

## S3 method for class 'sfc_MULTIPOINT'
plot(
  x,
  y,
  ...,
  lty = 1,
  lwd = 1,
  col = NA,
  border = 1,
  add = FALSE,
  rule = "evenodd",
  xpd = par("xpd")
)

## S3 method for class 'sfc_GEOGRAPHYCOLLECTION'
plot(
  x,
  y,
  ...,
  pch = 1,
  cex = 1,
  bg = 0,
  lty = 1,
  lwd = 1,
  col = 1,
  border = 1,
  add = FALSE
)

## S3 method for class 'sfc_GEOGRAPHY'
```

```

plot(
  x,
  y,
  ...,
  pch = 1,
  cex = 1,
  bg = 0,
  lty = 1,
  lwd = 1,
  col = ifelse(st_dimension(x) == 2, NA, 1),
  border = 1,
  add = FALSE
)
## S3 method for class 'sfg'
plot(x, ...)

plot_sf(
  x,
  xlim = NULL,
  ylim = NULL,
  asp = NA,
  axes = FALSE,
  bgc = par("bg"),
  ...,
  xaxs,
  yaxs,
  lab,
  setParUsrBB = FALSE,
  bgMap = NULL,
  expandBB = c(0, 0, 0, 0),
  graticule = NA_crs_,
  col_graticule = "grey",
  border,
  extent = x
)
sf.colors(n = 10, cutoff.tails = c(0.35, 0.2), alpha = 1, categorical = FALSE)

```

Arguments

<code>x</code>	object of class sf
<code>y</code>	ignored
<code>...</code>	further specifications, see plot_sf and plot and details.
<code>main</code>	title for plot (NULL to remove)
<code>pal</code>	palette function, similar to rainbow , or palette values; if omitted, <code>sf.colors</code> is used

nbreaks	number of colors breaks (ignored for factor or character variables)
breaks	either a numeric vector with the actual breaks, or a name of a method accepted by the <code>style</code> argument of classIntervals
max.plot	integer; lower boundary to maximum number of attributes to plot; the default value (9) can be overriden by setting the global option <code>sf_max.plot</code> , e.g. <code>options(sf_max.plot=2)</code>
key.pos	integer; side to plot a color key: 1 bottom, 2 left, 3 top, 4 right; set to NULL to omit key completely, 0 to only not plot the key, or -1 to select automatically. If multiple columns are plotted in a single function call by default no key is plotted and every submap is stretched individually; if a key is requested (and <code>col</code> is missing) all maps are colored according to a single key. Auto select depends on plot size, map aspect, and, if set, parameter <code>asp</code> .
key.length	amount of space reserved for the key along its axis, length of the scale bar
key.width	amount of space reserved for the key (incl. labels), thickness/width of the scale bar
reset	logical; if FALSE, keep the plot in a mode that allows adding further map elements; if TRUE restore original mode after plotting sf objects with attributes; see details.
logz	logical; if TRUE, use log10-scale for the attribute variable. In that case, <code>breaks</code> and <code>at</code> need to be given as log10-values; see examples.
extent	object with an <code>st_bbox</code> method to define plot extent; defaults to <code>x</code>
xlim	see plot.window
ylim	see plot.window
pch	plotting symbol
cex	symbol size
col	color for plotting features; if <code>length(col)</code> does not equal 1 or <code>nrow(x)</code> , a warning is emitted that colors will be recycled. Specifying <code>col</code> suppresses plotting the legend key.
bg	symbol background color
lwd	line width
lty	line type
type	plot type: 'p' for points, 'l' for lines, 'b' for both
add	logical; add to current plot? Note that when using <code>add=TRUE</code> , you may have to set <code>reset=FALSE</code> in the first plot command.
border	color of polygon border(s); using NA hides them
rule	see polypath ; for winding, exterior ring direction should be opposite that of the holes; with evenodd, plotting is robust against misspecified ring directions
xpd	see par ; sets polygon clipping strategy; only implemented for POLYGON and MULTIPOLYGON
asp	see below, and see par
axes	logical; should axes be plotted? (default FALSE)
bgc	background color

xaxs	see par
yaxs	see par
lab	see par
setParUsrBB	default FALSE; set the par “usr” bounding box; see below
bgMap	object of class <code>ggmap</code> , or returned by function <code>RgoogleMaps::GetMap</code>
expandBB	numeric; fractional values to expand the bounding box with, in each direction (bottom, left, top, right)
graticule	logical, or object of class <code>crs</code> (e.g., <code>st_crs(4326)</code> for a WGS84 graticule), or object created by st_graticule ; TRUE will give the WGS84 graticule or object returned by st_graticule
col_graticule	color to used for the graticule (if present)
n	integer; number of colors
cutoff.tails	numeric, in [0,0.5] start and end values
alpha	numeric, in [0,1], transparency
categorical	logical; do we want colors for a categorical variable? (see details)

Details

`plot.sf` maximally plots `max.plot` maps with colors following from attribute columns, one map per attribute. It uses `sf.colors` for default colors. For more control over placement of individual maps, set parameter `mfrow` with [par](#) prior to plotting, and plot single maps one by one; note that this only works in combination with setting parameters `key.pos=NULL` (no legend) and `reset=FALSE`.

`plot.sfc` plots the geometry, additional parameters can be passed on to control color, lines or symbols.

When setting `reset` to `FALSE`, the original device parameters are lost, and the device must be reset using `dev.off()` in order to reset it.

parameter `at` can be set to specify where labels are placed along the key; see examples.

`plot_sf` sets up the plotting area, axes, graticule, or webmap background; it is called by all `plot` methods before anything is drawn.

The argument `setParUsrBB` may be used to pass the logical value `TRUE` to functions within `plot.Spatial`. When set to `TRUE`, `par("usr")` will be overwritten with `c(xlim, ylim)`, which defaults to the bounding box of the spatial object. This is only needed in the particular context of graphic output to a specified device with given width and height, to be matched to the spatial object, when using `par("xaxs")` and `par("yaxs")` in addition to `par(mar=c(0,0,0,0))`.

The default aspect for map plots is 1; if however data are not projected (coordinates are long/lat), the aspect is by default set to $1/\cos(\text{My} * \pi/180)$ with `My` the y coordinate of the middle of the map (the mean of `ylim`, which defaults to the y range of bounding box). This implies an [Equirectangular projection](#).

non-categorical colors from `sf.colors` were taken from [bpy.colors](#), with modified `cutoff.tails` defaults If `categorical` is `TRUE`, default colors are from <https://colorbrewer2.org/> (if `n < 9`, Set2, else Set3).

Examples

```
nc = st_read(system.file("gpkg/nc.gpkg", package="sf"), quiet = TRUE)
# plot single attribute, auto-legend:
plot(nc["SID74"])
# plot multiple:
plot(nc[c("SID74", "SID79")]) # better use ggplot2::geom_sf to facet and get a single legend!
# adding to a plot of an sf object only works when using reset=FALSE in the first plot:
plot(nc["SID74"], reset = FALSE)
plot(st_centroid(st_geometry(nc)), add = TRUE)
# log10 z-scale:
plot(nc["SID74"], logz = TRUE, breaks = c(0,.5,1,1.5,2), at = c(0,.5,1,1.5,2))
# and we need to reset the plotting device after that, e.g. by
layout(1)
# when plotting only geometries, the reset=FALSE is not needed:
plot(st_geometry(nc))
plot(st_geometry(nc)[1], col = 'red', add = TRUE)
# add a custom legend to an arbitrary plot:
layout(matrix(1:2, ncol = 2), widths = c(1, lcm(2)))
plot(1)
.image_scale(1:10, col = sf.colors(9), key.length = lcm(8), key.pos = 4, at = 1:10)
sf.colors(10)
```

prefix_map

Map prefix to driver

Description

Map prefix to driver

Usage

```
prefix_map
```

Format

An object of class list of length 10.

proj_tools

Manage PROJ settings

Description

Manage PROJ search path and network settings

Usage

```
sf_proj_search_paths(paths = character(0))

sf_proj_network(enable = FALSE, url = character(0))

sf_proj_pipelines(
  source_crs,
  target_crs,
  authority = character(0),
  AOI = numeric(0),
  Use = "NONE",
  grid_availability = "USED",
  desired_accuracy = -1,
  strictContainment = FALSE,
  axis_order_authority_compliant = st_axis_order()
)
```

Arguments

paths	the search path to be set; omit if no paths need to be set
enable	logical; set this to enable (TRUE) or disable (FALSE) the proj network search facility
url	character; use this to specify and override the default proj network CDN
source_crs	object of class ‘crs’ or character
target_crs	object of class ‘crs’ or character
authority	character; constrain output pipelines to those of authority
AOI	length four numeric; desired area of interest for the resulting coordinate transformations (west, south, east, north, in degrees). For an area of interest crossing the anti-meridian, west will be greater than east.
Use	one of "NONE", "BOTH", "INTERSECTION", "SMALLEST", indicating how AOI’s of source_crs and target_crs are being used
grid_availability	character; one of "USED" (Grid availability is only used for sorting results. Operations where some grids are missing will be sorted last), "DISCARD" (Completely discard an operation if a required grid is missing), "IGNORED" (Ignore grid availability at all. Results will be presented as if all grids were available.), or "AVAILABLE" (Results will be presented as if grids known to PROJ (that is registered in the grid_alternatives table of its database) were available. Used typically when networking is enabled.)
desired_accuracy	numeric; only return pipelines with at least this accuracy
strictContainment	logical; default FALSE; permit partial matching of the area of interest; if TRUE strictly contain the area of interest. The area of interest is either as given in AOI, or as implied by the source/target coordinate reference systems

`axis_order_authority_compliant`

logical; if FALSE always choose ‘x’ or longitude for the first axis; if TRUE, follow the axis orders given by the coordinate reference systems when constructing the for the first axis; if FALSE, follow the axis orders given by

Value

‘sf_proj_search_paths()‘ returns the search path (possibly after setting it)

‘sf_proj_network‘ when called without arguments returns a logical indicating whether network search of datum grids is enabled, when called with arguments it returns a character vector with the URL of the CDN used (or specified with ‘url‘).

‘sf_proj_pipelines‘ returns a table with candidate coordinate transformation pipelines along with their accuracy; ‘NA‘ accuracy indicates ballpark accuracy.

`rawToHex`

Convert raw vector(s) into hexadecimal character string(s)

Description

Convert raw vector(s) into hexadecimal character string(s)

Usage

`rawToHex(x)`

Arguments

`x` raw vector, or list with raw vectors

`s2`

functions for spherical geometry, using s2 package

Description

functions for spherical geometry, using the s2 package based on the google s2geometry.io library

Usage

```
sf_use_s2(use_s2)
```

```
st_as_s2(x, ...)
```

```
## S3 method for class 'sf'  
st_as_s2(x, ...)
```

```
## S3 method for class 'sfc'  
st_as_s2(x, ..., oriented = FALSE, rebuild = FALSE)
```

Arguments

use_s2	logical; if TRUE, use the s2 spherical geometry package for geographical coordinate operations
x	object of class sf, sfc or sfg
...	passed on
oriented	logical; if FALSE, polygons that cover more than half of the globe are inverted; if TRUE, no reversal takes place and it is assumed that the inside of the polygon is to the left of the polygon's path.
rebuild	logical; call s2_rebuild on the geometry (think of this as a <code>st_make_valid</code> on the sphere)

Details

`st_as_s2` converts an sf POLYGON object into a form readable by s2.

Value

`sf_use_s2` returns the value of this variable before (re)setting it, invisibly if `use_s2` is not missing.

Examples

```
m = rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,-1))
m1 = rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,0), c(-1,-1))
m0 = m[5:1,]
mp = st_multipolygon(list(
  list(m, 0.8 * m0, 0.01 * m1 + 0.9),
  list(0.7*m, 0.6*m0),
  list(0.5*m0),
  list(m+2),
  list(m+4,(.9*m0)+4)
))
sf = st_sfc(mp, mp, crs = 'EPSG:4326')
s2 = st_as_s2(sf)
```

Description

Create sf, which extends data.frame-like objects with a simple feature list column

Usage

```
st_sf(
  ...,
  agr = NA_agr_,
  row.names,
  stringsAsFactors = sf_stringsAsFactors(),
  crs,
  precision,
  sf_column_name = NULL,
  check_ring_dir = FALSE,
  sfc_last = TRUE
)

## S3 method for class 'sf'
x[i, j, ..., drop = FALSE, op = st_intersects]

## S3 method for class 'sf'
print(x, ..., n = getOption("sf_max_print", default = 10))
```

Arguments

...	column elements to be binded into an sf object or a single <code>list</code> or <code>data.frame</code> with such columns; at least one of these columns shall be a geometry list-column of class <code>sfc</code> or be a list-column that can be converted into an <code>sfc</code> by st_as_sfc .
agr	character vector; see details below.
row.names	<code>row.names</code> for the created sf object
stringsAsFactors	logical; see st_read
crs	coordinate reference system, something suitable as input to st_crs
precision	numeric; see st_as_binary
sf_column_name	character; name of the active list-column with simple feature geometries; in case there is more than one and <code>sf_column_name</code> is <code>NULL</code> , the first one is taken.
check_ring_dir	see st_read
sfc_last	logical; if <code>TRUE</code> , <code>sfc</code> columns are always put last, otherwise column order is left unmodified.
x	object of class <code>sf</code>
i	record selection, see [.data.frame
j	variable selection, see [.data.frame
drop	logical, default <code>FALSE</code> ; if <code>TRUE</code> drop the geometry column and return a <code>data.frame</code> , else make the geometry sticky and return a <code>sf</code> object.
op	function; geometrical binary predicate function to apply when <code>i</code> is a simple feature object
n	maximum number of features to print; can be set globally by <code>options(sf_max_print=...)</code>

Details

`agr`, attribute-geometry-relationship, specifies for each non-geometry attribute column how it relates to the geometry, and can have one of following values: "constant", "aggregate", "identity". "constant" is used for attributes that are constant throughout the geometry (e.g. land use), "aggregate" where the attribute is an aggregate value over the geometry (e.g. population density or population count), "identity" when the attributes uniquely identifies the geometry of particular "thing", such as a building ID or a city name. The default value, `NA_agr_`, implies we don't know.

When a single value is provided to `agr`, it is cascaded across all input columns; otherwise, a named vector like `c(feature1='constant', ...)` will set `agr` value to 'constant' for the input column named `feature1`. See `demo(nc)` for a worked example of this.

When confronted with a `data.frame`-like object, `st_sf` will try to find a geometry column of class `sfc`, and otherwise try to convert list-columns when available into a geometry column, using `st_as_sfc`.

`[.sf` will return a `data.frame` or vector if the geometry column (of class `sfc`) is dropped (`drop=TRUE`), an `sfc` object if only the geometry column is selected, and otherwise return an `sf` object; see also `[.data.frame`; for `[.sf ...` arguments are passed to `op`.

Examples

```

g = st_sfc(st_point(1:2))
st_sf(a=3,g)
st_sf(g, a=3)
st_sf(a=3, st_sfc(st_point(1:2))) # better to name it!
# create empty structure with preallocated empty geometries:
nrows <- 10
geometry = st_sfc(lapply(1:nrows, function(x) st_geometrycollection()))
df <- st_sf(id = 1:nrows, geometry = geometry)
g = st_sfc(st_point(1:2), st_point(3:4))
s = st_sf(a=3:4, g)
s[1,]
class(s[1,])
s[,1]
class(s[,1])
s[,2]
class(s[,2])
g = st_sf(a=2:3, g)
pol = st_sfc(st_polygon(list(cbind(c(0,3,3,0,0),c(0,0,3,3,0)))))
h = st_sf(r = 5, pol)
g[h,]
h[g,]

```

Description

These functions are provided for compatibility with older version of `sf`. They may eventually be completely removed.

Usage

```
st_read_db(  
  conn = NULL,  
  table = NULL,  
  query = NULL,  
  geom_column = NULL,  
  EWKB = TRUE,  
  ...  
)
```

Arguments

conn	open database connection
table	table name
query	SQL query to select records; see details
geom_column	deprecated. Geometry column name
EWKB	logical; is the WKB of type EWKB? if missing, defaults to TRUE
...	parameter(s) passed on to st_as_sf

Details

The `geom_column` argument is deprecated. The function will automatically find the geometry type columns. For the RPostgreSQL drivers it will try to cast all the character columns, which can be long for very wide tables.

Details

`st_read_db` now a synonym for [st_read](#)
`st_write_db` now a synonym for [st_write](#)

sfc*Create simple feature geometry list column*

Description

Create simple feature geometry list column, set class, and add coordinate reference system and precision

Usage

```
st_sfc(
```

```

  ...,
  crs = NA_crs_,
  precision = 0,
  check_ring_dir = FALSE,
  dim,
  recompute_bbox = FALSE
)

```

Arguments

...	zero or more simple feature geometries (objects of class <code>sfg</code>), or a single list of such objects; NULL values will get replaced by empty geometries.
crs	coordinate reference system: integer with the EPSG code, or character with proj4string
precision	numeric; see st_as_binary
check_ring_dir	see st_read
dim	character; if this function is called without valid geometries, this argument may carry the right dimension to set empty geometries
recompute_bbox	logical; use TRUE to force recomputation of the bounding box

Details

A simple feature geometry list-column is a list of class c("stc_TYPE", "sfc") which most often contains objects of identical type; in case of a mix of types or an empty set, TYPE is set to the superclass GEOMETRY.

Value

an object of class `sfc`, which is a classed list-column with simple feature geometries.

Examples

```

pt1 = st_point(c(0,1))
pt2 = st_point(c(1,1))
(sfc = st_sfc(pt1, pt2))
d = st_sf(data.frame(a=1:2, geom=sfc))

```

`sf_extSoftVersion` *Provide the external dependencies versions of the libraries linked to sf*

Description

Provide the external dependencies versions of the libraries linked to sf

Usage

```
sf_extSoftVersion()
```

sf_project	<i>directly transform a set of coordinates</i>
------------	--

Description

directly transform a set of coordinates

Usage

```
sf_add_proj_units()

sf_project(
  from = character(0),
  to = character(0),
  pts,
  keep = FALSE,
  warn = TRUE,
  authority_compliant = st_axis_order()
)
```

Arguments

from	character description of source CRS, or object of class <code>crs</code> , or pipeline describing a transformation
to	character description of target CRS, or object of class <code>crs</code>
pts	two-, three- or four-column numeric matrix, or object that can be coerced into a matrix; columns 3 and 4 contain z and t values.
keep	logical value controlling the handling of unprojectable points. If ‘keep’ is ‘TRUE’, then such points will yield ‘Inf’ or ‘-Inf’ in the return value; otherwise an error is reported and nothing is returned.
warn	logical; if TRUE, warn when non-finite values are generated
authority_compliant	logical; TRUE means handle axis order authority compliant (e.g. EPSG:4326 implying x=lat, y=lon), FALSE means use visualisation order (i.e. always x=lon, y=lat)

Details

`sf_add_proj_units` loads the PROJ units ‘link’, ‘us_in’, ‘ind_yd’, ‘ind_ft’, and ‘ind_ch’ into the udunits database, and returns TRUE invisibly on success.

Value

two-column numeric matrix with transformed/converted coordinates, returning invalid values as Inf

Examples

```
sf_add_proj_units()
```

sgbp

Methods for dealing with sparse geometry binary predicate lists

Description

Methods for dealing with sparse geometry binary predicate lists

Usage

```
## S3 method for class 'sgbp'
print(x, ..., n = 10, max_nb = 10)

## S3 method for class 'sgbp'
t(x)

## S3 method for class 'sgbp'
as.matrix(x, ...)

## S3 method for class 'sgbp'
dim(x)
```

Arguments

x	object of class sgbp
...	ignored
n	integer; maximum number of items to print
max_nb	integer; maximum number of neighbours to print for each item

Details

sgbp are sparse matrices, stored as a list with integer vectors holding the ordered TRUE indices of each row. This means that for a dense, $m \times n$ matrix Q and a list L, if $Q[i, j]$ is TRUE then j is an element of $L[[i]]$. Reversed: when k is the value of $L[[i]][j]$, then $Q[i, k]$ is TRUE.

st*Create simple feature from a numeric vector, matrix or list*

Description

Create simple feature from a numeric vector, matrix or list

Usage

```
st_point(x = c(NA_real_, NA_real_), dim = "XYZ")

st_multipoint(x = matrix(numeric(0), 0, 2), dim = "XYZ")

st_linestring(x = matrix(numeric(0), 0, 2), dim = "XYZ")

st_polygon(x = list(), dim = if (length(x)) "XYZ" else "XY")

st_multilinestring(x = list(), dim = if (length(x)) "XYZ" else "XY")

st_multipolygon(x = list(), dim = if (length(x)) "XYZ" else "XY")

st_geometrycollection(x = list(), dims = "XY")

## S3 method for class 'sfg'
print(x, ..., width = 0)

## S3 method for class 'sfg'
head(x, n = 10L, ...)

## S3 method for class 'sfg'
format(x, ..., width = 30)

## S3 method for class 'sfg'
c(..., recursive = FALSE, flatten = TRUE)

## S3 method for class 'sfg'
as.matrix(x, ...)
```

Arguments

x for `st_point`, numeric vector (or one-row-matrix) of length 2, 3 or 4; for `st_linestring` and `st_multipoint`, numeric matrix with points in rows; for `st_polygon` and `st_multilinestring`, list with numeric matrices with points in rows; for `st_multipolygon`, list of lists with numeric matrices; for `st_geometrycollection` list with (non-geometrycollection) simple feature objects

dim	character, indicating dimensions: "XY", "XYZ", "XYM", or "XYZM"; only really needed for three-dimensional points (which can be either XYZ or XYM) or empty geometries; see details
dims	character; specify dimensionality in case of an empty (NULL) geometrycollection, in which case x is the empty list().
...	objects to be pasted together into a single simple feature
width	integer; number of characters to be printed (max 30; 0 means print everything)
n	integer; number of elements to be selected
recursive	logical; ignored
flatten	logical; if TRUE, try to simplify results; if FALSE, return geometrycollection containing all objects

Details

"XYZ" refers to coordinates where the third dimension represents altitude, "XYM" refers to three-dimensional coordinates where the third dimension refers to something else ("M" for measure); checking of the sanity of x may be only partial.

When flatten=TRUE, this method may merge points into a multipoint structure, and may not preserve order, and hence cannot be reverted. When given fish, it returns fish soup.

Value

object of the same nature as x, but with appropriate class attribute set

as.matrix returns the set of points that form a geometry as a single matrix, where each point is a row; use unlist(x, recursive = FALSE) to get sets of matrices.

Examples

```
(p1 = st_point(c(1,2)))
class(p1)
st_bbox(p1)
(p2 = st_point(c(1,2,3)))
class(p2)
(p3 = st_point(c(1,2,3), "XYM"))
pts = matrix(1:10, , 2)
(mp1 = st_multipoint(pts))
pts = matrix(1:15, , 3)
(mp2 = st_multipoint(pts))
(mp3 = st_multipoint(pts, "XYM"))
pts = matrix(1:20, , 4)
(mp4 = st_multipoint(pts))
pts = matrix(1:10, , 2)
(ls1 = st_linestring(pts))
pts = matrix(1:15, , 3)
(ls2 = st_linestring(pts))
(ls3 = st_linestring(pts, "XYM"))
pts = matrix(1:20, , 4)
(ls4 = st_linestring(pts))
```

```

outer = matrix(c(0,0,10,0,10,10,0,10,0,0),ncol=2, byrow=TRUE)
hole1 = matrix(c(1,1,1,2,2,2,2,1,1,1),ncol=2, byrow=TRUE)
hole2 = matrix(c(5,5,5,6,6,6,6,5,5,5),ncol=2, byrow=TRUE)
pts = list(outer, hole1, hole2)
(ml1 = st_multilinestring(pts))
pts3 = lapply(pts, function(x) cbind(x, 0))
(ml2 = st_multilinestring(pts3))
(ml3 = st_multilinestring(pts3, "XYM"))
pts4 = lapply(pts3, function(x) cbind(x, 0))
(ml4 = st_multilinestring(pts4))
outer = matrix(c(0,0,10,0,10,10,0,10,0,0),ncol=2, byrow=TRUE)
hole1 = matrix(c(1,1,1,2,2,2,2,1,1,1),ncol=2, byrow=TRUE)
hole2 = matrix(c(5,5,5,6,6,6,6,5,5,5),ncol=2, byrow=TRUE)
pts = list(outer, hole1, hole2)
(pl1 = st_polygon(pts))
pts3 = lapply(pts, function(x) cbind(x, 0))
(pl2 = st_polygon(pts3))
(pl3 = st_polygon(pts3, "XYM"))
pts4 = lapply(pts3, function(x) cbind(x, 0))
(pl4 = st_polygon(pts4))
pol1 = list(outer, hole1, hole2)
pol2 = list(outer + 12, hole1 + 12)
pol3 = list(outer + 24)
mp = list(pol1,pol2,pol3)
(mp1 = st_multipolygon(mp))
pts3 = lapply(mp, function(x) lapply(x, function(y) cbind(y, 0)))
(mp2 = st_multipolygon(pts3))
(mp3 = st_multipolygon(pts3, "XYM"))
pts4 = lapply(mp2, function(x) lapply(x, function(y) cbind(y, 0)))
(mp4 = st_multipolygon(pts4))
(gc = st_geometrycollection(list(p1, ls1, pl1, mp1)))
st_geometrycollection() # empty geometry
c(st_point(1:2), st_point(5:6))
c(st_point(1:2), st_multipoint(matrix(5:8,2)))
c(st_multipoint(matrix(1:4,2)), st_multipoint(matrix(5:8,2)))
c(st_linestring(matrix(1:6,3)), st_linestring(matrix(11:16,3)))
c(st_multilinestring(list(matrix(1:6,3))), st_multilinestring(list(matrix(11:16,3))))
pl = list(rbind(c(0,0), c(1,0), c(1,1), c(0,1), c(0,0)))
c(st_polygon(pl), st_polygon(pl))
c(st_polygon(pl), st_multipolygon(list(pl)))
c(st_linestring(matrix(1:6,3)), st_point(1:2))
c(st_geometrycollection(list(st_point(1:2), st_linestring(matrix(1:6,3)))), 
  st_geometrycollection(list(st_multilinestring(list(matrix(11:16,3))))))
c(st_geometrycollection(list(st_point(1:2), st_linestring(matrix(1:6,3)))), 
  st_multilinestring(list(matrix(11:16,3))), st_point(5:6),
  st_geometrycollection(list(st_point(10:11)))))


```

Description

functions only exported to be used internally by stars

Usage

```
.get_layout(bb, n, total_size, key.pos, key.length, mfrw = NULL)

.degAxis(side, at, labels, ..., lon, lat, ndiscr, reset)

.image_scale(
  z,
  col,
  breaks = NULL,
  key.pos,
  add.axis = TRUE,
  at = NULL,
  ...,
  axes = FALSE,
  key.length,
  logz = FALSE
)

.image_scale_factor(
  z,
  col,
  key.pos,
  add.axis = TRUE,
  ...,
  axes = FALSE,
  key.width,
  key.length
)
```

Arguments

bb	ignore
n	ignore
total_size	ignore
key.pos	ignore
key.length	ignore
mfrw	length-2 integer vector with number of rows, columns
side	ignore
at	ignore
labels	ignore
...	ignore

lon	ignore
lat	ignore
ndiscr	ignore
reset	ignore
z	ignore
col	ignore
breaks	ignore
add.axis	ignore
axes	ignore
logz	ignore
key.width	ignore

st_agr

get or set relation_to_geometry attribute of an sf object

Description

get or set relation_to_geometry attribute of an sf object

Usage

```
NA_agr_  
st_agr(x, ...)  
st_agr(x) <- value  
st_set_agr(x, value)
```

Arguments

x	object of class sf
...	ignored
value	character, or factor with appropriate levels; if named, names should correspond to the non-geometry list-column columns of x

Format

An object of class `factor` of length 1.

Details

`NA_agr_` is the `agr` object with a missing value.

st_as_binary*Convert sfc object to an WKB object***Description**

Convert sfc object to an WKB object

Usage

```
st_as_binary(x, ...)

## S3 method for class 'sfc'
st_as_binary(
  x,
  ...,
  EWKB = FALSE,
  endian = .Platform$endian,
  pureR = FALSE,
  precision = attr(x, "precision"),
  hex = FALSE
)

## S3 method for class 'sfg'
st_as_binary(
  x,
  ...,
  endian = .Platform$endian,
  EWKB = FALSE,
  pureR = FALSE,
  hex = FALSE,
  srid = 0
)
```

Arguments

<code>x</code>	object to convert
<code>...</code>	ignored
<code>EWKB</code>	logical; use EWKB (PostGIS), or (default) ISO-WKB?
<code>endian</code>	character; either "big" or "little"; default: use that of platform
<code>pureR</code>	logical; use pure R solution, or C++?
<code>precision</code>	numeric; if zero, do not modify; to reduce precision: negative values convert to float (4-byte real); positive values convert to round(x*precision)/precision. See details.
<code>hex</code>	logical; return as (unclassed) hexadecimal encoded character vector?
<code>srid</code>	integer; override srid (can be used when the srid is unavailable locally).

Details

`st_as_binary` is called on sfc objects on their way to the GDAL or GEOS libraries, and hence does rounding (if requested) on the fly before e.g. computing spatial predicates like `st_intersects`. The examples show a round-trip of an sfc to and from binary.

For the precision model used, see also <https://locationtech.github.io/jts/javadoc/org/locationtech/jts/geom/PrecisionModel.html>. There, it is written that: "... to specify 3 decimal places of precision, use a scale factor of 1000. To specify -3 decimal places of precision (i.e. rounding to the nearest 1000), use a scale factor of 0.001.". Note that ALL coordinates, so also Z or M values (if present) are affected.

Examples

```
# examples of setting precision:
st_point(c(1/3, 1/6)) %>% st_sfc(precision = 1000) %>% st_as_binary %>% st_as_sf
st_point(c(1/3, 1/6)) %>% st_sfc(precision = 100) %>% st_as_binary %>% st_as_sf
st_point(1e6 * c(1/3, 1/6)) %>% st_sfc(precision = 0.01) %>% st_as_binary %>% st_as_sf
st_point(1e6 * c(1/3, 1/6)) %>% st_sfc(precision = 0.001) %>% st_as_binary %>% st_as_sf
```

st_as_grob

Convert sf object to a grob*

Description

Convert sf* object to an grid graphics object (grob)

Usage

```
st_as_grob(x, ...)
```

Arguments

x	object to be converted into an object class grob
...	passed on to the xxxGrob function, e.g. gp = gpar(col = 'red')

st_as_sf

Convert foreign object to an sf object

Description

Convert foreign object to an sf object

Usage

```

st_as_sf(x, ...)

## S3 method for class 'data.frame'
st_as_sf(
  x,
  ...,
  agr = NA_agr_,
  coords,
  wkt,
  dim = "XYZ",
  remove = TRUE,
  na.fail = TRUE,
  sf_column_name = NULL
)

## S3 method for class 'sf'
st_as_sf(x, ...)

## S3 method for class 'sfc'
st_as_sf(x, ...)

## S3 method for class 'Spatial'
st_as_sf(x, ...)

## S3 method for class 'map'
st_as_sf(x, ..., fill = TRUE, group = TRUE)

## S3 method for class 'ppp'
st_as_sf(x, ...)

## S3 method for class 'psp'
st_as_sf(x, ...)

## S3 method for class 'lpp'
st_as_sf(x, ...)

## S3 method for class 's2_geography'
st_as_sf(x, ..., crs = st_crs(4326))

```

Arguments

<i>x</i>	object to be converted into an object class sf
...	passed on to st_sf , might included named arguments crs or precision
<i>agr</i>	character vector; see details section of st_sf
<i>coords</i>	in case of point data: names or numbers of the numeric columns holding coordinates

wkt	name or number of the character column that holds WKT encoded geometries
dim	passed on to st_point (only when argument coords is given)
remove	logical; when coords or wkt is given, remove these columns from data.frame?
na.fail	logical; if TRUE, raise an error if coordinates contain missing values
sf_column_name	character; name of the active list-column with simple feature geometries; in case there is more than one and sf_column_name is NULL, the first one is taken.
fill	logical; the value for fill that was used in the call to map .
group	logical; if TRUE, group id labels from map by their prefix before :
crs	coordinate reference system to be assigned; object of class crs

Details

setting argument wkt annihilates the use of argument coords. If x contains a column called "geometry", coords will result in overwriting of this column by the [sfc](#) geometry list-column. Setting wkt will replace this column with the geometry list-column, unless remove is FALSE.

Examples

```

pt1 = st_point(c(0,1))
pt2 = st_point(c(1,1))
st_sfc(pt1, pt2)
d = data.frame(a = 1:2)
d$geom = st_sfc(pt1, pt2)
df = st_as_sf(d)
d$geom = c("POINT(0 0)", "POINT(0 1)")
df = st_as_sf(d, wkt = "geom")
d$geom2 = st_sfc(pt1, pt2)
st_as_sf(d) # should warn
if (require(sp, quietly = TRUE)) {
  data(meuse, package = "sp")
  meuse_sf = st_as_sf(meuse, coords = c("x", "y"), crs = 28992, agr = "constant")
  meuse_sf[1:3,]
  summary(meuse_sf)
}
if (require(sp, quietly = TRUE)) {
  x = rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,-1))
  x1 = 0.1 * x + 0.1
  x2 = 0.1 * x + 0.4
  x3 = 0.1 * x + 0.7
  y = x + 3
  y1 = x1 + 3
  y3 = x3 + 3
  m = matrix(c(3, 0), 5, 2, byrow = TRUE)
  z = x + m
  z1 = x1 + m
  z2 = x2 + m
  z3 = x3 + m
  p1 = Polygons(list( Polygon(x[5:1,]), Polygon(x2), Polygon(x3),
    Polygon(y[5:1,]), Polygon(y1), Polygon(x1), Polygon(y3)), "ID1")
}

```

```

p2 = Polygons(list( Polygon(z[5:1,]), Polygon(z2), Polygon(z3), Polygon(z1)),
  "ID2")
r = SpatialPolygons(list(p1,p2))
a = suppressWarnings(st_as_sf(r))
summary(a)
demo(meuse, ask = FALSE, echo = FALSE)
summary(st_as_sf(meuse))
summary(st_as_sf(meuse.grid))
summary(st_as_sf(meuse.area))
summary(st_as_sf(meuse.riv))
summary(st_as_sf(as(meuse.riv, "SpatialLines")))
pol.grd = as(meuse.grid, "SpatialPolygonsDataFrame")
# summary(st_as_sf(pol.grd))
# summary(st_as_sf(as(pol.grd, "SpatialLinesDataFrame")))
}
if (require(spatstat.geom)) {
  g = st_as_sf(gorillas)
  # select only the points:
  g[st_is(g, "POINT"),]
}
if (require(spatstat.linnet)) {
  data(chicago)
  plot(st_as_sf(chicago)[["label"]])
  plot(st_as_sf(chicago)[-1,"label"])
}

```

st_as_sf*Convert foreign geometry object to an sfc object***Description**

Convert foreign geometry object to an sfc object

Usage

```

## S3 method for class 'pq_geometry'
st_as_sf(
  x,
  ...,
  EWKB = TRUE,
  spatialite = FALSE,
  pureR = FALSE,
  crs = NA_crs_
)

## S3 method for class 'list'
st_as_sf(x, ..., crs = NA_crs_)

## S3 method for class 'blob'

```

```
st_as_sfc(x, ...)

## S3 method for class 'bbox'
st_as_sfc(x, ...)

## S3 method for class 'WKB'
st_as_sfc(
  x,
  ...,
  EWKB = FALSE,
  spatialite = FALSE,
  pureR = FALSE,
  crs = NA_crs_
)

## S3 method for class 'raw'
st_as_sfc(x, ...)

## S3 method for class 'character'
st_as_sfc(x, crs = NA_integer_, ..., GeoJSON = FALSE)

## S3 method for class 'factor'
st_as_sfc(x, ...)

st_as_sfc(x, ...)

## S3 method for class 'SpatialPoints'
st_as_sfc(x, ..., precision = 0)

## S3 method for class 'SpatialPixels'
st_as_sfc(x, ..., precision = 0)

## S3 method for class 'SpatialMultiPoints'
st_as_sfc(x, ..., precision = 0)

## S3 method for class 'SpatialLines'
st_as_sfc(x, ..., precision = 0, forceMulti = FALSE)

## S3 method for class 'SpatialPolygons'
st_as_sfc(x, ..., precision = 0, forceMulti = FALSE)

## S3 method for class 'map'
st_as_sfc(x, ...)

## S3 method for class 's2_geography'
st_as_sfc(
  x,
  ...,
```

```
crs = st_crs(4326),
 endian = match(.Platform$endian, c("big", "little")) - 1L
)
```

Arguments

x	object to convert
...	further arguments
EWKB	logical; if TRUE, parse as EWKB (extended WKB; PostGIS: ST_AsEWKB), otherwise as ISO WKB (PostGIS: ST_AsBinary)
spatialite	logical; if TRUE, WKB is assumed to be in the spatialite dialect, see https://www.gaia-gis.it/gaia-sins/BLOB-Geometry.html ; this is only supported in native endian-ness (i.e., files written on system with the same endian-ness as that on which it is being read).
pureR	logical; if TRUE, use only R code, if FALSE, use compiled (C++) code; use TRUE when the endian-ness of the binary differs from the host machine (.Platform\$endian).
crs	coordinate reference system to be assigned; object of class crs
GeoJSON	logical; if TRUE, try to read geometries from GeoJSON text strings geometry, see <i>st_crs()</i>
precision	precision value; see <i>st_as_binary</i>
forceMulti	logical; if TRUE, force coercion into MULTIPOLYGON or MULTILINE objects, else autodetect
endian	integer; 0 or 1: defaults to the endian of the native machine

Details

When converting from WKB, the object x is either a character vector such as typically obtained from PostGIS (either with leading "0x" or without), or a list with raw vectors representing the features in binary (raw) form.

If x is a character vector, it should be a vector containing well-known-text, or Postgis EWKT or GeoJSON representations of a single geometry for each vector element.

If x is a factor, it is converted to character.

Examples

```
wkb = structure(list("01010000204071000000000000801A064100000000AC5C1441"), class = "WKB")
st_as_sf(wkb, EWKB = TRUE)
wkb = structure(list("0x01010000204071000000000000801A064100000000AC5C1441"), class = "WKB")
st_as_sf(wkb, EWKB = TRUE)
st_as_sf(st_as_binary(st_sfc(st_point(0:1)))[[1]], crs = 4326)
st_as_sf("SRID=3978;LINESTRING(1663106 -105415,1664320 -104617)")
```

st_as_text	<i>Return Well-known Text representation of simple feature geometry or coordinate reference system</i>
------------	--

Description

Return Well-known Text representation of simple feature geometry or coordinate reference system

Usage

```
## S3 method for class 'crs'  
st_as_text(x, ..., projjson = FALSE, pretty = FALSE)  
  
st_as_text(x, ...)  
  
## S3 method for class 'sfg'  
st_as_text(x, ...)  
  
## S3 method for class 'sfc'  
st_as_text(x, ..., EWKT = FALSE)
```

Arguments

- | | |
|----------|---|
| x | object of class sfg, sfc or crs |
| ... | modifiers; in particular digits can be passed to control the number of digits used |
| projjson | logical; if TRUE, return projjson form (requires GDAL 3.1 and PROJ 6.2), else return well-known-text form |
| pretty | logical; if TRUE, print human-readable well-known-text representation of a coordinate reference system |
| EWKT | logical; if TRUE, print SRID=xxx; before the WKT string if epsg is available |

Details

The returned WKT representation of simple feature geometry conforms to the [simple features access](#) specification and extensions (known as EWKT, supported by PostGIS and other simple features implementations for addition of a SRID to a WKT string).

Examples

```
st_as_text(st_point(1:2))  
st_as_text(st_sfc(st_point(c(-90,40)), crs = 4326), EWKT = TRUE)
```

<i>st_bbox</i>	<i>Return bounding of a simple feature or simple feature set</i>
----------------	--

Description

Return bounding of a simple feature or simple feature set

Usage

```
## S3 method for class 'bbox'  
is.na(x)  
  
st_bbox(obj, ...)  
  
## S3 method for class 'POINT'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTIPOINT'  
st_bbox(obj, ...)  
  
## S3 method for class 'LINESTRING'  
st_bbox(obj, ...)  
  
## S3 method for class 'POLYGON'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTILINESTRING'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTIPOLYGON'  
st_bbox(obj, ...)  
  
## S3 method for class 'GEOMETRYCOLLECTION'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTISURFACE'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTICURVE'  
st_bbox(obj, ...)  
  
## S3 method for class 'CURVEPOLYGON'  
st_bbox(obj, ...)  
  
## S3 method for class 'COMPOUNDCURVE'  
st_bbox(obj, ...)
```

```
## S3 method for class 'POLYHEDRALSURFACE'  
st_bbox(obj, ...)  
  
## S3 method for class 'TIN'  
st_bbox(obj, ...)  
  
## S3 method for class 'TRIANGLE'  
st_bbox(obj, ...)  
  
## S3 method for class 'CIRCULARSTRING'  
st_bbox(obj, ...)  
  
## S3 method for class 'sfc'  
st_bbox(obj, ...)  
  
## S3 method for class 'sf'  
st_bbox(obj, ...)  
  
## S3 method for class 'Spatial'  
st_bbox(obj, ...)  
  
## S3 method for class 'Raster'  
st_bbox(obj, ...)  
  
## S3 method for class 'Extent'  
st_bbox(obj, ..., crs = NA_crs_)  
  
## S3 method for class 'numeric'  
st_bbox(obj, ..., crs = NA_crs_)  
  
NA_bbox_  
  
## S3 method for class 'bbox'  
format(x, ...)
```

Arguments

x	object of class bbox
obj	object to compute the bounding box from
...	for format.bbox, passed on to format to format individual numbers
crs	object of class crs , or argument to st_crs , specifying the CRS of this bounding box.

Format

An object of class bbox of length 4.

Details

`NA_bbox_` represents the missing value for a bbox object

Value

a numeric vector of length four, with `xmin`, `ymin`, `xmax` and `ymax` values; if `obj` is of class `sf`, `sfc`, `Spatial` or `Raster`, the object returned has a class `bbox`, an attribute `crs` and a method to print the `bbox` and an `st_crs` method to retrieve the coordinate reference system corresponding to `obj` (and hence the bounding box). `st_as_sfc` has a methods for `bbox` objects to generate a polygon around the four bounding box points.

Examples

```
a = st_sf(a = 1:2, geom = st_sfc(st_point(0:1), st_point(1:2)), crs = 4326)
st_bbox(a)
st_as_sfc(st_bbox(a))
st_bbox(c(xmin = 16.1, xmax = 16.6, ymax = 48.6, ymin = 47.9), crs = st_crs(4326))
```

`st_cast`

Cast geometry to another type: either simplify, or cast explicitly

Description

Cast geometry to another type: either simplify, or cast explicitly

Usage

```
## S3 method for class 'MULTIPOLYGON'
st_cast(x, to, ...)

## S3 method for class 'MULTILINESTRING'
st_cast(x, to, ...)

## S3 method for class 'MULTIPOINT'
st_cast(x, to, ...)

## S3 method for class 'POLYGON'
st_cast(x, to, ...)

## S3 method for class 'LINESTRING'
st_cast(x, to, ...)

## S3 method for class 'POINT'
st_cast(x, to, ...)

## S3 method for class 'GEOMETRYCOLLECTION'
st_cast(x, to, ...)
```

```

## S3 method for class 'CIRCULARSTRING'
st_cast(x, to, ...)

## S3 method for class 'MULTISURFACE'
st_cast(x, to, ...)

## S3 method for class 'COMPOUNDCURVE'
st_cast(x, to, ...)

## S3 method for class 'MULTICURVE'
st_cast(x, to, ...)

## S3 method for class 'CURVE'
st_cast(x, to, ...)

st_cast(x, to, ...)

## S3 method for class 'sfc'
st_cast(x, to, ..., ids = seq_along(x), group_or_split = TRUE)

## S3 method for class 'sf'
st_cast(x, to, ..., warn = TRUE, do_split = TRUE)

## S3 method for class 'sfc_CIRCULARSTRING'
st_cast(x, to, ...)

```

Arguments

x	object of class sfg, sfc or sf
to	character; target type, if missing, simplification is tried; when x is of type sfg (i.e., a single geometry) then to needs to be specified.
...	ignored
ids	integer vector, denoting how geometries should be grouped (default: no grouping)
group_or_split	logical; if TRUE, group or split geometries; if FALSE, carry out a 1-1 per-geometry conversion.
warn	logical; if TRUE, warn if attributes are assigned to sub-geometries
do_split	logical; if TRUE, allow splitting of geometries in sub-geometries

Details

When converting a GEOMETRYCOLLECTION to COMPOUNDCURVE, MULTISURFACE or CURVEPOLYGON, the user is responsible for the validity of the resulting object: no checks are being carried out by the software.

the st_cast method for sf objects can only split geometries, e.g. cast MULTIPOINT into multiple POINT features. In case of splitting, attributes are repeated and a warning is issued when non-

constant attributes are assigned to sub-geometries. To merge feature geometries and attribute values, use [aggregate](#) or [summarise](#).

Value

object of class `to` if successful, or unmodified object if unsuccessful. If information gets lost while type casting, a warning is raised.

In case `to` is missing, `st_cast.sfc` will coerce combinations of "POINT" and "MULTIPOINT", "LINESTRING" and "MULTILINESTRING", "POLYGON" and "MULTIPOLYGON" into their "MULTI..." form, or in case all geometries are "GEOMETRYCOLLECTION" will return a list of all the contents of the "GEOMETRYCOLLECTION" objects, or else do nothing. In case `to` is specified, if `to` is "GEOMETRY", geometries are not converted, else, `st_cast` will try to coerce all elements into `to`; `ids` may be specified to group e.g. "POINT" objects into a "MULTIPOINT", if not specified no grouping takes place. If e.g. a "sfc_MULTIPOINT" is cast to a "sfc_POINT", the objects are split, so no information gets lost, unless `group_or_split` is FALSE.

Examples

```
# example(st_read)
nc = st_read(system.file("shape/nc.shp", package="sf"))
mpl <- nc$geometry[[4]]
#st_cast(x) ## error 'argument "to" is missing, with no default'
cast_all <- function(xg) {
  lapply(c("MULTIPOLYGON", "MULTILINESTRING", "MULTIPOINT", "POLYGON", "LINESTRING", "POINT"),
         function(x) st_cast(xg, x))
}
st_sfc(cast_all(mpl))
## no closing coordinates should remain for multipoint
any(duplicated(unclass(st_cast(mpl, "MULTIPOINT")))) ## should be FALSE
## number of duplicated coordinates in the linestrings should equal the number of polygon rings
## (... in this case, won't always be true)
sum(duplicated(do.call(rbind, unclass(st_cast(mpl, "MULTILINESTRING")))))
  ) == sum(unlist(lapply(mpl, length))) ## should be TRUE

p1 <- structure(c(0, 1, 3, 2, 1, 0, 0, 0, 2, 4, 4, 0), .Dim = c(6L, 2L))
p2 <- structure(c(1, 1, 2, 1, 1, 2, 2, 1), .Dim = c(4L, 2L))
st_polygon(list(p1, p2))
mls <- st_cast(nc$geometry[[4]], "MULTILINESTRING")
st_sfc(cast_all(mls))
mpt <- st_cast(nc$geometry[[4]], "MULTIPOINT")
st_sfc(cast_all(mpt))
pl <- st_cast(nc$geometry[[4]], "POLYGON")
st_sfc(cast_all(pl))
ls <- st_cast(nc$geometry[[4]], "LINESTRING")
st_sfc(cast_all(ls))
pt <- st_cast(nc$geometry[[4]], "POINT")
## st_sfc(cast_all(pt)) ## Error: cannot create MULTIPOLYGON from POINT
st_sfc(lapply(c("POINT", "MULTIPOINT"), function(x) st_cast(pt, x)))
s = st_multipoint(rbind(c(1,0)))
st_cast(s, "POINT")
```

`st_cast_sfc_default` *Coerce geometry to MULTI* geometry*

Description

Mixes of POINTS and MULTIPOLYPOINTS, LINESTRING and MULTILINESTRING, POLYGON and MULTIPOLYGON are returned as MULTIPOLYPOINTS, MULTILINESTRINGS and MULTIPOLYGONS respectively

Usage

```
st_cast_sfc_default(x)
```

Arguments

x	list of geometries or simple features
---	---------------------------------------

Details

Geometries that are already MULTI* are left unchanged. Features that can't be cast to a single MULTI* geometry are return as a GEOMETRYCOLLECTION

`st_collection_extract` *Given an object with geometries of type GEOMETRY or GEOMETRYCOLLECTION, return an object consisting only of elements of the specified type.*

Description

Similar to ST_CollectionExtract in PostGIS. If there are no sub-geometries of the specified type, an empty geometry is returned.

Usage

```
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)

## S3 method for class 'sfg'
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)
```

```
## S3 method for class 'sfc'
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)

## S3 method for class 'sf'
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)
```

Arguments

<code>x</code>	an object of class <code>sf</code> , <code>sfc</code> or <code>sfg</code> that has mixed geometry (GEOMETRY or GEOMETRYCOLLECTION).
<code>type</code>	character; one of "POLYGON", "POINT", "LINESTRING"
<code>warn</code>	logical; if TRUE, warn if attributes are assigned to sub-geometries when casting (see <code>st_cast</code>)

Value

An object having the same class as `x`, with geometries consisting only of elements of the specified type. For `sfg` objects, an `sfg` object is returned if there is only one geometry of the specified type, otherwise the geometries are combined into an `sfc` object of the relevant type. If any subgeometries in the input are MULTI, then all of the subgeometries in the output will be MULTI.

Examples

```
pt <- st_point(c(1, 0))
ls <- st_linestring(matrix(c(4, 3, 0, 0), ncol = 2))
poly1 <- st_polygon(list(matrix(c(5.5, 7, 7, 6, 5.5, 0, 0, -0.5, -0.5, 0), ncol = 2)))
poly2 <- st_polygon(list(matrix(c(6.6, 8, 8, 7, 6.6, 1, 1, 1.5, 1.5, 1), ncol = 2)))
multipoly <- st_multipolygon(list(poly1, poly2))

i <- st_geometrycollection(list(pt, ls, poly1, poly2))
j <- st_geometrycollection(list(pt, ls, poly1, poly2, multipoly))

st_collection_extract(i, "POLYGON")
st_collection_extract(i, "POINT")
st_collection_extract(i, "LINESTRING")

## A GEOMETRYCOLLECTION
aa <- rbind(st_sf(a=1, geom = st_sfc(i)),
st_sf(a=2, geom = st_sfc(j)))

## With sf objects
st_collection_extract(aa, "POLYGON")
```

```

st_collection_extract(aa, "LINESTRING")
st_collection_extract(aa, "POINT")

## With sfc objects
st_collection_extract(st_geometry(aa), "POLYGON")
st_collection_extract(st_geometry(aa), "LINESTRING")
st_collection_extract(st_geometry(aa), "POINT")

## A GEOMETRY of single types
bb <- rbind(
  st_sf(a = 1, geom = st_sfc(pt)),
  st_sf(a = 2, geom = st_sfc(ls)),
  st_sf(a = 3, geom = st_sfc(poly1)),
  st_sf(a = 4, geom = st_sfc(multipoly))
)

st_collection_extract(bb, "POLYGON")

## A GEOMETRY of mixed single types and GEOMETRYCOLLECTIONS
cc <- rbind(aa, bb)

st_collection_extract(cc, "POLYGON")

```

st_coordinates*retrieve coordinates in matrix form***Description**

retrieve coordinates in matrix form

Usage

st_coordinates(x, ...)

Arguments

x	object of class sf, sfc or sfg
...	ignored

Value

matrix with coordinates (X, Y, possibly Z and/or M) in rows, possibly followed by integer indicators L1,...,L3 that point out to which structure the coordinate belongs; for POINT this is absent (each coordinate is a feature), for LINESTRING L1 refers to the feature, for MULTIPOLYGON L1 refers to the main ring or holes, L2 to the ring id in the MULTIPOLYGON, and L3 to the simple feature.

st_crop*crop an sf object to a specific rectangle***Description**

crop an sf object to a specific rectangle

Usage

```
st_crop(x, y, ...)
## S3 method for class 'sfc'
st_crop(x, y, ..., xmin, ymin, xmax, ymax)

## S3 method for class 'sf'
st_crop(x, y, ...)
```

Arguments

<code>x</code>	object of class <code>sf</code> or <code>sfc</code>
<code>y</code>	numeric vector with named elements <code>xmin</code> , <code>ymin</code> , <code>xmax</code> and <code>ymax</code> , or object of class <code>bbox</code> , or object for which there is an <code>st_bbox</code> method to convert it to a <code>bbox</code> object
<code>...</code>	ignored
<code>xmin</code>	minimum x extent of cropping area
<code>ymin</code>	minimum y extent of cropping area
<code>xmax</code>	maximum x extent of cropping area
<code>ymax</code>	maximum y extent of cropping area

Details

setting arguments `xmin`, `ymin`, `xmax` and `ymax` implies that argument `y` gets ignored.

Examples

```
box = c(xmin = 0, ymin = 0, xmax = 1, ymax = 1)
pol = st_sfc(st_buffer(st_point(c(.5, .5)), .6))
pol_sf = st_sf(a=1, geom=pol)
plot(st_crop(pol, box))
plot(st_crop(pol_sf, st_bbox(box)))
# alternative:
plot(st_crop(pol, xmin = 0, ymin = 0, xmax = 1, ymax = 1))
```

st_crs	<i>Retrieve coordinate reference system from object</i>
--------	---

Description

Retrieve coordinate reference system from sf or sfc object
Set or replace retrieve coordinate reference system from object

Usage

```
st_crs(x, ...)

## S3 method for class 'sf'
st_crs(x, ...)

## S3 method for class 'numeric'
st_crs(x, ...)

## S3 method for class 'character'
st_crs(x, ...)

## S3 method for class 'sfc'
st_crs(x, ..., parameters = FALSE)

## S3 method for class 'bbox'
st_crs(x, ...)

## S3 method for class 'CRS'
st_crs(x, ...)

## S3 method for class 'crs'
st_crs(x, ...)

st_crs(x) <- value

## S3 replacement method for class 'sf'
st_crs(x) <- value

## S3 replacement method for class 'sfc'
st_crs(x) <- value

st_set_crs(x, value)

NA_crs_
```

```
## S3 method for class 'crs'
```

```

is.na(x)

## S3 method for class 'crs'
x$name

## S3 method for class 'crs'
format(x, ...)

st_axis_order(authority_compliant = logical(0))

```

Arguments

x	numeric, character, or object of class sf or sfc
...	ignored
parameters	logical; FALSE by default; if TRUE return a list of coordinate reference system parameters, with named elements <code>SemiMajor</code> , <code>InvFlattening</code> , <code>units_gdal</code> , <code>IsVertical</code> , <code>WktPretty</code> , and <code>Wkt</code>
value	one of (i) character: a string accepted by GDAL, (ii) integer, a valid EPSG value (numeric), or (iii) an object of class crs .
name	element name
authority_compliant	logical; specify whether axis order should be handled compliant to the authority; if omitted, the current value is printed.

Format

An object of class **crs** of length 2.

Details

The *crs functions create, get, set or replace the `crs` attribute of a simple feature geometry list-column. This attribute is of class **crs**, and is a list consisting of `input` (user input, e.g. "EPSG:4326" or "WGS84" or a proj4string), and `wkt`, an automatically generated wkt2 representation of the crs. If `x` is identical to the `wkt` representation, and the CRS has a name, this name is used for the `input` field.

Comparison of two objects of class **crs** uses the GDAL function `OGRSpatialReference::IsSame`.

In case a coordinate reference system is replaced, no transformation takes place and a warning is raised to stress this.

`NA_crs_` is the `crs` object with missing values for `input` and `wkt`.

the `$` method for `crs` objects retrieves named elements using the GDAL interface; named elements include "SemiMajor", "SemiMinor", "InvFlattening", "IsGeographic", "units_gdal", "IsVertical", "WktPretty", "Wkt", "Name", "proj4string", "epsg", "yx" and "ud_unit" (this may be subject to changes in future GDAL versions).

`format.crs` returns NA if the crs is missing valued, or else the name of a crs if it is different from "unknown", or else the user input if it was set, or else its "proj4string" representation;

`st_axis_order` can be used to get and set the axis order: TRUE indicates axes order according to the authority (e.g. EPSG:4326 defining coordinates to be latitude,longitude pairs), FALSE indicates the usual GIS (display) order (longitude,latitude). This can be useful when data are read, or have to be written, with coordinates in authority compliant order. The return value is the current state of this (FALSE, by default).

Value

If `x` is numeric, return `crs` object for EPSG:`x`; if `x` is character, return `crs` object for `x`; if `x` is of class `sf` or `sfc`, return its `crs` object.

Object of class `crs`, which is a list with elements `input` (length-1 character) and `wkt` (length-1 character). Elements may be NA valued; if all elements are NA the CRS is missing valued, and coordinates are assumed to relate to an arbitrary Cartesian coordinate system.

`st_axis_order` returns the (logical) current value if called without argument, or (invisibly) the previous value if it is being set.

Examples

```
sfc = st_sfc(st_point(c(0,0)), st_point(c(1,1)))
sf = st_sf(a = 1:2, geom = sfc)
st_crs(sf) = 4326
st_geometry(sf)
sfc = st_sfc(st_point(c(0,0)), st_point(c(1,1)))
st_crs(sfc) = 4326
sfc
sfc = st_sfc(st_point(c(0,0)), st_point(c(1,1)))
sfc %>% st_set_crs(4326) %>% st_transform(3857)
st_crs("EPSG:3857")$input
st_crs(3857)$proj4string
st_crs(3857)$b      # numeric
st_crs(3857)$units # character
pt = st_sfc(st_point(c(0, 60)), crs = 4326)
# st_axis_order() only has effect in GDAL >= 2.5.0:
st_axis_order() # query default: FALSE means interpret pt as (longitude latitude)
st_transform(pt, 3857)[[1]]
old_value = FALSE
if (sf_extSoftVersion()["GDAL"] >= "2.5.0")
  (old_value = st_axis_order(TRUE))
# now interpret pt as (latitude longitude), as EPSG:4326 prescribes:
st_axis_order() # query current value
st_transform(pt, 3857)[[1]]
st_axis_order(old_value) # set back to old value
```

Description

Get a list of the available GDAL drivers

Usage

```
st_drivers(what = "vector")
```

Arguments

what character: "vector" or "raster", anything else will return all drivers.

Details

The drivers available will depend on the installation of GDAL/OGR, and can vary; the `st_drivers()` function shows all the drivers that are readable, and which may be written. The field `vsi` refers to the driver's capability to read/create datasets through the VSI*L API. [See GDAL website for additional details on driver support](#).

Value

A `data.frame` with driver metadata.

Examples

```
st_drivers()
```

st_geometry

Get, set, replace or rename geometry from an sf object

Description

Get, set, replace or rename geometry from an `sf` object

Usage

```
## S3 method for class 'sfc'
st_geometry(obj, ...)

st_geometry(obj, ...)

## S3 method for class 'sf'
st_geometry(obj, ...)

## S3 method for class 'sfc'
st_geometry(obj, ...)

## S3 method for class 'sfg'
st_geometry(obj, ...)

st_geometry(x) <- value
```

```

st_set_geometry(x, value)

st_drop_geometry(x, ...)

## S3 method for class 'sf'
st_drop_geometry(x, ...)

## Default S3 method:
st_drop_geometry(x, ...)

```

Arguments

obj	object of class <code>sf</code> or <code>sfc</code>
...	ignored
x	object of class <code>data.frame</code> or <code>sf</code>
value	object of class <code>sfc</code> , or character to set, replace, or rename the geometry of x

Details

when applied to a `data.frame` and when `value` is an object of class `sfc`, `st_set_geometry` and `st_geometry<-` will first check for the existence of an attribute `sf_column` and overwrite that, or else look for list-columns of class `sfc` and overwrite the first of that, or else write the geometry list-column to a column named `geometry`. In case `value` is character and `x` is of class `sf`, the "active" geometry column is set to `x[[value]]`.

the replacement function applied to `sf` objects will overwrite the geometry list-column, if `value` is `NULL`, it will remove it and coerce `x` to a `data.frame`.

if `x` is of class `sf`, `st_drop_geometry` drops the geometry of its argument, and reclasses it accordingly; otherwise it does nothing.

Value

`st_geometry` returns an object of class `sfc`, a list-column with geometries

`st_geometry` returns an object of class `sfc`. Assigning geometry to a `data.frame` creates an `sf` object, assigning it to an `sf` object replaces the geometry list-column.

Examples

```

df = data.frame(a = 1:2)
sfc = st_sfc(st_point(c(3,4)), st_point(c(10,11)))
st_geometry(sfc)
st_geometry(df) <- sfc
class(df)
st_geometry(df)
st_geometry(df) <- sfc # replaces
st_geometry(df) <- NULL # remove geometry, coerce to data.frame
sf <- st_set_geometry(df, sfc) # set geometry, return sf
st_set_geometry(sf, NULL) # remove geometry, coerce to data.frame

```

st_geometry_type *Return geometry type of an object*

Description

Return geometry type of an object, as a factor

Usage

```
st_geometry_type(x, by_geometries = TRUE)
```

Arguments

<code>x</code>	object of class <code>sf</code> or <code>sfc</code>
<code>by_geometries</code>	logical; if TRUE, return geometry type of each geometry, else return geometry type of the set

Value

a factor with the geometry type of each simple feature geometry in `x`, or that of the whole set

st_graticule *Compute graticules and their parameters*

Description

Compute graticules and their parameters

Usage

```
st_graticule(
  x = c(-180, -90, 180, 90),
  crs = st_crs(x),
  datum = st_crs(4326),
  ...,
  lon = NULL,
  lat = NULL,
  ndiscr = 100,
  margin = 0.001
)
```

Arguments

x	object of class sf, sfc or sfg or numeric vector with bounding box given as (minx, miny, maxx, maxy).
crs	object of class crs, with the display coordinate reference system
datum	either an object of class crs with the coordinate reference system for the graticules, or NULL in which case a grid in the coordinate system of x is drawn, or NA, in which case an empty sf object is returned.
...	ignored
lon	numeric; degrees east for the meridians
lat	numeric; degrees north for the parallels
ndiscr	integer; number of points to discretize a parallel or meridian
margin	numeric; small number to trim a longlat bounding box that touches or crosses +/-180 long or +/-90 latitude.

Value

an object of class sf with additional attributes describing the type (E: meridian, N: parallel) degree value, label, start and end coordinates and angle; see example.

Use of graticules

In cartographic visualization, the use of graticules is not advised, unless the graphical output will be used for measurement or navigation, or the direction of North is important for the interpretation of the content, or the content is intended to display distortions and artifacts created by projection. Unnecessary use of graticules only adds visual clutter but little relevant information. Use of coastlines, administrative boundaries or place names permits most viewers of the output to orient themselves better than a graticule.

Examples

```
library(sf)
if (require(maps, quietly = TRUE)) {

  usa = st_as_sf(map('usa', plot = FALSE, fill = TRUE))
  laea = st_crs("+proj=laea +lat_0=30 +lon_0=-95") # Lambert equal area
  usa <- st_transform(usa, laea)

  bb = st_bbox(usa)
  bbox = st_linestring(rbind(c( bb[1],bb[2]),c( bb[3],bb[2]),
    c( bb[3],bb[4]),c( bb[1],bb[4]),c( bb[1],bb[2])))

  g = st_graticule(usa)
  plot(usa, xlim = 1.2 * c(-2450853.4, 2186391.9))
  plot(g[1], add = TRUE, col = 'grey')
  plot(bbox, add = TRUE)
  points(g$x_start, g$y_start, col = 'red')
  points(g$x_end, g$y_end, col = 'blue')
```

```

invisible(lapply(seq_len(nrow(g)), function(i) {
  if (g$type[i] == "N" && g$x_start[i] - min(g$x_start) < 1000)
    text(g[i,"x_start"], g[i,"y_start"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_start[i], pos = 2, cex = .7)
  if (g$type[i] == "E" && g$y_start[i] - min(g$y_start) < 1000)
    text(g[i,"x_start"], g[i,"y_start"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_start[i] - 90, pos = 1, cex = .7)
  if (g$type[i] == "N" && g$x_end[i] - max(g$x_end) > -1000)
    text(g[i,"x_end"], g[i,"y_end"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_end[i], pos = 4, cex = .7)
  if (g$type[i] == "E" && g$y_end[i] - max(g$y_end) > -1000)
    text(g[i,"x_end"], g[i,"y_end"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_end[i] - 90, pos = 3, cex = .7)
  }))
  plot(usa, graticule = st_crs(4326), axes = TRUE, lon = seq(-60,-130,by=-10))
})

```

st_is*test equality between the geometry type and a class or set of classes***Description**

test equality between the geometry type and a class or set of classes

Usage

```
st_is(x, type)
```

Arguments

x	object of class sf, sfc or sfg
type	character; class, or set of classes, to test against

Examples

```

st_is(st_point(0:1), "POINT")
sfc = st_sfc(st_point(0:1), st_linestring(matrix(1:6,,2)))
st_is(sfc, "POINT")
st_is(sfc, "POLYGON")
st_is(sfc, "LINESTRING")
st_is(st_sf(a = 1:2, sfc), "LINESTRING")
st_is(sfc, c("POINT", "LINESTRING"))

```

st_is_longlat	<i>Assert whether simple feature coordinates are longlat degrees</i>
---------------	--

Description

Assert whether simple feature coordinates are longlat degrees

Usage

```
st_is_longlat(x)
```

Arguments

- x object of class [sf](#) or [sfc](#), or otherwise an object of a class that has an [st_crs](#) method returning a [crs](#) object

Value

TRUE if x has geographic coordinates, FALSE if it has projected coordinates, or NA if `is.na(st_crs(x))`.

st_jitter	<i>jitter geometries</i>
-----------	--------------------------

Description

jitter geometries

Usage

```
st_jitter(x, amount, factor = 0.002)
```

Arguments

- x object of class [sf](#) or [sfc](#)
amount numeric; amount of jittering applied; if missing, the amount is set to factor * the bounding box diagonal; units of coordinates.
factor numeric; fractional amount of jittering to be applied

Details

jitters coordinates with an amount such that `runif(1, -amount, amount)` is added to the coordinates. x- and y-coordinates are jittered independently but all coordinates of a single geometry are jittered with the same amount, meaning that the geometry shape does not change. For longlat data, a latitude correction is made such that jittering in East and North directions are identical in distance in the center of the bounding box of x.

Examples

```
nc = st_read(system.file("gpkg/nc.gpkg", package="sf"))
pts = st_centroid(st_geometry(nc))
plot(pts)
plot(st_jitter(pts, .05), add = TRUE, col = 'red')
plot(st_geometry(nc))
plot(st_jitter(st_geometry(nc), factor = .01), add = TRUE, col = '#ff8888')
```

st_join

spatial join, spatial filter

Description

spatial join, spatial filter

Usage

```
st_join(x, y, join, ...)

## S3 method for class 'sf'
st_join(
  x,
  y,
  join = st_intersects,
  ...,
  suffix = c(".x", ".y"),
  left = TRUE,
  largest = FALSE
)

st_filter(x, y, ...)

## S3 method for class 'sf'
st_filter(x, y, ..., .predicate = st_intersects)
```

Arguments

x	object of class sf
y	object of class sf
join	geometry predicate function with the same profile as st_intersects ; see details
...	for st_join : arguments passed on to the join function or to st_intersection when largest is TRUE ; for st_filter arguments passed on to the .predicate function, e.g. prepared , or a pattern for st_relate
suffix	length 2 character vector; see merge
left	logical; if TRUE return the left join, otherwise an inner join; see details. see also left_join

largest	logical; if TRUE, return x features augmented with the fields of y that have the largest overlap with each of the features of x; see https://github.com/r-spatial/sf/issues/578
.predicate	geometry predicate function with the same profile as st_intersects ; see details

Details

alternative values for argument join are:

- [st_contains_properly](#)
- [st_contains](#)
- [st_covered_by](#)
- [st_covers](#)
- [st_crosses](#)
- [st_disjoint](#)
- [st_equals_exact](#)
- [st_equals](#)
- [st_is_within_distance](#)
- [st_nearest_feature](#)
- [st_overlaps](#)
- [st_touches](#)
- [st_within](#)
- any user-defined function of the same profile as the above

A left join returns all records of the x object with y fields for non-matched records filled with NA values; an inner join returns only records that spatially match.

To replicate the results of `st_within(x, y)` you will need to use `st_join(x, y, join = "st_within", left = FALSE)`.

Value

an object of class sf, joined based on geometry

Examples

```
a = st_sf(a = 1:3,
  geom = st_sfc(st_point(c(1,1)), st_point(c(2,2)), st_point(c(3,3))))
b = st_sf(a = 11:14,
  geom = st_sfc(st_point(c(10,10)), st_point(c(2,2)), st_point(c(2,2)), st_point(c(3,3))))
st_join(a, b)
st_join(a, b, left = FALSE)
# two ways to aggregate y's attribute values outcome over x's geometries:
st_join(a, b) %>% aggregate(list(.a.x), mean)
if (require(dplyr, quietly = TRUE)) {
  st_join(a, b) %>% group_by(a.x) %>% summarise(mean(a.y))
}
# example of largest = TRUE:
```

```

nc <- st_transform(st_read(system.file("shape/nc.shp", package="sf")), 2264)
gr = st_sf(
  label = apply(expand.grid(1:10, LETTERS[10:1])[2:1], 1, paste0, collapse = " "),
  geom = st_make_grid(st_as_sfc(st_bbox(nc))))
gr$col = sf.colors(10, categorical = TRUE, alpha = .3)
# cut, to check, NA's work out:
gr = gr[-(1:30),]
nc_j <- st_join(nc, gr, largest = TRUE)
# the two datasets:
opar = par(mfrow = c(2,1), mar = rep(0,4))
plot(st_geometry(nc_j))
plot(st_geometry(gr), add = TRUE, col = gr$col)
text(st_coordinates(st_centroid(gr)), labels = gr$label)
# the joined dataset:
plot(st_geometry(nc_j), border = 'black', col = nc_j$col)
text(st_coordinates(st_centroid(nc_j)), labels = nc_j$label, cex = .8)
plot(st_geometry(gr), border = 'green', add = TRUE)
par(opar)

```

st_layers*Return properties of layers in a datasource***Description**

Return properties of layers in a datasource

Usage

```
st_layers(dsn, options = character(0), do_count = FALSE)
```

Arguments

dsn	data source name (interpretation varies by driver - for some drivers, dsn is a file name, but may also be a folder, or contain the name and access credentials of a database)
options	character; driver dependent dataset open options, multiple options supported.
do_count	logical; if TRUE, count the features by reading them, even if their count is not reported by the driver

Value

list object of class **sf_layers** with elements

name name of the layer

geomtype list with for each layer the geometry types

features number of features (if reported; see **do_count**)

fields number of fields

crs list with for each layer the crs object

<code>st_line_sample</code>	<i>Sample points on a linear geometry</i>
-----------------------------	---

Description

Sample points on a linear geometry

Usage

```
st_line_sample(x, n, density, type = "regular", sample = NULL)
```

Arguments

<code>x</code>	object of class <code>sf</code> , <code>sfc</code> or <code>sfg</code>
<code>n</code>	integer; number of points to choose per geometry; if missing, <code>n</code> will be computed as <code>round(density * st_length(geom))</code> .
<code>density</code>	numeric; density (points per distance unit) of the sampling, possibly a vector of length equal to the number of features (otherwise recycled); <code>density</code> may be of class units.
<code>type</code>	character; indicate the sampling type, either "regular" or "random"
<code>sample</code>	numeric; a vector of numbers between 0 and 1 indicating the points to sample - if defined <code>sample</code> overrules <code>n</code> , <code>density</code> and <code>type</code> .

Examples

```
ls = st_sfc(st_linestring(rbind(c(0,0),c(0,1))),
            st_linestring(rbind(c(0,0),c(10,0))))
st_line_sample(ls, density = 1)
ls = st_sfc(st_linestring(rbind(c(0,0),c(0,1))),
            st_linestring(rbind(c(0,0),c(.1,0))), crs = 4326)
try(st_line_sample(ls, density = 1/1000)) # error
st_line_sample(st_transform(ls, 3857), n = 5) # five points for each line
st_line_sample(st_transform(ls, 3857), n = c(1, 3)) # one and three points
st_line_sample(st_transform(ls, 3857), density = 1/1000) # one per km
st_line_sample(st_transform(ls, 3857), density = c(1/1000, 1/10000)) # one per km, one per 10 km
st_line_sample(st_transform(ls, 3857), density = units::set_units(1, 1/km)) # one per km
# five equidistant points including start and end:
st_line_sample(st_transform(ls, 3857), sample = c(0, 0.25, 0.5, 0.75, 1))
```

st_make_grid	<i>Create a regular tessellation over the bounding box of an sf or sfc object</i>
---------------------	---

Description

Create a square or hexagonal grid covering the bounding box of the geometry of an sf or sfc object

Usage

```
st_make_grid(
  x,
  cellsize = c(diff(st_bbox(x)[c(1, 3)]), diff(st_bbox(x)[c(2, 4)]))/n,
  offset = st_bbox(x)[c("xmin", "ymin")],
  n = c(10, 10),
  crs = if (missing(x)) NA_crs_ else st_crs(x),
  what = "polygons",
  square = TRUE,
  flat_topped = FALSE
)
```

Arguments

x	object of class sf or sfc
cellsize	target cellsize
offset	numeric of length 2; lower left corner coordinates (x, y) of the grid
n	integer of length 1 or 2, number of grid cells in x and y direction (columns, rows)
crs	object of class crs ; coordinate reference system of the target of the target grid in case argument x is missing, if x is not missing, its crs is inherited.
what	character; one of: "polygons", "corners", or "centers"
square	logical; if FALSE, create hexagonal grid
flat_topped	logical; if TRUE generate flat topped hexagons, else generate pointy topped

Value

Object of class **sfc** (simple feature geometry list column) with, depending on **what** and **square**, square or hexagonal polygons, corner points of these polygons, or center points of these polygons.

Examples

```
plot(st_make_grid(what = "centers"), axes = TRUE)
plot(st_make_grid(what = "corners"), add = TRUE, col = 'green', pch=3)
sfc = st_sfc(st_polygon(list(rbind(c(0,0), c(1,0), c(1,1), c(0,0)))))
plot(st_make_grid(sfc, cellsize = .1, square = FALSE))
plot(sfc, add = TRUE)
# non-default offset:
```

```
plot(st_make_grid(sfc, cellsize = .1, square = FALSE, offset = c(0, .05 / (sqrt(3)/2))))  
plot(sfc, add = TRUE)  
nc = st_read(system.file("shape/nc.shp", package="sf"))  
g = st_make_grid(nc)  
plot(g)  
plot(st_geometry(nc), add = TRUE)  
# g[nc] selects cells that intersect with nc:  
plot(g[nc], col = '#ff000088', add = TRUE)
```

st_m_range*Return 'm' range of a simple feature or simple feature set*

Description

Return 'm' range of a simple feature or simple feature set

Usage

```
## S3 method for class 'm_range'  
is.na(x)  
  
st_m_range(obj, ...)  
  
## S3 method for class 'POINT'  
st_m_range(obj, ...)  
  
## S3 method for class 'MULTIPOINT'  
st_m_range(obj, ...)  
  
## S3 method for class 'LINESTRING'  
st_m_range(obj, ...)  
  
## S3 method for class 'POLYGON'  
st_m_range(obj, ...)  
  
## S3 method for class 'MULTILINESTRING'  
st_m_range(obj, ...)  
  
## S3 method for class 'MULTIPOLYGON'  
st_m_range(obj, ...)  
  
## S3 method for class 'GEOMETRYCOLLECTION'  
st_m_range(obj, ...)  
  
## S3 method for class 'MULTISURFACE'  
st_m_range(obj, ...)  
  
## S3 method for class 'MULTICURVE'
```

```

st_m_range(obj, ...)

## S3 method for class 'CURVEPOLYGON'
st_m_range(obj, ...)

## S3 method for class 'COMPOUNDCURVE'
st_m_range(obj, ...)

## S3 method for class 'POLYHEDRALSURFACE'
st_m_range(obj, ...)

## S3 method for class 'TIN'
st_m_range(obj, ...)

## S3 method for class 'TRIANGLE'
st_m_range(obj, ...)

## S3 method for class 'CIRCULARSTRING'
st_m_range(obj, ...)

## S3 method for class 'sfc'
st_m_range(obj, ...)

## S3 method for class 'sf'
st_m_range(obj, ...)

## S3 method for class 'numeric'
st_m_range(obj, ..., crs = NA_crs_)

NA_m_range_

```

Arguments

<code>x</code>	object of class <code>m_range</code>
<code>obj</code>	object to compute the m range from
<code>...</code>	ignored
<code>crs</code>	object of class <code>crs</code> , or argument to <code>st_crs</code> , specifying the CRS of this bounding box.

Format

An object of class `m_range` of length 2.

Details

`NA_m_range_` represents the missing value for a `m_range` object

Value

a numeric vector of length two, with `mmin` and `mmax` values; if `obj` is of class `sf` or `sfc` the object if `obj` is of class `sf` or `sfc` the object returned has a class `m_range`

Examples

```
a = st_sf(a = 1:2, geom = st_sfc(st_point(0:3), st_point(1:4)), crs = 4326)
st_m_range(a)
st_m_range(c(mmin = 16.1, mmax = 16.6), crs = st_crs(4326))
```

st_nearest_feature *get index of nearest feature*

Description

get index of nearest feature

Usage

```
st_nearest_feature(
  x,
  y,
  ...,
  check_crs = TRUE,
  longlat = isTRUE(st_is_longlat(x))
)
```

Arguments

<code>x</code>	object of class <code>sfg</code> , <code>sfc</code> or <code>sf</code>
<code>y</code>	object of class <code>sfg</code> , <code>sfc</code> or <code>sf</code> ; if missing, features in <code>x</code> will be compared to all remaining features in <code>x</code> .
<code>...</code>	ignored
<code>check_crs</code>	logical; should <code>x</code> and <code>y</code> be checked for CRS equality?
<code>longlat</code>	logical; does <code>x</code> have ellipsoidal coordinates?

Value

for each feature (geometry) in `x` the index of the nearest feature (geometry) in set `y`, or in the remaining set of `x` if `y` is missing; empty geometries result in NA indexes

See Also

[st_nearest_points](#) for finding the nearest points for pairs of feature geometries

Examples

```

ls1 = st_linestring(rbind(c(0,0), c(1,0)))
ls2 = st_linestring(rbind(c(0,0.1), c(1,0.1)))
ls3 = st_linestring(rbind(c(0,1), c(1,1)))
l1 = st_sfc(ls1, ls2, ls3)

p1 = st_point(c(0.1, -0.1))
p2 = st_point(c(0.1, 0.11))
p3 = st_point(c(0.1, 0.09))
p4 = st_point(c(0.1, 0.9))

(p = st_sfc(p1, p2, p3, p4))
try(st_nearest_feature(p, 1))
try(st_nearest_points(p, l1[st_nearest_feature(p,1)], pairwise = TRUE))

r = sqrt(2)/10
b1 = st_buffer(st_point(c(.1,.1)), r)
b2 = st_buffer(st_point(c(.9,.9)), r)
b3 = st_buffer(st_point(c(.9,.1)), r)
circles = st_sfc(b1, b2, b3)
plot(circles, col = NA, border = 2:4)
pts = st_sfc(st_point(c(.3,.1)), st_point(c(.6,.2)), st_point(c(.6,.6)), st_point(c(.4,.8)))
plot(pts, add = TRUE, col = 1)
# draw points to nearest circle:
nearest = try(st_nearest_feature(pts, circles))
if (inherits(nearest, "try-error")) # GEOS 3.6.1 not available
  nearest = c(1, 3, 2, 2)
ls = st_nearest_points(pts, circles[nearest], pairwise = TRUE)
plot(ls, col = 5:8, add = TRUE)
# compute distance between pairs of nearest features:
st_distance(pts, circles[nearest], by_element = TRUE)

```

st_nearest_points *get nearest points between pairs of geometries*

Description

get nearest points between pairs of geometries

Usage

```

st_nearest_points(x, y, ...)

## S3 method for class 'sfc'
st_nearest_points(x, y, ..., pairwise = FALSE)

## S3 method for class 'sfg'
st_nearest_points(x, y, ...)

```

```
## S3 method for class 'sf'
st_nearest_points(x, y, ...)
```

Arguments

x	object of class sfg, sfc or sf
y	object of class sfg, sfc or sf
...	ignored
pairwise	logical; if FALSE (default) return nearest points between all pairs, if TRUE, return nearest points between subsequent pairs.

Details

in case x lies inside y, when using S2, the end points are on polygon boundaries, when using GEOS the end point are identical to x.

Value

an [sfc](#) object with all two-point LINESTRING geometries of point pairs from the first to the second geometry, of length x * y, with y cycling fastest. See examples for ideas how to convert these to POINT geometries.

See Also

[st_nearest_feature](#) for finding the nearest feature

Examples

```
r = sqrt(2)/10
pt1 = st_point(c(.1,.1))
pt2 = st_point(c(.9,.9))
pt3 = st_point(c(.9,.1))
b1 = st_buffer(pt1, r)
b2 = st_buffer(pt2, r)
b3 = st_buffer(pt3, r)
(ls0 = st_nearest_points(b1, b2)) # sfg
(ls = st_nearest_points(st_sfc(b1), st_sfc(b2, b3))) # sfc
plot(b1, xlim = c(-.2,1.2), ylim = c(-.2,1.2), col = NA, border = 'green')
plot(st_sfc(b2, b3), add = TRUE, col = NA, border = 'blue')
plot(ls, add = TRUE, col = 'red')

nc = st_read(system.file("gpkg/nc.gpkg", package="sf"))
plot(st_geometry(nc))
ls = st_nearest_points(nc[1], nc)
plot(ls, col = 'red', add = TRUE)
pts = st_cast(ls, "POINT") # gives all start & end points
# starting, "from" points, corresponding to x:
plot(pts[seq(1, 200, 2)], add = TRUE, col = 'blue')
# ending, "to" points, corresponding to y:
plot(pts[seq(2, 200, 2)], add = TRUE, col = 'green')
```

<code>st_normalize</code>	<i>Normalize simple features</i>
---------------------------	----------------------------------

Description

`st_normalize` transforms the coordinates in the input feature to fall between 0 and 1. By default the current domain is set to the bounding box of the input, but other domains can be used as well

Usage

```
st_normalize(x, domain = st_bbox(x), ...)
```

Arguments

<code>x</code>	object of class sf, sfc or sfsg
<code>domain</code>	The domain <code>x</code> should be normalized from as a length 4 vector of the form <code>c(xmin, ymin, xmax, ymax)</code> . Defaults to the bounding box of <code>x</code>
<code>...</code>	ignored

Examples

```
p1 = st_point(c(7,52))
st_normalize(p1, domain = c(0, 0, 10, 100))

p2 = st_point(c(-30,20))
sfc = st_sfc(p1, p2, crs = 4326)
sfc
sfc_norm <- st_normalize(sfc)
st_bbox(sfc_norm)
```

<code>st_precision</code>	<i>Get precision</i>
---------------------------	----------------------

Description

Get precision
Set precision

Usage

```
st_precision(x)

st_set_precision(x, precision)

st_precision(x) <- value
```

Arguments

x	object of class sfc or sf
precision	numeric, or object of class units with distance units (but see details); see st_as_binary for how to do this.
value	precision value

Details

If precision is a units object, the object on which we set precision must have a coordinate reference system with compatible distance units.

Setting a precision has no direct effect on coordinates of geometries, but merely set an attribute tag to an sfc object. The effect takes place in [st_as_binary](#) or, more precise, in the C++ function CPL_write_wkb, where simple feature geometries are being serialized to well-known-binary (WKB). This happens always when routines are called in GEOS library (geometrical operations or predicates), for writing geometries using [st_write](#) or [write_sf](#), [st_make_valid](#) in package lwgeom; also [aggregate](#) and [summarise](#) by default union geometries, which calls a GEOS library function. Routines in these libraries receive rounded coordinates, and possibly return results based on them. [st_as_binary](#) contains an example of a roundtrip of sfc geometries through WKB, in order to see the rounding happening to R data.

The reason to support precision is that geometrical operations in GEOS or liblwgeom may work better at reduced precision. For writing data from R to external resources it is harder to think of a good reason to limiting precision.

See Also

[st_as_binary](#) for an explanation of what setting precision does, and the examples therein.

Examples

```
x <- st_sfc(st_point(c(pi, pi)))
st_precision(x)
st_precision(x) <- 0.01
st_precision(x)
```

st_read

Read simple features or layers from file or database

Description

Read simple features from file or database, or retrieve layer names and their geometry type(s)

Read PostGIS table directly through DBI and RPostgreSQL interface, converting Well-Know Binary geometries to sfc

Usage

```
st_read(dsn, layer, ...)

## S3 method for class 'character'
st_read(
  dsn,
  layer,
  ...,
  query = NA,
  options = NULL,
  quiet = FALSE,
  geometry_column = 1L,
  type = 0,
  promote_to_multi = TRUE,
  stringsAsFactors = sf_stringsAsFactors(),
  int64_as_string = FALSE,
  check_ring_dir = FALSE,
  fid_column_name = character(0),
  drivers = character(0),
  wkt_filter = character(0),
  optional = FALSE
)
read_sf(..., quiet = TRUE, stringsAsFactors = FALSE, as_tibble = TRUE)

## S3 method for class 'DBIObject'
st_read(
  dsn = NULL,
  layer = NULL,
  query = NULL,
  EWKB = TRUE,
  quiet = TRUE,
  as_tibble = FALSE,
  geometry_column = NULL,
  ...
)
```

Arguments

<code>dsn</code>	data source name (interpretation varies by driver - for some drivers, <code>dsn</code> is a file name, but may also be a folder, or contain the name and access credentials of a database); in case of GeoJSON, <code>dsn</code> may be the character string holding the geojson data. It can also be an open database connection.
<code>layer</code>	layer name (varies by driver, may be a file name without extension); in case <code>layer</code> is missing, <code>st_read</code> will read the first layer of <code>dsn</code> , give a warning and (unless <code>quiet = TRUE</code>) print a message when there are multiple layers, or give an error if there are no layers in <code>dsn</code> . If <code>dsn</code> is a database connection, then <code>layer</code> can be a table name or a database identifier (see Id). It is also possible to omit

	layer and rather use the query argument.
...	parameter(s) passed on to <code>st_as_sf</code>
query	SQL query to select records; see details
options	character; driver dependent dataset open options, multiple options supported. For possible values, see the "Open options" section of the GDAL documentation of the corresponding driver, and https://github.com/r-spatial/sf/issues/1157 for an example.
quiet	logical; suppress info on name, driver, size and spatial reference, or signaling no or multiple layers
geometry_column	integer or character; in case of multiple geometry fields, which one to take?
type	integer; ISO number of desired simple feature type; see details. If left zero, and <code>promote_to_multi</code> is TRUE, in case of mixed feature geometry types, conversion to the highest numeric type value found will be attempted. A vector with different values for each geometry column can be given.
<code>promote_to_multi</code>	logical; in case of a mix of Point and MultiPoint, or of LineString and MultiLineString, or of Polygon and MultiPolygon, convert all to the Multi variety; defaults to TRUE
<code>stringsAsFactors</code>	logical; logical: should character vectors be converted to factors? Default for <code>read_sf</code> or R version >= 4.1.0 is FALSE, for <code>st_read</code> and R version < 4.1.0 equal to <code>default.stringsAsFactors()</code>
<code>int64_as_string</code>	logical; if TRUE, Int64 attributes are returned as string; if FALSE, they are returned as double and a warning is given when precision is lost (i.e., values are larger than 2^53).
<code>check_ring_dir</code>	logical; if TRUE, polygon ring directions are checked and if necessary corrected (when seen from above: exterior ring counter clockwise, holes clockwise)
<code>fid_column_name</code>	character; name of column to write feature IDs to; defaults to not doing this
<code>drivers</code>	character; limited set of driver short names to be tried (default: try all)
<code>wkt_filter</code>	character; WKT representation of a spatial filter (may be used as bounding box, selecting overlapping geometries); see examples
<code>optional</code>	logical; passed to <code>as.data.frame</code> ; always TRUE when <code>as_tibble</code> is TRUE
<code>as_tibble</code>	logical; should the returned table be of class tibble or data.frame?
<code>EWKB</code>	logical; is the WKB of type EWKB? if missing, defaults to TRUE

Details

for `geometry_column`, see also https://trac.osgeo.org/gdal/wiki/rfc41_multiple_geometry_fields

for values for `type` see https://en.wikipedia.org/wiki/Well-known_text#Well-known_binary, but note that not every target value may lead to successful conversion. The typical conversion from

POLYGON (3) to MULTIPOLYGON (6) should work; the other way around (type=3), secondary rings from MULTIPOLYGONS may be dropped without warnings. `promote_to_multi` is handled on a per-geometry column basis; `type` may be specified for each geometry column.

Note that stray files in data source directories (such as *.dbf) may lead to spurious errors that accompany *.shp are missing.

In case of problems reading shapefiles from USB drives on OSX, please see <https://github.com/r-spatial/sf/issues/252>.

For query with a character dsn the query text is handed to 'ExecuteSQL' on the GDAL/OGR data set and will result in the creation of a new layer (and `layer` is ignored). See 'OGRSQL' https://gdal.org/user/ogr_sql_dialect.html for details. Please note that the 'FID' special field is driver-dependent, and may be either 0-based (e.g. ESRI Shapefile), 1-based (e.g. MapInfo) or arbitrary (e.g. OSM). Other features of OGRSQL are also likely to be driver dependent. The available layer names may be obtained with `st_layers`. Care will be required to properly escape the use of some layer names.

`read_sf` and `write_sf` are aliases for `st_read` and `st_write`, respectively, with some modified default arguments. `read_sf` and `write_sf` are quiet by default: they do not print information about the data source. `read_sf` returns an sf-tibble rather than an sf-data.frame. `write_sf` delete layers by default: it overwrites existing files without asking or warning.

if `table` is not given but `query` is, the spatial reference system (`crs`) of the table queried is only available in case it has been stored into each geometry record (e.g., by PostGIS, when using EWKB)

The function will automatically find the 'geometry' type columns for drivers that support it. For the other drivers, it will try to cast all the character columns, which can be slow for very wide tables.

Value

object of class `sf` when a layer was successfully read; in case argument `layer` is missing and data source dsn does not contain a single layer, an object of class `sf_layers` is returned with the layer names, each with their geometry type(s). Note that the number of layers may also be zero.

Note

The use of `system.file` in examples make sure that examples run regardless where R is installed: typical users will not use `system.file` but give the file name directly, either with full path or relative to the current working directory (see `getwd`). "Shapefiles" consist of several files with the same basename that reside in the same directory, only one of them having extension .shp.

See Also

[st_layers](#), [st_drivers](#)

Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
summary(nc) # note that AREA was computed using Euclidian area on lon/lat degrees

## only three fields by select clause
## only two features by where clause
nc_sql = st_read(system.file("shape/nc.shp", package="sf"),
```

```

query = "SELECT NAME, SID74, FIPS FROM \"nc\" WHERE BIR74 > 20000")
## Not run:
library(sp)
example(meuse, ask = FALSE, echo = FALSE)
try(st_write(st_as_sf(meuse), "PG:dbname=postgis", "meuse",
            layer_options = "OVERWRITE=true"))
try(st_meuse <- st_read("PG:dbname=postgis", "meuse"))
if (exists("st_meuse"))
  summary(st_meuse)

## End(Not run)

## Not run:
## note that we need special escaping of layer within single quotes (nc.gpkg)
## and that geom needs to be included in the select, otherwise we don't detect it
layer <- st_layers(system.file("gpkg/nc.gpkg", package = "sf"))$name[1]
nc_gpkg_sql = st_read(system.file("gpkg/nc.gpkg", package = "sf"),
                      query = sprintf("SELECT NAME, SID74, FIPS, geom FROM \"%s\" WHERE BIR74 > 20000", layer))

## End(Not run)
# spatial filter, as wkt:
wkt = st_as_text(st_geometry(nc[1,]))
# filter by (bbox overlaps of) first feature geometry:
st_read(system.file("gpkg/nc.gpkg", package="sf"), wkt_filter = wkt)
# read geojson from string:
geojson_txt <- paste("{\"type\":\"MultiPoint\", \"coordinates\":",
                     "[[3.2,4],[3,4.6],[3.8,4.4],[3.5,3.8],[3.4,3.6],[3.9,4.5]]}")
x = st_read(geojson_txt)
x
## Not run:
library(RPostgreSQL)
try(conn <- dbConnect(PostgreSQL(), dbname = "postgis"))
if (exists("conn") && !inherits(conn, "try-error")) {
  x = st_read(conn, "meuse", query = "select * from meuse limit 3;")
  x = st_read(conn, table = "public.meuse")
  print(st_crs(x)) # SRID resolved by the database, not by GDAL!
  dbDisconnect(conn)
}

## End(Not run)

```

st_relate

Compute DE9-IM relation between pairs of geometries, or match it to a given pattern

Description

Compute DE9-IM relation between pairs of geometries, or match it to a given pattern

Usage

```
st_relate(x, y, pattern = NA_character_, sparse = !is.na(pattern))
```

Arguments

x	object of class sf, sfc or sfg
y	object of class sf, sfc or sfg
pattern	character; define the pattern to match to, see details.
sparse	logical; should a sparse matrix be returned (TRUE) or a dense matrix?

Value

In case pattern is not given, `st_relate` returns a dense character matrix; element [i,j] has nine characters, referring to the DE9-IM relationship between $x[i]$ and $y[j]$, encoded as IxIy,IxBy,IxEy,BxIy,BxBy,BxEy,ExIy,ExBy where I refers to interior, B to boundary, and E to exterior, and e.g. BxIy the dimensionality of the intersection of the the boundary of $x[i]$ and the interior of $y[j]$, which is one of 0,1,2,F, digits denoting dimensionality, F denoting not intersecting. When pattern is given, a dense logical matrix or sparse index list returned with matches to the given pattern; see `st_intersection` for a description of the returned matrix or list. See also <https://en.wikipedia.org/wiki/DE-9IM> for further explanation.

Examples

```
p1 = st_point(c(0,0))
p2 = st_point(c(2,2))
pol1 = st_polygon(list(rbind(c(0,0),c(1,0),c(1,1),c(0,1),c(0,0)))) - 0.5
pol2 = pol1 + 1
pol3 = pol1 + 2
st_relate(st_sfc(p1, p2), st_sfc(pol1, pol2, pol3))
sfc = st_sfc(st_point(c(0,0)), st_point(c(3,3)))
grd = st_make_grid(sfc, n = c(3,3))
st_intersects(grd)
st_relate(grd, pattern = "****1****") # sides, not corners, internals
st_relate(grd, pattern = "****0****") # only corners touch
st_rook = function(a, b = a) st_relate(a, b, pattern = "F***1***")
st_rook(grd)
# queen neighbours, see \url{https://github.com/r-spatial/sf/issues/234#issuecomment-300511129}
st_queen <- function(a, b = a) st_relate(a, b, pattern = "F***T***")
```

`st_sample`

sample points on or in (sets of) spatial features

Description

Sample points on or in (sets of) spatial features. By default, returns a pre-specified number of points that is equal to `size` (if `type = "random"` and `exact = TRUE`) or an approximation of `size` otherwise. `spatstat` methods are interfaced and do not use the `size` argument, see examples.

Usage

```
st_sample(x, size, ...)

## S3 method for class 'sf'
st_sample(x, size, ...)

## S3 method for class 'sfc'
st_sample(
  x,
  size,
  ...,
  type = "random",
  exact = TRUE,
  warn_if_not_integer = TRUE,
  by_polygon = FALSE,
  progress = FALSE
)

## S3 method for class 'sfg'
st_sample(x, size, ...)
```

Arguments

<code>x</code>	object of class sf or sfc
<code>size</code>	sample size(s) requested; either total size, or a numeric vector with sample sizes for each feature geometry. When sampling polygons, the returned sampling size may differ from the requested size, as the bounding box is sampled, and sampled points intersecting the polygon are returned.
<code>...</code>	passed on to <code>sample</code> for multipoint sampling, or to <code>spatstat</code> functions for <code>spatstat</code> sampling types (see details)
<code>type</code>	character; indicates the spatial sampling type; one of <code>random</code> , <code>hexagonal</code> (triangular really), <code>regular</code> , or one of the <code>spatstat</code> methods such as <code>Thomas</code> for calling <code>spatstat.random::rThomas</code> (see Details).
<code>exact</code>	logical; should the length of output be exactly
<code>warn_if_not_integer</code>	logical; if FALSE then no warning is emitted if <code>size</code> is not an integer
<code>by_polygon</code>	logical; for MULTIPOLYGON geometries, should the effort be split by POLYGON? See https://github.com/r-spatial/sf/issues/1480 the same as specified by <code>size?</code> TRUE by default. Only applies to polygons, and when <code>type = "random"</code> .
<code>progress</code>	logical; if TRUE show progress bar (only if <code>size</code> is a vector).

Details

The function is vectorised: it samples `size` points across all geometries in the object if `size` is a single number, or the specified number of points in each feature if `size` is a vector of integers equal in length to the geometry of `x`.

if x has dimension 2 (polygons) and geographical coordinates (long/lat), uniform random sampling on the sphere is applied, see e.g. <http://mathworld.wolfram.com/SpherePointPicking.html>

For regular or hexagonal sampling of polygons, the resulting size is only an approximation.

As parameter called `offset` can be passed to control ("fix") regular or hexagonal sampling: for polygons a length 2 numeric vector (by default: a random point from `st_bbox(x)`); for lines use a number like `rnorm(1)`.

Sampling methods from package `spatstat` are interfaced (see examples), and need their own parameters to be set. For instance, to use `spatstat.random::rThomas()`, set `type = "Thomas"`.

Value

an `sfc` object containing the sampled POINT geometries

Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
p1 = st_sample(nc[1:3, ], 6)
p2 = st_sample(nc[1:3, ], 1:3)
plot(st_geometry(nc)[1:3])
plot(p1, add = TRUE)
plot(p2, add = TRUE, pch = 2)
x = st_sfc(st_polygon(list(rbind(c(0,0),c(90,0),c(90,90),c(0,90),c(0,0)))), crs = st_crs(4326))
plot(x, axes = TRUE, graticule = TRUE)
if (sf_extSoftVersion()["proj.4"] >= "4.9.0")
  plot(p1 <- st_sample(x, 1000), add = TRUE)
if (require(lwgeom, quietly = TRUE)) { # for st_segmentize()
  x2 = st_transform(st_segmentize(x, 1e4), st_crs("+proj=ortho +lat_0=30 +lon_0=45"))
  g = st_transform(st_graticule(), st_crs("+proj=ortho +lat_0=30 +lon_0=45"))
  plot(x2, graticule = g)
  if (sf_extSoftVersion()["proj.4"] >= "4.9.0") {
    p2 = st_transform(p1, st_crs("+proj=ortho +lat_0=30 +lon_0=45"))
    plot(p2, add = TRUE)
  }
}
x = st_sfc(st_polygon(list(rbind(c(0,0),c(90,0),c(90,10),c(0,90),c(0,0))))) # NOT long/lat:
plot(x)
p_exact = st_sample(x, 1000, exact = TRUE)
p_not_exact = st_sample(x, 1000, exact = FALSE)
length(p_exact); length(p_not_exact)
plot(st_sample(x, 1000), add = TRUE)
x = st_sfc(st_polygon(list(rbind(c(-180,-90),c(180,-90),c(180,90),c(-180,90),c(-180,-90)))), crs=st_crs(4326))
# FIXME:
#if (sf_extSoftVersion()["proj.4"] >= "4.9.0") {
#  p = st_sample(x, 1000)
#  st_sample(p, 3)
#}
# hexagonal:
sfc = st_sfc(st_polygon(list(rbind(c(0,0), c(1,0), c(1,1), c(0,0))))))
plot(sfc)
h = st_sample(sfc, 100, type = "hexagonal")
```

```

h1 = st_sample(sfc, 100, type = "hexagonal")
plot(h, add = TRUE)
plot(h1, col = 'red', add = TRUE)
c(length(h), length(h1)) # approximate!
pt = st_multipoint(matrix(1:20,,2))
ls = st_sf(st_linestring(rbind(c(0,0),c(0,1))),
  st_linestring(rbind(c(0,0),c(.1,0))),
  st_linestring(rbind(c(0,1),c(.1,1))),
  st_linestring(rbind(c(2,2),c(2,2.00001))))
st_sample(ls, 80)
plot(st_sample(ls, 80))
# spatstat example:
if (require(spatstat.random)) {
  x <- sf:::st_sf(sf:::st_polygon(list(rbind(c(0, 0), c(10, 0), c(10, 10), c(0, 0)))))
  # for spatstat.random::rThomas(), set type = "Thomas":
  pts <- st_sample(x, kappa = 1, mu = 10, scale = 0.1, type = "Thomas")
}

```

st_shift_longitude *Shift or re-center geographical coordinates for a Pacific view*

Description

All longitudes < 0 are added to 360, to avoid for instance parts of Alaska being represented on the far left and right of a plot because they have values straddling 180 degrees. In general, using a projected coordinate reference system is to be preferred, but this method permits a geographical coordinate reference system to be used. This is the sf equivalent of [recenter](#) in the sp package and ST_ShiftLongitude in PostGIS.

Usage

```

st_shift_longitude(x)

## S3 method for class 'sfc'
st_shift_longitude(x, ...)

## S3 method for class 'sf'
st_shift_longitude(x, ...)

```

Arguments

x	object of class sf or sfc
...	ignored

Examples

```
## sfc
pt1 = st_point(c(-170, 50))
pt2 = st_point(c(170, 50))
(sfc = st_sfc(pt1, pt2))
sfc = st_set_crs(sfc, 4326)
st_shift_longitude(sfc)

## sf
d = st_as_sf(data.frame(id = 1:2, geometry = sfc))
st_shift_longitude(d)
```

st_transform

Transform or convert coordinates of simple feature

Description

Transform or convert coordinates of simple feature

Usage

```
st_transform(x, crs, ...)

## S3 method for class 'sfc'
st_transform(
  x,
  crs = st_crs(x),
  ...,
  aoi = numeric(0),
  pipeline = character(0),
  reverse = FALSE,
  desired_accuracy = -1,
  allow_ballpark = TRUE,
  partial = TRUE,
  check = FALSE
)

## S3 method for class 'sf'
st_transform(x, crs = st_crs(x), ...)

## S3 method for class 'sfg'
st_transform(x, crs = st_crs(x), ...)

st_wrap_dateline(x, options, quiet)

## S3 method for class 'sfc'
st_wrap_dateline(x, options = "WRAPDATELINE=YES", quiet = TRUE)
```

```
## S3 method for class 'sf'
st_wrap_dateline(x, options = "WRAPDATELINE=YES", quiet = TRUE)

## S3 method for class 'sfg'
st_wrap_dateline(x, options = "WRAPDATELINE=YES", quiet = TRUE)

sf_proj_info(type = "proj", path)
```

Arguments

x	object of class sf, sfc or sfg
crs	target coordinate reference system: object of class ‘crs’, or input string for st_crs
...	ignored
aoi	area of interest, in degrees: WestLongitude, SouthLatitude, EastLongitude, NorthLatitude
pipeline	character; coordinate operation pipeline, for overriding the default operation
reverse	boolean; has only an effect when pipeline is defined: if TRUE, the inverse operation of the pipeline is applied
desired_accuracy	numeric; Only coordinate operations that offer an accuracy of at least the one specified will be considered; a negative value disables this feature (requires GDAL >= 3.3)
allow_ballpark	logical; are ballpark (low accuracy) transformations allowed? (requires GDAL >= 3.3)
partial	logical; allow for partial projection, if not all points of a geometry can be projected (corresponds to setting environment variable OGR_ENABLE_PARTIAL_REPROJECTION to TRUE)
check	logical; if TRUE, perform a sanity check on resulting polygons
options	character; should have "WRAPDATELINE=YES" to function; another parameter that is used is "DATELINEOFFSET=10" (where 10 is the default value)
quiet	logical; print options after they have been parsed?
type	character; one of <code>have_datum_files</code> , proj, ellps, datum, units or prime_meridians; see Details.
path	character; PROJ search path to be set

Details

Transforms coordinates of object to new projection. Features that cannot be transformed are returned as empty geometries. Transforms using the `pipeline=` argument may fail if there is ambiguity in the axis order of the specified coordinate reference system; if you need the traditional GIS order, use "OGC:CRS84", not "EPSG:4326". Extra care is needed with the ESRI Shapefile format, because WKT1 does not store axis order unambiguously.

The `st_transform` method for sfg objects assumes that the CRS of the object is available as an attribute of that name.

For a discussion of using options, see <https://github.com/r-spatial/sf/issues/280> and <https://github.com/r-spatial/sf/issues/541>

`sf_proj_info` lists the available projections, ellipses, datums, units, or data search path of the PROJ library when `type` is equal to `proj`, `ellps`, `datum`, `units` or `path`; when `type` equals `have_datum_files` a boolean is returned indicating whether datum files are installed and accessible (checking for conus).

for `PROJ >= 6`, `sf_proj_info` does not provide option `type = "datums"`. `PROJ < 6` does not provide the option `type = "prime_meridians"`.

for `PROJ >= 7.1.0`, the "units" query of `sf_proj_info` returns the `to_meter` variable as numeric, previous versions return a character vector containing a numeric expression.

See Also

Projecting simple feature geometries to projections not supported by GDAL may be done by `st_transform_proj`, part of package `lwgeom`.

`sf_project` projects a matrix of coordinates, bypassing GDAL altogether

Examples

```
p1 = st_point(c(7,52))
p2 = st_point(c(-30,20))
sfc = st_sfc(p1, p2, crs = 4326)
sfc
st_transform(sfc, 3857)
st_transform(st_sf(a=2:1, geom=sfc), "+init=epsg:3857")
try(st_transform(sfc, 3857, aoi = c(-280,-90,180,90)))
if (sf_extSoftVersion()["GDAL"] >= "3.0.0") {
  st_transform(sfc, pipeline =
    "+proj=pipeline +step +proj=axisswap +order=2,1" # reverse axes
  st_transform(sfc, pipeline =
    "+proj=pipeline +step +proj=axisswap +order=2,1", reverse = TRUE) # also reverse axes
}
nc = st_read(system.file("shape/nc.shp", package="sf"))
st_area(nc[1,]) # area from long/lat
st_area(st_transform(nc[1,], 32119)) # NC state plane, m
st_area(st_transform(nc[1,], 2264)) # NC state plane, US foot
library(units)
set_units(st_area(st_transform(nc[1,], 2264)), m^2)
st_transform(structure(p1, proj4string = "+init=epsg:4326"), "+init=epsg:3857")
st_wrap_dateline(st_sfc(st_linestring(rbind(c(-179,0),c(179,0))), crs = 4326))
if (require(maps, quietly = TRUE)) {
  wrld <- st_as_sf(maps::map("world", fill = TRUE, plot = FALSE))
  wrld_wrap <- st_wrap_dateline(wrld, options = c("WRAPDATELINE=YES", "DATELINEOFFSET=180"),
    quiet = TRUE)
  wrld_moll <- st_transform(wrld_wrap, "+proj=moll")
  plot(st_geometry(wrld_moll), col = "transparent")
}
sf_proj_info("datum")
```

st_viewport	Create viewport from sf, sfc or sfg object
-------------	--

Description

Create viewport from sf, sfc or sfg object

Usage

```
st_viewport(x, ..., bbox = st_bbox(x), asp)
```

Arguments

x	object of class sf, sfc or sfg object
...	parameters passed on to viewport
bbox	the bounding box used for aspect ratio
asp	numeric; target aspect ratio (y/x), see Details

Details

parameters width, height, xscale andyscale are set such that aspect ratio is honoured and plot size is maximized in the current viewport; others can be passed as ...

If asp is missing, it is taken as 1, except when `isTRUE(st_is_longlat(x))`, in which case it is set to $1.0 / \cos(y)$, with y the middle of the latitude bounding box.

Value

The output of the call to [viewport](#)

Examples

```
library(grid)
nc = st_read(system.file("shape/nc.shp", package="sf"))
grid.newpage()
pushViewport(viewport(width = 0.8, height = 0.8))
pushViewport(st_viewport(nc))
invisible(lapply(st_geometry(nc), function(x) grid.draw(st_as_grob(x, gp = gpar(fill = 'red')))))
```

<code>st_write</code>	<i>Write simple features object to file or database</i>
-----------------------	---

Description

Write simple features object to file or database

Usage

```

st_write(obj, dsn, layer, ...)

## S3 method for class 'sfc'
st_write(obj, dsn, layer, ...)

## S3 method for class 'sf'
st_write(
  obj,
  dsn,
  layer = NULL,
  ...,
  driver = guess_driver_can_write(dsn),
  dataset_options = NULL,
  layer_options = NULL,
  quiet = FALSE,
  factorsAsCharacter = TRUE,
  append = NA,
  delete_dsn = FALSE,
  delete_layer = !is.na(append) && !append,
  fid_column_name = NULL,
  config_options = character(0)
)

## S3 method for class 'data.frame'
st_write(obj, dsn, layer = NULL, ...)

write_sf(..., quiet = TRUE, append = FALSE, delete_layer = !append)

st_delete(
  dsn,
  layer = character(0),
  driver = guess_driver_can_write(dsn),
  quiet = FALSE
)

```

Arguments

<code>obj</code>	object of class <code>sf</code> or <code>sfc</code>
------------------	---

dsn	data source name. Interpretation varies by driver: can be a filename, a folder, a database name, or a Database Connection (we officially test support for <code>RPostgres::Postgres()</code> connections).
layer	layer name. Varies by driver, may be a file name without extension; for database connection, it is the name of the table. If layer is missing, the basename of dsn is taken.
...	other arguments passed to <code>dbWriteTable</code> when dsn is a Database Connection
driver	character; name of driver to be used; if missing and dsn is not a Database Connection, a driver name is guessed from dsn; <code>st_drivers()</code> returns the drivers that are available with their properties; links to full driver documentation are found at https://gdal.org/drivers/vector/index.html
dataset_options	character; driver dependent dataset creation options; multiple options supported.
layer_options	character; driver dependent layer creation options; multiple options supported.
quiet	logical; suppress info on name, driver, size and spatial reference
factorsAsCharacter	logical; convert factor levels to character strings (TRUE, default), otherwise into numbers when factorsAsCharacter is FALSE. For database connections, factorsAsCharacter is always TRUE.
append	logical; should we append to an existing layer, or replace it? if TRUE append, if FALSE replace. The default for <code>st_write</code> is NA which raises an error if the layer exists. The default for <code>write_sf</code> is FALSE, which overwrites any existing data. See also next two arguments for more control on overwrite behavior.
delete_dsn	logical; delete data source dsn before attempting to write?
delete_layer	logical; delete layer layer before attempting to write? The default for <code>st_write</code> is FALSE which raises an error if the layer exists. The default for <code>write_sf</code> is TRUE.
fid_column_name	character, name of column with feature IDs;
config_options	character, named vector with GDAL config options specified, this column is no longer written as feature attribute.

Details

Columns (variables) of a class not supported are dropped with a warning.

When updating an existing layer, records are appended to it if the updating object has the right variable names and types. If names don't match an error is raised. If types don't match, behaviour is undefined: GDAL may raise warnings or errors or fail silently.

When deleting layers or data sources is not successful, no error is emitted. `delete_dsn` and `delete_layer` should be handled with care; the former may erase complete directories or databases.

`st_delete` deletes layer(s) in a data source, or a data source if layers are omitted; it returns TRUE on success, FALSE on failure, invisibly.

Value

`obj`, invisibly

See Also

[st_drivers](#), [dbWriteTable](#)

Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
st_write(nc, paste0(tempdir(), "/", "nc.shp"))
st_write(nc, paste0(tempdir(), "/", "nc.shp"), delete_layer = TRUE) # overwrites
if (require(sp, quietly = TRUE)) {
  data(meuse, package = "sp") # loads data.frame from sp
  meuse_sf = st_as_sf(meuse, coords = c("x", "y"), crs = 28992)
  # writes X and Y as columns:
  st_write(meuse_sf, paste0(tempdir(), "/", "meuse.csv"), layer_options = "GEOMETRY=AS_XY")
  st_write(meuse_sf, paste0(tempdir(), "/", "meuse.csv"), layer_options = "GEOMETRY=AS_WKT",
           delete_dsn=TRUE) # overwrites
## Not run:
library(sp)
example(meuse, ask = FALSE, echo = FALSE)
try(st_write(st_as_sf(meuse), "PG:dbname=postgis", "meuse_sf",
            layer_options = c("OVERWRITE=yes", "LAUNDER=true")))
demo(nc, ask = FALSE)
try(st_write(nc, "PG:dbname=postgis", "sids", layer_options = "OVERWRITE=true"))

## End(Not run)
}
```

st_zm

Drop or add Z and/or M dimensions from feature geometries

Description

Drop Z and/or M dimensions from feature geometries, resetting classes appropriately

Usage

```
st_zm(x, ..., drop = TRUE, what = "ZM")
```

Arguments

x	object of class sfg, sf or sf
...	ignored
drop	logical; drop, or (FALSE) add?
what	character which dimensions to drop or add

Details

Only combinations `drop=TRUE, what = "ZM"`, and `drop=FALSE, what="Z"` are supported so far. In case `add=TRUE`, `x` should have XY geometry, and zero values are added for Z.

Examples

```
st_zm(st_linestring(matrix(1:32,8)))
x = st_sfc(st_linestring(matrix(1:32,8)), st_linestring(matrix(1:8,2)))
st_zm(x)
a = st_sf(a = 1:2, geom=x)
st_zm(a)
```

st_z_range

Return 'z' range of a simple feature or simple feature set

Description

Return 'z' range of a simple feature or simple feature set

Usage

```
## S3 method for class 'z_range'
is.na(x)

st_z_range(obj, ...)

## S3 method for class 'POINT'
st_z_range(obj, ...)

## S3 method for class 'MULTIPOINT'
st_z_range(obj, ...)

## S3 method for class 'LINESTRING'
st_z_range(obj, ...)

## S3 method for class 'POLYGON'
st_z_range(obj, ...)

## S3 method for class 'MULTILINESTRING'
st_z_range(obj, ...)

## S3 method for class 'MULTIPOLYGON'
st_z_range(obj, ...)

## S3 method for class 'GEOMETRYCOLLECTION'
st_z_range(obj, ...)

## S3 method for class 'MULTISURFACE'
st_z_range(obj, ...)

## S3 method for class 'MULTICURVE'
st_z_range(obj, ...)
```

```

## S3 method for class 'CURVEPOLYGON'
st_z_range(obj, ...)

## S3 method for class 'COMPOUNDCURVE'
st_z_range(obj, ...)

## S3 method for class 'POLYHEDRALSURFACE'
st_z_range(obj, ...)

## S3 method for class 'TIN'
st_z_range(obj, ...)

## S3 method for class 'TRIANGLE'
st_z_range(obj, ...)

## S3 method for class 'CIRCULARSTRING'
st_z_range(obj, ...)

## S3 method for class 'sfc'
st_z_range(obj, ...)

## S3 method for class 'sf'
st_z_range(obj, ...)

## S3 method for class 'numeric'
st_z_range(obj, ..., crs = NA_crs_)

NA_z_range_

```

Arguments

<code>x</code>	object of class <code>z_range</code>
<code>obj</code>	object to compute the z range from
<code>...</code>	ignored
<code>crs</code>	object of class <code>crs</code> , or argument to <code>st_crs</code> , specifying the CRS of this bounding box.

Format

An object of class `z_range` of length 2.

Details

`NA_z_range_` represents the missing value for a `z_range` object

Value

a numeric vector of length two, with zmin and zmax values; if obj is of class sf or sfc the object returned has a class z_range

Examples

```
a = st_sf(a = 1:2, geom = st_sfc(st_point(0:2), st_point(1:3)), crs = 4326)
st_z_range(a)
st_z_range(c(zmin = 16.1, zmax = 16.6), crs = st_crs(4326))
```

summary.sfc*Summarize simple feature column*

Description

Summarize simple feature column

Usage

```
## S3 method for class 'sfc'
summary(object, ..., maxsum = 7L, maxp4s = 10L)
```

Arguments

object	object of class sfc
...	ignored
maxsum	maximum number of classes to summarize the simple feature column to
maxp4s	maximum number of characters to print from the PROJ string

tibble*Summarize simple feature type for tibble*

Description

Summarize simple feature type for tibble

Summarize simple feature item for tibble

Usage

```
type_sum.sfc(x, ...)
obj_sum.sfc(x)
pillar_shaft.sfc(x, ...)
```

Arguments

- x object of class sfc
- ... ignored

Details

see [type_sum](#)

tidyverse

Tidyverse methods for sf objects (remove .sf suffix!)

Description

Tidyverse methods for sf objects. Geometries are sticky, use [as.data.frame](#) to let dplyr's own methods drop them. Use these methods without the .sf suffix and after loading the tidyverse package with the generic (or after loading package tidyverse).

Usage

```
dplyr_reconstruct.sf(data, template)

filter.sf(.data, ..., .dots)

arrange.sf(.data, ..., .dots)

group_by.sf(.data, ..., add = FALSE)

ungroup.sf(x, ...)

rowwise.sf(x, ...)

mutate.sf(.data, ..., .dots)

transmute.sf(.data, ..., .dots)

select.sf(.data, ...)

rename.sf(.data, ...)

slice.sf(.data, ..., .dots)

summarise.sf(.data, ..., .dots, do_union = TRUE, is_coverage = FALSE)

distinct.sf(.data, ..., .keep_all = FALSE)

gather.sf()
```

```
  data,
  key,
  value,
  ...,
  na.rm = FALSE,
  convert = FALSE,
  factor_key = FALSE
)

pivot_longer.sf(
  data,
  cols,
  names_to = "name",
  names_prefix = NULL,
  names_sep = NULL,
  names_pattern = NULL,
  names_ptypes = NULL,
  names_transform = NULL,
  names_repair = "check_unique",
  values_to = "value",
  values_drop_na = FALSE,
  values_ptypes = NULL,
  values_transform = NULL,
  ...
)

pivot_wider.sf(
  data,
  id_cols = NULL,
  names_from,
  names_prefix = "",
  names_sep = "_",
  names_glue = NULL,
  names_sort = FALSE,
  names_repair = "check_unique",
  values_from,
  values_fill = NULL,
  values_fn = NULL,
  ...
)

spread.sf(
  data,
  key,
  value,
  fill = NA,
  convert = FALSE,
  drop = TRUE,
```

```

    sep = NULL
  )

sample_n.sf(tbl, size, replace = FALSE, weight = NULL, .env = parent.frame())

sample_frac.sf(
  tbl,
  size = 1,
  replace = FALSE,
  weight = NULL,
  .env = parent.frame()
)

nest.sf(.data, ...)

separate.sf(
  data,
  col,
  into,
  sep = "[^[:alnum:]]+",
  remove = TRUE,
  convert = FALSE,
  extra = "warn",
  fill = "warn",
  ...
)

separate_rows.sf(data, ..., sep = "[^[:alnum:]]+", convert = FALSE)

unite.sf(data, col, ..., sep = "_", remove = TRUE)

unnest.sf(data, ..., .preserve = NULL)

inner_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)

left_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)

right_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)

full_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)

semi_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)

anti_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)

```

Arguments

data	see original function docs
------	----------------------------

template	see original function docs
.data	data object of class sf
...	other arguments
.dots	see corresponding function in package dplyr
add	see corresponding function in dplyr
x	A pair of data frames, data frame extensions (e.g. a tibble), or lazy data frames (e.g. from dbplyr or dtplyr). See <i>Methods</i> , below, for more details.
do_union	logical; in case <code>summary</code> does not create a geometry column, should geometries be created by unioning using st_union , or simply by combining using st_combine ? Using st_union resolves internal boundaries, but in case of unioning points, this will likely change the order of the points; see Details.
is_coverage	logical; if <code>do_union</code> is TRUE, use an optimized algorithm for features that form a polygonal coverage (have no overlaps)
.keep_all	see corresponding function in dplyr
key	see original function docs
value	see original function docs
na.rm	see original function docs
convert	see separate_rows
factor_key	see original function docs
cols	see original function docs
names_to	see original function docs
names_prefix	see original function docs
names_sep	see original function docs
names_pattern	see original function docs
names_ptypes	see original function docs
names_transform	see original function docs
names_repair	see original function docs
values_to	see original function docs
values_drop_na	see original function docs
values_ptypes	see original function docs
values_transform	see original function docs
id_cols	see original function docs
names_from	see original function docs
names_glue	see original function docs
names_sort	see original function docs
values_from	see original function docs
values_fill	see original function docs

values_fn	see original function docs
fill	see original function docs
drop	see original function docs
sep	see separate_rows
tbl	see original function docs
size	see original function docs
replace	see original function docs
weight	see original function docs
.env	see original function docs
col	see separate
into	see separate
remove	see separate
extra	see separate
.preserve	see unnest
y	A pair of data frames, data frame extensions (e.g. a tibble), or lazy data frames (e.g. from dbplyr or dtplyr). See <i>Methods</i> , below, for more details.
by	A character vector of variables to join by. If NULL, the default, <code>*_join()</code> will perform a natural join, using all variables in common across x and y. A message lists the variables so that you can check they're correct; suppress the message by supplying by explicitly. To join by different variables on x and y, use a named vector. For example, <code>by = c("a" = "b")</code> will match x\$a to y\$b. To join by multiple variables, use a vector with length > 1. For example, <code>by = c("a", "b")</code> will match x\$a to y\$a and x\$b to y\$b. Use a named vector to match different variables in x and y. For example, <code>by = c("a" = "b", "c" = "d")</code> will match x\$a to y\$b and x\$c to y\$d. To perform a cross-join, generating all combinations of x and y, use <code>by = character()</code> .
copy	If x and y are not from the same data source, and copy is TRUE, then y will be copied into the same src as x. This allows you to join tables across srcs, but it is a potentially expensive operation so you must opt into it.
suffix	If there are non-joined duplicate variables in x and y, these suffixes will be added to the output to disambiguate them. Should be a character vector of length 2.

Details

`select` keeps the geometry regardless whether it is selected or not; to deselect it, first pipe through `as.data.frame` to let dplyr's own `select` drop it.

In case one or more of the arguments (expressions) in the `summarise` call creates a geometry list-column, the first of these will be the (active) geometry of the returned object. If this is not the case, a geometry column is created, depending on the value of `do_union`.

In case `do_union` is FALSE, `summarise` will simply combine geometries using [c.sfg](#). When polygons sharing a boundary are combined, this leads to geometries that are invalid; see for instance <https://github.com/r-spatial/sf/issues/681>.

`distinct` gives distinct records for which all attributes and geometries are distinct; `st_equals` is used to find out which geometries are distinct.

`nest` assumes that a simple feature geometry list-column was among the columns that were nested.

Value

an object of class `sf`

Examples

```
if (require(dplyr, quietly = TRUE)) {
  nc = read_sf(system.file("shape/nc.shp", package="sf"))
  nc %>% filter(AREA > .1) %>% plot()
  # plot 10 smallest counties in grey:
  st_geometry(nc) %>% plot()
  nc %>% select(AREA) %>% arrange(AREA) %>% slice(1:10) %>% plot(add = TRUE, col = 'grey')
  title("the ten counties with smallest area")
  nc2 <- nc %>% mutate(area10 = AREA/10)
  nc %>% slice(1:2)
}
# plot 10 smallest counties in grey:
if (require(dplyr, quietly = TRUE)) {
  st_geometry(nc) %>% plot()
  nc %>% select(AREA) %>% arrange(AREA) %>% slice(1:10) %>% plot(add = TRUE, col = 'grey')
  title("the ten counties with smallest area")
}
if (require(dplyr, quietly = TRUE)) {
  nc$area_cl = cut(nc$AREA, c(0, .1, .12, .15, .25))
  nc %>% group_by(area_cl) %>% class()
}
if (require(dplyr, quietly = TRUE)) {
  nc2 <- nc %>% mutate(area10 = AREA/10)
}
if (require(dplyr, quietly = TRUE)) {
  nc %>% transmute(AREA = AREA/10, geometry = geometry) %>% class()
  nc %>% transmute(AREA = AREA/10) %>% class()
}
if (require(dplyr, quietly = TRUE)) {
  nc %>% select(SID74, SID79) %>% names()
  nc %>% select(SID74, SID79, geometry) %>% names()
  nc %>% select(SID74, SID79) %>% class()
  nc %>% select(SID74, SID79, geometry) %>% class()
}
if (require(dplyr, quietly = TRUE)) {
  nc2 <- nc %>% rename(area = AREA)
}
if (require(dplyr, quietly = TRUE)) {
  nc %>% slice(1:2)
}
if (require(dplyr, quietly = TRUE)) {
  nc$area_cl = cut(nc$AREA, c(0, .1, .12, .15, .25))
  nc.g <- nc %>% group_by(area_cl)
```

```

nc.g %>% summarise(mean(AREA))
nc.g %>% summarise(mean(AREA)) %>% plot(col = grey(3:6 / 7))
nc %>% as.data.frame %>% summarise(mean(AREA))
}
if (require(dplyr, quietly = TRUE)) {
  nc[c(1:100, 1:10), ] %>% distinct() %>% nrow()
}
if (require(tidyr, quietly = TRUE) && require(dplyr, quietly = TRUE)) {
  nc %>% select(SID74, SID79) %>% gather("VAR", "SID", -geometry) %>% summary()
}
if (require(tidyr, quietly = TRUE) && require(dplyr, quietly = TRUE)) {
  nc$row = 1:100 # needed for spread to work
  nc %>% select(SID74, SID79, geometry, row) %>%
    gather("VAR", "SID", -geometry, -row) %>%
    spread(VAR, SID) %>% head()
}
if (require(tidyr, quietly = TRUE) && require(dplyr, quietly = TRUE)) {
  storms.sf = st_as_sf(storms, coords = c("long", "lat"), crs = 4326)
  x <- storms.sf %>% group_by(name, year) %>% nest
  trs = lapply(x$data, function(tr) st_cast(st_combine(tr), "LINESTRING")[[1]]) %>%
    st_sfc(crs = 4326)
  trs.sf = st_sf(x[,1:2], trs)
  plot(trs.sf["year"], axes = TRUE)
}

```

transform.sf*transform method for sf objects***Description**

Can be used to create or modify attribute variables; for transforming geometries see [st_transform](#), and all other functions starting with [st_](#).

Usage

```
## S3 method for class 'sf'
transform(`_data`, ...)
```

Arguments

<code>_data</code>	object of class <code>sf</code>
<code>...</code>	Further arguments of the form <code>new_variable=expression</code>

Examples

```
a = data.frame(x1 = 1:3, x2 = 5:7)
st_geometry(a) = st_sfc(st_point(c(0,0)), st_point(c(1,1)), st_point(c(2,2)))
transform(a, x1_sq = x1^2)
transform(a, x1_x2 = x1*x2)
```

valid	<i>Check validity or make an invalid geometry valid</i>
-------	---

Description

Checks whether a geometry is valid, or makes an invalid geometry valid

Usage

```

st_is_valid(x, ...)

## S3 method for class 'sfc'
st_is_valid(x, ..., NA_on_exception = TRUE, reason = FALSE)

## S3 method for class 'sf'
st_is_valid(x, ...)

## S3 method for class 'sfg'
st_is_valid(x, ...)

st_make_valid(x, ...)

## S3 method for class 'sfg'
st_make_valid(x, ...)

## S3 method for class 'sfc'
st_make_valid(
  x,
  ...,
  oriented = FALSE,
  s2_options = s2::s2_options(snap = s2::s2_snap_precision(1e+07)),
  geos_method = "valid_structure",
  geos_keep_collapsed = TRUE
)

```

Arguments

- x object of class sfg, sfg or sf
- ... ignored
- NA_on_exception logical; if TRUE, for polygons that would otherwise raise a GEOS error (exception, e.g. for a POLYGON having more than zero but less than 4 points, or a LINESTRING having one point) return an NA rather than raising an error, and suppress warning messages (e.g. about self-intersection); if FALSE, regular GEOS errors and warnings will be emitted.
- reason logical; if TRUE, return a character with, for each geometry, the reason for invalidity, NA on exception, or "Valid Geometry" otherwise.

oriented	logical; only relevant if <code>st_is_longlat(x)</code> is TRUE; see <code>s2</code>
<code>s2_options</code>	only relevant if <code>st_is_longlat(x)</code> is TRUE; options for <code>s2_rebuild</code> , see <code>s2_options</code> and Details.
<code>geos_method</code>	character; either "valid_linework" (Original method, combines all rings into a set of noded lines and then extracts valid polygons from that linework) or "valid_structure" (Structured method, first makes all rings valid then merges shells and subtracts holes from shells to generate valid result. Assumes that holes and shells are correctly categorized.) (requires GEOS >= 3.10.1)
<code>geos_keep_collapsed</code>	logical; When this parameter is not set to FALSE, the "valid_structure" method will keep any component that has collapsed into a lower dimensionality. For example, a ring collapsing to a line, or a line collapsing to a point (requires GEOS >= 3.10.1)

Details

For projected geometries, `st_make_valid` uses the `lwgeom_makelvalid` method also used by the PostGIS command `ST_MakeValid` if the GEOS version linked to is smaller than 3.8.0, and otherwise the version shipped in GEOS; for geometries having ellipsoidal coordinates `s2::s2_rebuild` is being used.

if `s2_options` is not specified and `x` has a non-zero precision set, then this precision value will be used as the value in `s2_snap_precision`, passed on to `s2_options`, rather than the `1e7` default.

Value

`st_is_valid` returns a logical vector indicating for each geometries of `x` whether it is valid. `st_make_valid` returns an object with a topologically valid geometry.

Object of the same class as `x`

Examples

```
p1 = st_as_sfc("POLYGON((0 0, 0 10, 10 0, 10 10, 0 0))")
st_is_valid(p1)
st_is_valid(st_sfc(st_point(0:1), p1[[1]]), reason = TRUE)
library(sf)
x = st_sfc(st_polygon(list(rbind(c(0,0),c(0.5,0),c(0.5,0.5),c(0.5,0),c(1,0),c(1,1),c(0,1),c(0,0)))))
suppressWarnings(st_is_valid(x))
y = st_make_valid(x)
st_is_valid(y)
y %>% st_cast()
```

Description

vctrs methods for sf objects

Usage

```
vec_ptype2.sfc(x, y, ...)

## Default S3 method:
vec_ptype2.sfc(x, y, ..., x_arg = "x", y_arg = "y")

## S3 method for class 'sfc'
vec_ptype2.sfc(x, y, ...)

vec_cast.sfc(x, to, ...)

## S3 method for class 'sfc'
vec_cast.sfc(x, to, ...)

## Default S3 method:
vec_cast.sfc(x, to, ...)
```

Arguments

x	Vector types.
y	Vector types.
...	These dots are for future extensions and must be empty.
x_arg, y_arg	Argument names for x and y.
to	Type to cast to. If NULL, x will be returned as is.

Index

* **datasets**
 db_drivers, 10
 extension_map, 10
 prefix_map, 41
 st_agr, 55
 st_bbox, 64
 st_crs, 73
 st_m_range, 87
 st_z_range, 109

* **data**
 nc, 34
 .degAxis(stars), 53
 .get_layout(stars), 53
 .image_scale(stars), 53
 .image_scale_factor(stars), 53
 .stop_geos(internal), 31
 [.data.frame, 45, 46
 [.sf(sf), 44
 \$.crs(st_crs), 73

aggregate, 4, 5, 68, 93
aggregate(aggregate.sf), 4
aggregate.sf, 4
anti_join.sf(tidyverse), 112
arrange.sf(tidyverse), 112
as, 6
as.data.frame, 95, 112
as.matrix.sfg(st), 51
as.matrix.sgbp(sgbp), 50
as_Spatial(as), 6
as_Spatial(), 6

bind, 7
bind_cols, 7
bpy.colors, 40

c, 22
c.sfg, 5, 22, 116
c.sfg(st), 51
cbind, 7

cbind.sf(bind), 7
classIntervals, 39
coerce, crs, CRS-method(as), 6
coerce, sf, Spatial-method(as), 6
coerce, sfc, Spatial-method(as), 6
coerce, Spatial, sf-method(as), 6
coerce, Spatial, sfc-method(as), 6

data.frame, 7
db_drivers, 10
dbDataType, DBIObject, sf-method
 (dbDataType, PostgreSQLConnection, sf-method),
 8
dbDataType, PostgreSQLConnection, sf-method,
 8
dbWriteTable, 107, 108
dbWriteTable, DBIObject, character, sf-method
 (dbWriteTable, PostgreSQLConnection, character, sf-me
 8
dbWriteTable, PostgreSQLConnection, character, sf-method,
 8
dim.sgbp(sgbp), 50
distinct.sf, 20
distinct.sf(tidyverse), 112
dotsMethods, 7
dplyr_reconstruct.sf(tidyverse), 112

extension_map, 10

filter.sf(tidyverse), 112
format, 65
format.bbox(st_bbox), 64
format.crs(st_crs), 73
format.sfg(st), 51
full_join.sf(tidyverse), 112

gather.sf(tidyverse), 112
gdal, 10
gdal_addo, 14, 15
gdal_create(gdal), 10

gdal_crs (gdal), 10
gdal_extract (gdal), 10
gdal_inv_geotransform (gdal), 10
gdal_metadata (gdal), 10
gdal_polygonize (gdal), 10
gdal_rasterize (gdal), 10
gdal_read (gdal), 10
gdal_read_mdim (gdal), 10
gdal_subdatasets (gdal), 10
gdal_utils, 14, 15
gdal_write (gdal), 10
gdal_write_mdim (gdal), 10
geos_binary_ops, 16
geos_binary_pred, 19
geos_combine, 22
geos_measures, 23
geos_query, 25
geos Unary, 26
get_key_pos (plot), 35
getwd, 96
group_by_sf (tidyverse), 112

head.sfg (st), 51

Id, 94
inner_join.sf (tidyverse), 112
internal, 31
interpolate_aw, 31
intersect, 18
is.na.bbox (st_bbox), 64
is.na.crs (st_crs), 73
is.na.m_range (st_m_range), 87
is.na.z_range (st_z_range), 109
is_driver_available, 32
is_driver_can, 32
is_geometry_column, 33

left_join, 82
left_join.sf (tidyverse), 112

map, 59
merge, 82
merge.sf, 33
mutate.sf (tidyverse), 112

NA_agr_ (st_agr), 55
NA_bbox_ (st_bbox), 64
NA_crs_ (st_crs), 73
NA_m_range_ (st_m_range), 87

NA_z_range_ (st_z_range), 109
nc, 34
nest.sf (tidyverse), 112

obj_sum.sfc (tibble), 111
Ops, 34

par, 39, 40
pillar_shaft.sfc (tibble), 111
pivot_longer.sf (tidyverse), 112
pivot_wider.sf (tidyverse), 112
plot, 35, 38
plot.window, 39
plot_sf, 38
plot_sf (plot), 35
polypath, 39
prefix_map, 41
print.sf (sf), 44
print.sfg (st), 51
print.sgbp (sgbp), 50
proj_tools, 41

rainbow, 38
rawToHex, 43
rbind, 7
rbind.sf (bind), 7
read_sf (st_read), 93
recenter, 101
rename.sf (tidyverse), 112
right_join.sf (tidyverse), 112
rowwise.sf (tidyverse), 112
RPostgres::Postgres(), 107

s2, 43, 120
s2_distance, 23, 24
s2_distance_matrix, 23, 24
s2_options, 17, 18, 20, 120
s2_rebuild, 44, 120
sample, 99
sample_frac.sf (tidyverse), 112
sample_n.sf (tidyverse), 112
select.sf (tidyverse), 112
semi_join.sf (tidyverse), 112
separate, 116
separate.sf (tidyverse), 112
separate_rows, 115, 116
separate_rows.sf (tidyverse), 112
set_units, 24
setdiff, 18

sf, 4, 44, 74, 77, 78, 81, 86, 96, 115, 117
 sf-defunct, 46
 sf.colors (plot), 35
 sf_add_proj_units (sf_project), 49
 sf_extSoftVersion, 48
 sf_proj_info (st_transform), 102
 sf_proj_network (proj_tools), 41
 sf_proj_pipelines (proj_tools), 41
 sf_proj_search_paths (proj_tools), 41
 sf_project, 49, 104
 sf_use_s2 (s2), 43
 sfc, 47, 59, 74, 77, 78, 81, 86, 91
 sfc_GEOMETRYCOLLECTION (sfc), 47
 sfc_LINESTRING (sfc), 47
 sfc_MULTILINESTRING (sfc), 47
 sfc_MULTIPOINT (sfc), 47
 sfc_MULTIPOINT (sfc), 47
 sfc_POINT (sfc), 47
 sfc_POLYGON (sfc), 47
 sgbp, 21, 50
 slice.sf (tidyverse), 112
 spread.sf (tidyverse), 112
 st, 51
 st_agr, 55
 st_agr<- (st_agr), 55
 st_area (geos_measures), 23
 st_as_binary, 45, 48, 56, 62, 93
 st_as_grob, 57
 st_as_s2 (s2), 43
 st_as_sf, 47, 57, 95
 st_as_sfc, 45, 46, 60, 66
 st_as_text, 63
 st_axis_order (st_crs), 73
 st_bbox, 64, 72
 st_bind_cols (bind), 7
 st_boundary (geos_unary), 26
 st_buffer (geos_unary), 26
 st_cast, 24, 66, 70
 st_cast(), 6
 st_cast_sfc_default, 69
 st_centroid (geos_unary), 26
 st_collection_extract, 69
 st_combine, 115
 st_combine (geos_combine), 22
 st_contains, 83
 st_contains (geos_binary_pred), 19
 st_contains_properly, 83
 st_contains_properly
 (geos_binary_pred), 19
 st_convex_hull (geos_unary), 26
 st_coordinates, 71
 st_covered_by, 83
 st_covered_by (geos_binary_pred), 19
 st_covers, 83
 st_covers (geos_binary_pred), 19
 st_crop, 72
 st_crosses, 83
 st_crosses (geos_binary_pred), 19
 st_crs, 13, 45, 65, 73, 81, 88, 103, 110
 st_crs(), 62
 st_crs<- (st_crs), 73
 st_delete (st_write), 106
 st_difference, 23
 st_difference (geos_binary_ops), 16
 st_dimension, 24
 st_dimension (geos_query), 25
 st_disjoint, 83
 st_disjoint (geos_binary_pred), 19
 st_distance (geos_measures), 23
 st_drivers, 32, 75, 96, 108
 st_drop_geometry (st_geometry), 76
 st_equals, 83, 117
 st_equals (geos_binary_pred), 19
 st_equals_exact, 83
 st_equals_exact (geos_binary_pred), 19
 st_filter (st_join), 82
 st_geod_area, 24
 st_geod_distance, 24
 st_geod_segmentize, 28
 st_geometry, 76
 st_geometry<- (st_geometry), 76
 st_geometry_type, 78
 st_geometrycollection (st), 51
 st_graticule, 40, 78
 st_inscribed_circle (geos_unary), 26
 st_interpolate_aw (interpolate_aw), 31
 st_intersection, 21, 23, 98
 st_intersection (geos_binary_ops), 16
 st_intersects, 18, 57, 82, 83
 st_intersects (geos_binary_pred), 19
 st_is, 80
 st_is_empty (geos_query), 25
 st_is_longlat, 81
 st_is_simple (geos_query), 25
 st_is_valid (valid), 119
 st_is_within_distance, 83

st_is_within_distance
 (geos_binary_pred), 19
st_jitter, 81
st_join, 5, 82
st_layers, 15, 84, 96
st_length (geos_measures), 23
st_line_merge (geos Unary), 26
st_line_sample, 85
st_linestring (st), 51
st_m_range, 87
st_make_grid, 86
st_make_valid (valid), 119
st_minimum_rotated_rectangle
 (geos Unary), 26
st_multilinestring (st), 51
st_multipoint (st), 51
st_multipolygon (st), 51
st_nearest_feature, 83, 89, 91
st_nearest_points, 89, 90
st_node (geos Unary), 26
st_normalize, 92
st_overlaps, 83
st_overlaps (geos_binary_pred), 19
st_point, 59
st_point (st), 51
st_point_on_surface (geos Unary), 26
st_polygon (st), 51
st_polygonize (geos Unary), 26
st_precision, 92
st_precision<- (st_precision), 92
st_read, 45, 47, 48, 93
st_read_db (sf-defunct), 46
st_read_db, (sf-defunct), 46
st_relate, 21, 82, 97
st_reverse (geos Unary), 26
st_sample, 98
st_segmentize (geos Unary), 26
st_set_agr (st_agr), 55
st_set_crs (st_crs), 73
st_set_geometry (st_geometry), 76
st_set_precision (st_precision), 92
st_sf, 7, 58
st_sf (sf), 44
st_sfc (sfc), 47
st_shift_longitude, 101
st_simplify (geos Unary), 26
st_snap (geos_binary_ops), 16
st_sym_difference, 23
st_sym_difference (geos_binary_ops), 16
st_touches, 83
st_touches (geos_binary_pred), 19
st_transform, 102, 118
st_transform_proj, 104
st_triangulate (geos Unary), 26
st_union, 5, 18, 115
st_union (geos_combine), 22
st_viewport, 105
st_voronoi (geos Unary), 26
st_within, 83
st_within (geos_binary_pred), 19
st_wrap_dateline (st_transform), 102
st_write, 47, 93, 106
st_write_db (sf-defunct), 46
st_z_range, 109
st_zm, 108
st_zm(), 6
stars, 53
summarise, 68, 93
summarise (tidyverse), 112
summary.sfc, 111

t.sgbp (sgbp), 50
tibble, 111
tidyverse, 112
transform.sf, 118
transmute.sf (tidyverse), 112
type_sum, 112
type_sum.sfc (tibble), 111

ungroup.sf (tidyverse), 112
unite.sf (tidyverse), 112
unnest, 116
unnest.sf (tidyverse), 112

valid, 119
vctrs, 120
vec_cast.sfc (vctrs), 120
vec_ptype2.sfc (vctrs), 120
viewport, 105

write_sf, 93
write_sf (st_write), 106