

Package ‘tidyterra’

June 21, 2022

Title 'tidyverse' Methods and 'ggplot2' Utils for 'terra' Objects

Version 0.2.0

Description Extension of the 'tidyverse' for 'SpatRaster' and 'SpatVector' objects of the 'terra' package. It includes also new 'geom_' functions that provide a convenient way of visualizing 'terra' objects with 'ggplot2'.

License MIT + file LICENSE

URL <https://dieghernan.github.io/tidyterra/>,
<https://github.com/dieghernan/tidyterra>

BugReports <https://github.com/dieghernan/tidyterra/issues>

Depends R (>= 3.6.0)

Imports cli (>= 3.0.0), crayon, data.table, dplyr, ggplot2 (>= 3.1.0),
magrittr, rlang, scales, sf (>= 1.0.0), terra (>= 1.5-12),
tibble, tidy

Suggests isoband, knitr, lifecycle, maptiles, rmarkdown, s2, testthat
(>= 3.0.0), vdiff

VignetteBuilder knitr

Config/testthat/edition 3

Config/testthat/parallel true

Encoding UTF-8

LazyData true

RoxygenNote 7.2.0

NeedsCompilation no

Author Diego Hernangómez [aut, cre, cph]
(<<https://orcid.org/0000-0001-8457-4658>>),
Dewey Dunnington [ctb] (<<https://orcid.org/0000-0002-9415-4582>>, for
ggspatial code)

Maintainer Diego Hernangómez <diego.hernangomezherrero@gmail.com>

Repository CRAN

Date/Publication 2022-06-21 07:30:02 UTC

R topics documented:

as_coordinates	2
as_spatraster	3
as_tibble	4
autoplot	6
compare_spatrasters	8
cross_blended_hypsometric_tints_db	9
drop_na	10
filter	11
geom_spatraster	13
geom_spatraster_rgb	16
geom_spat_contour	18
ggspatvector	22
hypsometric_tints_db	24
is_regular_grid	25
mutate	26
pull	28
pull_crs	30
relocate	31
rename	33
replace_na	34
scale_fill_cross_blended	35
scale_fill_hypso	41
scale_fill_terrain	47
scale_fill_whitebox	49
scale_fill_wiki	51
select	53
slice	55
volcano2	59

Index **61**

as_coordinates	<i>Get cell number, row and column from a SpatRaster</i>
----------------	--

Description

as_coordinates() can be used to obtain the position of each cell on the SpatRaster matrix.

Usage

```
as_coordinates(x, as.raster = FALSE)
```

Arguments

x	A SpatRaster object
as.raster	If TRUE, the result is a SpatRaster object with three layers indicating the position of each cell (cell number, row and column).

Value

A tibble or a `SpatRaster` (if `as.raster = TRUE`) with the same number of rows (or cells) than the number of cells in `x`.

When `as.raster = TRUE` the resulting `SpatRaster` has the same crs, extension and resolution than `x`

See Also

[slice.SpatRaster\(\)](#)

Coercing objects: [as_spatraster\(\)](#), [as_tibble\(\)](#)

Examples

```
library(terra)

f <- system.file("extdata/cyl_temp.tif", package = "tidyterra")

r <- rast(f)

as_coordinates(r)
as_coordinates(r, as.raster = TRUE)

as_coordinates(r, as.raster = TRUE) %>% plot()
```

as_spatraster

Coerce a data frame to SpatRaster

Description

`as_spatraster()` turns an existing data frame or tibble, into a `SpatRaster`. This is a wrapper of [terra::rast\(\)](#) S4 method for `data.frame`.

Usage

```
as_spatraster(x, ..., xycols = 1:2, crs = "", digits = 6)
```

Arguments

<code>x</code>	A tibble or data frame.
<code>...</code>	additional arguments passed on to terra::rast() .
<code>xycols</code>	A vector of integers of length 2 determining the position of the columns that hold the x and y coordinates.
<code>crs</code>	A crs on several formats (PROJ.4, WKT, EPSG code, ..) or and spatial object from <code>sf</code> or <code>terra</code> that includes the target coordinate reference system. See pull_crs() . See Details .
<code>digits</code>	integer to set the precision for detecting whether points are on a regular grid (a low number of digits is a low precision).

Details

[Questioning] If no crs is provided and the tibble has been created with the method `as_tibble.SpatRaster()`, the crs is inferred from `attr(x, "crs")`.

Value

A `SpatRaster`.

terra equivalent

`terra::rast()`

See Also

`pull_crs()`

Coercing objects: `as_coordinates()`, `as_tibble()`

Examples

```
library(terra)

r <- rast(matrix(1:90, ncol = 3), crs = "epsg:3857")

r

# Create tibble
as_tbl <- as_tibble(r, xy = TRUE)

as_tbl

# From tibble
newrast <- as_spatraster(as_tbl, crs = "epsg:3857")
newrast
```

as_tibble

Coerce a Spat object to data frames*

Description

`as_tibble()` method for `SpatRaster` and `SpatVector`.

Usage

```
## S3 method for class 'SpatRaster'
as_tibble(x, ..., xy = FALSE, na.rm = FALSE, .name_repair = "unique")

## S3 method for class 'SpatVector'
as_tibble(x, ..., .name_repair = "unique")
```

Arguments

x	A SpatRaster created with <code>terra::rast()</code> or a SpatVector created with <code>terra::vect()</code> .
...	Arguments passed on to <code>terra::as.data.frame()</code>
xy	logical. If TRUE, the coordinates of each raster cell are included
na.rm	logical. If TRUE, cells that have a NA value in at least one layer are removed
.name_repair	Treatment of problematic column names: <ul style="list-style-type: none"> • "minimal": No name repair or checks, beyond basic existence, • "unique": Make sure names are unique and not empty, • "check_unique": (default value), no name repair, but check they are unique, • "universal": Make the names unique and syntactic • a function: apply custom name repair (e.g., <code>.name_repair = make.names</code> for names in the style of base R). • A purrr-style anonymous function, see <code>rlang::as_function()</code>

Value

A tibble.

terra equivalent

`terra::as.data.frame()`

Methods

Implementation of the **generic** `tibble::as_tibble()` function.

SpatRaster:

[Questioning] The tibble is returned with an attribute including the crs of the initial object in WKT format (see `pull_crs()`).

About layer names

When coercing SpatRaster objects to data frames, x and y names are reserved for geographic coordinates of each cell of the raster. It should be also noted that terra allows layers with duplicated names.

In the process of coercing a SpatRaster to a tibble, tidyterra may rename the layers of your SpatRaster for overcoming this issue. Specifically, layers may be renamed on the following cases:

- Layers with duplicated names
- When coercing to a tibble, if `xy = TRUE`, layers named x or y would be renamed.
- When working with tidyverse methods (i.e. `filter.SpatRaster()`), the latter would happen as well.

tidyterra would display a message informing of the changes on the names of the layer.

See Also

[tibble::as_tibble\(\)](#), [terra::as.data.frame\(\)](#)

Coercing objects: [as_coordinates\(\)](#), [as_spatraster\(\)](#)

Examples

```
library(terra)
# SpatRaster
f <- system.file("extdata/cyl_temp.tif", package = "tidyterra")
r <- rast(f)

as_tibble(r, na.rm = TRUE)

as_tibble(r, xy = TRUE)

# SpatVector

f <- system.file("extdata/cyl.gpkg", package = "tidyterra")
v <- vect(f)

as_tibble(v)
```

autoplot

Create a complete ggplot for SpatRasters

Description

`autoplot()` uses `ggplot2` to draw plots as the ones produced by [terra::plot\(\)](#)/[terra::plotRGB\(\)](#) in a single command.

Usage

```
## S3 method for class 'SpatRaster'
autoplot(
  object,
  mapping = aes(),
  rgb = FALSE,
  facets = TRUE,
  nrow = NULL,
  ncol = 2,
  ...
)
```

Arguments

object	A SpatRaster object.
mapping	Set of aesthetic mappings created by <code>aes()</code> or <code>aes_()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
rgb	Logical. Should be plotted as a RGB image?
facets	Logical. Should facets be displayed?
nrow, ncol	Number of rows and columns on the facet.
...	other arguments passed to <code>geom_spatraster()</code> or <code>geom_spatraster_rgb()</code> .

Details

Implementation of `ggplot2::autoplot()`.

Value

A ggplot2 layer

See Also

`ggplot2::autoplot()`

Other ggplot2 utils: `geom_spat_contour`, `geom_spatraster_rgb()`, `geom_spatraster()`, `ggspatvector`

Examples

```
file_path <- system.file("extdata/cyl_temp.tif", package = "tidyterra")

library(terra)
temp <- rast(file_path)

library(ggplot2)
autoplot(temp)

# With a tile

system.file("extdata/cyl_tile.tif", package = "tidyterra") %>%
  rast() %>%
  autoplot(rgb = TRUE)
```

compare_spatrasters *Compare attributes of two SpatRasters*

Description

Two SpatRasters are compatible (in terms of combining layers) if the crs, extent and resolution are similar. In those cases you can combine the SpatRasters simply as `c(x, y)`.

This function compares those attributes informing of the results. See **Solving issues** section for minimal guidance.

Usage

```
compare_spatrasters(x, y, digits = 6)
```

Arguments

<code>x, y</code>	SpatRaster objects
<code>digits</code>	Integer to set the precision for comparing the extent and the resolution.

Value

A invisible logical TRUE/FALSE indicating if the SpatRasters are compatible, plus an informative message flagging the issues found (if any).

Solving issues

On **non-equal crs**, try `terra::project()`. On **non-equal extent** try `terra::resample()`. On **non-equal resolution** you can try `terra::resample()`, `terra::aggregate()` or `terra::disagg()`.

See Also

Other helpers: `is_regular_grid()`, `pull_crs()`

Examples

```
library(terra)

x <- rast(matrix(1:90, ncol = 3), crs = "epsg:3857")

# Nothing
compare_spatrasters(x, x)

# Different crs
y_nocrs <- x
crs(y_nocrs) <- NA

compare_spatrasters(x, y_nocrs)
```



```
# Different extent
compare_spatrasters(x, x[1:10, ], drop = FALSE])

# Different resolution
y_newres <- x

res(y_newres) <- res(x) / 2
compare_spatrasters(x, y_newres)

# Everything

compare_spatrasters(x, project(x, "epsg:3035"))
```

cross_bledned_hypsometric_tints_db

Cross-blended Hypsometric Tints

Description

A tibble including the color map of 4 gradient palettes. All the palettes includes also a definition of colors limits in terms of elevation (meters), that can be used with `ggplot2::scale_fill_gradientn()`.

Format

A tibble of 41 rows and 6 columns. with the following fields:

- **pal**: Name of the palette.
- **limit**: Recommended elevation limit (in meters) for each color.
- **r,g,b**: Value of the red, green and blue channel (RGB color mode).
- **hex**: Hex code of the color.

Details

From Patterson & Jenny (2011):

More recently, the role and design of hypsometric tints have come under scrutiny. One reason for this is the concern that people misread elevation colors as climate or vegetation information. Cross-blended hypsometric tints, introduced in 2009, are a partial solution to this problem. They use variable lowland colors customized to match the differing natural environments of world regions, which merge into one another.

Source

Derived from Patterson, T., & Jenny, B. (2011). The Development and Rationale of Cross-blended Hypsometric Tints. *Cartographic Perspectives*, (69), 31 - 46. doi:10.14714/CP69.20.

See Also

[scale_fill_cross_bledned_c\(\)](#)

Other datasets: [hypsometric_tints_db](#), [volcano2](#)

Examples

```

data("cross_blended_hypsometric_tints_db")

cross_blended_hypsometric_tints_db

# Select a palette
warm <- cross_blended_hypsometric_tints_db %>%
  filter(pal == "warm_humid")

f <- system.file("extdata/asia.tif", package = "tidyterra")
r <- terra::rast(f)

library(ggplot2)

p <- ggplot() +
  geom_spatraster(data = r) +
  labs(fill = "elevation")

p +
  scale_fill_gradientn(colors = warm$hex)

# Use with limits
p +
  scale_fill_gradientn(
    colors = warm$hex,
    values = scales::rescale(warm$limit),
    limit = range(warm$limit),
    na.value = "lightblue"
  )

```

drop_na*Drop attributes of SpatVector objects containing missing values*

Description

drop_na() method drops geometries where any attribute specified by ... contains a missing value.

Usage

```

## S3 method for class 'SpatVector'
drop_na(data, ...)

```

Arguments

data	A SpatVector created with <code>terra::vect()</code> .
...	<code>tidy-select</code> Attributes to inspect for missing values. If empty, all attributes are used.

Value

A `Spat*` object of the same class than `.data`. See **Methods**.

Methods

Implementation of the generic `tidyr::drop_na()` function.

SpatVector:

The implementation of this method is performed on a by-attribute basis, meaning that NAs are assessed on the attributes (columns) of each vector (rows). The result is a `SpatVector` with potentially less geometries than the input

See Also

`tidyr::drop_na()`. **[Questioning]** A method for `SpatRaster` is also available, see `drop_na.SpatRaster()`.

Other `tidyr` methods: `replace_na()`

Examples

```
library(terra)

f <- system.file("extdata/cyl.gpkg", package = "tidyterra")

v <- terra::vect(f)

# Add NAs
v <- v %>% mutate(iso2 = ifelse(cpro <= "09", NA, cpro))

# Init
plot(v, col = "red")

# Mask with lyr.1
v %>%
  drop_na(iso2) %>%
  plot(col = "red")
```

 filter

Subset cells/geometries of Spat objects*

Description

The `filter()` function is used to subset `Spat*` objects, retaining all cells/geometries that satisfy your conditions. To be retained, the cell/geometry must produce a value of `TRUE` for all conditions.

It is possible to filter a `SpatRaster` by its geographic coordinates. You need to use `filter(.data, x > 42)`. Note that `x` and `y` are reserved names on `terra`, since they refer to the geographic coordinates of the layer.

See **Examples** and section About layer names on `as_tibble()`.

Usage

```
## S3 method for class 'SpatRaster'
filter(.data, ..., .preserve = FALSE, .keep_extent = TRUE)

## S3 method for class 'SpatVector'
filter(.data, ..., .preserve = FALSE)
```

Arguments

<code>.data</code>	A <code>SpatRaster</code> created with <code>terra::rast()</code> or a <code>SpatVector</code> created with <code>terra::vect()</code> .
<code>...</code>	data-masking Expressions that return a logical value, and are defined in terms of the layers/attributes in <code>.data</code> . If multiple expressions are included, they are combined with the <code>&</code> operator. Only cells/geometries for which all conditions evaluate to <code>TRUE</code> are kept. See Methods .
<code>.preserve</code>	Ignored for <code>Spat*</code> objects.
<code>.keep_extent</code>	Should the extent of the resulting <code>SpatRaster</code> be kept? On <code>FALSE</code> , <code>terra::trim()</code> is called so the extent of the result may be different of the extent of the output. See also <code>drop_na.SpatRaster()</code> .

Value

A `Spat*` object of the same class than `.data`. See **Methods**.

Methods

Implementation of the generic `dplyr::filter()` function.

SpatRaster:

Cells that do not fulfill the conditions on `...` are returned with value `NA`. On a multi-layer `SpatRaster` the `NA` is propagated across all the layers.

If `.keep_extent = TRUE` the returning `SpatRaster` has the same crs, extent, resolution and hence the same number of cells than `.data`. If `.keep_extent = FALSE` the outer `NA` cells are trimmed with `terra::trim()`, so the extent and number of cells may differ. The output would present in any case the same crs and resolution than `.data`.

`x` and `y` variables (i.e. the longitude and latitude of the `SpatRaster`) are also available internally for filtering. See **Examples**.

SpatVector:

This method relies on the implementation of `dplyr::filter()` method on the `sf` package. The result is a `SpatVector` with all the geometries that produce a value of `TRUE` for all conditions.

See Also

`dplyr::filter()`

Other `dplyr` methods: `mutate()`, `pull()`, `relocate()`, `rename()`, `select()`, `slice()`

Other single table verbs: `mutate()`, `rename()`, `select()`, `slice()`

Examples

```
library(terra)
f <- system.file("extdata/cyl_temp.tif", package = "tidyterra")

r <- rast(f) %>% select(tavg_04)

plot(r)

# Filter temps
r_f <- r %>% filter(tavg_04 > 11.5)

# Extent is kept
plot(r_f)

# Filter temps and extent
r_f2 <- r %>% filter(tavg_04 > 11.5, .keep_extent = FALSE)

# Extent has changed
plot(r_f2)

# Filter by geographic coordinates
r2 <- project(r, "epsg:4326")

r2 %>% plot()

r2 %>%
  filter(
    x > -4,
    x < -2,
    y > 42
  ) %>%
  plot()
```

Description

This geom is used to visualise SpatRaster objects (see [terra::rast\(\)](#)). The geom is designed for visualise the object by layers, as [terra::plot\(\)](#) does.

For plotting SpatRaster objects as map tiles (i.e. RGB SpatRaster), use [geom_spatraster_rgb\(\)](#).

The underlying implementation is based on [ggplot2::geom_raster\(\)](#).

Usage

```
geom_spatraster(
  mapping = aes(),
  data,
  na.rm = TRUE,
  show.legend = NA,
  inherit.aes = FALSE,
  interpolate = FALSE,
  maxcell = 5e+05,
  ...
)
```

Arguments

mapping	Set of aesthetic mappings created by aes() or aes_() . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	A <code>SpatRaster</code> object.
na.rm	If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed.
show.legend	logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. It can also be a named logical vector to finely select the aesthetics to display.
inherit.aes	If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. borders() .
interpolate	If <code>TRUE</code> interpolate linearly, if <code>FALSE</code> (the default) don't interpolate.
maxcell	positive integer. Maximum number of cells to use for the plot.
...	Other arguments passed on to layer() . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired <code>geom/stat</code> .

Value

A `ggplot2` layer

terra equivalent

[terra::plot\(\)](#)

Coords

When the `SpatRaster` does not present a crs (i.e., `terra::crs(rast) == ""`) the geom does not make any assumption on the scales.

On `SpatRaster` that have a crs, the geom uses [ggplot2::coord_sf\(\)](#) to adjust the scales. That means that also the **SpatRaster may be reprojected**.

Aesthetics

geom_spatraster() understands the following aesthetics:

- fill
- alpha

If fill is not provided, geom_spatraster() creates a ggplot2 layer with all the layers of the SpatRaster object. Use facet_wrap(~lyr) to display properly the SpatRaster layers.

If fill is used, it should contain the name of one layer that is present on the SpatRaster (i.e. geom_spatraster(data = rast, aes(fill = <name_of_lyr>)). Names of the layers can be retrieved using names(rast).

For alpha use computed variable. See section **Computed variables**.

Facets

You can use facet_wrap(~lyr) for creating a faceted plot by each layer of the SpatRaster object. See [ggplot2::facet_wrap\(\)](#) for details.

Computed variables

This geom computes internally some variables that are available for use as aesthetics, using (for example) aes(alpha = after_stat(value)) (see [ggplot2::after_stat\(\)](#)).

value Values of the SpatRaster.

lyr Name of the layer.

Source

Based on the layer_spatial() implementation on ggspatial package. Thanks to [Dewey Dunnington](#) and [ggspatial contributors](#).

See Also

[ggplot2::geom_raster\(\)](#), [ggplot2::coord_sf\(\)](#), [ggplot2::facet_wrap\(\)](#)

Other ggplot2 utils: [autoplot\(\)](#), [geom_spat_contour](#), [geom_spatraster_rgb\(\)](#), [ggspatvector](#)

Examples

```
# Avg temperature on spring in Castille and Leon (Spain)
file_path <- system.file("extdata/cyl_temp.tif", package = "tidyterra")

library(terra)
temp_rast <- rast(file_path)

library(ggplot2)

# Display a single layer
names(temp_rast)
```

```
ggplot() +
  geom_spatraster(data = temp_rast, aes(fill = tavg_04)) +
  # You can use coord_sf
  coord_sf(crs = 3857) +
  scale_fill_hypso_c()

# Display facets
ggplot() +
  geom_spatraster(data = temp_rast) +
  facet_wrap(~lyr, ncol = 2) +
  scale_fill_hypso_b()

# Non spatial rasters

no_crs <- rast(crs = NA, extent = c(0, 100, 0, 100), nlyr = 1)
values(no_crs) <- seq_len(ncell(no_crs))

ggplot() +
  geom_spatraster(data = no_crs)

# Downsample

ggplot() +
  geom_spatraster(data = no_crs, maxcell = 25)
```

geom_spatraster_rgb *Visualise SpatRaster objects as images*

Description

This geom is used to visualise `SpatRaster` objects (see `terra::rast()`) as RGB images. The layers are combined such that they represent the red, green and blue channel.

For plotting `SpatRaster` objects by layer values use `geom_spatraster()`.

The underlying implementation is based on `ggplot2::geom_raster()`.

Usage

```
geom_spatraster_rgb(
  mapping = aes(),
  data,
  interpolate = TRUE,
  r = 1,
  g = 2,
  b = 3,
```



```

    alpha = 1,
    maxcell = 5e+05,
    max_col_value = 255,
    ...
  )

```

Arguments

mapping	Ignored.
data	A SpatRaster object.
interpolate	If TRUE interpolate linearly, if FALSE (the default) don't interpolate.
r, g, b	Integer representing the number of layer of data to be considered as the red (r), green (g) and blue (b) channel.
alpha	The alpha transparency, a number in [0,1], see argument alpha in hsv .
maxcell	positive integer. Maximum number of cells to use for the plot.
max_col_value	Number giving the maximum of the color values range. When this is 255 (the default), the result is computed most efficiently. See grDevices::rgb() .
...	Other arguments passed on to layer() . These are often aesthetics, used to set an aesthetic to a fixed value, like colour = "red" or size = 3. They may also be parameters to the paired geom/stat.

Value

A ggplot2 layer

terra equivalent

[terra::plotRGB\(\)](#)

Coords

When the SpatRaster does not present a crs (i.e., `terra::crs(rast) == ""`) the geom does not make any assumption on the scales.

On SpatRaster that have a crs, the geom uses [ggplot2::coord_sf\(\)](#) to adjust the scales. That means that also the SpatRaster may be reprojected.

Aesthetics

No `aes()` is required. In fact, `aes()` will be ignored.

Source

Based on the `layer_spatial()` implementation on `ggspatial` package. Thanks to [Dewey Dunnington](#) and [ggspatial contributors](#).

See Also

`ggplot2::geom_raster()`, `ggplot2::coord_sf()`, `grDevices::rgb()`. You can get also RGB tiles from the `maptiles` package, see `maptiles::get_tiles()`.

Other `ggplot2` utils: `autoplot()`, `geom_spat_contour`, `geom_spatraster()`, `ggspatvector`

Examples

```
# Tile of Castille and Leon (Spain) from OpenStreetMap
file_path <- system.file("extdata/cyl_tile.tif", package = "tidyterra")

library(terra)
tile <- rast(file_path)

library(ggplot2)

ggplot() +
  geom_spatraster_rgb(data = tile) +
  # You can use coord_sf
  coord_sf(crs = 3035)

# Combine with sf objects
vect_path <- system.file("extdata/cyl.gpkg", package = "tidyterra")

cyl_sf <- sf::st_read(vect_path)

ggplot(cyl_sf) +
  geom_spatraster_rgb(data = tile) +
  geom_sf(aes(fill = iso2)) +
  coord_sf(crs = 3857) +
  scale_fill_viridis_d(alpha = 0.7)
```

`geom_spat_contour` *Plot SpatRaster contours*

Description

These geoms create contours of `SpatRaster` objects. To specify a valid surface, you should specify the layer on `aes(z = layer_name)`, otherwise all the layers would be consider for creating contours. See also **Facets** section.

The underlying implementation is based on `ggplot2::geom_contour()`.

Usage

```
geom_spatraster_contour(
  mapping = NULL,
  data,
  ...,
  maxcell = 5e+05,
  bins = NULL,
  binwidth = NULL,
  breaks = NULL,
  na.rm = TRUE,
  show.legend = NA,
  inherit.aes = TRUE
)

geom_spatraster_contour_filled(
  mapping = NULL,
  data,
  ...,
  maxcell = 5e+05,
  bins = NULL,
  binwidth = NULL,
  breaks = NULL,
  na.rm = TRUE,
  show.legend = NA,
  inherit.aes = TRUE
)
```

Arguments

mapping	Set of aesthetic mappings created by <code>aes()</code> or <code>aes_()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	A <code>SpatRaster</code> object.
...	Other arguments passed on to <code>layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired <code>geom/stat</code> .
maxcell	positive integer. Maximum number of cells to use for the plot.
bins	Number of contour bins. Overridden by <code>binwidth</code> .
binwidth	The width of the contour bins. Overridden by <code>breaks</code> .
breaks	One of: <ul style="list-style-type: none"> • Numeric vector to set the contour breaks • A function that takes the range of the data and <code>binwidth</code> as input and returns breaks as output. A function can be created from a formula (e.g. <code>~fullseq(x, .y)</code>). Overrides <code>binwidth</code> and <code>bins</code> . By default, this is a vector of length ten with <code>pretty()</code> breaks.

<code>na.rm</code>	If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed.
<code>show.legend</code>	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display.
<code>inherit.aes</code>	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> .

Value

A `ggplot2` layer

terra equivalent

`terra::contour()`

Aesthetics

`geom_spatraster_contour()` understands the following aesthetics:

- `z`
- `alpha`
- `colour`
- `linetype`
- `size`

Additionally, `geom_spatraster_contour_filled()` understands also the following aesthetics, as well as the ones listed above:

- `fill`

Check `ggplot2::geom_contour()` for more info.

Computed variables

This geom computes internally some variables that are available for use as aesthetics, using (for example) `aes(color = after_stat(<computed>))` (see `ggplot2::after_stat()`).

`level` Height of contour. For contour lines, this is numeric vector that represents bin boundaries. For contour bands, this is an ordered factor that represents bin ranges.

`nlevel` Height of contour, scaled to maximum of 1.

`lyr` Name of the layer.

`level_low`, `level_high`, `level_mid` (contour bands only) Lower and upper bin boundaries for each band, as well the mid point between the boundaries.

Coords

When the `SpatRaster` does not present a crs (i.e., `terra::crs(rast) == ""`) the geom does not make any assumption on the scales.

On `SpatRaster` that have a crs, the geom uses `ggplot2::coord_sf()` to adjust the scales. That means that also the **SpatRaster may be reprojected**.

Facets

You can use `facet_wrap(~lyr)` for creating a faceted plot by each layer of the `SpatRaster` object. See `ggplot2::facet_wrap()` for details.

See Also

[ggplot2::geom_contour\(\)](#)

Other `ggplot2` utils: [autoplot\(\)](#), [geom_spatraster_rgb\(\)](#), [geom_spatraster\(\)](#), [ggspatvector](#)

Examples

```
library(terra)

# Raster
f <- system.file("extdata/volcano2.tif", package = "tidyterra")
r <- rast(f)

library(ggplot2)

ggplot() +
  geom_spatraster_contour(data = r)

ggplot() +
  geom_spatraster_contour(
    data = r, aes(color = after_stat(level)),
    binwidth = 1,
    size = 0.4
  ) +
  scale_color_gradientn(
    colours = hcl.colors(20, "Inferno"),
    guide = guide_coloursteps()
  ) +
  theme_minimal()

# Filled with breaks
ggplot() +
  geom_spatraster_contour_filled(data = r, breaks = seq(80, 200, 10)) +
  scale_fill_hypso_d()

# Both lines and contours
ggplot() +
```

```
geom_spatraster_contour_filled(
  data = r, breaks = seq(80, 200, 10),
  alpha = .7
) +
geom_spatraster_contour(
  data = r, breaks = seq(80, 200, 2.5),
  color = "grey30",
  size = 0.1
) +
scale_fill_hypso_d()
```

ggspatvector

Visualise SpatVector objects

Description

This geom is used to visualise SpatVector objects (see `terra::vect()`). For simple plots, you will only need `geom_spatvector()`. For text and labels, you can use `geom_spatvector_text()` and `geom_spatvector_label()`.

The underlying implementation is based on `ggplot2::geom_sf()`.

Usage

```
geom_spatvector(mapping = aes(), data, na.rm = FALSE, show.legend = NA, ...)
```

```
geom_spatvector_label(
  mapping = aes(),
  data,
  na.rm = FALSE,
  show.legend = NA,
  ...
)
```

```
geom_spatvector_text(
  mapping = aes(),
  data,
  na.rm = FALSE,
  show.legend = NA,
  ...
)
```

Arguments

mapping	Set of aesthetic mappings created by <code>aes()</code> or <code>aes_()</code> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
---------	---

<code>data</code>	A <code>SpatVector</code> object, see <code>terra::vect()</code> .
<code>na.rm</code>	If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed.
<code>show.legend</code>	logical. Should this layer be included in the legends? <code>NA</code> , the default, includes if any aesthetics are mapped. <code>FALSE</code> never includes, and <code>TRUE</code> always includes. You can also set this to one of "polygon", "line", and "point" to override the default legend.
<code>...</code>	Other arguments passed on to <code>ggplot2::geom_sf()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> .

Details

See `ggplot2::geom_sf()` for details on aesthetics, etc.

Value

A `ggplot2` layer

terra equivalent

`terra::plot()`

See Also

`ggplot2::geom_sf()`

Other `ggplot2` utils: `autoplot()`, `geom_spat_contour`, `geom_spatraster_rgb()`, `geom_spatraster()`

Examples

```
# Create a SpatVector

extfile <- system.file("extdata/cyl.gpkg", package = "tidyterra")

cyl <- terra::vect(extfile)
class(cyl)
#' # Create a SpatVector

extfile <- system.file("extdata/cyl.gpkg", package = "tidyterra")

cyl <- terra::vect(extfile)
class(cyl)

library(ggplot2)

ggplot() +
  geom_spatvector(data = cyl)

# Avoid this!
if (FALSE) {
```

```
# Would produce an error

ggplot(cyl) +
  geom_spatvector()
}
# With params

ggplot() +
  geom_spatvector(data = cyl, aes(fill = name), color = NA) +
  scale_fill_viridis_d() +
  coord_sf(crs = 3857)

# Add labels
ggplot() +
  geom_spatvector(data = cyl, aes(fill = name), color = NA) +
  geom_spatvector_text(
    data = cyl, aes(label = iso2), fontface = "bold", size = 3,
    color = "red"
  ) +
  scale_fill_viridis_d(alpha = 0.4) +
  coord_sf(crs = 3857)
```

hypsometric_tints_db *Hypsometric palettes database*

Description

A tibble including the color map of 24 gradient palettes. All the palettes includes also a definition of colors limits in terms of elevation (meters), that can be used with `ggplot2::scale_fill_gradientn()`.

Format

A tibble of 829 rows and 6 columns. with the following fields:

- **pal**: Name of the palette.
- **limit**: Recommended elevation limit (in meters) for each color.
- **r,g,b**: Value of the red, green and blue channel (RGB color mode).
- **hex**: Hex code of the color.

Source

cpt-city: <http://soliton.vm.bytemark.co.uk/pub/cpt-city/>.

See Also

[scale_fill_hypso_c\(\)](#)

Other datasets: [cross_blended_hypsometric_tints_db](#), [volcano2](#)

Examples

```

data("hypsometric_tints_db")

hypsometric_tints_db

# Select a palette
wikicolors <- hypsometric_tints_db %>%
  filter(pal == "wiki-2.0")

f <- system.file("extdata/asia.tif", package = "tidyterra")
r <- terra::rast(f)

library(ggplot2)

p <- ggplot() +
  geom_spatraster(data = r) +
  labs(fill = "elevation")

p +
  scale_fill_gradientn(colors = wikicolors$hex)

# Use with limits
p +
  scale_fill_gradientn(
    colors = wikicolors$hex,
    values = scales::rescale(wikicolors$limit),
    limit = range(wikicolors$limit)
  )

```

is_regular_grid

Check if x and y positions conforms a regular grid

Description

Assess if the coordinates x,y of an object conforms a regular grid. This function is called by its side effects.

This function is internally called by [as_spatraster\(\)](#).

Usage

```
is_regular_grid(xy, digits = 6)
```

Arguments

xy	A matrix, data frame or tibble of at least two columns representing x and y coordinates.
digits	integer to set the precision for detecting whether points are on a regular grid (a low number of digits is a low precision).

Value

`invisible()` if is regular or an error message otherwise

See Also

[as_spatraster\(\)](#)

Other helpers: [compare_spatrasters\(\)](#), [pull_crs\(\)](#)

Examples

```
p <- matrix(1:90, nrow = 45, ncol = 2)

is_regular_grid(p)

# Jitter location
set.seed(1234)
jitter <- runif(length(p)) / 10e4
p_jitter <- p + jitter

# Need to adjust digits
is_regular_grid(p_jitter, digits = 4)
```

mutate	<i>Create, modify, and delete cell values/layers/attributes of Spat* objects</i>
--------	--

Description

`mutate()` adds new layers/attributes and preserves existing ones on a Spat* object. `transmute()` adds new layers/attributes and drops existing ones. New variables overwrite existing variables of the same name. Variables can be removed by setting their value to NULL.

Usage

```
## S3 method for class 'SpatRaster'
mutate(.data, ...)

## S3 method for class 'SpatVector'
mutate(.data, ...)

## S3 method for class 'SpatRaster'
transmute(.data, ...)

## S3 method for class 'SpatVector'
transmute(.data, ...)
```

Arguments

`.data` A `SpatRaster` created with `terra::rast()` or a `SpatVector` created with `terra::vect()`.
`...` `data-masking` Name-value pairs. The name gives the name of the layer/attribute in the output. See `dplyr::mutate()`.

Value

A `Spat*` object of the same class than `.data`. See **Methods**.

terra equivalent

Some terra methods for modifying cell values: `terra::ifel()`, `terra::classify()`, `terra::clamp()`, `terra::app()`, `terra::lapp()`, `terra::tapp()`

Methods

Implementation of the **generics** `dplyr::mutate()`, `dplyr::transmute()` functions.

SpatRaster:

Add new layers and preserves existing ones. The result is a `SpatRaster` with the same extent, resolution and crs than `.data`. Only the values (and possibly the number) of layers is modified. `transmute()` would keep only the layers created with `...`

SpatVector:

This method relies on the implementation of `dplyr::mutate()` method on the `sf` package. The result is a `SpatVector` with the modified (and possibly renamed) attributes on the function call. `transmute()` would keep only the attributes created with `...`

See Also

`dplyr::mutate()`, `dplyr::transmute()`

Other dplyr methods: `filter()`, `pull()`, `relocate()`, `rename()`, `select()`, `slice()`

Other single table verbs: `filter()`, `rename()`, `select()`, `slice()`

Examples

```
library(terra)

# SpatRaster method
f <- system.file("extdata/cyl_temp.tif", package = "tidyterra")
spatrast <- rast(f)

mod <- spatrast %>%
  mutate(exp_lyr1 = exp(tavg_04 / 10)) %>%
  select(tavg_04, exp_lyr1)

mod
plot(mod)
```

```
# SpatVector method
f <- system.file("extdata/cyl.gpkg", package = "tidyterra")
v <- vect(f)

v %>%
  mutate(cpro2 = paste0(cpro, "-Cyl")) %>%
  select(cpro, cpro2)
```

pull

Extract a single layer/attribute

Description

`pull()` is similar to `$` on a data frame. It's mostly useful because it looks a little nicer in pipes and it can optionally name the output.

It is possible to extract the geographic coordinates of a `SpatRaster`. You need to use `pull(.data, x, xy = TRUE)`. `x` and `y` are reserved names on `terra`, since they refer to the geographic coordinates of the layer.

See **Examples** and section About layer names on [as_tibble\(\)](#).

Usage

```
## S3 method for class 'SpatRaster'
pull(.data, var = -1, name = NULL, ...)

## S3 method for class 'SpatVector'
pull(.data, var = -1, name = NULL, ...)
```

Arguments

<code>.data</code>	A <code>SpatRaster</code> created with <code>terra::rast()</code> or a <code>SpatVector</code> created with <code>terra::vect()</code> .
<code>var</code>	A variable specified as: <ul style="list-style-type: none"> • a literal layer/attribute name • a positive integer, giving the position counting from the left • a negative integer, giving the position counting from the right. The default returns the last layer/attribute (on the assumption that's the column you've created most recently).
<code>name</code>	An optional parameter that specifies the column to be used as names for a named vector. Specified in a similar manner as <code>var</code> .
<code>...</code>	Arguments passed on to as_tibble()

Value

A vector the same number of cells/geometries as `.data`.

On `SpatRasters`, note that the default (`na.rm = FALSE`) would remove empty cells, so you may need to pass (`na.rm = FALSE`) to `...`. See [terra::as.data.frame\(\)](#).

terra equivalent

```
terra::values()
```

Methods

Implementation of the **generic** `dplyr::pull()` function.

SpatRaster:

When using option `na.rm = TRUE`, only cells with a value distinct to NA are extracted. See `terra::as.data.frame()`.

If `xy = TRUE` option is used, two columns names `x` and `y` (corresponding to the geographic coordinates of each cell) are available in position 1 and 2. Hence, `pull(.data, 1)` and `pull(.data, 1, xy = TRUE)` return different result.

SpatVector:

See `terra::as.data.frame()` options.

See Also

```
dplyr::pull()
```

Other dplyr methods: `filter()`, `mutate()`, `relocate()`, `rename()`, `select()`, `slice()`

Examples

```
library(terra)
f <- system.file("extdata/cyl_tile.tif", package = "tidyterra")
r <- rast(f)

# Extract second layer
r %>%
  pull(2) %>%
  head()

# With xy the first two cols are `x` (longitude) and `y` (latitude)
r %>%
  pull(2, xy = TRUE) %>%
  head()

# With renaming
r %>%
  mutate(cat = cut(cyl_tile_3, c(0, 100, 300))) %>%
  pull(cyl_tile_3, name = cat) %>%
  head()
```

`pull_crs`*Extract CRS on WKT format*

Description

Extract the WKT version of the CRS associated to a string, number of `sf/Spat*` object.

The **Well-known text (WKT)** representation of coordinate reference systems (CRS) is a character string that identifies precisely the parameters of each CRS. This is the current standard used on `sf` and `terra` packages.

Usage

```
pull_crs(.data, ...)
```

Arguments

<code>.data</code>	Input potentially including or representing a CRS. It could be a <code>sf/sfc</code> object, a <code>SpatRaster/SpatVector</code> object, a <code>crs</code> object from <code>sf::st_crs()</code> , a character (for example a proj4 string) or a integer (representing an EPSG code).
<code>...</code>	ignored

Details

Although the WKT representation is the same, `sf` and `terra` slightly differs. For example, a `sf` user could do:

```
sf::st_transform(x, 25830)
```

While a `terra` user needs to:

```
terra::project(bb, "epsg:25830")
```

Knowing the WKT would help to smooth workflows when working with different packages and object types.

Value

A WKT representation of the corresponding CRS.

Internals

This is a thin wrapper of `sf::st_crs()` and `terra::crs()`.

See Also

[terra::crs\(\)](#), [sf::st_crs\(\)](#)

Other helpers: [compare_spatrasters\(\)](#), [is_regular_grid\(\)](#)

Examples

```

# sf objects

sfobj <- sf::st_as_sfc("MULTIPOINT ((0 0), (1 1))", crs = 4326)

fromsf1 <- pull_crs(sfobj)
fromsf2 <- pull_crs(sf::st_crs(sfobj))

# terra

v <- terra::vect(sfobj)
r <- terra::rast(v)

fromterra1 <- pull_crs(v)
fromterra2 <- pull_crs(r)

# integers
fromint <- pull_crs(4326)

# Characters
fromchar <- pull_crs("epsg:4326")

all(
  fromsf1 == fromsf2,
  fromsf2 == fromterra1,
  fromterra1 == fromterra2,
  fromterra2 == fromint,
  fromint == fromchar
)

cat(fromsf1)

```

relocate

Change layer/attribute order

Description

Use `relocate()` to change layer/attribute positions, using the same syntax as `select()` to make it easy to move blocks of layers/attributes at once.

Usage

```

## S3 method for class 'SpatRaster'
relocate(.data, ..., .before = NULL, .after = NULL)

## S3 method for class 'SpatVector'
relocate(.data, ..., .before = NULL, .after = NULL)

```

Arguments

`.data` A `SpatRaster` created with `terra::rast()` or a `SpatVector` created with `terra::vect()`.
`...` `tidy-select` layers/attributes to move.
`.before, .after` `tidy-select` Destination of layers/attributes selected by `...`. Supplying neither will move layers/attributes to the left-hand side; specifying both is an error.

Value

A `Spat*` object of the same class than `.data`. See **Methods**.

terra equivalent

```
terra::subset(data, c("name_layer", "name_other_layer"))
```

Methods

Implementation of the generic `dplyr::relocate()` function.

SpatRaster:

Relocate layers of a `SpatRaster`.

SpatVector:

This method relies on the implementation of `dplyr::relocate()` method on the `sf` package. The result is a `SpatVector` with the attributes on a different order.

See Also

`dplyr::relocate()`

Other `dplyr` methods: `filter()`, `mutate()`, `pull()`, `rename()`, `select()`, `slice()`

Examples

```
library(terra)

f <- system.file("extdata/cyl_tile.tif", package = "tidyterra")
spatrast <- rast(f) %>% mutate(aa = 1, bb = 2, cc = 3)

names(spatrast)

spatrast %>%
  relocate(bb, .before = cyl_tile_3) %>%
  relocate(cyl_tile_1, .after = last_col())
```

rename	<i>Rename layers/attributes</i>
--------	---------------------------------

Description

rename() changes the names of individual layers/attributes using new_name = old_name syntax;
 rename_with() renames layers/attributes using a function.

Usage

```
## S3 method for class 'SpatRaster'
rename(.data, ...)

## S3 method for class 'SpatRaster'
rename_with(.data, .fn, .cols = everything(), ...)

## S3 method for class 'SpatVector'
rename(.data, ...)

## S3 method for class 'SpatVector'
rename_with(.data, .fn, .cols = everything(), ...)
```

Arguments

.data	A SpatRaster created with <code>terra::rast()</code> or a SpatVector created with <code>terra::vect()</code> .
...	For rename(): tidy-select Use new_name = old_name to rename selected variables. For rename_with(): additional arguments passed onto .fn.
.fn	A function used to transform the selected .cols. Should return a character vector the same length as the input.
.cols	tidy-select Columns to rename; defaults to all columns.

Value

A Spat* object of the same class than .data. See **Methods**.

terra equivalent

```
names(Spat*) <- c("a", "b", "c")
```

Methods

Implementation of the generic `dplyr::rename()` function.

SpatRaster:

Rename layers of a SpatRaster.

SpatVector:

This method relies on the implementation of `dplyr::rename()` method on the sf package. The result is a SpatVector with the renamed attributes on the function call.

See Also

`dplyr::rename()`

Other dplyr methods: `filter()`, `mutate()`, `pull()`, `relocate()`, `select()`, `slice()`

Other single table verbs: `filter()`, `mutate()`, `select()`, `slice()`

Examples

```
library(terra)
f <- system.file("extdata/cyl_tile.tif", package = "tidyterra")
spatrast <- rast(f) %>% mutate(aa = 1, bb = 2, cc = 3)

spatrast

spatrast %>% rename(
  this_first = cyl_tile_1,
  this_second = cyl_tile_2
)

spatrast %>% rename_with(
  toupper,
  .cols = starts_with("c")
)
```

replace_na

Replace NAs with specified values

Description

Replace NAs on layers/attributes with specified values

Usage

```
## S3 method for class 'SpatRaster'
replace_na(data, replace = list(), ...)

## S3 method for class 'SpatVector'
replace_na(data, replace, ...)
```

Arguments

data	A SpatRaster created with <code>terra::rast()</code> or a SpatVector created with <code>terra::vect()</code> .
replace	list of values, with one value for each layer/attribute that has NA values to be replaced.
...	Ignored

Value

A Spat* object of the same class than data. Geometries and spatial attributes are preserved.

terra equivalent

Use `r[is.na(r)] <- <replacement>`

See Also

`tidyr::replace_na()`

Other tidyr.methods: `drop_na()`

Examples

```
library(terra)

f <- system.file("extdata/cyl_temp.tif", package = "tidyterra")
r <- rast(f)

r %>% plot()

r %>%
  replace_na(list(tavg_04 = 6, tavg_06 = 20)) %>%
  plot()
```

scale_fill_cross_bleded

Cross blended Hypsometric Tints fill scales

Description

Implementation of the cross blended hypsometric gradients presented on [doi:10.14714/CP69.20](https://doi.org/10.14714/CP69.20). The following fill scales and palettes are provided:

- `scale_fill_cross_bleded_d()`: For discrete values.
- `scale_fill_cross_bleded_c()`: For continuous values.
- `scale_fill_cross_bleded_b()`: For binning continuous values.

- `cross_blended.colors()`: A gradient color palette. See also `grDevices::terrain.colors()` for details.

An additional set of scales is provided. These scales can act as **hypsothetic (or bathymetric) tints**.

- `scale_fill_cross_blended_tint_d()`: For discrete values.
- `scale_fill_cross_blended_tint_c()`: For continuous values.
- `scale_fill_cross_blended_tint_b()`: For binning continuous values.
- `cross_blended.colors2()`: A gradient color palette. See also `grDevices::terrain.colors()` for details.

See **Details**.

Usage

```
scale_fill_cross_blended_d(
  palette = "cold_humid",
  ...,
  alpha = 1,
  direction = 1
)
```

```
scale_fill_cross_blended_c(
  palette = "cold_humid",
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "colourbar"
)
```

```
scale_fill_cross_blended_b(
  palette = "cold_humid",
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "coloursteps"
)
```

```
cross_blended.colors(n, palette = "cold_humid", alpha = 1, rev = FALSE)
```

```
scale_fill_cross_blended_tint_d(
  palette = "cold_humid",
  ...,
  alpha = 1,
  direction = 1
)
```

```
scale_fill_cross_bleded_tint_c(
  palette = "cold_humid",
  ...,
  alpha = 1,
  direction = 1,
  values = NULL,
  limits = NULL,
  na.value = NA,
  guide = "colourbar"
)
```

```
scale_fill_cross_bleded_tint_b(
  palette = "cold_humid",
  ...,
  alpha = 1,
  direction = 1,
  values = NULL,
  limits = NULL,
  na.value = NA,
  guide = "coloursteps"
)
```

```
cross_bleded.colors2(n, palette = "cold_humid", alpha = 1, rev = FALSE)
```

Arguments

palette	A valid palette name. The name is matched to the list of available palettes, ignoring upper vs. lower case. See cross_bleded_hypsometric_tints_db for more info. Values available are: "arid", "cold_humid", "polar", "warm_humid".
...	Other arguments passed on to discrete_scale() , continuous_scale() , or binned_scale to control name, limits, breaks, labels and so forth.
alpha	The alpha transparency, a number in [0,1], see argument alpha in hsv .
direction	Sets the order of colors in the scale. If 1, the default, colors are ordered from darkest to lightest. If -1, the order of colors is reversed.
na.value	Missing values will be replaced with this value.
guide	A function used to create a guide or its name. See guides() for more information.
n	the number of colors (≥ 1) to be in the palette.
rev	logical indicating whether the ordering of the colors should be reversed.
values	if colours should not be evenly positioned along the gradient this vector gives the position (between 0 and 1) for each colour in the colours vector. See rescale() for a convenience function to map an arbitrary range to between 0 and 1.
limits	One of: <ul style="list-style-type: none"> • NULL to use the default scale range

- A numeric vector of length two providing limits of the scale. Use NA to refer to the existing minimum or maximum
- A function that accepts the existing (automatic) limits and returns new limits. Also accepts rlang `lambda` function notation. Note that setting limits on positional scales will **remove** data outside of the limits. If the purpose is to zoom, use the limit argument in the coordinate system (see `coord_cartesian()`).

Details

On `scale_fill_cross_blen` tint_* palettes, the position of the gradients and the limits of the palette are redefined. Instead of treating the color palette as a continuous gradient, they are rescaled to act as a hypsometric tint. A rough description of these tints are:

- Blue colors: Negative values.
- Green colors: 0 to 1.000 values.
- Browns: 1000 to 4.000 values.
- Whites: Values higher than 4.000.

The following orientation would vary depending on the palette definition (see `cross_blen` `hypsometric_tints_db` for an example on how this could be achieved).

Note that the setup of the palette may not be always suitable for your specific data. For example, raster of small parts of the globe (and with a limited range of elevations) may not be well represented. As an example, a raster with a range of values on [100, 200] would appear almost as an uniform color.

This could be adjusted using the `limits/values` provided by `ggplot2`.

`cross_blen.colors2()` provides a gradient color palette where the distance between colors is different depending of the type of color. In contrast, `cross_blen.colors()` provides an uniform gradient across colors. See **Examples**.

Value

The corresponding `ggplot2` layer with the values applied to the `fill` aesthetics.

Source

Patterson, T., & Jenny, B. (2011). The Development and Rationale of Cross-blended Hypsometric Tints. *Cartographic Perspectives*, (69), 31 - 46. doi:10.14714/CP69.20.

Patterson, T. (2004). *Using Cross-blended Hypsometric Tints for Generalized Environmental Mapping*. Accessed June 10, 2022. <http://www.shadedrelief.com/hypso/hypso.html>

See Also

`cross_blen` `hypsometric_tints_db`, `terra::plot()`, `terra::minmax()`, `ggplot2::scale_fill_viridis_c()`

Other gradient scales and palettes for hypsometry: `scale_fill_hypso`, `scale_fill_terrain`, `scale_fill_whitebox`, `scale_fill_wiki`

Examples

```

filepath <- system.file("extdata/volcano2.tif", package = "tidyterra")

library(terra)
volcano2_rast <- rast(filepath)

# Palette
plot(volcano2_rast, col = cross_bleded.colors(100, palette = "arid"))

# Palette with uneven colors
plot(volcano2_rast, col = cross_bleded.colors2(100, palette = "arid"))

library(ggplot2)
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_cross_bleded_c(palette = "cold_humid")

# Use hypsometric tint version...
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_cross_bleded_tint_c(palette = "cold_humid")

# ...but not suitable for the range of the raster: adjust
my_lims <- minmax(volcano2_rast) %>% as.integer() + c(-2, 2)

ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_cross_bleded_tint_c(
    palette = "cold_humid",
    limits = my_lims
  )

# Full map with true tints

f_asia <- system.file("extdata/asia.tif", package = "tidyterra")
asia <- rast(f_asia)

ggplot() +
  geom_spatraster(data = asia) +
  scale_fill_cross_bleded_tint_c(
    palette = "warm_humid",
    labels = scales::label_number(),
    breaks = c(-10000, 0, 5000, 8000),
    guide = guide_colorbar(
      direction = "horizontal",
      title.position = "top",
      barwidth = 25
    )
  ) +
  labs(fill = "elevation (m)") +

```

```

theme_minimal() +
theme(legend.position = "bottom")

# Binned
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_cross_blended_b(breaks = seq(70, 200, 25), palette = "arid")

# With limits and breaks
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_cross_blended_tint_b(
    breaks = seq(75, 200, 25),
    palette = "arid",
    limits = my_lims
  )

# With discrete values
factor <- volcano2_rast %>%
  mutate(cats = cut(elevation,
    breaks = c(100, 120, 130, 150, 170, 200),
    labels = c(
      "Very Low", "Low", "Average", "High",
      "Very High"
    )
  )
))

ggplot() +
  geom_spatraster(data = factor, aes(fill = cats)) +
  scale_fill_cross_blended_d(na.value = "gray10", palette = "cold_humid")

# Tint version
ggplot() +
  geom_spatraster(data = factor, aes(fill = cats)) +
  scale_fill_cross_blended_tint_d(
    na.value = "gray10",
    palette = "cold_humid"
  )

# Display all the cross-blended palettes

pals <- unique(cross_blended_hypsometric_tints_db$pal)

# Helper fun for plotting

ncols <- 128
rowcol <- grDevices::n2mfrow(length(pals))

opar <- par(no.readonly = TRUE)
par(mfrow = rowcol, mar = rep(1, 4))

```



```

for (i in pals) {
  image(
    x = seq(1, ncols), y = 1, z = as.matrix(seq(1, ncols)),
    col = cross_blenved.colors(ncols, i), main = i,
    ylab = "", xaxt = "n", yaxt = "n", bty = "n"
  )
}
par(opar)
# Display all the cross-blended palettes on version 2

pals <- unique(cross_blenved_hypsometric_tints_db$pal)

# Helper fun for plotting

ncols <- 128
rowcol <- grDevices::n2mfrow(length(pals))

opar <- par(no.readonly = TRUE)
par(mfrow = rowcol, mar = rep(1, 4))

for (i in pals) {
  image(
    x = seq(1, ncols), y = 1, z = as.matrix(seq(1, ncols)),
    col = cross_blenved.colors2(ncols, i), main = i,
    ylab = "", xaxt = "n", yaxt = "n", bty = "n"
  )
}
par(opar)

```

scale_fill_hypso

Gradient fill scales for representing hypsometry and bathymetry

Description

Implementation of a selection of gradient palettes available in [cpt-city](#).

The following fill scales and palettes are provided:

- `scale_fill_hypso_d()`: For discrete values.
- `scale_fill_hypso_c()`: For continuous values.
- `scale_fill_hypso_b()`: For binning continuous values.
- `hypso.colors()`: A gradient color palette. See also `grDevices::terrain.colors()` for details.

An additional set of scales is provided. These scales can act as **hypsometric (or bathymetric) tints**.

- `scale_fill_hypso_tint_d()`: For discrete values.
- `scale_fill_hypso_tint_c()`: For continuous values.
- `scale_fill_hypso_tint_b()`: For binning continuous values.

- `hypso.colors2()`: A gradient color palette. See also `grDevices::terrain.colors()` for details.

See **Details**.

Usage

```
scale_fill_hypso_d(palette = "etopo1_hypso", ..., alpha = 1, direction = 1)
```

```
scale_fill_hypso_c(  
  palette = "etopo1_hypso",  
  ...,  
  alpha = 1,  
  direction = 1,  
  na.value = NA,  
  guide = "colourbar"  
)
```

```
scale_fill_hypso_b(  
  palette = "etopo1_hypso",  
  ...,  
  alpha = 1,  
  direction = 1,  
  na.value = NA,  
  guide = "coloursteps"  
)
```

```
hypso.colors(n, palette = "etopo1_hypso", alpha = 1, rev = FALSE)
```

```
scale_fill_hypso_tint_d(  
  palette = "etopo1_hypso",  
  ...,  
  alpha = 1,  
  direction = 1  
)
```

```
scale_fill_hypso_tint_c(  
  palette = "etopo1_hypso",  
  ...,  
  alpha = 1,  
  direction = 1,  
  values = NULL,  
  limits = NULL,  
  na.value = NA,  
  guide = "colourbar"  
)
```

```
scale_fill_hypso_tint_b(  
  palette = "etopo1_hypso",
```

```

    ...,
    alpha = 1,
    direction = 1,
    values = NULL,
    limits = NULL,
    na.value = NA,
    guide = "coloursteps"
  )

```

```
hypso.colors2(n, palette = "etopo1_hypso", alpha = 1, rev = FALSE)
```

Arguments

palette	A valid palette name. The name is matched to the list of available palettes, ignoring upper vs. lower case. See hypso for more info. Values available are: "c3t1", "colombia", "colombia_bathy", "colombia_hypso", "dem_poster", "dem_print", "dem_screen", "etopo1", "etopo1_bathy", "etopo1_hypso", "gmt_globe", "gmt_globe_bathy", "gmt_globe_hypso", "moon", "moon_bathy", "moon_hypso", "pakistan", "spain", "usgs-gswa2", "utah_1", "wiki-2.0", "wiki-2.0_bathy", "wiki-2.0_hypso", "wiki-schwarzwald-cont".
...	Other arguments passed on to discrete_scale() , continuous_scale() , or binned_scale to control name, limits, breaks, labels and so forth.
alpha	The alpha transparency, a number in [0,1], see argument alpha in hsv .
direction	Sets the order of colors in the scale. If 1, the default, colors are ordered from darkest to lightest. If -1, the order of colors is reversed.
na.value	Missing values will be replaced with this value.
guide	A function used to create a guide or its name. See guides() for more information.
n	the number of colors (≥ 1) to be in the palette.
rev	logical indicating whether the ordering of the colors should be reversed.
values	if colours should not be evenly positioned along the gradient this vector gives the position (between 0 and 1) for each colour in the colours vector. See rescale() for a convenience function to map an arbitrary range to between 0 and 1.
limits	One of: <ul style="list-style-type: none"> • NULL to use the default scale range • A numeric vector of length two providing limits of the scale. Use NA to refer to the existing minimum or maximum • A function that accepts the existing (automatic) limits and returns new limits. Also accepts rlang lambda function notation. Note that setting limits on positional scales will remove data outside of the limits. If the purpose is to zoom, use the limit argument in the coordinate system (see coord_cartesian()).

Details

On `scale_fill_hypso_tint_*` palettes, the position of the gradients and the limits of the palette are redefined. Instead of treating the color palette as a continuous gradient, they are rescaled to act as a hypsometric tint. A rough description of these tints are:

- Blue colors: Negative values.
- Green colors: 0 to 1.000 values.
- Browns: 1000 to 4.000 values.
- Whites: Values higher than 4.000.

The following orientation would vary depending on the palette definition (see [hypsometric_tints_db](#) for an example on how this could be achieved).

Note that the setup of the palette may not be always suitable for your specific data. For example, raster of small parts of the globe (and with a limited range of elevations) may not be well represented. As an example, a raster with a range of values on `[100, 200]` would appear almost as an uniform color.

This could be adjusted using the `limits/values` provided by **ggplot2**.

`hypso.colors2()` provides a gradient color palette where the distance between colors is different depending of the type of color. In contrast, `hypso.colors()` provides an uniform gradient across colors. See **Examples**.

Value

The corresponding `ggplot2` layer with the values applied to the `fill` aesthetics.

Source

cpt-city: <http://soliton.vm.bytemark.co.uk/pub/cpt-city/>.

See Also

[hypsometric_tints_db](#), `terra::plot()`, `terra::minmax()`, `ggplot2::scale_fill_viridis_c()`

Other gradient scales and palettes for hypsometry: [scale_fill_cross_bleneded](#), [scale_fill_terrain](#), [scale_fill_whitebox](#), [scale_fill_wiki](#)

Examples

```
filepath <- system.file("extdata/volcano2.tif", package = "tidyterra")

library(terra)
volcano2_rast <- rast(filepath)

# Palette
plot(volcano2_rast, col = hypso.colors(100, palette = "wiki-2.0_hypso"))

# Palette with uneven colors
plot(volcano2_rast, col = hypso.colors2(100, palette = "wiki-2.0_hypso"))
```

```

library(ggplot2)
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_hypso_c(palette = "colombia_hypso")

# Use hypsometric tint version...
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_hypso_tint_c(palette = "colombia_hypso")

# ...but not suitable for the range of the raster: adjust
my_lims <- minmax(volcano2_rast) %>% as.integer() + c(-2, 2)

ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_hypso_tint_c(
    palette = "colombia_hypso",
    limits = my_lims
  )

# Full map with true tints

f_asia <- system.file("extdata/asia.tif", package = "tidyterra")
asia <- rast(f_asia)

ggplot() +
  geom_spatraster(data = asia) +
  scale_fill_hypso_tint_c(
    palette = "etopo1",
    labels = scales::label_number(),
    breaks = c(-10000, 0, 5000, 8000),
    guide = guide_colorbar(
      direction = "horizontal",
      title.position = "top",
      barwidth = 25
    )
  ) +
  labs(fill = "elevation (m)") +
  theme_minimal() +
  theme(legend.position = "bottom")

# Binned
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_hypso_b(breaks = seq(70, 200, 25), palette = "wiki-2.0_hypso")

# With limits and breaks
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_hypso_tint_b(

```

```

    breaks = seq(75, 200, 25),
    palette = "wiki-2.0_hypso",
    limits = my_lims
  )

# With discrete values
factor <- volcano2_rast %>% mutate(cats = cut(elevation,
  breaks = c(100, 120, 130, 150, 170, 200),
  labels = c(
    "Very Low", "Low", "Average", "High",
    "Very High"
  )
)
))

ggplot() +
  geom_spatraster(data = factor, aes(fill = cats)) +
  scale_fill_hypso_d(na.value = "gray10", palette = "dem_poster")

# Tint version
ggplot() +
  geom_spatraster(data = factor, aes(fill = cats)) +
  scale_fill_hypso_tint_d(na.value = "gray10", palette = "dem_poster")

# Display all the cpl_city palettes

pals <- unique(hypsometric_tints_db$pal)

# Helper fun for plotting

ncols <- 128
rowcol <- grDevices::n2mfrow(length(pals))

opar <- par(no.readonly = TRUE)
par(mfrow = rowcol, mar = rep(1, 4))

for (i in pals) {
  image(
    x = seq(1, ncols), y = 1, z = as.matrix(seq(1, ncols)),
    col = hypso.colors(ncols, i), main = i,
    ylab = "", xaxt = "n", yaxt = "n", bty = "n"
  )
}
par(opar)
# Display all the cpl_city palettes on version 2

pals <- unique(hypsometric_tints_db$pal)

# Helper fun for plotting

ncols <- 128
rowcol <- grDevices::n2mfrow(length(pals))

```

```
opar <- par(no.readonly = TRUE)
par(mfrow = rowcol, mar = rep(1, 4))

for (i in pals) {
  image(
    x = seq(1, ncols), y = 1, z = as.matrix(seq(1, ncols)),
    col = hypso.colors2(ncols, i), main = i,
    ylab = "", xaxt = "n", yaxt = "n", bty = "n"
  )
}
par(opar)
```

scale_fill_terrain *Terrain colour fill scales from grDevices*

Description

Implementation of the classic color palettes used by default by the terra package (see [terra::plot\(\)](#)). Three fill scales are provided:

- `scale_fill_terrain_d()`: For discrete values.
- `scale_fill_terrain_c()`: For continuous values.
- `scale_fill_terrain_b()`: For binning continuous values.

Usage

```
scale_fill_terrain_d(..., alpha = 1, direction = 1)
```

```
scale_fill_terrain_c(
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "colourbar"
)
```

```
scale_fill_terrain_b(
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "coloursteps"
)
```

Arguments

...	Other arguments passed on to discrete_scale() , continuous_scale() , or binned_scale to control name, limits, breaks, labels and so forth.
alpha	The alpha transparency, a number in [0,1], see argument alpha in hsv .
direction	Sets the order of colors in the scale. If 1, the default, colors are ordered from darkest to lightest. If -1, the order of colors is reversed.
na.value	Missing values will be replaced with this value.
guide	A function used to create a guide or its name. See guides() for more information.

Value

The corresponding ggplot2 layer with the values applied to the fill aesthetics.

See Also

[terra::plot\(\)](#), [ggplot2::scale_fill_viridis_c\(\)](#)

Other gradient scales and palettes for hypsometry: [scale_fill_cross_blended](#), [scale_fill_hypso](#), [scale_fill_whitebox](#), [scale_fill_wiki](#)

Examples

```

filepath <- system.file("extdata/volcano2.tif", package = "tidyterra")

library(terra)
volcano2_rast <- rast(filepath)

library(ggplot2)
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_terrain_c()

# Binned
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_terrain_b(breaks = seq(70, 200, 10))

# With discrete values
factor <- volcano2_rast %>% mutate(cats = cut(elevation,
  breaks = c(100, 120, 130, 150, 170, 200),
  labels = c(
    "Very Low", "Low", "Average", "High",
    "Very High"
  )
)
))

ggplot() +

```



```
geom_spatraster(data = factor, aes(fill = cats)) +
scale_fill_terrain_d(na.value = "gray10")
```

scale_fill_whitebox *Gradient fill scales from WhiteboxTools color schemes*

Description

Implementation of the gradient palettes provided by [WhiteboxTools](#). Three fill scales are provided:

- `scale_fill_whitebox_d()`: For discrete values.
- `scale_fill_whitebox_c()`: For continuous values.
- `scale_fill_whitebox_b()`: For binning continuous values.

Additionally, a color palette `whitebox.colors()` is provided. See also `grDevices::terrain.colors()` for details.

Usage

```
scale_fill_whitebox_d(palette = "high_relief", ..., alpha = 1, direction = 1)
```

```
scale_fill_whitebox_c(
  palette = "high_relief",
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "colourbar"
)
```

```
scale_fill_whitebox_b(
  palette = "high_relief",
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "coloursteps"
)
```

```
whitebox.colors(n, palette = "high_relief", alpha = 1, rev = FALSE)
```

Arguments

<code>palette</code>	A valid palette name. The name is matched to the list of available palettes, ignoring upper vs. lower case. Values available are: "atlas", "high_relief", "arid", "soft", "muted", "purple", "viridi", "gn_yl", "pi_y_g", "bl_yl_rd", "deep".
----------------------	---

...	Other arguments passed on to <code>discrete_scale()</code> , <code>continuous_scale()</code> , or <code>binned_scale</code> to control name, limits, breaks, labels and so forth.
alpha	The alpha transparency, a number in [0,1], see argument alpha in <code>hsv</code> .
direction	Sets the order of colors in the scale. If 1, the default, colors are ordered from darkest to lightest. If -1, the order of colors is reversed.
na.value	Missing values will be replaced with this value.
guide	A function used to create a guide or its name. See <code>guides()</code> for more information.
n	the number of colors (≥ 1) to be in the palette.
rev	logical indicating whether the ordering of the colors should be reversed.

Value

The corresponding ggplot2 layer with the values applied to the fill aesthetics.

Source

<https://github.com/jblindsay/whitebox-tools>, under MIT License. Copyright (c) 2017-2021 John Lindsay.

See Also

`terra::plot()`, `ggplot2::scale_fill_viridis_c()`

Other gradient scales and palettes for hypsometry: `scale_fill_cross_blended`, `scale_fill_hypso`, `scale_fill_terrain`, `scale_fill_wiki`

Examples

```
filepath <- system.file("extdata/volcano2.tif", package = "tidyterra")

library(terra)
volcano2_rast <- rast(filepath)

# Palette
plot(volcano2_rast, col = whitebox.colors(100))

library(ggplot2)
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_whitebox_c()

# Binned
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_whitebox_b(breaks = seq(70, 200, 10), palette = "atlas")

# With discrete values
factor <- volcano2_rast %>% mutate(cats = cut(elevation,
```

```

breaks = c(100, 120, 130, 150, 170, 200),
labels = c(
  "Very Low", "Low", "Average", "High",
  "Very High"
)
))

ggplot() +
  geom_spatraster(data = factor, aes(fill = cats)) +
  scale_fill_whitebox_d(na.value = "gray10", palette = "soft")

# Display all the whitebox palettes

pals <- c(
  "atlas", "high_relief", "arid", "soft", "muted", "purple",
  "viridi", "gn_yl", "pi_y_g", "bl_yl_rd", "deep"
)

# Helper fun for plotting

ncols <- 128
rowcol <- grDevices::n2mfrow(length(pals))

opar <- par(no.readonly = TRUE)
par(mfrow = rowcol, mar = rep(1, 4))

for (i in pals) {
  image(
    x = seq(1, ncols), y = 1, z = as.matrix(seq(1, ncols)),
    col = whitebox.colors(ncols, i), main = i,
    ylab = "", xaxt = "n", yaxt = "n", bty = "n"
  )
}
par(opar)

```

scale_fill_wiki

Gradient fill scales from Wikipedia color schemes

Description

Implementation based on the [Wikipedia Colorimetric conventions for topographic maps](#). Three fill scales are provided:

- `scale_fill_wiki_d()`: For discrete values.
- `scale_fill_wiki_c()`: For continuous values.
- `scale_fill_wiki_b()`: For binning continuous values.

Additionally, a color palette `wiki.colors()` is provided. See also `grDevices::terrain.colors()` for details.

Usage

```

scale_fill_wiki_d(..., alpha = 1, direction = 1)

scale_fill_wiki_c(
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "colourbar"
)

scale_fill_wiki_b(
  ...,
  alpha = 1,
  direction = 1,
  na.value = NA,
  guide = "coloursteps"
)

wiki.colors(n, alpha = 1, rev = FALSE)

```

Arguments

...	Other arguments passed on to discrete_scale() , continuous_scale() , or binned_scale to control name, limits, breaks, labels and so forth.
alpha	The alpha transparency, a number in [0,1], see argument alpha in hsv .
direction	Sets the order of colors in the scale. If 1, the default, colors are ordered from darkest to lightest. If -1, the order of colors is reversed.
na.value	Missing values will be replaced with this value.
guide	A function used to create a guide or its name. See guides() for more information.
n	the number of colors (≥ 1) to be in the palette.
rev	logical indicating whether the ordering of the colors should be reversed.

Value

The corresponding ggplot2 layer with the values applied to the fill aesthetics.

See Also

[terra::plot\(\)](#), [ggplot2::scale_fill_viridis_c\(\)](#)

Other gradient scales and palettes for hypsometry: [scale_fill_cross_blen](#)ded, [scale_fill_hypso](#), [scale_fill_terrain](#), [scale_fill_whitebox](#)

Examples

```

filepath <- system.file("extdata/volcano2.tif", package = "tidyterra")

library(terra)
volcano2_rast <- rast(filepath)

# Palette
plot(volcano2_rast, col = wiki.colors(100))

library(ggplot2)
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_wiki_c()

# Binned
ggplot() +
  geom_spatraster(data = volcano2_rast) +
  scale_fill_wiki_b(breaks = seq(70, 200, 10))

# With discrete values
factor <- volcano2_rast %>% mutate(cats = cut(elevation,
  breaks = c(100, 120, 130, 150, 170, 200),
  labels = c(
    "Very Low", "Low", "Average", "High",
    "Very High"
  )
))

ggplot() +
  geom_spatraster(data = factor, aes(fill = cats)) +
  scale_fill_wiki_d(na.value = "gray10")

```

select

Subset layers/attributes of Spat objects*

Description

Select (and optionally rename) attributes/layers in Spat* objects, using a concise mini-language. See **Methods**.

Usage

```

## S3 method for class 'SpatRaster'
select(.data, ...)

## S3 method for class 'SpatVector'
select(.data, ...)

```

Arguments

`.data` A `SpatRaster` created with `terra::rast()` or a `SpatVector` created with `terra::vect()`.
`...` `tidy-select` One or more unquoted expressions separated by commas. Layer/attribute names can be used as if they were positions in the `Spat*` object, so expressions like `x:y` can be used to select a range of layers/attributes.

Value

A `Spat*` object of the same class than `.data`. See **Methods**.

terra equivalent

`terra::subset()`

Methods

Implementation of the generic `dplyr::select()` function.

SpatRaster:

Select (and rename) layers of a `SpatRaster`. The result is a `SpatRaster` with the same extent, resolution and crs than `.data`. Only the number (and possibly the name) of layers is modified.

SpatVector:

This method relies on the implementation of `dplyr::select()` method on the `sf` package. The result is a `SpatVector` with the selected (and possibly renamed) attributes on the function call.

See Also

`dplyr::select()`, `terra::subset()`

Other `dplyr` methods: `filter()`, `mutate()`, `pull()`, `relocate()`, `rename()`, `slice()`

Other single table verbs: `filter()`, `mutate()`, `rename()`, `slice()`

Examples

```
library(terra)

# SpatRaster method

spatrast <- rast(
  crs = "epsg:3857",
  nrows = 10,
  ncols = 10,
  extent = c(100, 200, 100, 200),
  nlyr = 6,
  vals = seq_len(10 * 10 * 6)
)

spatrast %>% select(1)
```

```

# By name
spatrast %>% select(lyr.1:lyr.4)

# Rename
spatrast %>% select(a = lyr.1, c = lyr.6)

# SpatVector method

f <- system.file("extdata/cyl.gpkg", package = "tidyterra")

v <- vect(f)

v

v %>% select(1, 3)

v %>% select(iso2, name2 = cpro)

```

 slice

Subset cells/rows/columns/geometries using their positions

Description

`slice()` lets you index cells/rows/columns/geometries by their (integer) locations. It allows you to select, remove, and duplicate those dimensions of a `Spat*` object.

If you want to slice your `SpatRaster` by geographic coordinates use `filter.SpatRaster()` method.

It is accompanied by a number of helpers for common use cases:

- `slice_head()` and `slice_tail()` select the first or last cells/geometries.
- `slice_sample()` randomly selects cells/geometries.
- `slice_rows()` and `slice_cols()` allow to subset entire rows or columns, of a `SpatRaster`.
- `slice_colrows()` subsets regions of the raster by row and column position of a `SpatRaster`.

You can get a skeleton of your `SpatRaster` with the cell, column and row index with `as_coordinates()`.

See **Methods** for details.

Usage

```

## S3 method for class 'SpatRaster'
slice(.data, ..., .preserve = FALSE, .keep_extent = FALSE)

## S3 method for class 'SpatVector'
slice(.data, ..., .preserve = FALSE)

## S3 method for class 'SpatRaster'
slice_head(.data, ..., n, prop, .keep_extent = FALSE)

```

```
## S3 method for class 'SpatVector'
slice_head(.data, ..., n, prop)

## S3 method for class 'SpatRaster'
slice_tail(.data, ..., n, prop, .keep_extent = FALSE)

## S3 method for class 'SpatVector'
slice_tail(.data, ..., n, prop)

## S3 method for class 'SpatRaster'
slice_min(
  .data,
  order_by,
  ...,
  n,
  prop,
  with_ties = TRUE,
  .keep_extent = FALSE,
  na.rm = TRUE
)

## S3 method for class 'SpatVector'
slice_min(.data, order_by, ..., n, prop, with_ties = TRUE)

## S3 method for class 'SpatRaster'
slice_max(
  .data,
  order_by,
  ...,
  n,
  prop,
  with_ties = TRUE,
  .keep_extent = FALSE,
  na.rm = TRUE
)

## S3 method for class 'SpatVector'
slice_max(.data, order_by, ..., n, prop, with_ties = TRUE)

## S3 method for class 'SpatRaster'
slice_sample(
  .data,
  ...,
  n,
  prop,
  weight_by = NULL,
  replace = FALSE,
```



```

    .keep_extent = FALSE
  )

## S3 method for class 'SpatVector'
slice_sample(.data, ..., n, prop, weight_by = NULL, replace = FALSE)

slice_rows(.data, ...)

## S3 method for class 'SpatRaster'
slice_rows(.data, ..., .keep_extent = FALSE)

slice_cols(.data, ...)

## S3 method for class 'SpatRaster'
slice_cols(.data, ..., .keep_extent = FALSE)

slice_colrows(.data, ...)

## S3 method for class 'SpatRaster'
slice_colrows(.data, ..., cols, rows, .keep_extent = FALSE, inverse = FALSE)

```

Arguments

<code>.data</code>	A <code>SpatRaster</code> created with <code>terra::rast()</code> or a <code>SpatVector</code> created with <code>terra::vect()</code> .
<code>...</code>	data-masking Integer row values. Provide either positive values to keep, or negative values to drop. The values provided must be either all positive or all negative. Indices beyond the number of rows in the input are silently ignored. See Methods .
<code>.preserve</code>	Ignored for <code>Spat*</code> objects
<code>.keep_extent</code>	Should the extent of the resulting <code>SpatRaster</code> be kept? See also <code>terra::trim()</code> , <code>terra::extend()</code> .
<code>n, prop</code>	Provide either <code>n</code> , the number of rows, or <code>prop</code> , the proportion of rows to select. If neither are supplied, <code>n = 1</code> will be used. If a negative value of <code>n</code> or <code>prop</code> is provided, the specified number or proportion of rows will be removed. If <code>n</code> is greater than the number of rows in the group (or <code>prop > 1</code>), the result will be silently truncated to the group size. If the proportion of a group size does not yield an integer number of rows, the absolute value of <code>prop*nrow(.data)</code> is rounded down.
<code>order_by</code>	Variable or function of variables to order by.
<code>with_ties</code>	Should ties be kept together? The default, <code>TRUE</code> , may return more rows than you request. Use <code>FALSE</code> to ignore ties, and return the first <code>n</code> rows.
<code>na.rm</code>	Logical, should cells that present a value of <code>NA</code> removed when computing <code>slice_min()/slice_max()</code> ? The default is <code>TRUE</code> .
<code>weight_by</code>	Sampling weights. This must evaluate to a vector of non-negative numbers the same length as the input. Weights are automatically standardised to sum to 1.

replace	Should sampling be performed with (TRUE) or without (FALSE, the default) replacement.
cols, rows	Integer col/row values of the SpatRaster
inverse	If TRUE, .data is inverse-masked to the given selection. See terra::mask() .

Value

A `Spat*` object of the same class than `.data`. See **Methods**.

terra equivalent

[terra::subset\(\)](#), [terra::spatSample\(\)](#)

Methods

Implementation of the generic `dplyr::slice()` function.

SpatRaster:

The result is a `SpatRaster` with the crs and resolution of the input and where cell values of the selected cells/columns/rows are preserved.

Use `.keep_extent = TRUE` to preserve the extent of `.data` on the output. The non-selected cells would present a value of NA.

SpatVector:

This method relies on the implementation of `dplyr::slice()` method on the `sf` package. The result is a `SpatVector` where the attributes of the selected geometries are preserved.

See Also

[dplyr::slice\(\)](#), [terra::spatSample\(\)](#).

You can get a skeleton of your `SpatRaster` with the cell, column and row index with [as_coordinates\(\)](#).

If you want to slice by geographic coordinates use [filter.SpatRaster\(\)](#).

Other `dplyr` methods: [filter\(\)](#), [mutate\(\)](#), [pull\(\)](#), [relocate\(\)](#), [rename\(\)](#), [select\(\)](#)

Other single table verbs: [filter\(\)](#), [mutate\(\)](#), [rename\(\)](#), [select\(\)](#)

Examples

```
library(terra)

f <- system.file("extdata/cyl_temp.tif", package = "tidyterra")
r <- rast(f)

# Slice first 100 cells
r %>%
  slice(1:100) %>%
  plot()
```

```
# Rows
r %>%
  slice_rows(1:30) %>%
  plot()

# Cols
r %>%
  slice_cols(-(20:50)) %>%
  plot()

# Spatial sample
r %>%
  slice_sample(prop = 0.2) %>%
  plot()

# Slice regions
r %>%
  slice_colrows(
    cols = c(20:40, 60:80),
    rows = -c(1:20, 30:50)
  ) %>%
  plot()
```

volcano2

Updated Topographic Information on Auckland's Maungawhau Volcano

Description

Probably you already know the [volcano](#) dataset. This dataset provides updated information of Maungawhau (Mt. Eden) from [Toitu Te Whenua Land Information New Zealand](#), the Government's agency that provides free online access to New Zealand's most up-to-date land and seabed data.

Format

A matrix of 174 rows and 122 columns. Each value is the corresponding altitude in meters.

Note

Information needed for regenerating the original raster file:

- resolution: c(5, 5)
- extent: 1756969, 1757579, 5917003, 5917873 (xmin, xmax, ymin, ymax)
- coord. ref. : NZGD2000 / New Zealand Transverse Mercator 2000 (EPSG:2193)

Source

Auckland LiDAR 1m DEM (2013)

DEM for LiDAR data from the Auckland region captured in 2013. The original data has been downsampled to a resolution of 5m due to disk space constraints.

Data License: [CC BY 4.0](#)

See Also

[volcano](#)

Other datasets: [cross_blended_hypsometric_tints_db](#), [hypsometric_tints_db](#)

Examples

```
data("volcano2")
filled.contour(volcano2, color.palette = hypso.colors, asp = 1)
title(main = "volcano2 data: filled contour map")

# Geo-tag
# Empty raster

volcano2_raster <- terra::rast(volcano2)
terra::crs(volcano2_raster) <- pull_crs(2193)
terra::ext(volcano2_raster) <- c(1756968, 1757576, 5917000, 5917872)
names(volcano2_raster) <- "volcano2"

library(ggplot2)

ggplot() +
  geom_spatraster(data = volcano2_raster) +
  scale_fill_hypso_c() +
  labs(
    title = "volcano2 SpatRaster",
    subtitle = "Georeferenced",
    fill = "Elevation (m)"
  )
```

Index

- * **coerce**
 - as_coordinates, 2
 - as_spatraster, 3
 - as_tibble, 4
- * **datasets**
 - cross_blended_hypsometric_tints_db, 9
 - hypsometric_tints_db, 24
 - volcano2, 59
- * **dplyr.methods**
 - filter, 11
 - mutate, 26
 - pull, 28
 - relocate, 31
 - rename, 33
 - select, 53
 - slice, 55
- * **ggplot2.utils**
 - autoplot, 6
 - geom_spat_contour, 18
 - geom_spatraster, 13
 - geom_spatraster_rgb, 16
 - ggspatvector, 22
- * **gradients**
 - scale_fill_cross_blended, 35
 - scale_fill_hypso, 41
 - scale_fill_terrain, 47
 - scale_fill_whitebox, 49
 - scale_fill_wiki, 51
- * **helpers**
 - compare_spatrasters, 8
 - is_regular_grid, 25
 - pull_crs, 30
- * **single table verbs**
 - filter, 11
 - mutate, 26
 - rename, 33
 - select, 53
 - slice, 55
- * **tidyr.methods**
 - drop_na, 10
 - replace_na, 34
- aes(), 7, 14, 19, 22
- aes_(), 7, 14, 19, 22
- as_coordinates, 2, 4, 6
- as_coordinates(), 55, 58
- as_spatraster, 3, 3, 6
- as_spatraster(), 25, 26
- as_tibble, 3, 4, 4
- as_tibble(), 11, 28
- as_tibble.SpatRaster(), 4
- autoplot, 6, 15, 18, 21, 23
- bracket_double(), 14, 20
- binned_scale, 37, 43, 48, 50, 52
- borders(), 14, 20
- compare_spatrasters, 8, 26, 30
- continuous_scale(), 37, 43, 48, 50, 52
- coord_cartesian(), 38, 43
- cross_blended.colors
 - (scale_fill_cross_blended), 35
- cross_blended.colors2
 - (scale_fill_cross_blended), 35
- cross_blended_hypsometric_tints_db, 9, 24, 37, 38, 60
- discrete_scale(), 37, 43, 48, 50, 52
- dplyr::filter(), 12
- dplyr::mutate(), 27
- dplyr::pull(), 29
- dplyr::relocate(), 32
- dplyr::rename(), 33, 34
- dplyr::select(), 54
- dplyr::slice(), 58
- dplyr::transmute(), 27
- drop_na, 10, 35
- drop_na.SpatRaster(), 11, 12
- filter, 11, 27, 29, 32, 34, 54, 58

- `filter.SpatRaster()`, 5, 55, 58
- `geom_spat_contour`, 7, 15, 18, 18, 23
- `geom_spatraster`, 7, 13, 18, 21, 23
- `geom_spatraster()`, 7, 16
- `geom_spatraster_contour`
 - (`geom_spat_contour`), 18
- `geom_spatraster_contour_filled`
 - (`geom_spat_contour`), 18
- `geom_spatraster_rgb`, 7, 15, 16, 21, 23
- `geom_spatraster_rgb()`, 7, 13
- `geom_spatvector` (`ggspatvector`), 22
- `geom_spatvector_label` (`ggspatvector`), 22
- `geom_spatvector_text` (`ggspatvector`), 22
- `ggplot2::after_stat()`, 15, 20
- `ggplot2::autoplot()`, 7
- `ggplot2::coord_sf()`, 14, 15, 17, 18, 21
- `ggplot2::facet_wrap()`, 15, 21
- `ggplot2::geom_contour()`, 18, 20, 21
- `ggplot2::geom_raster()`, 13, 15, 16, 18
- `ggplot2::geom_sf()`, 22, 23
- `ggplot2::scale_fill_gradientn()`, 9, 24
- `ggplot2::scale_fill_viridis_c()`, 38, 44, 48, 50, 52
- `ggspatvector`, 7, 15, 18, 21, 22
- `grDevices::rgb()`, 17, 18
- `grDevices::terrain.colors()`, 36, 41, 42, 49, 51
- `guides()`, 37, 43, 48, 50, 52
- `hsv`, 17, 37, 43, 48, 50, 52
- `hypso.colors` (`scale_fill_hypso`), 41
- `hypso.colors2` (`scale_fill_hypso`), 41
- `hypso.metric_tints_db`, 9, 24, 43, 44, 60
- `is_regular_grid`, 8, 25, 30
- `lambda`, 38, 43
- `layer()`, 14, 17, 19
- `maptiles::get_tiles()`, 18
- `mutate`, 12, 26, 29, 32, 34, 54, 58
- `pretty()`, 19
- `pull`, 12, 27, 28, 32, 34, 54, 58
- `pull_crs`, 8, 26, 30
- `pull_crs()`, 3–5
- `relocate`, 12, 27, 29, 31, 34, 54, 58
- `rename`, 12, 27, 29, 32, 33, 54, 58
- `rename_with.SpatRaster` (`rename`), 33
- `rename_with.SpatVector` (`rename`), 33
- `replace_na`, 11, 34
- `rescale()`, 37, 43
- `rlang::as_function()`, 5
- `scale_fill_cross_blen`, 35, 44, 48, 50, 52
- `scale_fill_cross_blen_b`
 - (`scale_fill_cross_blen`), 35
- `scale_fill_cross_blen_c`
 - (`scale_fill_cross_blen`), 35
- `scale_fill_cross_blen_c()`, 9
- `scale_fill_cross_blen_d`
 - (`scale_fill_cross_blen`), 35
- `scale_fill_cross_blen_tint_b`
 - (`scale_fill_cross_blen`), 35
- `scale_fill_cross_blen_tint_c`
 - (`scale_fill_cross_blen`), 35
- `scale_fill_cross_blen_tint_d`
 - (`scale_fill_cross_blen`), 35
- `scale_fill_hypso`, 38, 41, 48, 50, 52
- `scale_fill_hypso_b` (`scale_fill_hypso`), 41
- `scale_fill_hypso_c` (`scale_fill_hypso`), 41
- `scale_fill_hypso_c()`, 24
- `scale_fill_hypso_d` (`scale_fill_hypso`), 41
- `scale_fill_hypso_tint_b`
 - (`scale_fill_hypso`), 41
- `scale_fill_hypso_tint_c`
 - (`scale_fill_hypso`), 41
- `scale_fill_hypso_tint_d`
 - (`scale_fill_hypso`), 41
- `scale_fill_terrain`, 38, 44, 47, 50, 52
- `scale_fill_terrain_b`
 - (`scale_fill_terrain`), 47
- `scale_fill_terrain_c`
 - (`scale_fill_terrain`), 47
- `scale_fill_terrain_d`
 - (`scale_fill_terrain`), 47
- `scale_fill_whitebox`, 38, 44, 48, 49, 52
- `scale_fill_whitebox_b`
 - (`scale_fill_whitebox`), 49
- `scale_fill_whitebox_c`
 - (`scale_fill_whitebox`), 49
- `scale_fill_whitebox_d`
 - (`scale_fill_whitebox`), 49

scale_fill_wiki, [38](#), [44](#), [48](#), [50](#), [51](#)
scale_fill_wiki_b(scale_fill_wiki), [51](#)
scale_fill_wiki_c(scale_fill_wiki), [51](#)
scale_fill_wiki_d(scale_fill_wiki), [51](#)
select, [12](#), [27](#), [29](#), [32](#), [34](#), [53](#), [58](#)
select(), [31](#)
sf::st_crs(), [30](#)
slice, [12](#), [27](#), [29](#), [32](#), [34](#), [54](#), [55](#)
slice.SpatRaster(), [3](#)
slice_colrows(slice), [55](#)
slice_cols(slice), [55](#)
slice_head.SpatRaster(slice), [55](#)
slice_head.SpatVector(slice), [55](#)
slice_max.SpatRaster(slice), [55](#)
slice_max.SpatVector(slice), [55](#)
slice_min.SpatRaster(slice), [55](#)
slice_min.SpatVector(slice), [55](#)
slice_rows(slice), [55](#)
slice_sample.SpatRaster(slice), [55](#)
slice_sample.SpatVector(slice), [55](#)
slice_tail.SpatRaster(slice), [55](#)
slice_tail.SpatVector(slice), [55](#)

terra::aggregate(), [8](#)
terra::app(), [27](#)
terra::as.data.frame(), [5](#), [6](#), [28](#), [29](#)
terra::clamp(), [27](#)
terra::classify(), [27](#)
terra::contour(), [20](#)
terra::crs(), [30](#)
terra::disagg(), [8](#)
terra::extend(), [57](#)
terra::ifel(), [27](#)
terra::lapp(), [27](#)
terra::mask(), [58](#)
terra::minmax(), [38](#), [44](#)
terra::plot(), [6](#), [13](#), [14](#), [23](#), [38](#), [44](#), [47](#), [48](#),
[50](#), [52](#)
terra::plotRGB(), [6](#), [17](#)
terra::project(), [8](#)
terra::rast(), [3–5](#), [12](#), [13](#), [16](#), [27](#), [28](#), [32](#),
[33](#), [35](#), [54](#), [57](#)
terra::resample(), [8](#)
terra::spatSample(), [58](#)
terra::subset(), [54](#), [58](#)
terra::tapp(), [27](#)
terra::trim(), [12](#), [57](#)
terra::values(), [29](#)

terra::vect(), [5](#), [10](#), [12](#), [22](#), [23](#), [27](#), [28](#), [32](#),
[33](#), [35](#), [54](#), [57](#)
tibble::as_tibble(), [5](#), [6](#)
tidyr::drop_na(), [11](#)
tidyr::replace_na(), [35](#)
transmute(mutate), [26](#)

volcano, [59](#), [60](#)
volcano2, [9](#), [24](#), [59](#)

whitebox.colors(scale_fill_whitebox),
[49](#)
wiki.colors(scale_fill_wiki), [51](#)