

Package ‘visualize’

January 8, 2020

Type Package

Title Graph Probability Distributions with User Supplied Parameters
and Statistics

Version 4.4.0

Depends R (>= 3.0.0)

Description Graphs the pdf or pmf and highlights what area or probability is present in user defined locations. Visualize is able to provide lower tail, bounded, upper tail, and two tail calculations. Supports strict and equal to inequalities. Also provided on the graph is the mean and variance of the distribution.

License MIT + file LICENSE

URL <https://github.com/coatless/visualize>,
<http://thecoatlessprofessor.com/projects/visualize/>

BugReports <https://github.com/coatless/visualize/issues>

Encoding UTF-8

RoxygenNote 6.1.1

NeedsCompilation no

Author James Balamuta [aut, cph, cre]
(<<https://orcid.org/0000-0003-2826-8458>>)

Maintainer James Balamuta <james.balamuta@gmail.com>

Repository CRAN

Date/Publication 2020-01-08 22:20:02 UTC

R topics documented:

visualize-package	2
visualize.beta	3
visualize.binom	4
visualize.cauchy	5
visualize.chisq	6

visualize.continuous	7
visualize.discrete	8
visualize.exp	9
visualize.f	10
visualize.gamma	11
visualize.geom	12
visualize.hyper	13
visualize.it	14
visualize.lnorm	15
visualize.logis	16
visualize.nbinom	17
visualize.norm	18
visualize.pois	19
visualize.t	20
visualize.unif	21
visualize.wilcox	22

Index	24
--------------	-----------

visualize-package *visualize: Graph Probability Distributions with User Supplied Parameters and Statistics*

Description

Graphs the pdf or pmf and highlights what area or probability is present in user defined locations. Visualize is able to provide lower tail, bounded, upper tail, and two tail calculations. Supports strict and equal to inequalities. Also provided on the graph is the mean and variance of the distribution.

Author(s)

Maintainer: James Balamuta <james.balamuta@gmail.com> (0000-0003-2826-8458) [copyright holder]

See Also

Useful links:

- <https://github.com/coatless/visualize>
- <http://thecoatlessprofessor.com/projects/visualize/>
- Report bugs at <https://github.com/coatless/visualize/issues>

Examples

```
## visualize.it acts as the general wrapper.
## For guided application of visualize, see the visualize.distr_name list.
# Binomial distribution evaluated at lower tail.
visualize.it(dist = 'binom', stat = 2, params = list(size = 4, prob = .5),
             section = "lower", strict = TRUE)
visualize.binom(stat = 2, size = 4, prob = .5, section = "lower", strict = TRUE)

# Set to shade inbetween a bounded region.
visualize.it(dist = 'norm', stat = c(-1, 1), list(mu = 0, sd = 1), section = "bounded")
visualize.norm(stat = c(-1, 1), mu = 0, sd = 1, section = "bounded")

# Gamma distribution evaluated at upper tail.
visualize.it(dist = 'gamma', stat = 2, params = list(alpha = 2, theta = 1), section = "upper")
visualize.gamma(stat = 2, alpha = 2, theta = 1, section = "upper")
```

visualize.beta

Visualize Beta Distribution

Description

Generates a plot of the Beta distribution with user specified parameters.

Usage

```
visualize.beta(stat = 1, alpha = 3, beta = 2, section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
alpha	alpha is considered to be <i>shape1</i> by R's implementation of the beta distribution. alpha must be greater than 0.
beta	beta is considered to be <i>shape2</i> by R's implementation of the beta distribution. beta must be greater than 0.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dbeta\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.beta(stat = 1, alpha = 2, beta = 3, section = "lower")

# Evaluates bounded region.
visualize.beta(stat = c(.5,1), alpha = 4, beta = 3, section = "bounded")

# Evaluates upper tail.
visualize.beta(stat = 1, alpha = 2, beta = 3, section = "upper")
```

visualize.binom

Visualize Binomial Distribution

Description

Generates a plot of the Binomial distribution with user specified parameters.

Usage

```
visualize.binom(stat = 1, size = 3, prob = 0.5, section = "lower",
                 strict = FALSE)
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
size	size of sample.
prob	probability of picking object.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".
strict	Determines whether the probability will be generated as a strict (<code><</code> , <code>></code>) or equal to (<code>=</code>) inequality. <code>strict=</code> requires either <code>values = 0</code> or <code>=FALSE</code> for equal to OR <code>values = 1</code> or <code>=TRUE</code> for strict. For bounded condition use: <code>strict=c(0,1)</code> or <code>strict=c(FALSE,TRUE)</code> .

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#) , [dbinom\(\)](#).

Examples

```
# Evaluates lower tail with equal to inequality.  
visualize.binom(stat = 1, size = 3, prob = 0.5, section = "lower", strict = FALSE)  
  
# Evaluates bounded region with lower bound equal to and upper bound strict inequality.  
visualize.binom(stat = c(1,2), size = 5, prob = 0.35, section = "bounded", strict = c(0,1))  
  
# Evaluates upper tail with strict inequality.  
visualize.binom(stat = 1, size = 3, prob = 0.5, section = "upper", strict = TRUE)
```

visualize.cauchy *Visualize Cauchy Distribution*

Description

Generates a plot of the Cauchy distribution with user specified parameters.

Usage

```
visualize.cauchy(stat = 1, location = 2, scale = 1,  
section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as stat = c(lower_bound,upper_bound). Otherwise, a simple stat = desired_point will suffice.
location	location parameter
scale	scale parameter
section	Select how you want the statistic(s) evaluated via section= either "lower","bounded", "upper", or"tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dcauchy\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.cauchy(stat = 1, location = 4, scale = 2, section = "lower")

# Evaluates bounded region.
visualize.cauchy(stat = c(3,5), location = 5, scale = 3, section = "bounded")

# Evaluates upper tail.
visualize.cauchy(stat = 1, location = 4, scale = 2, section = "upper")
```

visualize.chisq

Visualize Chi-squared Distribution

Description

Generates a plot of the Chi-squared distribution with user specified parameters.

Usage

```
visualize.chisq(stat = 1, df = 3, section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
df	degrees of freedom of Chi-squared distribution.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dchisq\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.chisq(stat = 1, df = 3, section = "lower")
# Evaluates bounded region.
visualize.chisq(stat = c(1,2), df = 6, section = "bounded")
# Evaluates upper tail.
visualize.chisq(stat = 1, df = 3, section = "upper")
```

visualize.continuous *Graphing function for Continuous Distributions.*

Description

Handles how continuous distributions are graphed. Users should not use this function. Instead, users should use [visualize.it\(\)](#).

Usage

```
visualize.continuous(dist, stat = c(0, 1), params, section = "lower")
```

Arguments

dist	contains the distribution from visualize.distributions() .
stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
params	A list that must contain the necessary parameters for each distribution. For example, <code>params = list(mu = 1, sd = 1)</code> would be for a normal distribution with mean 1 and standard deviation 1. If you are not aware of the parameters for the distribution, consider using the <code>visualize.dist_name</code> functions listed under the "See Also" section.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Author(s)

James Balamuta

See Also

`visualize.it()`, `visualize.beta()`, `visualize.chisq()`, `visualize.exp()`, `visualize.gamma()`,
`visualize.norm()`, `visualize.unif()`, `visualize.cauchy()*`, `visualize.f()*`, `visualize.lnorm()*`,
`visualize.t()*`, `visualize.wilcox()*`, `visualize.logis()*`.
 * = added in v2.0.

Examples

```
# Function does not have dist look up, must go through visualize.it
visualize.it(dist='norm', stat = c(0,1), params = list(mu = 1, sd = 1), section = "bounded")
```

`visualize.discrete` *Graphing function for Discrete Distributions.*

Description

Handles how discrete distributions are graphed. Users should not use this function. Instead, users should use `link{visualize.it}`.

Usage

```
visualize.discrete(dist, stat = c(0, 1), params, section = "lower",
                   strict)
```

Arguments

<code>dist</code>	contains the distribution from <code>link{visualize.distributions}</code> .
<code>stat</code>	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
<code>params</code>	A list that must contain the necessary parameters for each distribution. For example, <code>params = list(n = 5,prob = .25)</code> would be for a binomial distribution with size 5 and probability .75. If you are not aware of the parameters for the distribution, consider using the <code>visualize.dist_name</code> functions listed under the "See Also" section.
<code>section</code>	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".
<code>strict</code>	Determines whether the probability will be generated as a strict (<code><</code> , <code>></code>) or equal to (<code><=</code> , <code>>=</code>) inequality. <code>strict=</code> requires either <code>values = 0</code> or <code>=FALSE</code> for equal to OR <code>values = 1</code> or <code>=TRUE</code> for strict. For bounded condition use: <code>strict=c(0,1)</code> or <code>strict=c(FALSE,TRUE)</code> .

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [visualize.binom\(\)](#), [visualize.geom\(\)](#), [visualize.hyper\(\)](#), [visualize.nbinom\(\)](#),
[visualize.pois\(\)](#).

Examples

```
# Function does not have dist look up, must go through visualize.it
visualize.it(dist='geom', stat = c(2,4), params = list(prob = .75), section = "bounded",
              strict = c(0,1))
```

visualize.exp

Visualize Exponential Distribution

Description

Generates a plot of the Exponential distribution with user specified parameters.

Usage

```
visualize.exp(stat = 1, theta = 1, section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
theta	vector of rates
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dexp\(\)](#).

Examples

```
# Evaluates lower tail.  
visualize.exp(stat = .5, theta = 3, section = "lower")  
  
# Evaluates bounded region.  
visualize.exp(stat = c(1,2), theta = 3, section = "bounded")  
  
# Evaluates upper tail.  
visualize.exp(stat = .5, theta = 3, section = "upper")
```

visualize.f *Visualize F distribution*

Description

Generates a plot of the F distribution with user specified parameters.

Usage

```
visualize.f(stat = 1, df1 = 5, df2 = 4, section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
df1	First Degrees of Freedom
df2	Second Degrees of Freedom
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [df\(\)](#).

Examples

```
# Evaluates lower tail.  
visualize.f(stat = 1, df1 = 5, df2 = 4, section = "lower")  
  
# Evaluates bounded region.  
visualize.f(stat = c(3,5), df1 = 6, df2 = 3, section = "bounded")  
  
# Evaluates upper tail.  
visualize.f(stat = 1, df1 = 5, df2 = 4, section = "upper")
```

visualize.gamma *Visualize Gamma Distribution*

Description

Generates a plot of the Gamma distribution with user specified parameters.

Usage

```
visualize.gamma(stat = 1, alpha = 1, theta = 1, section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
alpha	alpha is considered to be <i>shape</i> by R's implementation of the gamma distribution. alpha must be greater than 0.
theta	theta is considered to be <i>rate</i> by R's implementation of the gamma distribution. theta must be greater than 0.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dgamma\(\)](#).

Examples

```
# Evaluate lower tail.
visualize.gamma(stat = 1, alpha = 3, theta = 1, section = "lower")

# Evaluate bounded section.
visualize.gamma(stat = c(0.75,1), alpha = 3, theta = 1, section = "bounded")

# Evaluate upper tail.
visualize.gamma(stat = 1, alpha = 3, theta = 1, section = "upper")
```

visualize.geom

Visualize Geometric Distribution

Description

Generates a plot of the Geometric distribution with user specified parameters.

Usage

```
visualize.geom(stat = 1, prob = 0.3, section = "lower",
               strict = FALSE)
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
prob	probability of picking object.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".
strict	Determines whether the probability will be generated as a strict (<code><</code> , <code>></code>) or equal to (<code><=</code> , <code>>=</code>) inequality. <code>strict=</code> requires either <code>values = 0</code> or <code>=FALSE</code> for equal to OR <code>values =1</code> or <code>=TRUE</code> for strict. For bounded condition use: <code>strict=c(0,1)</code> or <code>strict=c(FALSE,TRUE)</code> .

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#) , [dgeom\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.geom(stat = 1, prob = 0.5, section = "lower", strict = FALSE)

# Evaluates bounded region.
visualize.geom(stat = c(1,3), prob = 0.35, section = "bounded", strict = c(0,1))

# Evaluates upper tail.
visualize.geom(stat = 1, prob = 0.5, section = "upper", strict = 1)
```

visualize.hyper

Visualize Hypergeometric Distribution

Description

Generates a plot of the Hypergeometric distribution with user specified parameters.

Usage

```
visualize.hyper(stat = 1, m = 5, n = 4, k = 2, section = "lower",
                 strict = FALSE)
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
m	m white balls. m must be greater than 0.
n	n black balls. n must be greater than 0.
k	draw k balls without replacement.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".
strict	Determines whether the probability will be generated as a strict (<code><</code> , <code>></code>) or equal to (<code><=</code> , <code>>=</code>) inequality. <code>strict=</code> requires either <code>values = 0</code> or <code>=FALSE</code> for equal to OR <code>values = 1</code> or <code>=TRUE</code> for strict. For bounded condition use: <code>strict=c(0,1)</code> or <code>strict=c(FALSE,TRUE)</code> .

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#) , [dhyper\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.hyper(stat = 1, m=4, n=5, k=3, section = "lower", strict = 0)

# Evaluates bounded region.
visualize.hyper(stat = c(2,4), m=14, n=5, k=2, section = "bounded", strict = c(0,1))

# Evaluates upper tail.
visualize.hyper(stat = 1, m=4, n=5, k=3, section = "upper", strict = 1)
```

visualize.it

Visualize's Processing Function

Description

Acts as a director of traffic and first line of error handling regarding submitted visualization requests. This function should only be used by advanced users.

Usage

```
visualize.it(dist = "norm", stat = c(0, 1), params = list(mu = 0, sd = 1), section = "lower", strict = c(0, 1))
```

Arguments

dist	a string that should be contain a supported probability distributions name in R. Supported continuous distributions: "beta", "chisq", "exp", "gamma", "norm", and "unif". Supported discrete distributions: "binom", "geom", "hyper", "nbinom", and "pois".
stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
params	A list that must contain the necessary parameters for each distribution. For example, <code>params = list(mu = 1, sd = 1)</code> would be for a normal distribution with mean 1 and standard deviation 1. If you are not aware of the parameters for the distribution, consider using the <code>visualize.dist</code> functions listed under the "See Also" section.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".
strict	Determines whether the probability will be generated as a strict (<code><</code> , <code>></code>) or equal to (<code><=</code> , <code>>=</code>) inequality. <code>strict=</code> requires either <code>values = 0</code> or <code>=FALSE</code> for strict OR <code>values =1</code> or <code>=TRUE</code> for equal to. For bounded condition use: <code>strict=c(0,1)</code> or <code>strict=c(FALSE,TRUE)</code> .

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

References

<http://cran.r-project.org/web/views/Distributions.html>

See Also

[visualize.beta\(\)](#), [visualize.chisq\(\)](#), [visualize.exp\(\)](#), [visualize.gamma\(\)](#), [visualize.norm\(\)](#),
[visualize.unif\(\)](#), [visualize.binom\(\)](#), [visualize.geom\(\)](#), [visualize.hyper\(\)](#), [visualize.nbinom\(\)](#),
[visualize.pois\(\)](#).

Examples

```
# Defaults to lower tail evaluation  
visualize.it(dist = 'norm', stat = 1, list(mu = 3 , sd = 2), section = "lower")  
  
# Set to evaluate the upper tail.  
visualize.it(dist = 'norm', stat = 1, list(mu=3,sd=2),section="upper")  
  
# Set to shade inbetween a bounded region.  
visualize.it(dist = 'norm', stat = c(-1,1), list(mu=0,sd=1), section="bounded")  
  
# Gamma distribution evaluated at upper tail.  
visualize.it(dist = 'gamma', stat = 2, params = list(alpha=2,beta=1),section="upper")  
  
# Binomial distribution evaluated at lower tail.  
visualize.it('binom', stat = 2, params = list(n=4,p=.5))
```

Description

Generates a plot of the Log Normal distribution with user specified parameters.

Usage

```
visualize.lnorm(stat = 1, meanlog = 3, sdlog = 1,  
section = "lower")
```

Arguments

<code>stat</code>	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound, upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
<code>meanlog</code>	Mean of the distribution
<code>sdlog</code>	Standard deviation of the distribution
<code>section</code>	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dlnorm\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.lnorm(stat = 1, meanlog = 3, sdlog = 1, section = "lower")

# Evaluates bounded region.
visualize.lnorm(stat = c(3,5), meanlog = 3, sdlog = 3, section = "bounded")

# Evaluates upper tail.
visualize.lnorm(stat = 1, meanlog = 3, sdlog = 1, section = "upper")
```

Description

Generates a plot of the Logistic distribution with user specified parameters.

Usage

```
visualize.logis(stat = 1, location = 3, scale = 1,
                 section = "lower")
```

Arguments

<code>stat</code>	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound, upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
<code>location</code>	Location of the distribution.
<code>scale</code>	Scale of the distribution.
<code>section</code>	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dlogis\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.logis(stat = 1, location = 4, scale = 2, section = "lower")

# Evaluates bounded region.
visualize.logis(stat = c(3,5), location = 4, scale = 2, section = "bounded")

# Evaluates upper tail.
visualize.logis(stat = 1, location = 4, scale = 2, section = "upper")
```

Description

Generates a plot of the Negative Binomial distribution with user specified parameters.

Usage

```
visualize.nbinom(stat = 1, size = 6, prob = 0.5, section = "lower",
                  strict = FALSE)
```

Arguments

<code>stat</code>	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound, upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
<code>size</code>	number of objects.
<code>prob</code>	probability of picking object.
<code>section</code>	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".
<code>strict</code>	Determines whether the probability will be generated as a strict (<code><</code> , <code>></code>) or equal to (<code><=</code> , <code>>=</code>) inequality. <code>strict=</code> requires either <code>values = 0</code> or <code>= FALSE</code> for equal to OR <code>values = 1</code> or <code>= TRUE</code> for strict. For bounded condition use: <code>strict=c(0,1)</code> or <code>strict=c(FALSE,TRUE)</code> .

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#) , [dnbinom\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.nbinom(stat = 1, size = 5, prob = 0.5, section = "lower", strict = 0)

# Evaluates bounded region.
visualize.nbinom(stat = c(1,3), size = 10, prob = 0.35, section = "bounded",
                 strict = c(TRUE, FALSE))

# Evaluates upper tail.
visualize.nbinom(stat = 1, size = 5, prob = 0.5, section = "upper", strict = 1)
```

Description

Generates a plot of the Normal distribution with user specified parameters.

Usage

```
visualize.norm(stat = 1, mu = 0, sd = 1, section = "lower")
```

Arguments

<code>stat</code>	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
<code>mu</code>	mean of the Normal Distribution.
<code>sd</code>	standard deviation of the Normal Distribution.
<code>section</code>	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

See Also

[visualize.it\(\)](#) , [dnorm\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.norm(stat = 1, mu = 4, sd = 5, section = "lower")

# Evaluates bounded region.
visualize.norm(stat = c(3,6), mu = 5, sd = 3, section = "bounded")

# Evaluates upper tail.
visualize.norm(stat = 1, mu = 3, sd = 2, section = "upper")
```

visualize.pois *Visualize Poisson Distribution*

Description

Generates a plot of the Poisson distribution with user specified parameters.

Usage

```
visualize.pois(stat = 1, lambda = 3.5, section = "lower",
               strict = FALSE)
```

Arguments

<code>stat</code>	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
<code>lambda</code>	lambda value of the Poisson Distribution.
<code>section</code>	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

strict Determines whether the probability will be generated as a strict ($<$, $>$) or equal to (\leq , \geq) inequality. **strict=** requires either values = 0 or =FALSE for equal to OR values =1 or =TRUE for strict. For bounded condition use: **strict=c(0,1)** or **strict=c(FALSE,TRUE)**.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#) , [dpois\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.pois(stat = 1, lambda = 2, section = "lower", strict = FALSE)

# Evaluates bounded region.
visualize.pois(stat = c(1,3), lambda = 3, section = "bounded", strict = c(0,1))

# Evaluates upper tail.
visualize.pois(stat = 1, lambda = 2, section = "upper", strict = 1)
```

visualize.t

Visualize Student's t distribution

Description

Generates a plot of the Student's t distribution with user specified parameters.

Usage

```
visualize.t(stat = 1, df = 3, section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as stat = c(lower_bound,upper_bound) . Otherwise, a simple stat = desired_point will suffice.
df	Degrees of freedom
section	Select how you want the statistic(s) evaluated via section= either "lower","bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dt\(\)](#).

Examples

```
# Evaluates lower tail.  
visualize.t(stat = 1, df = 4, section = "lower")  
  
# Evaluates bounded region.  
visualize.t(stat = c(3,5), df = 6, section = "bounded")  
  
# Evaluates upper tail.  
visualize.t(stat = 1, df = 4, section = "upper")
```

visualize.unif

Visualize Uniform Distribution

Description

Generates a plot of the Uniform distribution with user specified parameters.

Usage

`visualize.unif(stat = 1, a = 0, b = 1, section = "lower")`

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
a	starting point. Note: $a < b$
b	end point. Note: $b > a$
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dunif\(\)](#).

Examples

```
# Evaluates lower tail.
visualize.unif(stat = 8.75, a = 7, b = 10, section = "lower")

# Evaluates bounded region.
visualize.unif(stat = c(3,6), a = 1, b = 7, section = "bounded")

# Evaluates upper tail.
visualize.unif(stat = 2, a = 1, b = 5, section = "upper")
```

visualize.wilcox *Visualize Cauchy Distribution*

Description

Generates a plot of the Wilcoxon Rank Sum distribution with user specified parameters.

Usage

```
visualize.wilcox(stat = 1, m = 7, n = 3, section = "lower")
```

Arguments

stat	a statistic to obtain the probability from. When using the "bounded" condition, you must supply the parameter as <code>stat = c(lower_bound,upper_bound)</code> . Otherwise, a simple <code>stat = desired_point</code> will suffice.
m	Sample size from group 1.
n	Sample size from group 2.
section	Select how you want the statistic(s) evaluated via <code>section=</code> either "lower", "bounded", "upper", or "tails".

Value

Returns a plot of the distribution according to the conditions supplied.

Author(s)

James Balamuta

See Also

[visualize.it\(\)](#), [dwilcox\(\)](#).

Examples

```
# Evaluates lower tail.  
visualize.wilcox(stat = 1, m = 7, n = 3, section = "lower")  
  
# Evaluates bounded region.  
visualize.wilcox(stat = c(2,3), m = 5, n = 4, section = "bounded")  
  
# Evaluates upper tail.  
visualize.wilcox(stat = 1, m = 7, n = 3, section = "upper")
```

Index

*Topic **visualize**

visualize.beta, 3
 visualize.binom, 4
 visualize.cauchy, 5
 visualize.chisq, 6
 visualize.continuous, 7
 visualize.discrete, 8
 visualize.exp, 9
 visualize.f, 10
 visualize.gamma, 11
 visualize.geom, 12
 visualize.hyper, 13
 visualize.it, 14
 visualize.lnorm, 15
 visualize.logis, 16
 visualize.nbinom, 17
 visualize.norm, 18
 visualize.pois, 19
 visualize.t, 20
 visualize.unif, 21
 visualize.wilcox, 22

 dbeta(), 4
 dbinom(), 5
 dcauchy(), 6
 dchisq(), 7
 dexp(), 9
 df(), 10
 dgamma(), 11
 dgeom(), 12
 dhyper(), 13
 dlnorm(), 16
 dlogis(), 17
 dnbinom(), 18
 dnorm(), 19
 dpois(), 20
 dt(), 21
 dunif(), 21
 dwilcox(), 22

visualize(visualize-package), 2
 visualize-package, 2
 visualize.beta, 3
 visualize.beta(), 8, 15
 visualize.binom, 4
 visualize.binom(), 9, 15
 visualize.cauchy, 5
 visualize.cauchy(), 8
 visualize.chisq, 6
 visualize.chisq(), 8, 15
 visualize.continuous, 7
 visualize.discrete, 8
 visualize.distributions(), 7
 visualize.exp, 9
 visualize.exp(), 8, 15
 visualize.f, 10
 visualize.f(), 8
 visualize.gamma, 11
 visualize.gamma(), 8, 15
 visualize.geom, 12
 visualize.geom(), 9, 15
 visualize.hyper, 13
 visualize.hyper(), 9, 15
 visualize.it, 14
 visualize.it(), 4–13, 16–22
 visualize.lnorm, 15
 visualize.lnorm(), 8
 visualize.logis, 16
 visualize.logis(), 8
 visualize.nbinom, 17
 visualize.nbinom(), 9, 15
 visualize.norm, 18
 visualize.norm(), 8, 15
 visualize.pois, 19
 visualize.pois(), 9, 15
 visualize.t, 20
 visualize.t(), 8
 visualize.unif, 21
 visualize.unif(), 8, 15

`visualize.wilcox`, [22](#)
`visualize.wilcox()`, [8](#)