

Enrico Schumann
es@enricoschumann.net

PMWR provides several methods for toLatex.

Monthly returns

For a timeseries (e.g. zoo or xts), the function returns provides monthly returns.

```
> returns(DAX, period = "month")
```

	Jan	Feb	MÃd'r	Apr	Mai	Jun	Jul	Aug	Sep	Okt	Nov	Dez	YTD
2014	-1.0	4.1	-1.4	0.5	3.5	-1.1	-4.3	0.7	0.0	-1.6	7.0	-1.8	4.3
2015	9.1	6.6	5.0	-4.3	-0.4	-4.1	3.3	-9.3	-5.8	12.3	4.9	-5.6	9.6

To have such a table placed into a L^AT_EX file, you can put the following snippet into a Sweave file.

```
\begin{tabular}{rrrrrrrrrrrrrrr}
<<results=tex,echo=false>>=
toLatex(returns(DAX, period = "month"), ytd = "\\textsc{ytd}")
@
\end{tabular}
```

The results will look like this:

	Jan	Feb	MÃd'r	Apr	Mai	Jun	Jul	Aug	Sep	Okt	Nov	Dez	YTD
2014	-1.0	4.1	-1.4	0.5	3.5	-1.1	-4.3	0.7	0.0	-1.6	7.0	-1.8	4.3
2015	9.1	6.6	5.0	-4.3	-0.4	-4.1	3.3	-9.3	-5.8	12.3	4.9	-5.6	9.6

NAVseries

Summaries of NAVseries contain a number of statistics that can be placed into L^AT_EX templates.

```
> returns(DAX, period = "annualised")
```

```
6.9% [02 Jan 2014 -- 30 Dez 2015]
```

We first compute summaries.

```
> DAX <- summary(as.NAVseries(DAX, title = "DAX"))
> REXP <- summary(as.NAVseries(REXP, title = "REXP"))
> toLatex(DAX, REXP, template = "%title: %return\\% \\\")
```

```
DAX: 6.9\\% \\  
REXP: 3.8\\% \\  


```

Note that the template was recycled, i.e. it was used for both series. We may also pass separate templates for each series.

```
> tmpl <- c("Equities (%title) made %return\\%, with a drawdown of %mdd\\%;",
            "bonds (%title) returned %return\\%.")
> toLatex(DAX, REXP, template = tmpl)
```

```
Equities (DAX) made 6.9\\%, with a drawdown of 23.8\\%;
bonds (REXP) returned 3.8\\%.
```

The keyword %sparkline adds a sparkline:

```
> toLatex(DAX, template = "The DAX %sparkline made %return\\% during the period.")
The DAX  made 6.9% during the period.
```


















































Since templates are recycled, we can easily create rows for \LaTeX tables, such as this one:

		Return p.a.	Volatility
DAX		6.9	18.0
REXP		3.8	1.9

...which is produced by the following call:

```
> toLatex(DAX, REXP,
          template = "%title & %sparkline & %return & %volatility \\\\" )
```

When several NAV series are passed to toLatex, all sparkline plots use the same y-scale. It is then straightforward to produce tables such as the following one, in which we have sorted 50 random series by total return (see the vignette source for the code).

Return	Vol		Return	Vol		Return	Vol	
39.3	14.0		3.3	15.4		-5.2	16.4	
29.0	16.5		2.8	14.5		-8.1	17.0	
27.8	15.5		1.1	16.1		-9.0	16.1	
24.2	16.8		0.8	16.8		-9.1	15.9	
21.5	15.2		0.7	17.1		-10.8	16.7	
19.7	15.6		0.5	16.1		-11.0	15.4	
18.9	15.9		-0.2	15.8		-11.3	14.6	
17.3	15.3		-0.3	15.8		-13.0	14.9	
15.4	14.3		-0.6	16.3		-13.5	15.3	
14.5	15.5		-0.7	14.2		-14.0	17.0	
11.4	14.9		-2.1	16.6		-14.3	15.6	
11.2	15.6		-2.6	16.2		-14.6	17.4	
11.1	16.2		-3.2	15.8		-17.7	15.5	
11.1	15.3		-3.3	16.7		-25.5	16.3	
9.6	15.5		-3.4	15.7		-25.9	15.3	
5.5	16.1		-3.9	15.4		-29.0	15.8	
4.6	16.3		-4.6	16.1	