

Changes in spsurvey

February 3, 2012

NEWS

spsurvey News

CHANGES IN spsurvey VERSION 2.3 (Released 2012-02-03)

NEW FEATURES:

- Created a function named `change.analysis` that conducts change analysis for a collection of response variables (categorical and continuous) generated by two probability surveys.
- Created functions named `change.est`, `changevar.prop`, and `changevar.mean` to calculate estimates of change and its associated variance.
- Created a vignette that presents cumulative distribution function (CDF) analysis of a GRTS survey designs.
- Added a function named `ash1.wgt` that computes the average shifted histogram (ASH) for weighted data.
- Created an `.onAttach` function that prints a message when the `spsurvey` package is attached. Modified the `.onLoad` function to remove a startup message and to check whether package `sp` is installed. If not, the package is installed using the `install.packages` function.

BUG FIXES:

- Modified function `grtspts` to correct an error that occurs when argument `src.frame` equals "att.frame" and the number of hierarchical levels equals eleven.
- Modified C functions `printAddrList`, `printColCharList`, and `printDbf` to replace calls to the `printf` function with calls to the `Rprintf` function.
- Modified C function `pickAreaSamplePoints` to correct an error that occurs when selecting sample points for `PolygonZ` and `PolygonM` type shapefiles.

CHANGES IN spsurvey VERSION 2.2 (Released 2011-05-16)

NEW FEATURES:

- In order to reduce package size, removed demonstration (demo) R scripts and the associated data directory.
- Created vignettes that present analyses of GRTS survey designs for finite, linear, and areal resources.
- Created a function named `attrisk.analysis` that conducts attributable risk analysis for a collection of response variables generated by a probability survey.

- Created functions named `attrisk.est` and `attrisk.var` to calculate estimates of attributable risk and its associated variance.
- Modified function `relrisk.est` to change the way the relative risk estimate is calculated for a stratified sample.
- Modified functions `cat.analysis`, `cont.analysis`, `cont.cdfctest`, `relrisk.analysis`, `category.est`, `cdf.est`, `cdf.decon`, `total.est`, `cdf.test`, `relrisk.est`, `catvar.prop`, `catvar.size`, `cdfvar.prop`, `cdfvar.total`, `cdfvar.size.prop`, `cdfvar.size.total`, `dcdvar.prop`, `dcdvar.total`, `dcdvar.size.prop`, `dcdvar.size.total`, `total.var`, `cdfvar.test`, and `relrisk.var` to allow variance estimates to be calculated when a two stage sample has stage one sampling units that contain a single stage two sampling unit. Variance for those stage one sampling units is calculated using the mean of the variance estimates for stage one sampling units that contain two or more stage two sampling units.
- Modified function `grtslin` to improve efficiency of sample point selection. Created a C function named `insideLinearGridCell` that, for each grid cell selected to receive a sample point, returns the ID value for shapefile records contained in the cell and the clipped length of the polyline segments within the cell for each record. Created a C function named `pickLinearSamplePoints` that selects sample points.
- Modified function `grtsarea` to improve efficiency of sample point selection. Created a C function named `insideAreaGridCell` that, for each grid cell selected to receive a sample point, returns the ID value for shapefile records contained in the cell and the clipped area of the polygon within the cell for each record. Created a C function named `pickAreaSamplePoints` that selects sample points.

BUG FIXES:

- Modified function `input.check` to include determination of whether a valid value was provided for argument `vartype`.
- Modified function `grts` so that correct survey design weights are created for linear and areal designs when the type of random selection is "continuous".
- Modified functions `grtspts`, `grtslin`, and `grtsarea` to execute without error for a stratum sample size of one.
- Modified function `dframe.check` to terminate execution when missing values are encountered in the logical variable of the sites data frame.

CHANGES IN `spsurvey` VERSION 2.1 (Released 2009-10-29)

NEW FEATURES:

- Created vignettes that present examples of GRTS survey designs for finite, linear, and areal resources.
- Created a function named `geodalbers` that projects latitude and longitude (spheroid) models of the globe to Albers projection in the plane.
- Modified function `dsgnsum` to produce summary tables for the actual set of design variables that are present rather than a standard set of design variables.
- Modified function `dframe.check` to terminate execution when missing site ID values or repeated site ID values are encountered in the `sites`, `design`, `subpop`, `data.cat`, `data.cont`, or `data.rr` data frames. Note that `dframe.check` is called by functions `cat.analysis`, `cont.analysis`, `cont.cdfctest`, and `relrisk.analysis`.

BUG FIXES:

- Modified function `cont.cdfctest` to correct an error caused by improper handling of an empty subpopulation.

- Modified function `relrisk.analysis` to correct an error resulting from inclusion of more than one response variable in the `response.var` argument.

CHANGES IN `spsurvey` VERSION 2.0 (Released 2008-06-16)

NEW FEATURES:

- Eliminated use of argument `unitsize` (known sum of size-weights) by package functions. Restricted argument `popsiz` to provide only the known size of the resource for use in ratio adjustment of estimators. Created a new argument named `pcfsiz` to provide resource size for calculation of finite and continuous population correction factors for single-stage samples.
- Modified functions `cat.analysis`, `cont.analysis`, `cont.cdf.test`, and `relrisk.analysis` to add logical variables to their argument lists that specify use of finite or continuous population correction factors or use of size-weights in analysis routines.
- Modified functions `category.est`, `cdf.decon`, `cdf.est`, `cdf.test`, `relrisk.est` and `total.est` to add logical variables to their argument lists that specify use of finite or continuous population correction factors or use of size-weights.

BUG FIXES:

- Modified function `irs` to eliminate checking for existence of x-coordinates and y-coordinates when the type of frame is "finite" and the frame is included in the `att.frame` data frame.
- Modified C functions `parseFields` and `readDbfFile` to ensure that blank values in the shapefile attributes (dbf) file are converted to R missing values (NA).
- Modified C function `writeDbfFile` to output blank values for R missing values (NA) when creating the shapefile attributes (dbf) file.
- Modified functions `grts`, `irs`, and `sp2shape` to ensure that an output shapefile attributes (dbf) file containing character variables with missing values can be read without error.

CHANGES IN `spsurvey` VERSION 1.7 (Released 2007-11-09)

NEW FEATURES:

- Created a function named `cont.cdf.test` that tests for differences between cumulative distribution functions (CDFs) for pairs of subpopulations within a population `Type` for a collection of response variables generated by a probability survey. Also, modified function `cdf.test` so that it is consistent with functions that are called by high-level functions `cat.analysis` and `cont.analysis`.
- Modified function `grtspts` so that, when source of the frame equals "att.frame", the current number of grid levels for hierarchical randomization and the final number of grid levels is printed to the console while the function is executing.
- Created a function named `relrisk.analysis` that conducts relative risk analysis for a collection of response variables generated by a probability survey. Also, renamed function `relrisk` to `relrisk.est` and modified the function so that it is consistent with functions that are called by high-level functions `cat.analysis` and `cont.analysis`.
- Modified function `grtspts` and C function `numLevels` to terminate the algorithm for determining the number of grid levels for hierarchical randomization when the maximum value of total inclusion probability for the grid cells stops changing as the number of levels increases.
- Created functions named `cdf.plot` and `cont.cdfplot` that create cumulative distribution function (CDF) plots using the data frame named "CDF" contained in the output object created by function `cont.analysis`. Function `cdf.plot` creates a single CDF plot, and function `cont.cdfplot` creates a set of CDF plots.

- Created a function named `read.sas` that can read SAS datasets or a SAS XPORT (transport) file.

BUG FIXES:

- Modified C functions `intersect`, `linSampleIRS`, `lintFcn`, and `linSample` to eliminate warning messages that were generated during package creation.
- Modified function `grts` so that argument `do.sample` provides a value for each stratum.
- Modified C functions `getRecordShapeSizes`, `readDbfFile`, `parsePoints`, `parsePointsZ`, `parsePointsM`, `parsePolygon`, `parsePolygonZ`, and `parsePolygonM` to generate error messages and terminate execution when a shapefile containing a Null record is encountered.
- Modified functions `irslin` and `irsarea` in addition to C function `getRecordIDs` to ensure that sample points are selected in random order for linear and areal IRS designs.
- Modified function `grts` to ensure that, when the type of random selection is "unequal", an oversample is apportioned correctly whenever the category sample sizes are proportional to the oversample size.

CHANGES IN `spsurvey` VERSION 1.6 (Released 2007-01-18)

NEW FEATURES:

- For C functions that read shapefiles from the current directory, replaced calls to `_findfirst` and `_findnext` with code using calls to `readdir`. These changes were implemented to facilitate portability of the package.
- Created a C function named `matchFiles` that determines whether file names in the current directory have a desired file extension. This change was implemented to facilitate portability of the package.

BUG FIXES:

- Modified functions `grts` and `irs` to accommodate use of a factor for the ID variable in the attributes data frame.
- Modified functions `grts` and `irs` to ensure that sample weights are correctly adjusted when an oversample is present and the type of random selection is "Continuous".

CHANGES IN `spsurvey` VERSION 1.5 (Released 2006-12-06)

NEW FEATURES:

- None.

BUG FIXES:

- Modified C functions `getRecordShapeSizes` and `lintFcn` to accommodate Polyline shapefiles that have multiple parts.

CHANGES IN `spsurvey` VERSION 1.4 (Released 2006-10-10)

NEW FEATURES:

- Modified functions `dsgnsum` and `sp2shape` to accommodate the change in representation from `AttributeList` to `data.frame` for the data slot of `sp` package objects belonging to class `SpatialPointsDataFrame`.
- Modified functions `grts` and `irs` to print a warning message when the type of frame equals "finite" and a stratum name in the design list matches only a single value in the stratum column of the attributes data frame. For this case, function `grtspts` or `irspts` is not called since the sample will be composed of a single point.

- Modified functions `grts`, `grtspts`, `grtslin`, and `grtsarea` to change the maximum value allowed for arguments `startlev` (the initial number of hierarchical levels to use for the GRTS grid) and `maxlev` (the maximum number of hierarchical levels to use for the GRTS grid) from 12 to 11.
- Added an example polylines dataset to the data directory.
- Modified functions `grts` and `irs` to allow use of an `sp` package object as the source of the frame. An argument named `sp.object` was added to the argument list for `grts` and `irs`.
- Modified functions `grts`, `grtspts`, `grtslin`, `grtsarea`, `irs`, `irspts`, `irslin`, and `irsarea` to remove use of argument `xy.frame` as an option for source of the frame. Then modified functions `grts`, `grtspts`, `irs`, and `irspts` to allow incorporation of frame coordinates into the attributes data frame when the type of frame equals "finite". Also, removed argument `elmsize` from functions `grts` and `irs` since the argument no longer was required.

BUG FIXES:

- Modified functions `grts` and `irs` to print a warning message when the type of frame equals "finite" and a stratum name in the design list matches only a single value in the stratum column of the attributes data frame. For this case, function `grtspts` or `irspts` is not called since the sample will be composed of a single point.
- Modified functions `grts` and `irs` to ensure that the ID values for elements of the frame provided in `att.frame` are unique.
- Modified functions `grts` and `irs` to ensure that valid values are provided for the `panel` and `caty.n` arguments in the design list.

CHANGES IN spsurvey VERSION 1.3 (Released 2006-08-01)**NEW FEATURES:**

- Added an example polygons dataset to the data directory.
- Incorporated the CHANGES, README, and UserGuide files into the help page.

BUG FIXES:

- None.

CHANGES IN spsurvey VERSION 1.2 (Released 2006-06-27)**NEW FEATURES:**

- Created a function named `sp2shape` and a C function named `writeShapeFilePolygon` that convert objects created by package `sp` to ESRI shapefiles. Also, renamed the C function `writeShapeFile` to `writeShapeFilePoint`.

BUG FIXES:

- Modified function `irsarea` and created a C function named `getRecordIDs` to ensure that an IRS sample is selected when argument `type.frame` is set to "area" in function `irs`.

CHANGES IN spsurvey VERSION 1.1 (Released 2006-05-31)**NEW FEATURES:**

- Modified the C functions so that the package can accommodate M-type shapefiles.

BUG FIXES:

- Modified functions `grts` and `irs` to ensure that the levels of `mdcaty` (the variable in the attributes data frame that specifies the unequal probability category for each element in the frame) are equivalent to the names in `caty.n` (the vector of sample sizes for each category in `mdcaty`, which is required for each element of the design list for which the selection type is "Unequal").
- Modified functions `grts` and `irs` to ensure that the columns of `xy.frame` are named "x" and "y" when `xy.frame` is provided and `type.frame` equals "finite".
- Modified functions `grts` and `irs` so that the sample weights are correctly adjusted when an oversample is requested and the realized sample size is less than the desired sample size.

CHANGES IN `spsurvey` VERSION 1.0 (Released 2006-05-05)

NEW FEATURES:

- This is the original version of the package.

BUG FIXES:

- None.